



**Universal Mobile Telecommunications System (UMTS);
Universal Terrestrial Radio Access (UTRA)
repeater planning guidelines and system analysis
(3GPP TR 25.956 version 13.0.0 Release 13)**



Reference

RTR/TSGR-0425956vd00

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Report (TR) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology	2
Foreword.....	5
1 Scope	6
2 References	6
3 Definitions, symbols and abbreviations	6
3.1 Definitions.....	6
3.2 Symbols.....	7
3.3 Abbreviations	7
4 System Impacts of Repeaters	7
4.1 Error Vector Magnitude (EVM)	7
4.2 Peak Code Domain Error (PCDE).....	8
4.3 Frequency error	8
4.4 Adjacent Channel Leakage Ratio (ACLR).....	8
4.5 Time Delay	9
4.6 Location Services (LCS)	10
4.6.1 OTDOA	10
4.6.2 Cell coverage based positioning method	11
4.6.3 Network assisted GPS methods	11
4.7 Automatic Gain Control (AGC)	11
4.8 Adjacent Channel Rejection Ratio (ACRR).....	12
5 Planning with Repeaters.....	12
5.1 Sole System.....	12
5.1.1 Antenna Isolation.....	12
5.1.2 Coupling loss measurements.....	13
5.1.3 Gain Settings.....	13
5.1.4 Delay.....	14
5.2 Co-existence with UTRA FDD	14
5.2.1 Out of band gain	14
5.2.2 Isolation	14
5.2.2.1 Example on application of equations	15
5.3 Co-existence with UTRA TDD	16
5.3.1 Isolation	16
5.4 Co-existence with GSM 900 and/or DCS 1800.....	16
5.4.1 Isolation	16
5.5 Environments with low minimum coupling loss (MCL).....	16
5.5.1 Normal repeater parameters	16
5.5.2 Repeater parameters adjusted to low MCL.....	17
5.6 Analysis of out of band gain in the 3 rd adjacent channel	18
5.6.1 MCL=70 dB.....	18
5.6.2 MCL=40 dB.....	18
6 System Simulations and Analysis	19
6.1 Down-link co-existence simulations	19
6.2 Outdoor coverage (High CL _{Rep-UE})	21
6.3 Indoor coverage (Low CL _{Rep-UE})	22
6.4 Repeater up-link co-existence simulations	23
6.4.1 General.....	23
6.4.2 Simulation Assumptions	25
6.4.3 Results	25
6.4.4 Conclusion	26

6.5	Repeater ACRR system impact simulations.....	26
6.5.1	General.....	26
6.5.2	Simulation Description	27
6.5.2.1	Infrastructure.....	27
6.5.2.2	Preparation.....	27
6.5.2.3	Connection.....	28
6.5.2.4	Iterations	28
6.5.2.5	Parameters used through out the simulations.....	29
6.5.3	Results	31
6.5.3.1	288 m between repeater A and BSB	31
6.5.3.2	164 m minimum distance between repeater A and BSB	45
6.5.4	Conclusions.....	58
6.5.5	Comments	58
Annex A:	Change History	59
History		60

Foreword

This Technical Report has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The purpose of the following document is to describe planning guidelines and system scenarios for UTRA repeaters. In addition it also contains simulations and analysis of the usage of repeaters in UMTS networks.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3GPP TR 25.942

[2] R4-030365

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply, unless otherwise stated:




Figure 3.1

$ACRR_{RepA}$	Adjacent Channel Rejection Ratio for repeater A.
ACG_{RepA}	Adjacent Channel Gain for repeater A.
$CL_{BSA-UEA}$	Coupling Loss between Base Station A and the User Equipment A.
$CL_{RepA-UEA}$	Coupling Loss between Repeater A and User Equipment A.
d_{RepA}	Group delay of repeater A.
$EDoCL_{BSA-RepA}$	Effective Donor Coupling Loss between the donor Base Station A and the Repeater A.