Butterfly Valves: Double-flanged, Lugand Wafer-type, and Butt-welding Ends

API STANDARD 609 NINTH EDITION, APRIL 2021

API MONOGRAM PROGRAM EFFECTIVE DATE: OCTOBER 2021



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Users of this standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, "shall" denotes a minimum requirement to conform to the standard.

Should: As used in a standard, "should" denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, "may" denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, "can" denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

For API Monogram Program licensees and APIQR Program registrants, this standard shall become effective on the program date printed on the cover but may be used voluntarily from the date of publication.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

		Pag
	Scope	1
	Normative References	1
	Terms and Definitions	2
	Pressure-temperature Ratings	3
	Valve Rating	3
	Shell Rating	3
	Seat Rating	
	Differential Pressure Rating	4
	Design	
	General	
	Body	
	Face-to-face Dimensions	
	Valve Body Flange Facings	
	Disc Clearance	
	Shaft and Shaft Seals	
	Piping Connection External Bolt Holes	
	Valve Body Seat Retainer—Category B Valves Only	
	Operating Mechanisms	
	Antistatic Design (Electrical Continuity Between Disc, Shaft, and Body)	
	Materials	12
	Body	
	Pressure Boundary Elements	
	Process Wetted Parts	
	Packing or Shaft Seal Materials	
	Gland Bolting	
	Operating Mechanisms—Category B Valves Only	12
	Testing, Inspection, and Examination	12
	Inspection and Examination	
	Pressure Tests	13
	Electrical Continuity Test	13
	Repair of Defects	13
	Markings	13
	Packaging and Shipping	
	Coatings	
	Shaft Packing	
	Packaging	
	Spare Parts	14
	Purchase Order Information	14
~	Δ	15

Contents

		Page	
Annex B (informative) Information to be Specified by Purchaser			
Annex C (informative) Typical Butterfly Valve Construction and Nomenclature			
Annex	CD (normative) Disc-to-pipe Clearances	21	
Biblio	Bibliography		
Figure	es		
1 2 C.1 C.2 C.3 D.1 D.2	External Bolting Options for Lug- and Wafer-type Valves Limitations for Flange Face Interruptions That Fall Within the Gasket Seating Area Typical Part Nomenclature for Category A Concentric Disc Type Typical Part Nomenclature for Category B Offset Disc Type Typical Offset-type Constructions Disc-to-pipe Clearance for Category A Concentric Disc Type Disc-to-pipe Clearance for Category B Offset Disc Type	11 18 19 20	
Table	s		
1 2 3a 3b 3c D.1	Minimum Seat Pressure-temperature Ratings for Category B Valves	6 7 7	

Butterfly Valves: Double-flanged, Lug- and Wafer-type, and Butt-welding Ends

1 Scope

- **1.1** This standard covers design, materials, face-to-face dimensions, pressure-temperature ratings, and examination, inspection, and test requirements for gray iron, ductile iron, bronze, steel, nickel-based alloy, or special alloy butterfly valves.
- **1.2** The following two categories of butterfly valves are included:
- a) Category A—Manufacturer's rated cold working pressure (CWP) butterfly valves, usually with a concentric disc and seat configuration. Sizes covered are NPS 2 to NPS 60 for valves having ASME class 125 or class 150 flange bolting patterns.
- b) Category B—ASME class and pressure-temperature-rated butterfly valves that have an offset seat and either an eccentric or a concentric disc configuration. Sizes covered are listed below:
 - for lug and wafer, class 150 and 300: NPS 2 to NPS 60;
 - for lug and wafer, class 600: NPS 3 to NPS 60;
 - for double-flanged short and long pattern, class 150, 300, and 600: NPS 3 to NPS 60;
 - for butt-welding ends, class 150, 300 and 600: NPS 3 to 60;

Information to be specified by the purchaser is shown in Annex B.

1.3 Valve configurations include double-flanged, lug- and wafer-type with facings that permit installation between ASME and MSS flanges and butt-welding ends. Configurations conform to the standards and specifications listed in Section 2. Typical valve construction and nomenclature for valve parts are shown in Annex C.

2 Normative References

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any addenda) applies.

API Standard 598, Valve Inspection and Testing

API Standard 607, Fire Test for Quarter-turn Valves and Valves Equipped with Nonmetallic Seats

API Standard 641, Type Testing of Quarter-turn Valves for Fugitive Emissions

ASME B1.1¹, Unified Inch Screw Threads (UN, UNR, and UNJ Thread Forms)

ASME B16.5, Pipe Flanges and Flanged Fittings: NPS 1/2 through NPS 24, Metric/Inch Standard

ASME B16.24, Cast Copper Alloy Pipe Flanges, Flanged Fittings, and Valves: Classes 150, 300, 600, 900, 1500 and 2500

ASME B16.25, Buttwelding Ends

ASME B16.34, Valves—Flanged, Threaded, and Welding End

¹ ASME International, Two Park Avenue, New York, New York 10016-5990, www.asme.org.