

ETSI TS 132 300 V14.0.0 (2017-04)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
Telecommunication management;
Configuration Management (CM);
Name convention for Managed Objects
(3GPP TS 32.300 version 14.0.0 Release 14)**



Reference

RTS/TSGS-0532300ve00

Keywords

GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	5
Introduction	5
1 Scope	7
2 References	7
3 Definitions and abbreviations.....	8
3.1 Definitions	8
3.1.1 Void	8
3.1.2 Void	8
3.1.3 Managed Object and Network Resource	8
3.1.4 Name.....	8
3.1.5 Name space	8
3.1.6 Global Root and Local Root	9
3.1.7 Distinguished Name and Relative Distinguished Name	9
3.2 Abbreviations	9
4 System overview	10
4.1 System context	10
5 Name Convention for Managed Objects	10
6 Representations of Distinguished Name (DN)	11
7 String Representation of DN	12
7.A Overview	12
7.B Allowed character sets.....	12
7.1 Converting DN from ASN.1 to String.....	12
7.1.1 Rule for one-string DN	12
7.1.1.1 Converting RDNSequence	12
7.1.1.2 Converting RelativeDistinguishedName.....	13
7.1.1.3 Converting AttributeTypeAndValue.....	13
7.1.2 Rule for multi-string DN.....	13
7.1.2.1 Converting RDNSequence	13
7.1.2.2 Converting RelativeDistinguishedName	13
7.1.2.3 Converting AttributeTypeAndValue.....	13
7.2 Character syntax	14
7.3 EBNF of DN String Representation	14
7.4 Maximum size of DN string.....	17
8 Examples of DN in string representation	18
9 Usage Scenario.....	19
9.1 DN prefix usage	19
Annex A (normative): Mapping of RDN AttributeType to Strings	20
Annex B (normative): Rule for MO Designers regarding AttributeType interpretation.....	21
Annex C (informative): DN Prefix and Local Distinguished Name (LDN).....	23
Annex D (informative): Interpreting EBNF [13].....	25
Annex E (informative): IOC/MOC name recommendation.....	27

Annex F (informative): **Change history**28
History29

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

CM actions may be requested as part of an implementation programme (e.g. additions and deletions), as part of an optimisation programme (e.g. modifications), and to maintain the overall Quality of Service (QoS). The CM actions are initiated either as single actions on single NEs of the 3G network, or as part of a complex procedure involving actions on many resources/objects in one or several NEs.

Background

Traditionally, multiple name conventions have been used by different vendors' NEs, or even within the same vendor, to name network resources. The following problems have thus arisen:

- Different classes of NE have used different name conventions. Network Management applications, when interfacing with these NEs, have been required to understand multiple name conventions to manage the NEs.
- Network management applications (e.g. Fault Management application), when interfacing with other applications (e.g. Configuration Management application, trouble ticket system) have been required to understand multiple name conventions.
- When a customer purchased multiple classes of NEs from the same or different vendors, the customer was confronted with multiple name conventions.
- Without a name convention, it is difficult to integrate IRP conformant vendors' resource name space (see subclause 3.1.5 for definition of name space) into the customer's Enterprise name space.

Benefits

The benefits of using the subject name convention to name 3G network resources for network management purposes are as follows:

- A resource name is guaranteed to be unambiguous in that it refers to, at most, one network resource. Unambiguous naming of managed network resources is necessary for interoperability among managing applications and systems.

- The resource name syntax is specified such that management applications can be designed with assurance that its name-parsing algorithm needs not be modified in the future. We can derive this benefit only if the subject name convention is widely accepted.

The root and upper portions of the name hierarchy are based on name infrastructure of Domain Name System (DNS) (see IETF RFC 2247 [5]). The subject name convention can naturally fit in DNS and can integrate well with other hierarchical naming systems, such as ITU-T Recommendation X.500 [2].

1 Scope

A more detailed background and introduction of the IRP concept is given in 3GPP TS 32.150 [16].

To perform network management tasks, co-operating applications require identical interpretation of names assigned to network resources under management. Such names are required to be unambiguous as well. The present document recommends one name convention for network resources under management in the IRP context.

To facilitate integration of network management information obtained via multiple IRPs based on different IRP Solution Set technologies, identical network resource name semantics shall be conveyed in all IRPs. The present document specifies one such name convention.

The present document also specifies an IOC/MOC name recommendation (see annex E) in order to avoid potential problems with valid characters in some programming languages.

In this document, the name convention and name recommendation (see annex E) are specified for MO instances whose MO class stereotype is IOC. These specifications are also for MO instances whose MO class stereotype is Support IOC (SupportIOC).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] Void.
- [2] ITU-T Recommendation X.500 (1993): "Information technology - Open Systems Interconnection - The Directory: Overview of concepts, models and services".
- [3] T. Howes, ISBN 1-57870-070-1: "Understanding and Deploying LDAP Directory Services".
- [4] IETF RFC 1737 (1994): "Functional Requirements for Uniform Resource Names".
- [5] IETF RFC 2247 (1998): "Using Domains in LDAP/X.500 Distinguished Names".
- [6] IETF RFC 1035 (1987): "Domain names - implementation and specification".
- [7] IETF RFC 2253 (1997): "Lightweight Directory Access Protocol (v3): UTF-8 String Representation of Distinguished Names".
- [8] 3GPP TS 32.111-2: "Telecommunication management; Fault Management; Part 2: Alarm Integration Reference Point (IRP): Information Service (IS)".
- [9] 3GPP TS 32.622: "Telecommunication management; Configuration Management (CM); Generic network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [10] Void.
- [11] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [12] 3GPP TS 32.102: "Telecommunication management; Architecture".