

BSI Standards Publication

Wind energy generation systems

Part 24: Lightning protection



National foreword

This British Standard is the UK implementation of EN IEC 61400-24:2019. It is identical to IEC 61400-24:2019. It supersedes BS EN 61400-24:2010, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee PEL/88, Wind turbines.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019 Published by BSI Standards Limited 2019

ISBN 978 0 580 96575 3

ICS 27.180

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 September 2019.

Amendments/corrigenda issued since publication

Date Text affected

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN IEC 61400-24

August 2019

ICS 27.180

Supersedes EN 61400-24:2010 and all of its amendments and corrigenda (if any)

English Version

Wind energy generation systems - Part 24: Lightning protection (IEC 61400-24:2019)

Systèmes de génération d'énergie éolienne - Partie 24 : Protection contre la foudre (IEC 61400-24:2019) Windenergieanlagen - Teil 24: Blitzschutz (IEC 61400-24:2019)

This European Standard was approved by CENELEC on 2019-08-07. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

EN IEC 61400-24:2019 (E)

European foreword

The text of document 88/709/FDIS, future edition 2 of IEC 61400-24, prepared by IEC/TC 88 "Wind energy generation systems" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 61400-24:2019.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2020-05-07 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the document have to be withdrawn

This document supersedes EN 61400-24:2010 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 61400-24:2019 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60060-1:2010	NOTE	Harmonized as EN 60060-1:2010 (not modified)
IEC 60071 (series)	NOTE	Harmonized as EN 60071 (series)
IEC 60071-2:2018	NOTE	Harmonized as EN IEC 60071-2:2018 (not modified)
IEC 60099-4	NOTE	Harmonized as EN 60099-4
IEC 60099-5	NOTE	Harmonized as EN IEC 60099-5
IEC 60204-1	NOTE	Harmonized as EN 60204-1
IEC 60204-11	NOTE	Harmonized as EN IEC 60204-11
IEC 60243 (series)	NOTE	Harmonized as EN 60243 (series)
IEC 60243-1	NOTE	Harmonized as EN 60243-1
IEC 60243-3	NOTE	Harmonized as EN 60243-3
IEC 60464-2	NOTE	Harmonized as EN 60464-2
IEC 60587	NOTE	Harmonized as EN 60587
IEC 62561 (series)	NOTE	Harmonized as EN IEC 62561 (series)
IEC 62561-1	NOTE	Harmonized as EN 62561-1
IEC 62793	NOTE	Harmonized as EN IEC 62793
IEC 62858	NOTE	Harmonized as EN 62858

CONTENTS

FC	DREWO	RD	11
1	Scop	e	13
2	Norm	ative references	13
3	Term	s and definitions	15
4	Symb	ools and units	21
5	Abbr	eviated terms	24
6		ning environment for wind turbine	
	6.1	General	
	6.2	Lightning current parameters and lightning protection levels (LPL)	
7	Light	ning exposure assessment	26
	7.1	General	26
	7.2	Assessing the frequency of lightning affecting a single wind turbine or a group of wind turbines	28
	7.2.1	Categorization of lightning events	28
	7.2.2	Estimation of average number of lightning flashes to a single or a group of wind turbines	28
	7.2.3	Estimation of average annual number of lightning flashes near the wind turbine $(N_{\hbox{\scriptsize M}})$	31
	7.2.4	Estimation of average annual number of lightning flashes to the service lines connecting the wind turbines ($N_{\rm L}$)	32
	7.2.5	Estimation of average annual number of lightning flashes near the service lines connecting the wind turbine (N_{\parallel})	32
	7.3	Assessing the risk of damage	33
	7.3.1	Basic equation	33
	7.3.2		34
	7.3.3	Assessment of the risk component due to flashes near the wind turbine (S2)	34
	7.3.4	Assessment of risk components due to flashes to a service line connected to the wind turbine (S3)	35
	7.3.5	Assessment of risk component due to flashes near a service line connected to the wind turbine (S4)	35
8	Light	ning protection of subcomponents	36
	8.1	General	36
	8.1.1	Lightning protection level (LPL)	36
	8.1.2	3 31 ()	
	8.2	Blades	
	8.2.1	General	
	8.2.2	•	
	8.2.3		
	8.2.4	3	
	8.2.5		
	8.3 8.3.1	Nacelle and other structural components	
	8.3.1		
	8.3.3		
	8.3.4	•	
	8.3.5		
	8.3.6		

	8.4 M	echanical drive train and yaw system	44
	8.4.1	General	44
	8.4.2	Bearings	44
	8.4.3	Hydraulic systems	45
	8.4.4	Spark gaps and sliding contacts	46
	8.4.5	Verification	46
	8.5 E	lectrical low-voltage systems and electronic systems and installations	46
	8.5.1	General	46
	8.5.2	Equipotential bonding within the wind turbine	50
	8.5.3	LEMP protection and immunity levels	51
	8.5.4	Shielding and line routing	
	8.5.5	SPD protection	
	8.5.6	Testing methods for system immunity tests	
	8.6 E	lectrical high-voltage (HV) power systems	
9		g of wind turbines	
		eneral	
	9.1.1	Purpose and scope	
	9.1.2	Basic requirements	
	9.1.3	Earth electrode arrangements	
	9.1.4	Earthing system impedance	
		quipotential bonding	
	9.2.1	General	
	9.2.1	Lightning equipotential bonding for metal installations	
		tructural components	
	9.3.1	General	
	9.3.1	Metal tubular type tower	
		Metal reinforced concrete towers	
	9.3.3		
	9.3.4	Lattice tower	
	9.3.5	Systems inside the tower	
	9.3.6	Concrete foundation	
	9.3.7	Rocky area foundation	
	9.3.8	Metal mono-pile foundation	
	9.3.9	Offshore foundation	
		lectrode shape dimensions	
		xecution and maintenance of the earthing system	
10		al safety	
11	Docum	entation of lightning protection system	66
	11.1 G	eneral	66
	11.2 D	ocumentation necessary during assessment for design evaluation	66
	11.2.1	General	66
	11.2.2	General documentation	66
	11.2.3	Documentation for rotor blades	66
	11.2.4	Documentation of mechanical systems	67
	11.2.5	Documentation of electrical and electronic systems	67
	11.2.6	Documentation of earthing and bonding systems	67
	11.2.7	Documentation of nacelle cover, hub and tower lightning protection	
		systems	
		ite-specific information	
	11.4 D	ocumentation to be provided in the manuals for LPS inspections	68

11.5	Manuals	68
12 Inspe	ection of lightning protection system	68
12.1	Scope of inspection	68
12.2	Order of inspections	68
12.2.	1 General	68
12.2.	2 Inspection during production of the wind turbine	69
12.2.		
12.2.	·	
12.2.		
12.3	Maintenance	
	informative) The lightning phenomenon in relation to wind turbines	
A.1	Lightning environment for wind turbines	
A.1.1		
A.1.2		
A. 1.2 A. 1.3		
A. 1.3 A. 1.4	3 3 3	
A. 1.2 A. 1.5	-	
	·	
A.2	Lightning current parameters relevant to the point of strike	
A.3	Leader current without return stroke	
A.4	Lightning electromagnetic impulse, LEMP, effects	
	informative) Lightning exposure assessment	
B.1	General	84
B.2	Methodology to estimate the average annual flashes or strokes to the wind turbines of a wind farm and upward lightning activity in wind turbines	
B.2.1	General	84
B.2.2	Methodology to determine average annual flashes to turbines of a wind farm estimation by increase of the location factor to consider upward lightning from wind turbines	84
B.2.3		
B.3	Explanation of terms	
	Damage and loss	88
B.3.2		
B.3.3		
B.3.4	·	
B.3.5		
B.4	Assessing the probability of damage to the wind turbine	
B.4.1		
B.4.2		
B.4.3		
B.4.4		
B.4.5		
B.4.6	•	
B.4.7		

B.4.8	Probability, $P_{f W}$, that a lightning flash to a service line will cause failure of internal systems	97
B.4.9	Probability, P ₇ , that a lightning flash near an incoming service line will	
	cause failure of internal systems	
B.4.1	, ,	
B.4.1	, e , i	
	Assessing the amount of loss L_X in a wind turbine	
B.5.1	General	
B.5.2	, ,	
-	informative) Protection methods for blades	
	General	
C.1.1	31 1	
C.1.2	3	
	Protection methods	
C.2.1		103
C.2.2	the surface	
C.2.3		
C.2.4	,	105
C.2.5	· · · · · · · · · · · · · · · · · · ·	
C.3	CFRP structural components	
C.4	Particular concerns with conducting components	
C.5	Interception efficiency	
C.6	Dimensioning of lightning protection systems	109
C.7	Blade-to-hub connection	
C.8	WTG blade field exposure	111
C.8.1		
C.8.2	• • • • • • • • • • • • • • • • • • • •	
C.8.3	•	
Annex D (normative) Test specifications	113
D.1	General	113
D.2	High-voltage strike attachment tests	113
D.2.1	Verification of air termination system effectiveness	113
D.2.2	Initial leader attachment test	113
D.2.3	Subsequent stroke attachment test	123
D.3	High-current physical damage tests	127
D.3.1	General	127
D.3.2	Arc entry test	127
D.3.3	Conducted current test	132
	informative) Application of lightning environment and lightning protection Z)	137
E.1	Lightning environment for blades	137
E.1.1	Application	
E.1.2		
E.1.3		
E.2	Definition of lightning protection zones for turbines (not blades)	139
E.2.1	General	139
E.2.2	LPZ 0	140
E.2.3	Other zones	141

E.2.4	Zone boundaries	142
E.2.5	Zone protection requirements	143
	formative) Selection and installation of a coordinated SPD protection in	146
	ocation of SPDs	
	Selection of SPDs	
	nstallation of SPDs	_
	invironmental stresses of SPDs	
	SPD status indication and SPD monitoring in case of an SPD failure	
F.6 S	Selection of SPDs with regard to protection level $(U_{ m p})$ and system level mmunity	
	Selection of SPDs with regard to overvoltages created within wind turbines	
F.8 S	Selection of SPDs with regard to discharge current (I_{n}) and impulse current (I_{n}) and impulse current (I_{n})	
	iniprofile Iformative) Information on bonding and shielding and installation technique	
•	Additional information on bonding	
	Additional information on shielding and installation technique	
	formative) Testing methods for system level immunity tests	
•	, -	
•	ormative) Earth termination system	
	General	
I.1.1	Types of earthing systems	
1.1.2	Construction	
	lectrode shape dimensions	
1.2.1	Type of arrangement	
1.2.2	Frequency dependence on earthing impedance	
	Earthing resistance expressions for different electrode configurations	
Annex J (in	formative) Example of defined measuring points	167
•	formative) Classification of lightning damage based on risk management	
	General	
	ightning damage in blade	
K.2.1	Classification of blade damage due to lightning	
K.2.2	Possible cause of blade damage due to lightning	
K.2.3	Countermeasures against blade damage due to lightning	
	ightning damage to other components	
K.3.1	Classification of damage in other components due to lightning	
K.3.2	Countermeasures against lightning damage to other components	
K.4 T	ypical lightning damage questionnaire	
K.4.1	General	
K.4.2	Sample of questionnaire	173
Annex L (in	formative) Monitoring systems	177
Annex M (ir	nformative) Guidelines for small wind turbines	179
Annex N (in	formative) Guidelines for verification of blade similarity	180
•	Seneral	
	Similarity constraints	
	oformative) Guidelines for validation of numerical analysis methods	
•	General	
	Blade voltage and current distribution	
	ndirect effects analysis	
U.S II	1UII CUI CII CUIS AII AI VOIS	104

Annex P (informative) Testing of rotating components	185
P.1 General	185
P.2 Test specimen	185
P.2.1 Test specimen representing a stationary / quasi stationary bearing	185
P.2.2 Test specimen representing a rotating bearing	
P.3 Test setup	
P.3.1 Test set-up representing a stationary/quasi-stationary bearing	
P.3.2 Test set-up representing a rotating bearing	
P.4 Test procedure	
Annex Q (informative) Earthing systems for wind farms	
Bibliography	
bibliography	130
Figure 1 – Collection area of the wind turbine	30
Figure 2 – Example of collection area for a complete wind farm (A_{DWF}) with 10 wind	
turbines (black points) considering overlapping	31
Figure 3 – Collection area of wind turbine of height $H_{\rm B}$ and another structure of height $H_{\rm D}$ connected by underground cable of length $L_{\rm C}$	33
Figure 4 – Examples of possible SPM (surge protection measures)	49
Figure 5 – Interconnecting two LPZ 1 using SPDs	50
Figure 6 – Interconnecting two LPZ 1 using shielded cables or shielded cable ducts	50
Figure 7 –Magnetic field inside an enclosure due to a long connection cable from enclosure entrance to the SPD	53
Figure 8 –Additional protective measures	
Figure 9 – Examples of placement of HV arresters in two typical main electrical circuits of wind turbines	58
Figure A.1 – Processes involved in the formation of a downward initiated cloud-to-ground flash	74
Figure A.2 – Typical profile of a negative cloud-to-ground flash	
Figure A.3 – Definitions of short stroke parameters (typically $T_2 < 2 \text{ ms}$)	
Figure A.4 – Definitions of long stroke parameters (typically 2 ms $< T_{long} < 1$ s)	
Figure A.5 – Possible components of downward flashes (typical in flat territory and to	70
lower structures)	78
Figure A.6 – Typical profile of a positive cloud-to-ground flash	79
Figure A.7 – Processes involved in the formation of an upward initiated cloud-to-	
ground flash during summer and winter conditions	79
Figure A.8 – Typical profile of a negative upward initiated flash	80
Figure A.9 – Possible components of upward flashes (typical to exposed and/or higher structures)	81
Figure B.1 – Winter lightning world map based on LLS data and weather conditions	86
Figure B.2 – Detailed winter lightning maps based on LLS data and weather conditions	87
Figure B.3 – Ratio <i>h/d</i> description	
Figure C.1 – Types of wind turbine blades	
Figure C.2 – Lightning protection concepts for large modern wind turbine blades	
Figure C.3 – Voltages between lightning current path and sensor wiring due to the	
mutual coupling and the impedance of the current path	
Figure D.1 – Example of initial leader attachment test setup A	115

Figure D.2 – Possible orientations for the initial leader attachment test setup A	116
Figure D.3 – Definition of the blade length axis during strike attachment tests	117
Figure D.4 – Example of the application of angles during the HV test	117
Figure D.5 – Example of leader connection point away from test specimen	118
Figure D.6 – Initial leader attachment test setup B	119
Figure D.7 – Typical switching impulse voltage rise to flashover (100 μ s per division)	121
Figure D.8 – Subsequent stroke attachment test arrangement	124
Figure D.9 – Lightning impulse voltage waveform	125
Figure D.10 – Lightning impulse voltage chopped on the front	125
Figure D.11 – HV electrode positions for the subsequent stroke attachment test	127
Figure D.12 – High-current test arrangement for the arc entry test	129
Figure D.13 – Typical jet diverting test electrodes	130
Figure D.14 – Example of an arrangement for conducted current tests	134
Figure E.1 – Examples of generic blade lightning environment definition	138
Figure E.2 – Rolling sphere method applied on wind turbine	141
Figure E.3 – Mesh with large mesh dimension for nacelle with GFRP cover	142
Figure E.4 – Mesh with small mesh dimension for nacelle with GFRP cover	142
Figure E.5 – Two cabinets both defined as LPZ 2 connected via the shield of a shielded cable	143
Figure E.6 – Example: division of wind turbine into different lightning protection zones	144
Figure E.7 – Example of how to document a surge protection measures (SPM) system by division of the electrical system into protection zones with indication of where circuits cross LPZ boundaries and showing the long cables running between tower	
base and nacelle	
Figure F.1 – Point-to-point installation scheme	
Figure F.2 – Earthing connection installation scheme	
Figure G.1 – Two control cabinets located on different metallic planes inside a nacelle	
Figure G.2 – Magnetic coupling mechanism	
Figure G.3 – Measuring of transfer impedance	
Figure H.1 – Example circuit of a SPD discharge current test under service conditions	
Figure H.2 – Typical test set-up for injection of test current	
Figure H.3 – Example circuit of an induction test for lightning currents	
Figure I.1 – Minimum length (l_1) of each earth electrode according to the class of LPS	
Figure I.2 – Frequency dependence on the impedance to earth	
Figure J.1 – Example of measuring points	167
Figure K.1 – Recommended countermeasures schemes according to the incident classification	171
Figure K.2 – Blade outlines for marking locations of damage	
Figure N.1 – Definitions of blade aerofoil nomenclature	182
Figure O.1 – Example geometry for blade voltage and current distribution simulations	183
Figure O.2 – Example geometry for nacelle indirect effects simulations	
Figure P.1 – Possible test setup for a pitch bearing	
	185
Figure P.2 – Possible injection of test current into a pitch bearing	185 186
	185 186

Table 1 – Maximum values of lightning parameters according to LPL (adapted from IEC 62305-1)	25
Table 2 – Minimum values of lightning parameters and related rolling sphere radius corresponding to LPL (adapted from IEC 62305-1)	26
Table 3 – Collection areas A_{L} and A_{I} of service line depending on whether aerial or buried	33
Table 4 – Parameters relevant to the assessment of risk components for wind turbine (corresponds to IEC 62305-2)	36
Table 5 – Verification of bearing and bearing protection design concepts	45
Table 6 – LPS General inspection intervals	70
Table A.1 – Cloud-to-ground lightning current parameters	77
Table A.2 – Upward initiated lightning current parameters	81
Table A.3 – Summary of the lightning threat parameters to be considered in the calculation of the test values for the different LPS components and for the different LPL	
Table B.1 – Recommended values of individual location factors	85
Table B.2 – Range of upward lightning activity as a function of winter lightning activity for wind farm located in flat terrain	88
Table B.3 – Values of probability, P_A , that a lightning flash to a wind turbine will cause shock to human beings owing to dangerous touch and step voltages (corresponds to IEC 62305-2)	93
Table B.4 – Values of reduction factor $r_{\rm t}$ as a function of the type of surface of soil or floor (corresponds to IEC 62305-2)	93
Table B.5 – Values of factor P_0 according to the position of a person in the exposed area (corresponds to IEC 62305-2)	94
Table B.6 – Values of probability, P_{LPS} , depending on the protection measures to protect the exposed areas of the wind turbine against direst lightning flash and to reduce physical damage (corresponds to IEC 62305-2)	94
Table B.7 – Values of probability P_S that a flash to a wind turbine will cause dangerous sparking (corresponds to IEC 62305-2)	95
Table B.8 – Values of reduction factor $r_{\rm p}$ as a function of provisions taken to reduce the consequences of fire (corresponds to IEC 62305-2)	95
Table B.9 – Values of reduction factor $r_{\rm f}$ as a function of risk of fire of the wind turbine (corresponds to IEC 62305-2)	95
Table B.10 – Values of probability P_{L1} depending on the line type and the impulse withstand voltage U_{W} of the equipment (corresponds to IEC 62305-2)	98
Table B.11 – Loss values for each zone (corresponds to IEC 62305-2)	99
Table B.12 – Typical mean values of L_T , L_D , L_F and L_O (corresponds to IEC 62305-2)	
Table C.1 – Material, configuration and minimum nominal cross-sectional area of airtermination conductors, air-termination rods, earth lead-in rods and down conductors ^a (corresponds to IEC 62305-3)	. 109
Table C.2 – Physical characteristics of typical materials used in lightning protection systems (corresponds to IEC 62305-1)	. 110
Table C.3 – Temperature rise [K] for different conductors as a function of W/R (corresponds to IEC 62305-1)	. 111
Table C.4 – Range of distribution of direct strikes from field campaigns collecting data on attachment distribution vs. the distance from the tip of wind turbine blades, 39 m to 45 m blades with and without CFRP	. 112
	131

Table D.2 – Test current parameters for winter lightning exposure testing (duration	
maximum 1 s)	
Table D.3 – Test current parameters corresponding to LPL I	135
Table D.4 – Test current parameters corresponding to LPL I (for flexible paths)	135
Table D.5 – Test current parameters for winter lightning exposure testing (duration maximum 1 s)	136
Table E.1 – Blade area definition for the example in concept A	139
Table E.2 – Blade area definition for the example in concept B	139
Table E.3 – Definition of lightning protection zones according to IEC 62305-1	140
Table F.1 – Discharge and impulse current levels for TN systems given in IEC 60364-5-53	149
Table F.2 – Example of increased discharge and impulse current levels for TN systems	149
Table I.1 – Impulse efficiency of several ground rod arrangements relative to a 12 m vertical ground rod (100 %)	164
Table I.2 – Symbols used in Tables I.3 to I.6	164
Table I.3 – Formulae for different earthing electrode configurations	165
Table I.4 – Formulae for buried ring electrode combined with vertical rods	165
Table I.5 – Formulae for buried ring electrode combined with radial electrodes	166
Table I.6 – Formulae for buried straight horizontal electrode combined with vertical rods	166
Table J.1 – Measuring points and resistances to be recorded	168
Table K.1 – Classification of blade damage due to lightning	170
Table K.2 – Matrix of blade damages due to lightning, taking account of risk management	172
Table K.3 – Classification of damage to other components due to lightning	
Table L.1 – Considerations relevant for wide area lightning detection systems	177
Table L.2 – Considerations relevant for local active lightning detection systems	178
Table L.3 – Considerations relevant for local passive lightning detection systems	
Table N.1 – Items to be checked and verified when evaluating similarity	181
Table P.1 – Test sequence for high current testing of rotating components	188

INTERNATIONAL ELECTROTECHNICAL COMMISSION

WIND ENERGY GENERATION SYSTEMS -

Part 24: Lightning protection

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61400-24 has been prepared by IEC technical committee 88: Wind energy generation systems.

This second edition cancels and replaces the first edition, published in 2010. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) it is restructured with a main normative part, while informative information is placed in annexes.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
88/709/FDIS	88/713/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61400 series, published under the general title *Wind energy generation systems*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

WIND ENERGY GENERATION SYSTEMS -

Part 24: Lightning protection

1 Scope

This part of IEC 61400 applies to lightning protection of wind turbine generators and wind power systems. Refer to Annex M guidelines for small wind turbines.

This document defines the lightning environment for wind turbines and risk assessment for wind turbines in that environment. It defines requirements for protection of blades, other structural components and electrical and control systems against both direct and indirect effects of lightning. Test methods to validate compliance are included.

Guidance on the use of applicable lightning protection, industrial electrical and EMC standards including earthing is provided.

Guidance regarding personal safety is provided.

Guidelines for damage statistics and reporting are provided.

Normative references are made to generic standards for lightning protection, low-voltage systems and high-voltage systems for machinery and installations and electromagnetic compatibility (EMC).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60364-4-44, Low-voltage electrical installations – Part 4-44: Protection for safety – Protection against voltage disturbances and electromagnetic disturbances

IEC 60364-5-53, Electrical installations of buildings – Part 5-53: Selection and erection of electrical equipment – Isolation, switching and control

IEC 60364-5-54, Low-voltage electrical installations – Part 5-54: Selection and erection of electrical equipment – Earthing arrangements and protective conductors

IEC 60364-6, Low-voltage electrical installations – Part 6: Verification

IEC TS 60479-1, Effects of current on human beings and livestock - Part 1: General aspects

IEC TR 60479-4, Effects of current on human beings and livestock – Part 4: Effects of lightning strokes

IEC 60664-1, Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests

IEC 61000 (all parts), Electromagnetic compatibility (EMC)