

ASME B29.15M-1997
(Revision of ASME B29.15M-1995)

STEEL ROLLER TYPE CONVEYOR CHAINS, ATTACHMENTS, AND SPROCKET TEETH

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Intentionally left blank



The American Society of
Mechanical Engineers

A N A M E R I C A N N A T I O N A L S T A N D A R D

STEEL ROLLER TYPE CONVEYOR CHAINS, ATTACHMENTS, AND SPROCKET TEETH

ASME B29.15M-1997
(Revision of ASME B29.15M-1995)

Date of Issuance: October 31, 1997

This Standard will be revised when the Society approves the issuance of a new edition. There will be no addenda or written interpretations of the requirements of this Standard issued to this edition.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Consensus Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment which provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable Letters Patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations issued in accordance with governing ASME procedures and policies which preclude the issuance of interpretations by individual volunteers.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
345 East 47th Street, New York, NY 10017

Copyright © 1997 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All Rights Reserved
Printed in U.S.A.

FOREWORD

(This Foreword is not part of ASME B29.15M-1997.)

Chains of the type covered by this Standard were introduced late in the nineteenth century. These chains met with considerable success on material conveyors and elevators. Manufacturers developed and marketed many sizes and types in the following years.

In the 1920s, a working group from the producers of these chains was formed to standardize them. In 1972, a subcommittee of American National Standards Committee B29 was appointed with American Chain Association members from the engineering steel chain industry to expand and update the existing standards.

The 1997 revision of this Standard incorporates the new definition of Minimum Ultimate Tensile Strength (M.U.T.S.), as well as updated sprocket symbols.

This revision was approved by the American National Standards Institute on April 17, 1997.

Intentionally left blank

ASME STANDARDS COMMITTEE B29 Chains, Attachments, and Sprockets for Power Transmission and Conveying

(The following is the roster of the Committee at the time of approval of this Standard.)

OFFICERS

C. B. Norberg, *Chair*
R. H. Uttke, *Vice Chair*
J. L. Wright, *Vice Chair*
K. M. Padilla, *Secretary*

COMMITTEE PERSONNEL

E. B. Beardslee, Beardslee Transmission Equipment Co., Long Island City, New York
L. E. Hampel, Allied-Locke Industries, Inc., Dixon, Illinois
J. Kane, U.S. Tsubaki Inc., Holyoke, Massachusetts
C. McDonald, Jervis B. Webb Co., New Hudson, Michigan
D. Moore, Jeffrey Chain Co., Morristown, Tennessee
C. B. Norberg, Consultant, Ithaca, New York
V. D. Petershack, Hitachi Maxco Ltd., Oconomowoc, Wisconsin
R. A. Reinfried, Conveyor Equipment Manufacturers Association, Manassas, Virginia
S. Rhoad, Webster Industries, Inc., Tiffin, Ohio
K. J. Smith, Drives, Inc., Fulton, Illinois
R. H. Uttke, Rexnord Corp., Milwaukee, Wisconsin
J. L. Wright, Consultant, Indianapolis, Indiana
D. N. Zwiep, Worcester Polytechnic Institute, Worcester, Massachusetts

Intentionally left blank

CONTENTS

Foreword	iii
Standards Committee Roster	v
1 Definitions	1
2 General Chain Proportions and Designations	1
3 Dimensions of Chain Links	1
4 Attachment Dimensions	1
5 Sprocket Tooth Form	1
Figures	
1 Steel Roller Type Conveyor Chains	2
2 Dimensions of Chain Links	4
3 Sprocket Tooth Form	5
Tables	
1 General Chain Dimensions, M.U.T.S., Strand Length, and Measuring Load	3
2 Maximum and Minimum Controlling Dimensions for Interchangeable Chain Links	5
3 Chain Clearance Dimensions	6
4 A-1 Attachments	7
5 A-2 Attachments	8
6 A-42 Attachments	9
7 K-1 Attachments	10
8 K-2 Attachments	11
9 Sprockets — Maximum Eccentricity and Face Runout Tolerances	12
10 Sprocket Factors	12

Intentionally left blank

STEEL ROLLER TYPE CONVEYOR CHAINS, ATTACHMENTS, AND SPROCKET TEETH

1 DEFINITIONS

M.U.T.S.: Minimum Ultimate Tensile Strength, the minimum force at which an unused, undamaged chain could fail when subjected to a single tensile loading test.

steel roller type conveyor chains: a series of roller links having steel bushings with rollers to contact the sprocket teeth, alternating with links comprised of sidebars and pins, which articulate in the steel bushings of the roller link (see Fig. 1).

2 GENERAL CHAIN PROPORTIONS AND DESIGNATIONS

2.1 M.U.T.S.

(a) M.U.T.S. is not a working load. The M.U.T.S. greatly exceeds the maximum force that may be applied to the chain.

(b) Test Procedure: A tensile force is slowly applied, in a uniaxial direction, to the ends of the chain sample.

(c) The tensile test is a destructive test. Even though the chain may not visibly fail when subjected to the Minimum Ultimate Tensile Force, it will have been damaged and will be unfit for service.

Pins and bushings are fixed in the sidebar pitch holes by either press fits and/or mechanical locks, such as flats, to prevent rotation of the pins and bushings in the sidebar pitch holes.

2.2 Measuring Load

The measuring load in pounds or newtons, listed in Table 1, is the load under which a dry or lightly lubricated chain should be measured for length.

2.3 Strand Length Tolerance

New chains under measuring load may be over the theoretical length up to 0.38 in. in 120 in. (9.7 mm in 3048 mm), but must not be under the theoretical length. Maximum and minimum strand lengths for each chain are listed in Table 1.

3 DIMENSIONS OF CHAIN LINKS

To assure interchangeability of links as produced by the different makers of chain, standard maximum and minimum dimensions are listed in Tables 2 and 3. They are not actual dimensions used in manufacturing, but limiting dimensions, maximum or minimum, required to assure the desired interchangeability. (The metric equivalent dimensions are for reference only.) Dimensions are shown in Fig. 2, where

B = inside diameter of bushing

D = pin diameter

F = overall chain height

H = roller diameter

J = pin head to centerline

K = pin end to centerline

P = assembled chain pitch (this is a theoretical reference dimension used for basic calculations)

T = sidebar thickness

U = sidebar height

V = sidebar end clearance radius

W = inside width of roller link

X = outside width of roller link

Z = width between outer sidebars

4 ATTACHMENT DIMENSIONS

See Tables 4, 5, 6, 7, and 8 for various attachment type dimensions.

5 SPROCKET TOOTH FORM

5.1 Nomenclature

Figure 3 and other parts of this Standard utilize the following nomenclature (see also Tables 9 and 10):

C_b = undersize compensation (typically 0.06 in., 1.5 mm)

C_c = chain clearance circle

C_{cf} = chain clearance circle factor (see Table 10)

C_p = pitch line clearance

D_b = bottom diameter