

INTERNATIONAL STANDARD

IEC 62217

First edition
2005-10

Polymeric insulators for indoor and outdoor use with a nominal voltage >1 000 V – General definitions, test methods and acceptance criteria

© IEC 2005 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembe, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

V

For price, see current catalogue

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope and object.....	6
2 Normative references	6
3 Terms and definitions	7
4 Identification.....	9
5 Environmental conditions.....	9
6 Information on transport, storage and installation	10
7 Classification of tests	10
7.1 Design tests	10
7.2 Type tests	10
7.3 Sample tests	10
7.4 Routine tests	11
8 General requirements for insulator test specimens	11
9 Design tests	11
9.1 General	11
9.2 Tests on interfaces and connections of end fittings.....	11
9.3 Tests on shed and housing material	14
9.4 Tests on the core material	17
Annex A (normative) Wheel test.....	22
Annex B (normative) Test at multiple stresses	24
Annex C (informative) Difference between the tracking and erosion and accelerated ageing tests on polymeric insulators	30
Annex D (informative) Recommended application of tests.....	31
Annex E (informative) Explanation of the concept of classes for the design tests.....	32
Bibliography.....	33
Figure 1 – Example of boiling container for the water diffusion test.....	19
Figure 2 – Examples of test specimen for core material	20
Figure 3 – Electrodes for the voltage test.....	21
Figure 4 – Voltage test circuit	21
Figure A.1 – Test arrangement of the tracking wheel test.....	23
Figure B.1 — Typical layout of the test specimens in the chamber and main dimensions of the chamber	24
Figure B.2 – Multiple stress cycle	27
Figure B.3 – Typical layout of the rain and salt fog spray systems and the xenon lamp.....	28
Figure B.4 – Spectrum of xenon arc lamp and solar spectrum	28
Figure B.5 – Reference porcelain insulator	29
Table 1 – Normal environmental conditions.....	9
Table 2 – Initial NaCl content of the water as a function of the specimen dimensions.....	16

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**POLYMERIC INSULATORS FOR INDOOR AND OUTDOOR USE
WITH A NOMINAL VOLTAGE >1 000 V –
GENERAL DEFINITIONS, TEST METHODS
AND ACCEPTANCE CRITERIA**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62217 has been prepared by IEC technical committee 36: Insulators.

The text of this standard is based on the following documents:

FDIS	Report on voting
36/244/FDIS	36/245/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

Polymeric insulators consist either of one insulating material (resin insulators) or two or several insulating materials (composite insulators). The insulating materials are generally cross-linked organic materials synthesized from carbon or silicon chemistry and form the insulating body. Insulating materials can be composed from organic materials containing various inorganic and organic ingredients, such as fillers and extenders. End fittings are often used at the ends of the insulating body to transmit mechanical loads. Despite these common features, the materials used and the construction details employed by different manufacturers may be widely different.

Some tests have been grouped together as "design tests", to be performed only once for insulators of the same design. The design tests are intended to eliminate insulator designs, materials or manufacturing technologies which are not suitable for high-voltage applications. The influence of time on the electrical properties of the complete polymeric insulator and its components (core material, housing, interfaces, etc.) has been considered in specifying the design tests in order to ensure a satisfactory life-time under normal operating and environmental conditions.

Pollution tests, according to IEC 60507 or IEC 61245, are not included in this International Standard, their applicability to composite insulators not having been proven. The results of such pollution tests performed on insulators made of polymeric materials do not correlate with experience obtained from service. Specific pollution tests for polymeric insulators are still under consideration.

The tracking and erosion tests given in this standard are considered as screening tests intended to reject materials or designs which are inadequate. These tests are not intended to predict long-term performance for insulator designs under cumulative service stresses. For more information, see Annex C.

Composite insulators are used in both a.c. and d.c. applications. In spite of this fact a specific tracking and erosion test procedure for d.c. applications as a design test has not yet been defined and accepted. The 1 000 h a.c. tracking and erosion test described in this standard is used to establish a minimum requirement for the tracking resistance of the housing material.

IEC Guide 111 has been followed during preparation of this standard wherever possible.

POLYMERIC INSULATORS FOR INDOOR AND OUTDOOR USE WITH A NOMINAL VOLTAGE >1 000 V – GENERAL DEFINITIONS, TEST METHODS AND ACCEPTANCE CRITERIA

1 Scope and object

This International Standard is applicable to polymeric insulators whose insulating body consists of one or various organic materials. Polymeric insulators covered by this standard include both solid core and hollow insulators. They are intended for use on overhead lines and in indoor and outdoor equipment with a rated voltage greater than 1 000 V.

The object of this standard is

- to define the common terms used for polymeric insulators,
- to prescribe common test methods for design tests on polymeric insulators,
- to prescribe acceptance or failure criteria, if applicable,
- to give recommendations for polymeric insulator test standards or product standards, complemented by specific requirements as needed.

These tests, criteria and recommendations are intended to ensure a satisfactory life-time under normal operating and environmental conditions (see Clause 5).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60060-1, *High-voltage test techniques – Part 1: General definitions and test requirements*

IEC 60068-2-11, *Basic environmental testing procedures – Part 2: Tests, Test KA: Salt mist*

IEC 60507, *Artificial pollution tests on high-voltage insulators to be used on a.c. systems*

IEC 60695-11-10, *Fire hazard testing – Part 11-10: Test flames – 50 W horizontal and vertical flame test methods*

IEC 60721-1, *Classification of environmental conditions – Part 1: Environmental parameters and their severities*

IEC 60815, *Guide for the selection of insulators in respect of polluted conditions*

IEC Guide 111, *Electrical high-voltage equipment in high-voltage substations – Common recommendations for product standards*

ISO 868, *Plastics and ebonite – Determination of indentation hardness by means of a durometer (Shore hardness)*

ISO 4287, *Geometrical Product Specifications (GPS) – Surface texture: Profile method – Terms, definitions and surface texture parameters*

ISO 4892-1, *Plastics – Methods of exposure to laboratory light sources – Part 1: General Guidance*

ISO 4892-2, *Plastics – Methods of exposure to laboratory light sources – Part 2: Xenon-arc sources*

ISO 4892-3, *Plastics – Methods of exposure to laboratory light sources – Part 3: Fluorescent UV lamps*