# **Burners for Fired Heaters in General Refinery Services**

API RECOMMENDED PRACTICE 535 THIRD EDITION, MAY 2014

REAFFIRMED, FEBRUARY 2024



## **Special Notes**

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Users of this Standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, "shall" denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, "should" denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Washington, DC 20001, standards@api.org.

# Contents

		Page
1	Scope	1
2	Normative References	1
3	Terms and Definitions	1
4 4.1 4.2 4.3	Mechanical Components for Burners	9 9
5 5.1 5.2 5.3	Environmental Considerations  General  Noise  Flue Gas Emissions	22
6 6.1 6.2 6.3 6.4 6.5 6.6	Burner Selection General Draft. Flame Stability Design Excess Air Combustion Air Preheat Turbine Exhaust Gas Combustion Air Adjustment.	26 28 28 29
7 7.1 7.2	Gas Firing	30
8 8.1 8.2 8.3 8.4 8.5 8.6 8.7	Liquid Fuel Firing.  Types of Fuel Oil  Atomization  Fuel Physical Properties.  Liquid Fuel Turndown  Design Excess Air Recommendations  Flame Characteristics  Burner Heat Release  Combination Firing	33 34 36 39 39 39
9 9.1 9.2 9.3 9.4	Low NOx Burners  General  NOx Formation Chemistry  Approximate Method to Convert NOx Measurement in ppmvd to lb/MBtu (HHV)  Low NOx Burner Development	40 40 40 41
9.5 9.6 9.7 9.8 9.9	Staged Air Burners	43 44 45

# **Contents**

		Page
9.10	Fuel Treatment	49
9.11	Retrofit Considerations	49
10	Burner Operation	52
	General	
10.2	Excess Air Controls	52
11	Maintenance	56
11.1	Shipping	56
	Burner Parts Inspection	
	Installation and Initial Setup	
	Post-installation Checkout	
11.5		
12	Testing	
	General	
	Test Requirements	
	Test Fuels	
	Pilot and Igniters	
	Main Burner Test	
	Test Instrumentation	
12.8	Measurements	. 66
13	Troubleshooting	67
-	Burner Plugging.	
	Troubleshooting Gas Fired Low NOx Burners	
	Burner Operation Troubleshooting Table	
14	Considerations for Safe Operation	70
	General	
	Flooding	
14.3	Afterburning	75
	Insufficient Draft	
	Fuel Leak in Burner Riser	
	Liquid in Fuel Gas Line to Burners	
	Debris in Fuel Gas Lines	
	Oil Atomization Issues	
Ann	ex A (informative) Burner Datasheets	77
Bibli	iography	84
Figu	ires	
1	Raw Gas Burner	. 10
2	Premix Gas Burner	. 11
3	Radiant Wall Burner	
4	Combination Oil and Gas Burner	
5	Low NO <sub>v</sub> Staged Air Combination Oil and Gas Burner	14

# **Contents**

		Page
6	Low NO <sub>x</sub> Staged Fuel Gas Burner	15
7	Effect of Excess Air on NO <sub>x</sub> Emissions	23
8	Effect of Combustion Air Temperature on NO <sub>x</sub> Emissions	23
9	Effect of the Firebox Temperature on NO <sub>x</sub> Production	
10	Effect of Hydrogen Content of Fuel Gas on NO <sub>x</sub> Emission	
11	Effect of Fuel Nitrogen Content on NO <sub>x</sub> Emission	
12	Inside Mix Atomizer	
13	Port Mix or Steam Assist Atomizer	
14	Approximate Conversion Factor from Btu × 106/hr to ppmv (3 % O <sub>2</sub> , Dry Basis), Based on	
	Typical Refinery Fuel Gas	41
15	Staged Air Burner (Typical)	
16	Staged Fuel Burner (Typical)	44
17	Example of One Type of Internal Flue Gas Recirculation Burner	45
18	Burner-to-furnace Interaction	47
19	Natural Draft Heater Adjustment Flow Chart	53
20	Typical Draft Profile in a Natural Draft Heater	55
21	Typical Burner Test Setup	68
Tab	les	
1	Clarification Table Comparing Definitions in API 560 and API 535	9
2	Air Register Characteristic	
3	Fuel Gas Burner Components	
4	Fuel Oil Burner Components	
5	Burning Housing	
6	Burner Tile	
7	Effects of Reduced Excess Air on Burner Emissions.	
8	Typical Excess Air on Raw Gas Burners	
9	Typical Excess Air on Premix Burners	
10	Recommended Viscosity for Typical Fuel Oil Atomizers	
11	Typical Turndown of Liquid Fuel Atomizers	
12	Typical Excess Air for Liquid Fuels	
13	Typical NO <sub>x</sub> Emissions for Gas Firing	
14	Typical NO <sub>x</sub> Emissions for Oil Firing	
15	Optimum Excess Air Levels	
16	Minimum Recommended Test Procedure to Verify Burner Operating Envelope and Emissions	
. •	for Burners	64
17	Pilot Testing Procedure (Optional)	
18	Gas Burners	
19	Additional Considerations for Oil Burners	
20	Additional Considerations for Low NO. Burners	

# Burners for Fired Heaters in General Refinery Services

## 1 Scope

This recommended practice (RP) provides guidelines for the selection and/or evaluation of burners installed in fired heaters in general refinery services. Details of fired heater and related equipment designs are considered only where they interact with the burner selection. This RP does not provide rules for design but indicates areas that need attention. It offers information and descriptions of burner types available to the designer/user for purposes of selecting the appropriate burner for a given application.

The burner types discussed are those currently in industry use. It is not intended to imply that other burner types are not available or recommended. Many of the individual features described in these guidelines will be applicable to most burner types.

In addition to specification of burners, this RP has been updated to include practical guidelines for troubleshooting in service burners as well as including considerations for safe operation.

## 2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies. Changes in referenced standards, codes, and specifications shall be mutually agreed to by the owner and the vendor.

API Standard 560, Fired Heaters for General Refinery Services

## 3 Terms and Definitions

For the purposes of this document, the following definitions apply.

#### 3.1

## adiabatic flame temperature

Temperature that results from a complete combustion process without any heat transfer or changes in kinetic or potential energy.

#### 3.2

#### aerosols

A suspension of fine solid or liquid particles in gas (smoke, fog, and mist are aerosols).

#### 3.3

#### air/fuel ratio

The ratio of the combustion air flow rate to the fuel flow rate. This may either be in mass or volume units and needs to be specified.

#### 3.4

## air register

That part of a burner that can admit combustion air through openings around the burner assembly.

#### 3.5

#### atomization

The breaking of a liquid into tiny droplets to improve fuel—air mixing, thereby improving combustion efficiency. Steam, air, and fuel gas can be used as atomizing media. Steam is the most common in the refining industry. Atomization may also be accomplished by mechanical means.