BS EN 50585:2014



BSI Standards Publication

Communications protocol to transport satellite delivered signals over IP networks



BS EN 50585:2014 BRITISH STANDARD

National foreword

This British Standard is the UK implementation of EN 50585:2014.

The UK participation in its preparation was entrusted to Technical Committee EPL/100/4, Cable distribution equipment and systems.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014. Published by BSI Standards Limited 2014

ISBN 978 0 580 82994 9

ICS 33.170

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 June 2014.

Amendments issued since publication

Date Text affected

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 50585

May 2014

ICS 33.170

English Version

Communications protocol to transport satellite delivered signals over IP networks

Protocole de communication pour le transport des signaux transmis par satellite sur les réseaux IP

Kommmunikationsprotokoll zum Transport von Satellitensignalen über IP-Netze

This European Standard was approved by CENELEC on 2014-03-24. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents		
Forewo	ord	5
Introdu	ıction	6
1	Scope	7
2	Normative references	
3	Terms, definitions and abbreviations	
3.1	Terms and definitions	
3.2	Abbreviations	
4	Basic description of SAT>IP system	
4 4.1	SAT>IP concept	
4.1	•	
	Network topology	
4.3	Client functionality	
4.4	Specification compliance	
4.5	Usage scenarios	
5	Protocol specification	
5.1	General	11
5.2	UPnP addressing	13
5.2.1	General	
5.2.2	DHCP addressing	
5.2.3	Auto-IP addressing	
5.3	UPnP Discovery	
5.3.1	General	
5.3.2 5.3.3	Simple service description protocol SSDP	
5.3.4	DEVICE ID negotiation	
5.3.5	Client Search Requests	
5.4	UPnP Description	
5.4.1	General	
5.4.2	XML Device Description	
5.5	RTSP Control	26
5.5.1	General	. 26
5.5.2	Real time streaming protocol RTSP	
5.5.3	Setting up a new session	
5.5.4	Starting the playout of a media stream (PLAY)	
5.5.5	Maintaining a session (OPTIONS)	
5.5.6 5.5.7	Modifying a media stream	
5.5.8	Listing available media streams (DESCRIBE)	
5.5.9	Closing the session and stopping the playout (<i>TEARDOWN</i>)	40
5.5.10	RTSP Methods	41
5.5.11	Uniform Resource Identifyer (URI)	
5.5.12	Query Syntax	
5.5.13 5.5.14	Example of RTSP sequence diagram	
5.5.15	Status Code Definitions	
	RTCP Announcements	
5.5.17	HTTP based requests	58

5.6	Media Transport	58
5.6.1 5.6.2	RTP TransportHTTP Streaming	
5.7	Media Formats	59
6	Dynamic versus Static Server Operation	59
6.1	Dynamic Operation (default)	59
6.2	Static Operation	59
6.3	Mixed Operation	60
Annex	A (informative) Usage scenarios	61
A .1	IP Adapter / IP Multiswitch	61
A.2	IP LNB	61
A.3	Master STB	61
A.4	Universal Service Gateway	62
A.5	IP based SMATV / Multi-Dwelling Units	62
Annex	B (informative) Client Implementation Guidelines	64
B.1	General	64
B.2	RTSP Clients	64
B.2.1	Definition	64
B.2.2	Client Setup and Configuration Settings	
B.2.3 B.2.4	Service Discovery	
B.3	IGMPv3 Clients	
B.3.1	Definition	
B.3.1	Client Setup and Configuration Settings	
Annex	C (informative) Example of SAT>IP Message Exchanges	
C.1	Example 1: Unicast Session Setup (no front-end selected) plus three additional channel	
	changes	
C.2	Example 2: Multicast Session Setup with front-end selection and destination address/port	
	D (informative) Support for DVB-T/-T2 (optional)	
D.1	General	
D.2	Implementation	74
Annex	E (informative) SAT>IP trademark and certification	76
E.1	Trademark	76
E.2	Artwork	
E.3	Certification	76
Bibliog	raphy	77
Figures	S	
Figure '	1 — Basic principle of the SAT>IP system	7
Figure 2	2 — Different types of live media servers	11
Figure 3	3 — SAT>IP protocol stack	12
Figure 4	4 — Comparison between SAT>IP and DLNA	12
Figure !	5 — NOTIFY message timing	14
Figure 6	6 — DEVICE ID allocation timing	17
Figure 8	8 — RTSP Control Example	26
	9 — Client with two RTSP sessions on the same SAT>IP server carried in different concur	
TCP co	nnections	27

Figure 10 — Client with two RTSP sessions on the same SAT>IP server carried in one TCP connection given time	
Figure 11 — Stream owner setting up a session and defining the transport	
Figure 12 — Non-stream owner joining an already existing multicast stream and defining the transport	
Figure 13 — Non-stream owner joining an already existing unicast stream and defining the transport	31
Figure 14 — Server Stream Output State Machine	35
Figure 15 — RTSP State Machine	42
Figure 16 — Operation of SAT>IP in the presence of multiple satellite positions	46
Figure 17 — Server internal source and frontend selection matrix	46
Figure 18 — Media stream object definition	47
Figure 19 — Example of a sequence diagram for RTSP operation	48
Figure 20 — Example of SAT>IP multicast network diagram	49
Figure 21 — General membership query message timing	49
Figure 22 — Group specific query timing	51
Figure 23 — Transport stream IP encapsulation	59
Figure 24 — Example of SAT>IP system using static server operation	60
Figure A.1 — IP Multiswitch application	61
Figure A.2 — SAT>IP conversion inside an IP-LNB	
Figure A.3 — Master-Slave application	62
Figure A.4 — Universial Service Gateway application	62
Figure A.5 — IP based SMATV application	63
Figure B.1 — Example of auto-configuration set-up	66
Figure F 1	76

Foreword

This document (EN 50585:2014) has been prepared by CLC/TC 209 "Cable networks for television signals, sound signals and interactive services".

The following dates are fixed:

•	latest date by which this document has to be implemented at national level by publication of an identical national standard or by	(dop)	2015-03-24
•	endorsement latest date by which the national standards conflicting with this document have to be withdrawn	(dow)	2017-03-24

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. [CEN / CENELEC / CEN and CENELEC] shall not be held responsible for identifying any or all such patent rights.

Introduction

This standard describes a new communication protocol for the distribution of satellite signals onto IP networks. It effectively "translates" TV signals, received from satellites in the DVB-S and DVB-S2 formats and supplied in the first intermediate frequency range (1st IF range), into signals for use on internet-based devices in the IP world. This technology enables the reception of satellite TV on devices that do not have an integrated satellite receiver. Satellite signals can thus be transported via every IP infrastructure with or without cable.

This way, the entire satellite household can be provided with TV and sound radio programmes on tablets, PCs, laptops, smart phones, connected TVs, game consoles and media players.

This technology concept is commonly referred to as SAT>IP 1).

¹⁾ SAT>IP is a short-term which covers the complete system for the transposition of SAT-IF signals to IP-based signals. This term is used in a widespread manner for marking software and hardware components used in such systems. More details are given in informative Annex E.

1 Scope

This European Standard describes the SAT>IP communication protocol. It enables a SAT>IP server to forward satellite delivered signals to SAT>IP clients over IP networks. The typical use case would be the transport of television programs that were received from the satellite by the SAT>IP server to the SAT>IP client via the IP network. SAT>IP specifies a control protocol as well as the media transport (Figure 1).



Figure 1 — Basic principle of the SAT>IP system

SAT>IP is **not** a device specification.

The SAT>IP protocol distinguishes between SAT>IP clients and SAT>IP servers.

SAT>IP Clients

SAT>IP clients may reside in set-top boxes equipped with an IP interface or may be implemented as software applications running on programmable hardware such as Tablets, PCs, Smartphones, Connected Televisions.

SAT>IP Servers

SAT>IP servers may take various forms ranging from large MDU headends servicing whole buildings or communities to in-home IP multiswitches to simple IP adapters for a set-top box to, ultimately, IP LNBs.

Actual devices may be clients or servers or both depending on their feature set.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 29341-1-1, Information technology — UPnP Device Architecture — Part 1.1: UPnP Device Architecture Version 1.1

ETSI TS 101 154 V1.9.1, Digital Video Broadcasting (DVB); Specification for the use of Video and Audio Coding in Broadcasting Applications based on the MPEG-2 Transport Stream

RFC 2113 – IP Router Alert Option (Internet Engineering Task Force (IETF))

RFC 2131 – DHCP (Dynamic Host Configuration Protocol) (Internet Engineering Task Force (IETF))

RFC 2250 – RTP Payload Format for MPEG1/MPEG2 Video (Internet Engineering Task Force (IETF))

RFC 2279 – UTF-8, a transformation format of ISO 10646 (Internet Engineering Task Force (IETF))

RFC 2326 – Real Time Streaming Protocol (RTSP) (Internet Engineering Task Force (IETF))

RFC 3376 - Internet Group Management Protocol, Version 3 (Internet Engineering Task Force (IETF))

RFC 3550 - RTP: A Transport Protocol for Real-Time Applications (Internet Engineering Task Force (IETF))

RFC 4566 - SDP: Session Description Protocol (Internet Engineering Task Force (IETF))

draft-cai-ssdp-v1-03 - Simple Service Discovery Protocol/1.0 (Internet Engineering Task Force (IETF))