BS ISO 1887:2014



BSI Standards Publication

Textile glass — Determination of combustible-matter content



BS ISO 1887:2014 BRITISH STANDARD

National foreword

This British Standard is the UK implementation of ISO 1887:2014. It supersedes BS ISO 1887:1995 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee PRI/42, Fibre reinforced thermosetting plastics and prepregs.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014. Published by BSI Standards Limited 2014

ISBN 978 0 580 74660 4

ICS 59.100.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 September 2014.

Amendments issued since publication

Date Text affected

INTERNATIONAL STANDARD

ISO 1887:2014 ISO 1887

Fourth edition 2014-09-01

Textile glass — Determination of combustible-matter content

Verre textile — Détermination de la teneur en matières combustibles



BS ISO 1887:2014 **ISO 1887:2014(E)**



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Co	ontents	Page
Fore	reword	iv
1	Scope	
2	Terms and definitions	1
3	Principle	
4	Apparatus	1
5	Test specimens 5.1 Selection of test specimens 5.2 Number of test specimens	2
6	Procedure 6.1 Precautions to be taken during test 6.2 Weighing the specimen holder 6.3 Weighing the dried test specimen plus holder 6.4 Weighing the calcinated test specimen plus holder	
7	Expression of results	5
8	Precision	5
9	Test report	5

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 61, *Plastics*, Subcommittee SC 13, *Composites and reinforcement fibres*.

This fourth edition cancels and replaces the third edition (ISO 1887:1995), which has been technically revised.

Textile glass — Determination of combustible-matter content

1 Scope

This International Standard specifies a method for the determination of the combustible-matter content of products made from textile glass, such as continuous-filament yarns, staple-fibre yarns, rovings, chopped strands, milled fibres, fabrics, chopped-strand and continuous-filament mats, and other glass reinforcements.

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

2.1

combustible-matter content

ratio of the mass of material removed on calcination from a dried textile glass product to the mass of the dried product

Note 1 to entry: This ratio is expressed as a percentage in this International Standard. It is equal to the content of size or finish on the textile glass product when the size or finish is completely combustible without significant residue (i.e. primarily organic products).

3 Principle

Test specimens, dried under prescribed conditions, are weighed before and after calcination at a temperature of 625 $^{\circ}$ C $^{\pm}$ 20 $^{\circ}$ C or, with types of glass which are unstable at this temperature, at a temperature between 500 $^{\circ}$ C and 600 $^{\circ}$ C, also kept constant to within 20 $^{\circ}$ C.

4 Apparatus

- **4.1 Air-circulation oven**, for drying specimens, capable of being maintained at 105 °C \pm 5 °C or the chosen drying temperature and maintained to within \pm 5 °C (see <u>6.3</u>).
- **4.2 Muffle furnace**, capable of being maintained, with a tolerance of ±20 °C, at any desired temperature up to 625 °C, the temperature being measured at the centre of the muffle furnace with the door closed.
- **4.3 Desiccator**, containing a suitable desiccant, for example silica gel, calcium chloride, phosphorous(V) oxide.
- **4.4 Specimen holder**, made from a material stable at the test temperature, allowing the best possible air circulation around the test specimen and designed to prevent loss of material. The holder may be a porcelain crucible, a basket made of stainless-steel gauze, etc.
- **4.5 Stainless-steel tongs**, for handling test specimens and holders.
- **4.6 Balance**, accurate to 0,1 mg.
- **4.7 Polished-metal templates**, for the preparation of test specimens.