

BSI Standards Publication

Maritime navigation and radiocommunication equipment and systems – Automatic Identification Systems (AIS)

Part 2: Class A shipborne equipment of the automatic identification system (AIS) – Operational and performance requirements, methods of test and required test results (IEC 61993-2:2018)



National foreword

This British Standard is the UK implementation of EN IEC 61993-2:2018. It is identical to IEC 61993-2:2018. It supersedes BS EN 61993-2:2013, which will be withdrawn on 23 August 2021.

The UK participation in its preparation was entrusted to Technical Committee EPL/80, Maritime navigation and radiocommunication equipment and systems.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018 Published by BSI Standards Limited 2018

ISBN 978 0 580 94427 7

ICS 33.060.20; 47.020.70

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 November 2018.

Amendments/corrigenda issued since publication

Date Text affected

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN IEC 61993-2

October 2018

ICS 47.020.70

Supersedes EN 61993-2:2013

English Version

Maritime navigation and radiocommunication equipment and systems - Automatic Identification Systems (AIS) - Part 2: Class A shipborne equipment of the automatic identification system (AIS) - Operational and performance requirements, methods of test and required test results (IEC 61993-2:2018)

Matériels et systèmes de navigation et de radiocommunication maritimes - Systèmes d'identification automatique (AIS) Partie 2: Équipements AIS de type Classe A embarqués - Exigences d'exploitation et de fonctionnement, méthodes d'essai et résultats d'essai exigés (IEC 61993-2:2018)

Navigations- und Funkkommunikationsgeräte und -systeme für die Seeschifffahrt - Automatische Identifikationssysteme (AIS) - Teil 2: Geräte der Klasse A des universellen automatischen Identifikationssystems (AIS) für Schiffe - Betriebs- und Leistungsanforderungen, Prüfverfahren und geforderte Prüfergebnisse (IEC 61993-2:2018)

This European Standard was approved by CENELEC on 2018-08-23. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 80/888/FDIS, future edition 3 of IEC 61993-2, prepared by IEC/TC 80 "Maritime navigation and radiocommunication equipment and systems" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 61993-2:2018.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2019-05-23 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2021-08-23

This document supersedes EN 61993-2:2013.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 61993-2:2018 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61097-14	NOTE	Harmonized as EN 61097-14
IEC 61108-1	NOTE	Harmonized as EN 61108-1
IEC 61108-2	NOTE	Harmonized as EN 61108-2
IEC 61162-3	NOTE	Harmonized as EN 61162-3
IEC 61924-2	NOTE	Harmonized as EN 61924-2
IEC 62287-1	NOTE	Harmonized as EN 62287-1
IEC 62320-1	NOTE	Harmonized as EN 62320-1
IEC 62320-2	NOTE	Harmonized as EN 62320-2

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	EN/HD	<u>Year</u>
IEC 60945	2002	Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results	EN 60945	2002
IEC 61108	serie	s Maritime navigation and radiocommunication equipment and systems - Global navigation satellite systems (GNSS)	EN 61108	series
IEC 61162-1	2016	Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 1: Single talker and multiple listeners	EN 61162-1	2016
IEC 61162-2	-	Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 2: Single talker and multiple listeners, high-speed transmission	EN 61162-2	-
IEC 61162-450	2018	Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 450: Multiple talkers and multiple listeners - Ethernet interconnection	EN IEC 61162-450	2018
IEC 61162-460	-	Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 460: Multiple talkers and multiple listeners - Ethernet interconnection - Safety and security	EN IEC 61162-460	-
IEC 62288	-	Maritime navigation and radiocommunication equipment and systems - Presentation of navigation-related information on shipborne navigational displays - General requirements, methods of testing and required test results	EN 62288	-
IEC 62388	-	Maritime navigation and radiocommunication equipment and systems - Shipborne radar - Performance requirements, methods of testing and required test results	EN 62388	-

EN IEC 61993-2:2018 (E)

IEC 62923-1 -	Maritime navigation and radiocommunication equipment and systems - Bridge alert management - Part 1: Operational and performance requirements, methods of testing and required test results	-	-
IEC 62923-2 -	Maritime navigation and radiocommunication equipment and systems – Bridge alert management - Part 2: Alert and cluster identifiers and other additional features	EN 62923-2 ¹	-
ITU-R 2012 Recommendation M.1084-5	Interim solutions for improved efficiency in the use of the band 156-174 MHz by stations in the maritime mobile service	-	-
ITU-R 2014 Recommendation M.1371-5	Technical characteristics for an automatic identification system using time-division multiple access in the VHF maritime mobile band	-	-
ITU-R - Recommendation M.493-14	Digital selective-calling system for use in the maritime mobile service	-	-
ITU-R - Recommendation M.541-10	Operational procedures for the use of digital selectivecalling equipment in the maritime mobile service	-	-
ITU-R - Recommendation M.825-3	Characteristics of a transponder system using digital selective calling techniques for use with vessel traffic services and ship-to-ship identification	-	-
ITU-T - Recommendation O.153	Basic parameters for the measurement of error performance at bit rates below the primary rate	-	-
IMO Resolution- A.694 (17)	General requirements for shipborne radio equipment forming part of the Global Maritime Distress and Safety System (GMDSS) and for electronic navigational aids		
IMO Resolution- MSC.302(87)	Performance standards for Bridge Alert Management		
IMO Resolution- MSC.43(64)	Guidelines and Criteria for Ship Reporting Systems (as amended by MSC.111(73))		
IMO Resolution- MSC.74(69)	Performance standards for an Universal sphipborne automatic identification systems (AIS)		

-

¹ Under preparation. Stage at the time of publication: FprEN 62923-2:2018.

CONTENTS

FC	DREWO	RD	.10
1	Scop	e	.12
2	Norm	native references	.12
3	Term	s, definitions and abbreviated terms	.13
	3.1	Terms and definitions	.13
	3.2	Abbreviated terms	.14
4	Gene	eral requirements	.15
	4.1	General	.15
	4.1.1	Overview	.15
	4.1.2	General requirements	.15
	4.1.3	Capabilities of the AIS	.15
	4.1.4	Additional requirements	.15
	4.1.5	Transmitter shutdown procedure	.16
	4.1.6	Quality assurance	.16
	4.2	Modes of operation	.16
	4.3	Manuals	.16
	4.4	Marking and identification	.16
5	Othe	r requirements	.17
	5.1	Environmental, power supply, special purpose and safety requirements	.17
	5.2	Display of information	.17
	5.3	Update of software	.17
6	Perfo	ormance requirements	.17
	6.1	Composition	.17
	6.2	Time and position	18
	6.2.1	Source for UTC	18
	6.2.2	Source for AIS position reporting	.18
	6.3	User interface	.19
	6.4	Identification	.19
	6.5	Information	.19
	6.5.1	Information provided by the AIS	.19
	6.5.2	Information reporting intervals	.20
	6.5.3	Ship reporting capacity	.21
	6.6	Event log	.21
	6.7	Permissible initialization period	.22
	6.8	Power supply	
	6.9	Technical characteristics	.22
	6.10	Alerts and indications, fall-back arrangements	.22
	6.10.	• •	
	6.10.	3	
	6.11	Display, input and output	
	6.11.	, , ,	
	6.11.		
	6.11.		
	6.11.	'	
	6.11.		
	6.12	Protection from invalid controls	35

IEC 61993-2:2018 © IEC 2018

7	Tech	nical requirements	35
	7.1	General	35
	7.2	Physical layer	35
	7.2.1	General	36
	7.2.2	Transmitter parameters	36
	7.2.3	Receiver parameters	37
	7.3	Link layer	37
	7.3.1	General	37
	7.3.2	Link sublayer 1: Medium Access Control (MAC)	38
	7.3.3	Link sublayer 2: Data Link Service (DLS)	38
	7.3.4	Link sublayer 3 – Link Management Entity (LME)	38
	7.4	Network layer	41
	7.4.1	General	41
	7.4.2	Management of regional operating settings	41
	7.5	Transport layer	42
	7.6	Presentation interface	42
	7.6.1	General	42
	7.6.2	Automatic input of sensor data	43
	7.6.3	High speed input/output ports	44
	7.6.4		
	7.6.5	•	
	7.6.6	·	
	7.6.7		
8	Long	-range applications	57
	8.1	General	57
	8.2	Long-range application by two-way interface	57
	8.2.1	General	
	8.2.2	9	
	8.2.3	•	
	8.2.4		
	8.2.5	•	
	8.3	Long-range application by broadcast	
9	Test	conditions	59
	9.1	Normal and extreme test conditions	59
	9.1.1	Normal test conditions	59
	9.1.2	Extreme test conditions	59
	9.2	Standard test environment	59
	9.3	Additional test arrangements	60
	9.3.1	Arrangements for test signals applied to the receiver input	
	9.3.2		
	9.3.3		
	9.3.4	'	
	9.3.5	,	
	9.3.6		
	9.3.7	•	
	9.4	Common test conditions for protection from invalid controls	
	9.5	Measurement uncertainties	
10	Test	signals	61

-4-

IEC 61993-2:2018 © IEC 2018

10.1	Stand	ard test signal number 1 (DSC)	61
10.2	Stand	lard test signal number 2 (TDMA)	61
10.3	Stand	ard test signal number 3 (TDMA)	61
10.4	Stand	lard test signal number 4 (PRBS)	62
10.5	Stand	lard test signal number 5 (PRBS)	62
Powe	r supp	ply, special purpose and safety tests	63
Enviro	onmer	ntal tests	63
EMC	tests .		63
Opera	ational	l tests	63
•			
		•	
		·	
		•	
		•	
		-	
		•	
_		·	
14.4.2			
14.5		•	
		·	
14.5.2	2 R	Required results	71
14.6	Initiali	ization period	71
14.6.1	1 N	Nethod of measurement	71
14.6.2	2 R	Required results	71
14.7	Techn	nical characteristics	71
14.7.1	1 C	Channel selection	71
14.7.2	2 T	ransceiver protection	71
14.7.3	3 A	Automatic power setting	72
14.8	Alerts	and indicators, fall-back arrangements	72
14.8.1	1 L	oss of power supply	72
14.8.2	2 N	Nonitoring of functions and integrity	72
14.8.3	3 N	Nonitoring of sensor data	75
14.9	Displa	ay, input and output	78
14.9.1	1 D	Data input/output facilities	79
14.9.2	2 Ir	nitiate message transmission	79
14.9.3	3 C	Communication test	80
14.9.4	4 S	System control	80
14.9.5	5 D	Display of received targets	81
14.9.6	3 D	Display of position quality	82
14.9.7	7 D	Display of targets if optional filter is implemented	82
14.9.8	3 D	Display of received safety related messages	83
	10.2 10.3 10.4 10.5 Powe Environment of the service	10.2 Stand 10.3 Stand 10.4 Stand 10.5 Stand 10.5 Stand 10.5 Stand 10.5 Stand 10.5 Stand 10.6 Power supp Environment EMC tests Operationa 14.1 Identi 14.1.1 A 14.1.2 A 14.1.3 F 14.1.4 A 14.1.5 E 14.1.6 M 14.2.1 M 14.2.2 F 14.3 Inform 14.3.1 I 14.3.2 F 14.4 Event 14.4.1 M 14.4.2 F 14.5 Softw 14.5.1 M 14.5.2 F 14.6 Initial 14.6.1 M 14.6.2 F 14.7 Techn 14.7.1 C 14.7.2 T 14.7.3 A 14.8 Alerts 14.8.1 L 14.8.2 M 14.8.3 M 14.9 Displa 14.9.1 E 14.9.3 C 14.9.5 E 14.9.6 E 14.9.7 E	10.2 Standard test signal number 2 (TDMA) 10.3 Standard test signal number 4 (PRBS). 10.4 Standard test signal number 5 (PRBS). 10.5 Standard test signal number 5 (PRBS). Power supply, special purpose and safety tests. Environmental tests. EMC tests. Operational tests. 14.1 Identification and operating modes. 14.1.1 Autonomous mode. 14.1.2 Assigned mode. 14.1.3 Polled mode. 14.1.4 Addressed operation. 14.1.5 Broadcast operation. 14.1.6 Multiple slot messages. 14.2 Manuals, marking and identification. 14.2.1 Method of measurement. 14.2.2 Required results. 14.3 Information provided by the AIS. 14.3.1 Information provided by the AIS. 14.3.2 Reporting intervals. 14.4 Event log. 14.4.1 Method of measurement. 14.4.2 Required results. 14.5 Software update. 14.5.1 Method of measurement. 14.5.2 Required

	14.9.9	Presentation of navigation information	83
15	Physical t	ests	83
	15.1 TDN	//A transmitter	84
	15.1.1	Frequency error	84
	15.1.2	Carrier power	84
	15.1.3	Slotted transmission spectrum	85
	15.1.4	Modulation accuracy	86
	15.1.5	Transmitter output power characteristics	86
	15.2 TDN	MA receivers	87
	15.2.1	Sensitivity	
	15.2.2	Error behaviour at high input levels	88
	15.2.3	Co-channel rejection	
	15.2.4	Adjacent channel selectivity	
	15.2.5	Spurious response rejection	
	15.2.6	Intermodulation response rejection and blocking	92
	15.2.7	Transmit to receive switching time	
	15.2.8	Immunity to out-of-band energy	
		ducted spurious emissions	
	15.3.1	Spurious emissions from the transmitter	
	15.3.2	Spurious emissions from the receiver	
16	Specific to	ests of link layer	95
	16.1 TDN	MA synchronisation	95
	16.1.1	Synchronisation test using UTC	95
	16.1.2	Synchronisation test using UTC with repeated messages	96
	16.1.3	Synchronisation test without UTC, semaphore	96
	16.1.4	Synchronisation test without UTC	97
	16.1.5	Reception of un-synchronised messages	
	16.2 Time	e division (frame format)	
	16.2.1	Method of measurement	97
	16.2.2	Required results	
	16.3 Syn	chronisation and jitter accuracy	97
	16.3.1	Definition	
	16.3.2	Method of measurement	
	16.3.3	Required results	
		a encoding (bit stuffing)	
	16.4.1	Method of measurement	
	16.4.2	Required results	
		ne check sequence	
	16.5.1	Method of measurement	
	16.5.2	Required results	
		allocation (channel access protocols)	
	16.6.1	Network entry	
	16.6.2	Autonomous scheduled transmissions (SOTDMA)	
	16.6.3	Autonomous scheduled transmissions (ITDMA)	
	16.6.4	Safety related/binary message transmission	
	16.6.5	Transmission of Message 5 (ITDMA)	
	16.6.6	Assigned operation	
	16.6.7	Group assignment	
	16.6.8	Fixed allocated transmissions (FATDMA)	.104

	16.6.9	Randomisation of message transmissions	105
	16.7 Me	ssage formats	105
	16.7.1	Received messages	105
	16.7.2	Transmitted messages	105
17	Specific	tests of network layer	106
	17.1 Dua	al channel operation – Alternate transmissions	106
	17.1.1	Method of measurement	
	17.1.2	Required results	106
	17.2 Re	gional area designation by VDL message	
	17.2.1	Method of measurement	
	17.2.2	Required results	
	17.3 Re	gional area designation by serial message	
		gional area designation with lost position	
	17.4.1	Method of measurement	
	17.4.2	Required results	107
	17.5 Pov	ver setting	
	17.5.1	Method of measurement	
	17.5.2	Required results	108
	17.6 Me	ssage priority handling	
	17.6.1	Method of measurement	
	17.6.2	Required results	108
	17.7 Slo	t reuse and FATDMA reservations	108
	17.7.1	Method of measurement	108
	17.7.2	Required results	108
	17.8 Ma	nagement of received regional operating settings	109
	17.8.1	Test for replacement or erasure of dated or remote regional operating settings	109
	17.8.2	Test of correct input via presentation interface or MKD	110
	17.8.3	Test of addressed telecommand	110
	17.8.4	Test for invalid regional operating areas	111
	17.9 Co	ntinuation of autonomous mode reporting interval	111
	17.9.1	Method of test	111
	17.9.2	Required results	111
18	Specific	tests of transport layer	111
	18.1 Add	dressed messages	112
	18.1.1	Transmission	
	18.1.2	Acknowledgement	112
	18.1.3	Transmission retry	
	18.1.4	Acknowledgement of addressed safety related messages	
	18.1.5	Behaviour of NavStatus 14 reception	
	18.2 Inte	errogation responses	
		·	
	18.2.1	Method of measurement	113
19	18.2.1 18.2.2	Method of measurementRequired results	
	18.2.2	Method of measurementRequired resultspresentation interface tests	113
	18.2.2 Specific	Required resultspresentation interface tests	113 113
	18.2.2 Specific 19.1 Ge	Required resultspresentation interface testsneral	113 113
	18.2.2 Specific 19.1 Ge 19.2 Cho	Required results presentation interface tests neral ecking manufacturer's documentation	113113113
	18.2.2 Specific 19.1 Ge 19.2 Cho 19.3 Ele	Required results presentation interface tests neral ecking manufacturer's documentation ctrical test	113113113113
	18.2.2 Specific 19.1 Ge 19.2 Cho 19.3 Ele 19.3.1	Required results presentation interface tests neral ecking manufacturer's documentation	113113113114

IEC 61993-2:2018 © IEC 2018

19.4 Test	of input sensor interface performance	.114
19.4.1	Method of measurement	.114
19.4.2	Required results	.114
19.5 Test	of sensor input	.114
19.5.1	Test of GNS input	.114
19.5.2	Test of RMC input	.115
19.5.3	Test of DTM input	.115
19.5.4	Test of GBS input	.116
19.5.5	Test of VBW input	.117
19.5.6	Test of VTG input	.117
19.5.7	Test of HDT/THS input	.117
19.5.8	Test of ROT input	.118
19.5.9	Test of different inputs	.118
19.5.10	Test of multiple inputs	.119
19.6 Test	of high speed output	.119
19.6.1	Method of measurement	
19.6.2	Required results	.119
19.7 High	speed output interface performance	
19.7.1	Method of measurement	
19.7.2	Required results	.120
19.8 Out	but of undefined VDL messages	
19.8.1	Method of measurement	
19.8.2	Required results	.120
19.9 Test	of high speed input	
19.9.1	General	
19.9.2	Test of VSD input sentence	.120
19.9.3	Test of SSD input sentence	
19.9.4	Test of EPV input sentence	
19.9.5	Test of the Pilot Port access level	
20 Long-rang	ge functionality tests	.122
	g-range application by two-way interface	
20.1.1	LR interrogation	
20.1.2	LR "all ships" interrogation	
20.1.3	Consecutive LR "all ships" interrogations	
	g-range application by broadcast	
20.2.1	Long-range broadcast	
20.2.2	Multiple assignment operation	
_	mative) Block diagram of AIS	
	native) AIS interface overview	
•	•	
•	native) DSC functionality	
	Compatibility	
	receiver tests	
C.2.1	Maximum sensitivity	
C.2.2	Error behaviour at high input levels	
C.2.3	Co-channel rejection	
C.2.4	Adjacent channel selectivity	
C.2.5	Spurious response rejection	
C.2.6	Intermodulation response rejection	. 130

C.2.7 Blockii	ng or desensitisation	131
C.2.8 Condu	cted spurious emissions from the receiver	132
C.3 DSC function	onality tests	132
C.3.1 Definit	ion	132
C.3.2 Method	d of measurement	132
C.3.3 Requir	ed results	133
` '	Alert handling with ALR/ACK	
Annex E (normative)	Calculation of area size and distance	136
E.1 Importance	of a common method for area size and distance calculations	136
E.2 Calculation	of area sizes	136
E.3 Calculation	of general distances	137
	al	
	circle	
	o-line distance	137
	New interface sentences – Sender signature authentication	138
	Updated interface sentences	
	opution interface sentences	
	voyage static data	
	Conversion between IEC 61162-1 sentences and IEC 61162-3	140
	bers	142
Annex I (normative) I	Extended tow dimension values	144
,	nd background	
•		
Bibliography		146
Figure 1 – OSI layer r	model	35
Figure 2 – Power vers	sus time characteristics	36
Figure 3 – Format for	repeating four-packet cluster	62
Figure 4 – Measurem	ent arrangement for frequency error	84
	ent arrangement for carrier power	
_	nask for slotted transmission	
-	ent arrangement for modulation accuracy	
	ent arrangement	
_	ent arrangement with two generators	
_		
•	PER/BER measuring equipment	
<u> </u>	JP	
-	to receive switching time measurement setup	
•	area scenario	
<u> </u>	ement arrangement for inter-modulation	
Figure D.1 – State dia	agram of IEC 61993-2 Ed.2 Alert handling	135
Figure I.1 – Input, ext	ension and transmitted dimensional values	145
Table 1 –Talker IDs fo	or automatic detection of electronic position fixing system type	19
	reporting intervals for autonomous mode	21

detecteddetections for Birr and reaction of the system to the condition	23
Table 4 – Classification of required alerts	24
Table 5 – Mapping between BAM alert states and ALR alert states	25
Table 6 – Sensor status indications signalled using TXT sentence formatter	26
Table 7 – Position sensor fall-back conditions	27
Table 8 – Use of accuracy (PA) flag	28
Table 9 – ROT sensor fallback conditions	29
Table 10 – Identification of locating devices when active	30
Table 11 – Identification of locating devices when in test mode	30
Table 12 – Identification of locating devices for type approval testing	31
Table 13 – Message display on MKD	32
Table 14 – Position quality	33
Table 15 – Transmitter parameters	36
Table 16 – Power versus time characteristics	37
Table 17 – Receiver parameters	37
Table 18 – Use of VDL messages	39
Table 19 – Presentation interface access	43
Table 20 – IEC 61162-1 sensor sentences	44
Table 21 – AIS high-speed input data and formats	46
Table 22 – AIS high-speed output data and formats	47
Table 23 – Property identifiers	48
Table 24 – AIS Long-range communications input data and formats	51
Table 25 – LR output data formats	52
Table 26 – Default input transmission groups with applicable sentences	53
Table 27 – TAG block parameters	53
Table 28 – CRP sentences applicable for Class A AIS	54
Table 29 – Tests to be repeated for IEC 61162-450 interface	56
Table 30 – LR data types	58
Table 31 – Content of first two packets	62
Table 32 – Fixed PRS data derived from Recommendation ITU-T 0.153	62
Table 33 – Peak frequency deviation versus time	86
Table 34 – Tests to be performed	92
Table 35 – Primary channels for each region	107
Table D.1 – IEC 61993-2:2012 alert states	134
Table D.2 – IEC 61993-2:2012 alert events	
Table E.1 – Coordinate points	136
Table H.1 – Conversion between IEC 61162-1 and IEC 61162-3	142

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – AUTOMATIC IDENTIFICATION SYSTEMS (AIS) –

Part 2: Class A shipborne equipment of the automatic identification system (AIS) – Operational and performance requirements, methods of test and required test results

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61993-2 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This third edition cancels and replaces the second edition published in 2012. This edition constitutes a technical revision.

This edition includes the following technical changes with respect to the previous edition:

- a) it incorporates the technical characteristics included in Recommendation ITU-R M.1371-5:2014;
- b) it introduces the concept of locating device groups in order to include EPIRB AIS and MOB AIS in addition to AIS SART;
- c) it adds security features for configuration input by introducing a new sentence SSA;

IEC 61993-2:2018 © IEC 2018

_ 11 _

- d) it adds optional implementation of IEC 61162-450/460 interfaces;
- e) it adds requirements for bridge alert management (BAM);
- f) it introduces extended dimension values used by towing vessels;
- g) it adds a software update requirement.

The text of this document is based on the following documents:

FDIS	Report on voting
80/888/FDIS	80/890/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61993 series, published under the general title *Maritime* navigation and radiocommunication equipment and systems – Automatic identification systems (AIS), can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – AUTOMATIC IDENTIFICATION SYSTEMS (AIS) –

Part 2: Class A shipborne equipment of the automatic identification system (AIS) – Operational and performance requirements, methods of test and required test results

1 Scope

This part of IEC 61993 specifies the minimum operational and performance requirements, methods of testing and required test results conforming to performance standards adopted by IMO in Resolution MSC.74(69):1998, Annex 3. This document incorporates the applicable technical characteristics of Class A shipborne equipment included in Recommendation ITU-R M.1371 and takes into account the ITU Radio Regulations, where applicable. In addition, it takes account of IMO Resolution A.694(17) to which IEC 60945 is associated. When a requirement in this document is different from IEC 60945, the requirement of this document takes precedence.

This document also specifies the minimum requirements both for the means to input and display data and for the interfaces to other equipment suitable to be used as means of input and display data.

NOTE All text of this document that is identical to that in IMO resolution MSC.74(69):1998, Annex 3, or to that in ITU-R Recommendation M.1371 is printed in *italics*, and references to the resolution (abbreviated to "A3") or the recommendation (abbreviated to "M.1371") and paragraph numbers are indicated in parentheses, for instance (A3/3.3) or (M.1371-5/A2-3.3) respectively.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945:2002, Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results

IEC 61108 (all parts), Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS)

IEC 61162-1:2016, Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners

IEC 61162-2, Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 2: Single talker and multiple listeners, high-speed transmission

IEC 61162-450:2018, Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 450: Multiple talkers and multiple listeners – Ethernet interconnection

IEC 61162-460, Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 460: Multiple talkers and multiple listeners – Ethernet interconnection – Safety and security