

AMERICAN NATIONAL STANDARD

Dryseal Pipe Threads (Inch)

ANSI B1.20.3 - 1976

(REVISION AND REDESIGNATION OF B2.2-1968)

REAFFIRMED 1998

FOR CURRENT COMMITTEE PERSONNEL
PLEASE SEE ASME MANUAL AS-11

SECRETARIAT

SOCIETY OF AUTOMOTIVE ENGINEERS
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS

PUBLISHED BY

THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS

United Engineering Center 345 East 47th Street New York, N. Y. 10017

ACCEPTANCE NOTICE

The above non-Government document was adopted (with exception listed below) on 31 Oct 1980 and is approved for use by the Federal agencies. The indicated industry group has furnished the clearance required by existing regulations. Copies of the document are stocked by the DoD Single Stock Point, Naval Publications and Forms Center, Philadelphia, PA 19120, for issue to DoD activities only. Contractors and industry groups must obtain copies directly from:

The American Society of Mechanical Engineers
United Engineering Center, 345 East 47th Street,
New York, NY 10017 or

The American National Standards Institute,
1430 Broadway, New York, NY 10018.

Title of Document: Dryseal Pipe Threads (Inch)

Date of Specific Issue Adopted: 18 November 1976

Releasing Industry Group: The American Society of Mechanical Engineers

Exception: The Federal agencies use of this Standard is subject to all the requirements and limitations of FED-STD-H28/8 - Screw-Thread Standards for Federal Services Section 8, Dryseal Pipe Threads.

Military Custodians:

Army - AR
Navy - AS
Air Force - 11

Review Activities:

Army - AT, AV, ER, ME, MI
Navy - OS, SH, YD

Civil Agency Coordinating Activities:

Commerce - NBS
DOT - ACO, FHW, FIS, FRA, RDS
GSA - FSS, PCD
HUD - TCS
Interior - BPA
Justice - FPI
NASA - JFK, LRC, MSF
USDA - AFS

Military Coordinating Activity:

DLA-IS
(Project THDS-0034)

NOTICE: When reaffirmation, amendment, revision, or cancellation of this standard is initially proposed, the industry group responsible for this standard shall inform the military coordinating activity of the proposed change and request their participation.

AREA THDS

No part of this document may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

FOREWORD

In 1913 a Committee on the Standardization of Pipe Threads was organized for the purpose of re-editing and expanding the Briggs Standard. The American Gas Association and The American Society of Mechanical Engineers served as joint sponsors. After six years of work, this committee completed the revised standard for taper pipe thread which was published in the ASME "Transactions" of 1919, and was approved as an American Standard by the then American Engineering Standards Committee (later changed to American Standards Association) in December, 1919. It was the first standard to receive this designation under the ASA procedure, and was later republished in pamphlet form.

In the years which followed, the need for a further revision of this American Standard became evident as well as the necessity of adding to it the recent developments in pipe threading practice. Accordingly, the Sectional Committee on the Standardization of Pipe Threads, B2, was organized in 1927 under the joint sponsorship of the A.G.A. and the ASME.

During the following 15 years, several meetings were held leading to approval by the members of the Sectional Committee, of the April 1941 draft. The revision was approved by the sponsors and ASA and published as an American Standard in October 1942.

Shortly after publication of the 1942 standard, the Committee undertook preparation of a complete revision. The text and tables were re-arranged and expanded to include Dryseal pipe threads, and an extensive appendix was added to provide additional data on the application of pipe threads and to record in abbreviated form the several special methods which were established for gaging some of the various applications of pipe threads.

The resulting proposal was designated an American Standard on December 11, 1945. The section covering Dryseal Pipe Threads in ASA B2.1-1945 was deleted and developed as a separate standard designated ASA B2.2-1960, Dryseal Pipe Threads. Another updating occurred with republication as USAS B2.2-1968.

In 1973, Standards Committee B2 was absorbed by American National Standards Institute Standard Committee B1 and reorganized as subcommittee 20. A complete rewrite of the B2.2-1968 document was undertaken with the product thread data in separate documents from the gaging standards for Dryseal Pipe threads. The system of renumbering, to include metric revisions, is as follows:

ANSI B1.20.3-1976	Inch Dryseal Pipe Threads
ANSI B1.20.4-1976	Metric Dryseal Pipe Threads
ANSI B1.20.5-197	Gaging for Inch Dryseal Pipe Threads
ANSI B1.20.6-197	Gaging for Metric Dryseal Pipe Threads

Since the product thread documents are being published before completion of the new gaging standards, the gaging data in the B2.2-1968 Standard should be used until superseded by publication of the new B1.20.5 and B1.20.6 gaging standards.

ANSI B1.20.3 and B1.20.4 were approved by ANSI Committee B1 for publication as official ANSI Standards and thereupon submitted to the Secretariat and the American National Standards Institute. They were approved and formally designated as American National Standards on November 18, 1976.

Intentionally left blank

AMERICAN NATIONAL STANDARDS COMMITTEE B1 Standardization and Unification of Screw Threads

(The following is the roster of the Committee at the time of approval of this standard)

Organized June, 1921
Reorganized February, 1929

SPONSORS: Society of Automotive Engineers
The American Society of Mechanical Engineers

SCOPE: Nomenclature of screw threads; form of threads; diameter and pitches of screws for various uses; classification of thread fits, tolerances and allowances for threaded parts; and the gaging of threads. Screw threads for fire hose couplings are not included within the scope.

T. C. Baumgartner, Chairman
J. B. Levy, Vice-Chairman
S. W. Taylor, Secretary

AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC.

Propulsion Technical Committee

D. H. Secord, Pratt & Whitney Aircraft, E. Hartford, Connecticut

National Aerospace Standards Committee

E. L. Wall, McDonell Aircraft Company, St. Louis, Missouri

AIRCRAFT LOCKNUT MANUFACTURERS ASSOCIATION

Charles Fineran, ESNA Division, American Amerace Corporation, Union, N.J.

AIR INDUSTRIES CORPORATION

Edward Clark, Air Industries Corporation, Garden Grove, California

Alex Butovich, Alternate, Air Industries Corporation, Garden Grove, California

AMERICAN MEASURING TOOL MANUFACTURERS ASSOCIATION

Dale Dodge, Pennoyer-Dodge Company, Glendale, California

AMERICAN SOCIETY OF MECHANICAL ENGINEERS, THE

Edward McHugh, Professor, Clarkson College of Technology, Potsdam, New York

ANTIFRICTION BEARING MANUFACTURERS ASSOCIATION

William J. Derner, Bearing Division, FMC Corporation, Indianapolis, Indiana

ASSOCIATION OF AMERICAN RAILROADS

Engineering Division

C. C. Herrick, New York Central System, New York, New York

BELOIT TOOL CORPORATION

Phillip V. Pastore, Beloit Tool Corporation, South Beloit, Illinois

J. O. Heinze, Alternate, Beloit Tool Corporation, South Beloit, Illinois

BENDIX CORPORATION, THE

Dale Story, The Bendix Corporation, South Beloit, Illinois

CLARK EQUIPMENT COMPANY

D. N. Badgley, Clark Equipment Company, Battle Creek, Michigan

COMPUTERS & BUSINESS EQUIPMENT MANUFACTURERS ASSOCIATION

H. G. Atwater (observer), International Business Machine Corporation, Endicott, New York

COMPRESSED GAS ASSOCIATION, INC.

M. E. Steczynski, Steczynski & Associates, Chicago, Illinois

E. A. Olsen, Alternate, Compressed Gas Associate, Inc., New York, New York

DEFENSE INDUSTRIAL SUPPLY CENTER

Eli Schwartz, Defense Industrial Supply Center, Philadelphia, Pennsylvania

Francis S. Ciccarone, Alternate, Defense Industrial Supply Center, Philadelphia, Pennsylvania

FARM & INDUSTRIAL EQUIPMENT INSTITUTE

C. W. Stockwell (observer), International Harvester Co., Hinsdale, Illinois

FORD MOTOR COMPANY

S. E. Mallen, Ford Motor Company, Dearborn, Michigan

J. F. Nagy, Alternate, Ford Motor Company, Dearborn, Michigan

GEOMETRIC TOOL CORPORATION

E. S. Zook, Geometric Tool, New Haven, Connecticut

GREENFIELD TAP & DIE DIVISION OF TRW INC.

D. J. Emanuelli, Greenfield Tape & Die, A United-Greenfield Division of TRW Inc., Greenfield, Massachusetts

HANSON-WHITNEY COMPANY, THE

S. I. Kanter, The Hanson-Whitney Company, Hartford, Connecticut

HI-SHEAR CORPORATION

M. M. Schuster, Hi-Shear Corporation, Torrance, California

INDUSTRIAL FASTENERS INSTITUTE

T. C. Baumgartner, Chairman, Standard Pressed Steel Company, Jenkintown, Pennsylvania

R. B. Belford, Industrial Fasteners Institute, Cleveland, Ohio

R. M. Harris, Alternate, Bethlehem Steel Company, Lebanon, Pennsylvania

D. D. Wheeler, Armco Steel Corporation, Kansas City, Missouri

R. W. Groover, Bethlehem Steel Company, Lebanon, Pennsylvania

K. E. McCullough, Alternate, Standard Pressed Steel Company, Jenkintown, Pennsylvania

J. C. McMurray, Russell, Burdsall & Ward Bolt & Nut Company, Port Chester, New York

JOHNSON GAGE COMPANY, THE

R. S. Chamerda, The Johnson Gage Co., Bloomfield, Connecticut

Stanley Johnson, Alternate, The Johnson Gage Co., Bloomfield, Connecticut

MANUFACTURERS STANDARDIZATION SOCIETY OF THE VALVE & FITTINGS INDUSTRY

J. R. Welshman, Grinnel Corp., Providence, Rhode Island

METAL CUTTING TOOL INSTITUTE

Tap and Die Division

C. G. Erickson, Pratt & Whitney Small Tool Division, Colt Industries, Inc., W. Hartford, Connecticut

NATIONAL AUTOMATIC SPRINKLER & FIRE CONTROL ASSOCIATION

Frank Hills, Colligan Fyr-Protexion, Indianapolis, Indiana

Ray Malek, Paul J. Gruneau Company, Milwaukee, Wisconsin

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION

F. V. Kupchak, Westinghouse Electric Corporation, Pittsburgh, Pennsylvania

J. B. Levy, Vice-Chairman, General Electric Company, Schenectady, New York

R. L. Mancini, Alternate, National Electrical Manufacturers Association, New York, New York

NATIONAL MACHINE TOOL BUILDERS' ASSOCIATION

Thomas Lenhart, The Cleveland Twist Drill Company, Cleveland, Ohio

REED ROLLED THREAD DIE COMPANY

Joseph F. Dickson, Reed Rolled Thread Die Company, Nolden, Massachusetts

SOCIETY OF AUTOMOTIVE ENGINEERS

C. H. Baker, Jr., Muncie, Indiana

J. E. Long, GM Corporation, GM Technical Center, Warren, Michigan

L. R. Strang, Caterpillar Tractor Company, E. Peoria, Illinois

SOCIETY OF MANUFACTURING ENGINEERS

M. Davidson, Thredco Company, Troy, Michigan
J. S. Urso, Sepulveda, California
Dale Story, The Bendix Corporation, South Beloit, Illinois

SOCKET SCREW PRODUCTS BUREAU

E. J. Heldmann, The Holo-Krome Screw Corporation, Hartford, Connecticut

TELEPHONE GROUP, THE

R. H. Van Horn, Bell Telephone Laboratories, Inc., Columbus, Ohio
F. P. Balacek, Alternate, Bell Telephone Laboratories, Inc., Columbus, Ohio
L. L. Parrish, Alternate, Western Electric Company, Inc., Chicago, Illinois

U.S. MACHINE, CAP, WOOD & TAPPING SCREW BUREAU

R. M. Byrne, U.S. Screw Service Bureaus, New York, New York
E. F. Tauscher, Alternate, Pheoll Manufacturing Company, Chicago, Illinois

U.S. DEPARTMENT OF THE ARMY

Irwin Rosen, USA Mobility Equipment Company, Fort Belvoir, Virginia
M. L. Fruechtenicht, Alternate, Redstone Arsenal, Alabama
John McAdams, Alternate, U.S. Army Materiel Command, Alexandria, Virginia

Watervliet Arsenal

J. J. Fiscella, Watervliet, New York

U.S. DEPARTMENT OF COMMERCE

National Bureau of Standards

A. G. Strang, National Bureau of Standards, Optical Physics Division, Washington, D.C.

U.S. DEPARTMENT OF THE NAVY

Naval Ship Engineering Center (NSSC)

J. Kelly, Naval Ship Systems Command, Washington, D.C.

U.S. DEPARTMENT OF THE AIR FORCE

Edward Sosnowski, Aeronautical Systems Division, Wright-Patterson Air Force Base, Dayton, Ohio
F. Hannon, Alternate, Aeronautical Systems Division, Wright-Patterson Air Force Base, Dayton, Ohio
R. B. Norwood, Robbins Air Force Base, Georgia

VALLEY BOLT COMPANY

C. O. Franklin, Marion, Iowa

VAN KEUREN COMPANY

R. W. Lamport, The Van Keuren Company, Watertown, Massachusetts

INDIVIDUAL MEMBERS

S. C. Adamek, (observer), Pheoll Manufacturing Company, Chicago, Illinois
C. T. Appleton, Jefferson, Massachusetts
W. E. Bour, Santa Monica, California
W. S. Brown, Roanoke, Virginia
J. F. Cramer, Des Moines, Washington
R. B. Donahue, Xerox Corporation, Rochester, New York
E. W. Drescher, Bulova Watch Company, Inc., Flushing, New York
I. H. Fullmer (observer), Silver Springs, Maryland
W. E. Hay, The Pipe Machinery Company, Wickliffe, Ohio
A. R. Machell, Jr., Xerox Corporation, Rochester, New York
A. E. Masterson, Watervliet, New York
P. V. Miller (observer), Santa Maria, California
H. G. Muenchinger, Continental Screw Company, New Bedford, Massachusetts
Frank Tisch, Desert Hot Springs, California
R. P. Trowbridge, GM Technical Center, Warren, Michigan
J. E. Watson, Philadelphia, Pennsylvania

PERSONNEL OF SUBCOMMITTEE NO. 20 ON PIPE THREADS

D. N. Badgley, Chairman, Clark Equipment Company, Battle Creek, Michigan
W. E. Bour, Gardena, California
R. J. Browning, Southern Gage Company, Erin, Tennessee
J. A. Casner, Youngstown Steel Company, Youngstown, Ohio
W. O. Clinedinst, Consulting Engineer, Pittsburgh, Pennsylvania
M. Davidson, Southfield, Michigan
H. W. Ellison, General Motors Technical Center, Warren, Michigan
L. S. Feldheim, Secretary, The Weatherhead Company, Cleveland, Ohio
J. O. Heinze, Regal-Beloit Corporation, South Beloit, Illinois
J. S. Hinske, Parker-Hannifin Corporation, Tube Fitting Division, Cleveland, Ohio
D. F. Hubbard, Long Island Lighting Company, Hicksville, New York
S. I. Kanter, The Hanson-Whitney Company, Hartford, Connecticut
W. A. Keaton, Vice Chairman, General Motors Technical Center, Warren, Michigan
W. C. Matlock, Stockham Valves & Fittings, Birmingham, Alabama
R. S. Piotrowski, Mack Trucks, Inc., Allentown, Pennsylvania
P. V. Pastore, Regal-Beloit Corporation, South Beloit, Illinois
W. M. Roll, Deere & Company, Moline, Illinois
M. Rose, Southern Gage Company, Erin, Tennessee
R. J. Ross, Wheeling-Pittsburgh Steel Corporation, Benwood, West Virginia
C. J. Schim, Ford Motor Company, Dearborn, Michigan
J. Shields, Jackes-Evans Manufacturing Company, Jackson, Mississippi
J. Turton, The Bendix Corporation, South Beloit, Illinois
A. G. Strang, National Bureau of Standards, Washington, D.C.

CONTENTS

		Page
Section 1	Product Threads	1
1.1	Introduction.	1
1.2	Thread Types	2
1.3	Thread Designations and Notation	3
1.3.1	NPTF Thread Class	3
1.3.2	Designation of Plated Threads	3
1.4	Applications.	3
1.4.1	Type.	3
1.4.1.1	NPTF	3
1.4.1.2	PTF-SAE SHORT	3
1.4.1.3	NPSF	4
1.4.1.4	NPSI.	4
1.4.2	CLASS	4
1.4.2.1	NPTF CLASS 1.	4
1.4.2.2	NPTF CLASS 2.	4
1.5	Assembly Limitations.	4
1.6	Thread Form and Tolerance	4
1.7	Basic Dimensions.	7
1.7.1	NPTF Threads	7
1.7.2	PTF-SAE SHORT, External Threads.	8
1.7.3	PTF-SAE SHORT, Internal Threads	9
1.7.4	NPSF Threads.	10
1.7.5	NPSI Threads	10
Appendix A	Letter Symbols and Formulas	11
A.1	Symbols Designating the Dimensions of Pipe Threads.	11
A.2	Formulas for Diameter and Length of Thread	11
Appendix B	Suggested Tap Drill Sizes for Internal Dryseal Pipe Threads	14
Appendix C	Special Short, Special Extra Short, Fine, and Special Diameter-Pitch Combination Dryseal Pipe Threads	15
C.1	Dryseal Special Short Taper Pipe Thread, PTF-SPL SHORT	15
C.2	Dryseal Special Extra Short Taper Pipe Thread, PTF-SPL EXTRA SHORT	15
C.3	Limitations of Assembly.	15
C.4	Dryseal Fine Taper Thread Series, F-PTF.	16
C.5	Dryseal Special Diameter-Pitch Combination Series, SPL-PTF	16
C.6	Formulas for Diameter and Length of Thread	16
C.7	Designations.	16
Table 1	Recommended Limitations of Assembly Among the Various Types of Dryseal Threads	5
2	Reference Dimensions for Assembled Engagement of Dryseal Pipe Threads	5
3	Basic Dimensions for NPTF Threads	7
4	Basic Dimensions for PTF-SAE SHORT, External Threads	8

	Page
Table 5 Basic Dimensions for PTF-SAE SHORT, Internal Threads	9
6 Dimensional Data for NPSF Threads	10
7 Dimensional Data for NPSI Threads	10
A1 Pipe Thread Symbols	12
B1 Suggested Tap Drill Sizes for Internal Dryseal Pipe Threads	14
C1 Basic Dimensions of Dryseal Fine Taper Pipe Thread, F-PTF	18
C2 Basic Dimensions of Dryseal Special Taper Pipe Thread, SPL-PTF (For Thin Wall Nominal Size OD Tubing)	19
Figure 1 Extreme Mating Conditions for Dryseal Pipe Threads	2
2 Thread Form and Limits on Root and Crest Tuncation of Product Threads	6
A1 Application of Pipe Thread Symbols	13
C1 Comparison of Special Dryseal Threads with Standard Length Dryseal Threads	17

AMERICAN NATIONAL STANDARD

INCH DRYSEAL PIPE THREADS

SECTION I
PRODUCT THREADS

1.1 Introduction

Dryseal pipe threads are based on the USA (American) pipe thread, however, they differ from the USA (American) pipe thread in that they are designed to seal pressure-tight joints without the necessity of using sealing compounds. To accomplish this some modification of thread form and greater accuracy in manufacture is required. The roots of both the external and internal threads are truncated slightly more than the crests, i.e. roots have wider flats than crests, so that metal-to-metal contact occurs at the crests and roots coincident with or prior to flank contact, see Figure 1. Thus as the threads are assembled by wrenching, the roots of the threads crush the sharper crests of the mating threads. This sealing action at both the major and minor diameters tends to prevent spiral leakage and makes the joints pressure-tight without the necessity of using sealing compounds, provided that the mating threads are in accordance with standard specifications and tolerances and are not damaged by galling in assembly. The control of crest and root truncation is simplified by the use of properly designed threading tools. Also, it is desirable that both external and internal threads have full thread height for the L_1 length. However, where not functionally objectionable, the use of a compatible lubricant or sealant may be used to minimize the possibility of galling. This is desirable in assembling Dryseal pipe threads in refrigeration and other systems to effect a pressure-tight seal.¹

1.1.1 In order to obtain a pressure tight seal using Dryseal pipe threads without a sealer, it is necessary to hold crest and root truncation of both internal and external threads within the limits specified. Unless this is done by use of threading tools with the crest and root truncation controlled so as to assure repro-

duction on the product threads, it is necessary to use a system of measuring or a system of gaging and measuring to determine conformance.

1.1.2 Even without truncation gages, the standard practice of using two separate thread gages for Dryseal pipe threads, each with a difference in truncation, length of engagement and point of engagement, provides a more detailed check of angle, lead and taper deviations than is required for non-dryseal taper pipe threads.

1.1.3 One method of checking crest truncation is by using 6 step plain gages. It should be recognized that this method may give misleading results in that the crest truncation of the product threads is always less (flat narrower) than that indicated by the position of the gages, the degree of inconsistency depending on the angle, lead and taper deviations present in the product thread.

1.1.4 Another method employs both crest and root truncation check gages. The root check gage is made with a thread form having an included angle of 50 degrees and with a smaller gage crest flat than the root flat to be checked. The major diameter of this gage is controlled in relation to 6 gaging steps in a similar manner to the plain 6 step crest check gage. Like the crest check gage, the results may be somewhat misleading except that in the case of the root check gage, the root truncation of the product thread is always more (flat wider) than is indicated by the position of the gages.

1.1.5 Unless lead, angle and taper of product threads are very well controlled, use of 6 step crest and root check gages will result in product threads with narrower crest flats and wider root flats than envisioned by the dryseal tolerances. Use of such a gaging system could result in rejection of threads which would actually conform to the dryseal tolerances specified. The only completely reliable referee method for determining whether crest and root truncation has been

¹ The refrigeration industry has generally accepted the use of a sealant to obtain an absolute pressure-tight joint, when assembling taper pipe threads.