

# Special Purpose Gear Units for Petroleum, Chemical and Gas Industry Services

ANSI/API STANDARD 613  
FIFTH EDITION, FEBRUARY 2003

ERRATA, DECEMBER 5, 2005

REAFFIRMED, AUGUST 2007



AMERICAN PETROLEUM INSTITUTE





# Special Purpose Gear Units for Petroleum, Chemical and Gas Industry Services

**Downstream Segment**

ANSI/API STANDARD 613  
FIFTH EDITION, FEBRUARY 2003

ERRATA, DECEMBER 5, 2005

REAFFIRMED, AUGUST 2007



AMERICAN PETROLEUM INSTITUTE



## SPECIAL NOTES

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations under local, state, or federal laws.

Information concerning safety and health risks and proper precautions, with respect to particular materials and conditions, should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. Sometimes a one-time extension of up to two years will be added to this review cycle. This publication will no longer be in effect five years after its publication date as an operative API standard or, where an extension has been granted, upon republication. Status of the publication can be ascertained from the API Downstream Segment [telephone (202) 682-8000]. A catalog of API publications and materials is published annually and updated quarterly by API, 1220 L Street, N.W., Washington, D.C. 20005, [www.api.org](http://www.api.org).

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this standard or comments and questions concerning the procedures under which this standard was developed should be directed in writing to the Director, Standards Department, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005, [standards@api.org](mailto:standards@api.org). Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the general manager.

API standards are published to facilitate the broad availability of proven, sound engineering and operating practices. These standards are not intended to obviate the need for applying sound engineering judgment regarding when and where these standards should be utilized. The formulation and publication of API standards is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

*All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, N.W., Washington, D.C. 20005.*

## FOREWORD

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any federal, state, or municipal regulation with which this publication may conflict.

Suggested revisions are invited and should be submitted to the standardization manager, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005.



# CONTENTS

	Page
1 GENERAL . . . . .	1
1.1 Scope . . . . .	1
1.2 Applications . . . . .	1
1.3 Alternative Designs . . . . .	1
1.4 Conflicting Requirements . . . . .	1
1.5 Definition of Terms . . . . .	1
1.6 Reference Publications . . . . .	3
1.7 Standards . . . . .	3
1.8 Units of Measure . . . . .	3
2 BASIC DESIGN . . . . .	3
2.1 General . . . . .	3
2.2 Rating . . . . .	5
2.3 Casings . . . . .	8
2.4 Casing Connections . . . . .	10
2.5 Gear Elements . . . . .	11
2.6 Dynamics . . . . .	13
2.7 Bearings and Bearing Housings . . . . .	20
2.8 Lubrication . . . . .	22
2.9 Materials . . . . .	22
2.10 Nameplates and Rotation Arrows . . . . .	23
3 ACCESSORIES . . . . .	23
3.1 General . . . . .	23
3.2 Couplings and Guards . . . . .	23
3.3 Mounting Plates . . . . .	24
3.4 Controls and Instrumentation . . . . .	25
3.5 Piping and Appurtenances . . . . .	26
3.6 Special Tools . . . . .	26
4 INSPECTION, TESTING, AND PREPARATION FOR SHIPMENT . . . . .	26
4.1 General . . . . .	26
4.2 Inspection . . . . .	26
4.3 Testing . . . . .	28
4.4 Preparation for Shipment . . . . .	30
5 VENDOR'S DATA . . . . .	32
5.1 General . . . . .	32
5.2 Proposals . . . . .	32
5.3 Contract Data . . . . .	33
APPENDIX A SPECIAL PURPOSE GEAR UNITS DATA SHEETS . . . . .	35
APPENDIX B REFERENCES . . . . .	45
APPENDIX C COUPLINGS FOR HIGH SPEED GEAR UNITS . . . . .	47
APPENDIX D RATED LOAD CURVES FOR THRUST BEARINGS WITH STANDARD 6 × 6 SHOES . . . . .	49
APPENDIX E MATERIAL SPECIFICATIONS FOR SPECIAL PURPOSE GEAR UNITS PAGE . . . . .	53

APPENDIX F	VENDOR DRAWING AND DATA REQUIREMENTS . . . . .	55
APPENDIX G	RESIDUAL UNBALANCE WORK SHEETS . . . . .	61
APPENDIX H	GEAR INSPECTION (INFORMATIVE) . . . . .	73
APPENDIX I	INSPECTOR'S CHECKLIST . . . . .	77
APPENDIX J	RATING COMPARISON API 613 VS. AGMA 2101 . . . . .	81
APPENDIX K	SHAFT END SIZING METHOD . . . . .	85
APPENDIX L	TYPICAL MOUNTING PLATES . . . . .	87

#### Tables

1	Driver Trip Speeds . . . . .	3
2	Shaft Assembly Combinations . . . . .	5
3	Minimum Gear Service Factors . . . . .	6
4	Material Index Numbers and Maximum $L/d$ Ratios . . . . .	7
5	Allowable Bending Stress Number, $S_a$ . . . . .	7
6	Minimum Tubing Wall Thickness . . . . .	9
7	Drain Pipe Sizes . . . . .	10
8	Pitch Line Velocities . . . . .	12
9	Casing Vibration Levels . . . . .	20
10	Maximum Severity of Defects in Castings . . . . .	27
E-1	Gear Unit Housings . . . . .	54
E-2	Shafts, Pinions, and Gear Wheels . . . . .	54
E-3	Fabricated Gears . . . . .	54
J-1	Allowable Contact Stress Per API . . . . .	82
J-2	Allowable Bending Stress Per API . . . . .	82
J-3	AGMA Grade 1 Allowable Stress Numbers . . . . .	83

#### Figures

1	Shaft Assembly Designations (for Parallel-shaft, Single-and Double-helical One- and Two-stage Speed Increasers and Reducers) . . . . .	4
2	Shaft Rotation Designations . . . . .	5
3	Material Index Number, Through Hardened . . . . .	7
4	Allowable Bending Stress Number, $S_a$ . . . . .	8
5	Typical Torsiograph Modification . . . . .	13
6	Undamped Critical Speed Map . . . . .	15
7A	Typical Mode Shapes—SI Units . . . . .	16
7B	Typical Mode Shapes—Customary Units . . . . .	16
8	Back-to-back Locked-torque Test (Typical) . . . . .	31
C-1	Couplings for Gear Units . . . . .	48
D-1	Rated Load Curves for Thrust Bearings with Standard $6 \times 6$ Shoes: Outside Diameters from 5 in. – 8 in. . . . .	50
D-2	Rated Load Curves for Thrust Bearings with Standard $6 \times 6$ Shoes: Outside Diameters from 9 in. – 15 in. . . . .	51
G-1	(Blank) Residual Unbalance Work Sheet . . . . .	63
G-2	(Blank) Residual Unbalance Polar Plot Work Sheet . . . . .	64
G-3	Sample Residual Unbalance Work Sheet for Left Plane . . . . .	65
G-4	Sample Residual Unbalance Polar Plot Work Sheet for Left Plane . . . . .	66
G-5	Sample Residual Unbalance Work Sheet for Right Plane . . . . .	67
G-6	Sample Residual Unbalance Polar Plot Work Sheet for Right Plane . . . . .	68
G-7	Work Sheet—Customary . . . . .	69
G-8	Polar Plot—Customary . . . . .	70



	Page
G-9 Work Sheet—SI . . . . .	71
G-10 Polar Plot—SI . . . . .	72
H-1 Tooth Alignment (Lead) Modification of Helical Pinion . . . . .	74
H-2 Profile Modification . . . . .	75
L-1 Mounting Plate with Subplates . . . . .	87
L-2 Mounting Plate without Subplates . . . . .	88



# Special Purpose Gear Units for Petroleum, Chemical, and Gas Industry Services

## 1 General

### 1.1 SCOPE

This standard covers the minimum requirements for special-purpose, enclosed, precision single- and double-helical one- and two-stage speed increasers and reducers of parallel-shaft design for petroleum, chemical and gas industry services. This standard is primarily intended for gear units that are in continuous service without installed spare equipment. Gear sets furnished to this standard shall be considered matched sets.

Note: The purchase of a spare set of gear rotors or a complete gear unit does not mean that the equipment is spared.

This standard includes related lubricating systems, controls, instrumentation, and other auxiliary equipment. This standard is not intended to apply to gear units in general-purpose service, which are covered by API Std 677; to gears integral with other equipment, such as integrally geared compressors covered by Std 617 or Std 672; or to gears other than helical.

Note: A bullet (●) at the beginning of a paragraph indicates that either a decision is required or further information is to be provided by the purchaser. This information should be indicated on the data sheets (see Appendix A); otherwise, it should be stated in the quotation request or in the order.

### 1.2 APPLICATIONS

The following gear-driven applications may be covered by this standard:

- a. Speed increasers, including those for centrifugal compressors, axial compressors, blowers, rotary positive displacement compressors, separators, and centrifugal pumps.
- b. Speed reducers, including those for reciprocating compressors, rotary positive displacement compressors, centrifugal compressors, centrifugal pumps, extruders, generators, and fans.

### 1.3 ALTERNATIVE DESIGNS

The vendor may offer alternative designs. Any exceptions to the standard including, alternate design differences from this standard, shall be clearly stated in the proposal as required by 5.2.1.

### 1.4 CONFLICTING REQUIREMENTS

In case of conflict between this standard and the inquiry, the inquiry shall govern. At the time of the order, the order shall govern.

## 1.5 DEFINITION OF TERMS

Terms used in this standard are defined in 1.5.1 through 1.5.38.

**1.5.1 axially (horizontally) split** refers to casing joints that are parallel to the shaft centerline.

**1.5.2 The bending stress number (S)** corresponds to the likelihood of fatigue cracking at the tooth root fillet. If this stress is excessive, it may lead to failure of the gear teeth.

**1.5.3 critical speed** is a shaft rotational speed at which the rotor bearing support system is in a state of resonance (see 2.6.1).

**1.5.4** The use of the word **design** in any term (such as design horsepower, design pressure, design temperature, or design speed) should be avoided in the purchaser's specifications. This terminology should be used only by the equipment designer and the manufacturer.

**1.5.5 gauss levels** refers to the magnetic field level of a component measured with a "Hall effect" probe, with no interference from adjacent magnetic part or structures.

**1.5.6 gear** refers to either the pinion or the gear wheel.

**1.5.7 The gear service factor (SF)** is the factor that is applied to the tooth pitting index and the bending stress number, depending on the characteristics of the driver and the driven equipment, to account for differences in potential overload, shock load, and/or continuous oscillatory torque characteristics.

**1.5.8 gear unit** is the complete power transmission assembly including the housing, gears, and bearings.

**1.5.9 gear unit rated power** is the maximum power specified by the purchaser on the data sheet and stamped on the nameplate (see 2.2.1).

**1.5.10 gear wheel (bull gear)** refers to the lowest speed rotor.

**1.5.11 A hunting tooth combination** exists for mating gears when a tooth on the pinion does not repeat contact with a tooth on the gear wheel until it has contacted all the other gear wheel teeth.

**1.5.12 informative element:** Describes part of the standard which is provided for information and to assist in the understanding or use of the standard. Compliance with an informative part of the standard is not mandated.

Note: An appendix may be informative or normative as indicated.

**1.5.13 lead modification:** A calculated machined deviation of the pinion and/or the gear wheel tooth flank from the