## Recommended Practice for Lightning Protection of Aboveground Storage Tanks for Flammable or Combustible Liquids

**Downstream Segment** 

API RECOMMENDED PRACTICE 545 FIRST EDITION, OCTOBER 2009



### **Special Notes**

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Where applicable, authorities having jurisdiction should be consulted.

Work sites and equipment operations may differ. Users are solely responsible for assessing their specific equipment and premises in determining the appropriateness of applying the Recommended Practice. At all times users should employ sound business, scientific, engineering, and judgment safety when using this Recommended Practice.

#### Foreword

This Recommended Practice (RP) is based on the accumulated knowledge and experience of purchasers and manufacturers of welded steel oil storage tanks of various sizes and capacities for internal pressures not more than 17.2 kPa (2 ½ psi) gauge. This RP is meant to be a purchase specification to facilitate the manufacture and procurement of storage tanks for the petroleum industry. If the tanks are purchased in accordance with this RP, the purchaser is required to specify certain basic requirements. The purchaser may want to modify, delete, or amplify sections of this RP, but reference to this RP shall not be made on the nameplates of or on the manufacturer's certification for tanks that do not fulfill the minimum requirements of this RP or that exceed its limitations. It is strongly recommended that any modifications, deletions, or amplifications be made by supplementing this RP rather than by rewriting or incorporating sections of it into another complete RP. The design rules given in this RP are minimum requirements. More stringent design rules specified by the purchaser or furnished by the manufacturer are acceptable when mutually agreed upon by the purchaser and the manufacturer. This RP is not to be interpreted as approving, recommending, or endorsing any specific design or as limiting the method of design or construction.

Shall: As used in a RP, "shall" denotes a minimum requirement in order to conform to the specification.

Should: As used in a RP, "should" denotes a recommendation or that which is advised but not required in order to conform to the specification.

This RP is not intended to cover storage tanks that are to be erected in areas subject to regulations more stringent than the specifications in this RP. When this RP is specified for such tanks, it should be followed insofar as it does not conflict with local requirements. The purchaser is responsible for specifying any jurisdictional requirements applicable to the design and construction of the tank. After revisions to this RP have been issued, they may be applied to tanks that are to be completed after the date of issue. The tank nameplate shall state the date of the edition of the RP and any revision to that edition to which the tank has been designed and constructed. Each edition, revision, or addendum to this RP may be used beginning with the date of issuance shown on the cover page for that edition, revision, or addendum. Each edition, revision, or addendum to this RP becomes effective six months after the date of issuance for equipment that is certified as being constructed, and tested per this RP. During the six-month time between the date of issuance of the edition, revision, or addendum and the effective date, the purchaser and the manufacturer shall specify to which edition, revision, or addendum the equipment is to be constructed and tested. API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any federal, state, or municipal regulation with which this publication may conflict.

API standards are published as an aid to procurement of standardized equipment and materials and/or as good practice procedures. These standards are not intended to inhibit purchasers or producers from purchasing or producing products made to specifications other than those of API.

This publication was produced following API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard.

Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, API, 1220 L Street, NW, Washington, DC 20005.

Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the Director of Standards. Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, 1220 L Street, NW, Washington, DC 20005.

A catalogue of API publications can be found at www.api.org/publications.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, <a href="mailto:standards@api.org">standards@api.org</a>.

### **Contents**

	P	age
1 1.1	Scope	
1.2	Application of Requirements to New and Existing Tanks	
2	Normative References	1
3	Terms and Definitions	2
4 4.1 4.2	Protection of Specific Types of Tanks	3
5	Metal Thickness	4
6	Inspection and Maintenance Requirements	4
Ann	ex A (informative) General	5
Ann	ex B (informative) Understanding Lightning Discharge and its Secondary Effects	. 11
Ann	ex C (informative) Different Seal Types	. 12
Figu		_
	The Process of Attachment from Lightning Cloud to a Tank	
	Current Routes for Flash to a) Top of Shell, b) Floating Roof, c) Ground Near a Floating-roof Tank	
Tabl	e e	
<b>A.1</b>	Lightning Parameters	8

# Recommended Practice for Lightning Protection of Aboveground Storage Tanks for Flammable or Combustible Liquids

### 1 Scope

API RP 545, First Edition, Recommended Practice for Lightning Protection of Aboveground Storage Tanks for Flammable or Combustible Liquids, replaces the requirements of API 2003 regarding lightning protection for preventing fires in storage tanks with flammable or combustible contents. This recommended practice (RP) provides guidance and information to assist owners/operators with lightning protection for tanks. This RP does not provide complete protection for all possible lightning stroke occurrences.

### 1.1 Applicability

This RP is applicable to tanks as described in API 650.

### 1.2 Application of Requirements to New and Existing Tanks

The requirements of this RP shall apply to new or reconstructed tanks. The requirements may be applied to existing tanks at the discretion of the owner/operator.

### 2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API/EI Technical Report 545-A, Verification of lightning protection requirements for above ground hydrocarbon storage tanks

API Standard 650, Welded Tanks for Oil Storage

API Standard 653, Tank Inspection, Repair, Alteration, and Reconstruction

API Standard 2003, Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents

ASTM D3453 1, Standard Specification for Flexible Cellular Materials

BS EN 14015 <sup>2</sup>, Specification for the design and manufacture of site built, vertical, cylindrical, flat-bottomed, above ground, welded, steel tanks for the storage of liquids at ambient temperature and above

EMMUA 159 <sup>3</sup>, Users' Guide to the Inspection, Maintenance and Repair of Aboveground Vertical Cylindrical Steel Storage Tanks

NFPA 780 <sup>4</sup>, Standard for the Installation of Lightning Protection Systems

SAE ARP 5412<sup>5</sup>, Aircraft Lightning Environment and Related Test Waveforms

<sup>&</sup>lt;sup>1</sup> ASTM International, 100 Barr Harbor Drive, West Conshohocken, Pennsylvania 19428, www.astm.org.

<sup>&</sup>lt;sup>2</sup> European Committee for Standardization, Avenue Marnix 17, B-1000, Brussels, Belgium, www.cen.eu.

The Engineering Equipment and Material Users' Association, 10-12 Lovat Lane, London, EC3R 8DN, United Kingdom, www.eemua.org.

<sup>&</sup>lt;sup>4</sup> National Fire Protection Association, 1 Batterymarch Park, Quincy, Massachusetts 02169-7471, www.nfpa.org.

<sup>&</sup>lt;sup>5</sup> Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, Pennsylvania 15096-0001, www.sae.org.