

ETSI TS 136 300 V12.7.0 (2015-10)



LTE;
**Evolved Universal Terrestrial Radio Access (E-UTRA)
and Evolved Universal Terrestrial
Radio Access Network (E-UTRAN);
Overall description;
Stage 2**
(3GPP TS 36.300 version 12.7.0 Release 12)



Reference

RTS/TSGR-0236300vc70

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	14
1 Scope	15
2 References	15
3 Definitions, symbols and abbreviations	17
3.1 Definitions	17
3.2 Abbreviations	19
4 Overall architecture	23
4.1 Functional Split	23
4.2 Void.....	25
4.2.1 Void	25
4.2.2 Void	25
4.3 Radio Protocol architecture	25
4.3.1 User plane	25
4.3.2 Control plane	26
4.4 Synchronization.....	27
4.5 IP fragmentation.....	27
4.6 Support of HeNBs	27
4.6.1 Architecture	27
4.6.2 Functional Split.....	29
4.6.3 Interfaces.....	31
4.6.3.1 Protocol Stack for S1 User Plane	31
4.6.3.2 Protocol Stacks for S1 Control Plane	31
4.6.3.3 Protocol Stack for S5 interface.....	32
4.6.3.4 Protocol Stack for SGi interface.....	32
4.6.3.5 Protocol Stack for X2 User Plane and X2 Control Plane	32
4.6.4 Void	32
4.6.5 Support of LIPA with HeNB	32
4.6.6 Support of X2 GW	34
4.6.6.1 Enhanced TNL Address Discovery	35
4.6.6.2 Routing of X2AP messages	35
4.6.6.3 (H)eNB unavailability	35
4.6.6.4 (H)eNB registration	35
4.7 Support for relaying.....	35
4.7.1 General.....	35
4.7.2 Architecture	35
4.7.3 S1 and X2 user plane aspects.....	36
4.7.4 S1 and X2 control plane aspects	37
4.7.5 Radio protocol aspects	38
4.7.6 Signalling procedures	39
4.7.6.1 RN attach procedure.....	39
4.7.6.2 E-RAB activation/modification.....	40
4.7.6.3 RN startup procedure	40
4.7.6.4 RN detach procedure	41
4.7.6.5 Neighbouring Information Transfer	42
4.7.6.6 Mobility to or from RN	42
4.7.7 Relay Node OAM Aspects	42
4.7.7.1 Architecture.....	42
4.7.7.2 OAM Traffic QoS Requirements	43
4.7.7.3 Security Aspects.....	43
4.7.7.4 Void.....	43
4.7.7.5 OAM Requirements for Configuration Parameters.....	43

4.7.7.5.1	Parameters Associated with Relay Bearer Mapping.....	43
4.8	Support of SIPTO at the Local Network	43
4.8.1	General.....	43
4.8.2	SIPTO at the Local Network with collocated L-GW	43
4.8.3	Support for SIPTO@LN with Stand-Alone Gateway.....	45
4.9	Support for Dual Connectivity	45
4.9.1	General.....	45
4.9.2	Radio Protocol Architecture	45
4.9.3	Network Interfaces.....	45
4.9.3.1	E-UTRAN Control Plane for Dual Connectivity	45
4.9.3.2	E-UTRAN User Plane for Dual Connectivity	46
5	Physical Layer for E-UTRA.....	47
5.1	Downlink Transmission Scheme	49
5.1.1	Basic transmission scheme based on OFDM.....	49
5.1.2	Physical-layer processing	49
5.1.3	Physical downlink control channels.....	50
5.1.4	Downlink Reference signal and synchronization signals.....	50
5.1.5	Downlink multi-antenna transmission	51
5.1.6	MBSFN transmission.....	51
5.1.7	Physical layer procedure	51
5.1.7.1	Link adaptation	51
5.1.7.2	Power Control	51
5.1.7.3	Cell search.....	51
5.1.8	Physical layer measurements definition.....	51
5.1.9	Coordinated Multi-Point transmission	52
5.2	Uplink Transmission Scheme	52
5.2.1	Basic transmission scheme	52
5.2.2	Physical-layer processing	52
5.2.3	Physical uplink control channel	53
5.2.4	Uplink Reference signal.....	53
5.2.5	Random access preamble.....	53
5.2.6	Uplink multi-antenna transmission	53
5.2.7	Physical channel procedure.....	54
5.2.7.1	Link adaptation	54
5.2.7.2	Uplink Power control	54
5.2.7.3	Uplink timing control	54
5.2.8	Coordinated Multi-Point reception	54
5.3	Transport Channels.....	54
5.3.1	Mapping between transport channels and physical channels.....	56
5.4	E-UTRA physical layer model	57
5.4.1	Void	57
5.4.2	Void	57
5.5	Carrier Aggregation.....	57
5.6	Sidelink	57
5.6.1	Basic transmission scheme	58
5.6.2	Physical-layer processing	58
5.6.3	Physical Sidelink control channel	58
5.6.4	Sidelink reference signals	58
5.6.5	Physical channel procedure.....	58
5.6.5.1	Sidelink power control	58
6	Layer 2.....	58
6.1	MAC Sublayer.....	60
6.1.1	Services and Functions	60
6.1.2	Logical Channels	61
6.1.2.1	Control Channels.....	61
6.1.2.2	Traffic Channels.....	61
6.1.3	Mapping between logical channels and transport channels	62
6.1.3.1	Mapping in Uplink	62
6.1.3.2	Mapping in Downlink	62
6.1.3.3	Mapping in Sidelink	63

6.2	RLC Sublayer	63
6.2.1	Services and Functions	63
6.2.2	PDU Structure.....	63
6.3	PDCP Sublayer.....	64
6.3.1	Services and Functions	64
6.3.2	PDU Structure.....	64
6.4	Carrier Aggregation.....	65
6.5	Dual Connectivity.....	66
7	RRC	67
7.1	Services and Functions	67
7.2	RRC protocol states & state transitions	68
7.3	Transport of NAS messages	69
7.4	System Information	69
7.5	Carrier Aggregation.....	70
7.6	Dual Connectivity.....	71
8	E-UTRAN identities.....	72
8.1	E-UTRAN related UE identities.....	72
8.2	Network entity related Identities	72
8.3	Sidelink communication related identities	73
9	ARQ and HARQ	73
9.1	HARQ principles.....	73
9.2	ARQ principles.....	74
9.3	Void.....	74
10	Mobility.....	74
10.1	Intra E-UTRAN	75
10.1.1	Mobility Management in ECM-IDLE	75
10.1.1.1	Cell selection.....	75
10.1.1.2	Cell reselection.....	76
10.1.1.3	Void.....	76
10.1.1.4	Void.....	76
10.1.1.5	Void.....	76
10.1.2	Mobility Management in ECM-CONNECTED.....	76
10.1.2.1	Handover	77
10.1.2.1.1	C-plane handling	77
10.1.2.1.2	U-plane handling	80
10.1.2.2	Path Switch	81
10.1.2.2.1	Path Switch upon handover	81
10.1.2.2.2	Path Update upon Dual Connectivity specific activities.....	81
10.1.2.3	Data forwarding	82
10.1.2.3.1	For RLC-AM DRBs	82
10.1.2.3.2	For RLC-UM DRBs	83
10.1.2.3.3	SRB handling	83
10.1.2.3.4	User data forwarding for Dual Connectivity	83
10.1.2.4	Void.....	83
10.1.2.5	Void.....	83
10.1.2.6	Void.....	83
10.1.2.7	Timing Advance.....	83
10.1.2.8	Dual Connectivity operation	84
10.1.2.8.1	SeNB Addition	84
10.1.2.8.2	SeNB Modification.....	85
10.1.2.8.2.1	Intra-MeNB handover involving SCG change	88
10.1.2.8.3	SeNB Release	89
10.1.2.8.4	Change of SeNB	90
10.1.2.8.5	MeNB to eNB Change.....	91
10.1.2.8.6	SCG change	92
10.1.3	Measurements	93
10.1.3.1	Intra-frequency neighbour (cell) measurements.....	94
10.1.3.2	Inter-frequency neighbour (cell) measurements.....	95
10.1.4	Paging and C-plane establishment	95

10.1.5	Random Access Procedure	95
10.1.5.1	Contention based random access procedure.....	96
10.1.5.2	Non-contention based random access procedure	97
10.1.5.3	Interaction model between L1 and L2/3 for Random Access Procedure	99
10.1.6	Radio Link Failure	99
10.1.7	Radio Access Network Sharing	100
10.1.8	Handling of Roaming and Area Restrictions for UEs in ECM-CONNECTED	101
10.1.8a	Handling of Roaming and Access Restrictions for UEs in ECM-CONNECTED	101
10.2	Inter RAT	101
10.2.1	Cell reselection	101
10.2.2	Handover	102
10.2.2a	Inter-RAT cell change order to GERAN with NACC	102
10.2.2b	Inter-RAT handovers from E-UTRAN	102
10.2.2b.1	Data forwarding	102
10.2.2b.1.1	For RLC-AM bearers	102
10.2.2b.1.2	For RLC-UM bearers	103
10.2.3	Measurements	103
10.2.3.1	Inter-RAT handovers from E-UTRAN	103
10.2.3.2	Inter-RAT handovers to E-UTRAN	103
10.2.3.3	Inter-RAT cell reselection from E-UTRAN	103
10.2.3.4	Limiting measurement load at UE	103
10.2.4	Network Aspects.....	104
10.2.5	CS fallback.....	104
10.3	Mobility between E-UTRAN and Non-3GPP radio technologies	105
10.3.1	UE Capability Configuration	105
10.3.2	Mobility between E-UTRAN and cdma2000 network	105
10.3.2.1	Tunnelling of cdma2000 Messages over E-UTRAN between UE and cdma2000 Access Nodes	105
10.3.2.2	Mobility between E-UTRAN and HRPD.....	106
10.3.2.2.1	Mobility from E-UTRAN to HRPD	106
10.3.2.2.1.1	HRPD System Information Transmission in E-UTRAN	106
10.3.2.2.1.2	Measuring HRPD from E-UTRAN.....	107
10.3.2.2.1.2.1	Idle Mode Measurement Control	107
10.3.2.2.1.2.2	Active Mode Measurement Control	107
10.3.2.2.1.2.3	Active Mode Measurement	107
10.3.2.2.1.3	Pre-registration to HRPD Procedure	107
10.3.2.2.1.4	E-UTRAN to HRPD Cell Re-selection.....	107
10.3.2.2.1.5	E-UTRAN to HRPD Handover.....	107
10.3.2.2.2	Mobility from HRPD to E-UTRAN	108
10.3.2.3	Mobility between E-UTRAN and cdma2000 1xRTT	108
10.3.2.3.1	Mobility from E-UTRAN to cdma2000 1xRTT.....	108
10.3.2.3.1.1	cdma2000 1xRTT System Information Transmission in E-UTRAN	108
10.3.2.3.1.2	Measuring cdma2000 1xRTT from E-UTRAN	108
10.3.2.3.1.2.1	Idle Mode Measurement Control	108
10.3.2.3.1.2.2	Active Mode Measurement Control.....	108
10.3.2.3.1.2.3	Active Mode Measurement	109
10.3.2.3.1.3	E-UTRAN to cdma2000 1xRTT Cell Re-selection.....	109
10.3.2.3.1.4	E-UTRAN to cdma2000 1xRTT Handover	109
10.3.2.3.2	Mobility from cdma2000 1xRTT to E-UTRAN	109
10.3.2.3.3	1xRTT CS Fallback	109
10.3.3	CDMA2000 interworking in LTE shared networks.....	111
10.4	Area Restrictions	111
10.4a	Roaming and Access Restrictions	111
10.5	Mobility to and from CSG and Hybrid cells	112
10.5.0	Principles for idle-mode mobility with CSG cells	112
10.5.0.1	Intra-frequency mobility	112
10.5.0.2	Inter-frequency mobility	112
10.5.0.3	Inter-RAT Mobility	112
10.5.1	Inbound mobility to CSG cells	112
10.5.1.1	RRC_IDLE.....	112
10.5.1.2	RRC_CONNECTED.....	112
10.5.2	Outbound mobility from CSG cells	115
10.5.2.1	RRC_IDLE.....	115

10.5.2.2	RRC_CONNECTED.....	115
10.6	Measurement Model.....	115
10.7	Hybrid Cells	116
10.7.1	RRC_IDLE	116
10.7.2	RRC_CONNECTED	116
10.7.2.1	Inbound Mobility	116
10.7.2.2	Outbound Mobility.....	116
11	Scheduling and Rate Control.....	116
11.1	Basic Scheduler Operation	116
11.1.1	Downlink Scheduling	117
11.1.2	Uplink Scheduling	118
11.2	Activation/Deactivation Mechanism	118
11.3	Measurements to Support Scheduler Operation	119
11.4	Rate Control of GBR, MBR and UE-AMBR	119
11.4.1	Downlink	119
11.4.2	Uplink	119
11.4.3	UE-AMBR for Dual Connectivity	119
11.5	CQI reporting for Scheduling	120
11.6	Explicit Congestion Notification.....	120
12	DRX in RRC_CONNECTED	120
13	QoS.....	122
13.1	Bearer service architecture	122
13.2	QoS parameters	123
13.3	QoS support in Hybrid Cells	123
14	Security.....	124
14.1	Overview and Principles	124
14.2	Security termination points.....	126
14.3	State Transitions and Mobility	127
14.3.1	RRC_IDLE to RRC_CONNECTED	127
14.3.2	RRC_CONNECTED to RRC_IDLE	127
14.3.3	Intra E-UTRAN Mobility	127
14.3.4	SeNB Removal	128
14.4	AS Key Change in RRC_CONNECTED.....	128
14.5	Security Interworking.....	128
14.6	RN integrity protection for DRB(s).....	128
15	MBMS	128
15.1	General	129
15.1.1	E-MBMS Logical Architecture.....	130
15.1.2	E-MBMS User Plane Protocol Architecture	131
15.1.3	E-MBMS Control Plane Protocol Architecture	132
15.2	MBMS Cells.....	132
15.2.1	MBMS-dedicated cell	132
15.2.2	MBMS/Unicast-mixed cell	132
15.3	MBMS Transmission.....	133
15.3.1	General.....	133
15.3.2	Single-cell transmission	133
15.3.3	Multi-cell transmission	133
15.3.4	MBMS Reception States.....	134
15.3.5	MCCH Structure	135
15.3.6	MBMS signalling on BCCH	135
15.3.7	MBMS User Data flow synchronisation.....	135
15.3.8	Synchronisation of MCCH Update Signalling via M2	136
15.3.9	IP Multicast Distribution	137
15.4	Service Continuity.....	137
15.5	Network sharing	138
15.6	Network Functions for Support of Multiplexing	139
15.7	Procedures	139
15.7.1	Procedures for Broadcast mode	139
15.7.1.1	Session Start procedure	139

15.7.1.2	Session Stop procedure	141
15.7a	M1 Interface	141
15.7a.1	M1 User Plane	141
15.8	M2 Interface	142
15.8.1	M2 Control Plane.....	142
15.8.2	M2 Interface Functions.....	143
15.8.2.1	General	143
15.8.2.2	MBMS Session Handling Function.....	143
15.8.2.3	MBMS Scheduling Information Provision Function	143
15.8.2.4	M2 Interface Management Function	143
15.8.2.5	M2 Configuration Function.....	143
15.8.2.6	MBMS Service Counting Function.....	143
15.8.2.7	MBMS Service Suspension and Resumption Function.....	143
15.8.2.8	MBMS Overload Notification Function.....	144
15.8.3	M2 Interface Signalling Procedures.....	144
15.8.3.1	General	144
15.8.3.2	MBMS Session signalling procedure	144
15.8.3.3	MBMS Scheduling Information procedure	144
15.8.3.4	M2 Interface Management procedures.....	144
15.8.3.4.1	Reset procedure	144
15.8.3.4.2	Error Indication procedure.....	144
15.8.3.5	M2 Configuration procedures	144
15.8.3.5.1	M2 Setup procedure	144
15.8.3.5.2	eNB Configuration Update procedure	144
15.8.3.5.3	MCE Configuration Update procedure.....	144
15.8.3.6	MBMS Service Counting procedures	144
15.8.3.6.1	MBMS Service Counting procedure	144
15.8.3.6.2	MBMS Service Counting Results Report procedure	145
15.8.3.7	MBMS Overload Notification procedure.....	145
15.9	M3 Interface	145
15.9.1	M3 Control Plane.....	145
15.9.2	M3 Interface Functions	145
15.9.2.1	General	145
15.9.2.2	MBMS Session Handling Function.....	146
15.9.2.3	M3 Interface Management Function	146
15.9.2.4	M3 Configuration Function.....	146
15.9.3	M3 Interface Signalling Procedures.....	146
15.9.3.1	General	146
15.9.3.2	MBMS Session signalling procedure	146
15.9.3.3	M3 Interface Management procedures.....	146
15.9.3.3.1	Reset procedure	146
15.9.3.3.2	Error Indication procedure.....	146
15.9.3.4	M3 Configuration procedures	146
15.9.3.4.1	M3 Setup procedure	146
15.9.3.4.2	MCE Configuration Update procedure.....	147
15.10	MBMS Counting	147
15.10.1	General.....	147
15.10.2	Counting Procedure	147
16	Radio Resource Management aspects	147
16.1	RRM functions	147
16.1.1	Radio Bearer Control (RBC)	147
16.1.2	Radio Admission Control (RAC).....	148
16.1.3	Connection Mobility Control (CMC)	148
16.1.4	Dynamic Resource Allocation (DRA) - Packet Scheduling (PS)	148
16.1.5	Inter-cell Interference Coordination (ICIC)	148
16.1.5.1	UE configurations for time domain ICIC.....	149
16.1.5.2	OAM requirements for time domain ICIC	149
16.1.5.2.1	Configuration for CSG cell.....	149
16.1.5.2.2	Configuration for interfering non-CSG cell.....	149
16.1.6	Load Balancing (LB)	150
16.1.7	Inter-RAT Radio Resource Management	150

16.1.8	Subscriber Profile ID for RAT/Frequency Priority.....	150
16.1.9	Inter-eNB CoMP.....	150
16.1.10	Cell on/off and cell discovery	150
16.2	RRM architecture	151
16.2.1	Centralised Handling of certain RRM Functions.....	151
16.2.2	De-Centralised RRM	151
16.2.2.1	UE History Information	151
16.2.3	Void	151
16.3	UE assistance information for RRM and UE power optimisations	151
17	Void.....	151
17.1	Void.....	151
18	UE capabilities	151
19	S1 Interface	153
19.1	S1 User plane	153
19.2	S1 Control Plane.....	153
19.2.1	S1 Interface Functions	154
19.2.1.1	S1 Paging function	155
19.2.1.2	S1 UE Context Management function.....	155
19.2.1.3	Initial Context Setup Function	155
19.2.1.3a	UE Context Modification Function.....	155
19.2.1.4	Mobility Functions for UEs in ECM-CONNECTED	155
19.2.1.4.1	Intra-LTE Handover	155
19.2.1.4.2	Inter-3GPP-RAT Handover.....	155
19.2.1.5	E-RAB Service Management function.....	155
19.2.1.6	NAS Signalling Transport function.....	155
19.2.1.7	NAS Node Selection Function (NNSF)	155
19.2.1.8	S1-interface management functions	156
19.2.1.9	MME Load balancing Function	156
19.2.1.10	Location Reporting Function	156
19.2.1.11	Warning Message Transmission function.....	156
19.2.1.12	Overload Function.....	156
19.2.1.13	RAN Information Management Function	156
19.2.1.14	S1 CDMA2000 Tunnelling function.....	156
19.2.1.15	Configuration Transfer Function.....	156
19.2.1.16	LPPa Signalling Transport function	157
19.2.1.17	Trace Function	157
19.2.1.18	UE Radio Capability Match.....	157
19.2.2	S1 Interface Signalling Procedures	157
19.2.2.1	Paging procedure.....	157
19.2.2.2	S1 UE Context Release procedure	157
19.2.2.2.1	S1 UE Context Release (EPC triggered)	157
19.2.2.2.2	S1 UE Context Release Request (eNB triggered).....	158
19.2.2.3	Initial Context Setup procedure.....	158
19.2.2.3a	UE Context Modification procedure	159
19.2.2.4	E-RAB signalling procedures.....	160
19.2.2.4.1	E-RAB Setup procedure	160
19.2.2.4.2	E-RAB Modification procedure	161
19.2.2.4.3	E-RAB Release procedure.....	162
19.2.2.4.4	E-RAB Release Indication procedure	162
19.2.2.4.5	E-RAB Modification Indication procedure	163
19.2.2.5	Handover signalling procedures	163
19.2.2.5.1	Handover Preparation procedure	163
19.2.2.5.2	Handover Resource Allocation procedure	164
19.2.2.5.3	Handover Notification procedure	165
19.2.2.5.4	Handover Cancellation	165
19.2.2.5.5	Path Switch procedure	165
19.2.2.5.6	Message sequence diagrams	166
19.2.2.5.7	eNB Status Transfer procedure	174
19.2.2.5.8	MME Status Transfer procedure	175
19.2.2.6	NAS transport procedures	175

19.2.2.7	S1 interface Management procedures	177
19.2.2.7.1	Reset procedure	177
19.2.2.7.1a	eNB initiated Reset procedure	177
19.2.2.7.1b	MME initiated Reset procedure	177
19.2.2.7.2	Error Indication functions and procedures	178
19.2.2.7.2a	eNB initiated error indication	178
19.2.2.7.2b	MME initiated error indication	178
19.2.2.8	S1 Setup procedure	178
19.2.2.9	eNB Configuration Update procedure	179
19.2.2.9a	eNB Configuration Transfer procedure	179
19.2.2.10	MME Configuration Update procedure	180
19.2.2.10a	MME Configuration Transfer procedure	180
19.2.2.11	Location Reporting procedures	181
19.2.2.11.1	Location Reporting Control procedure	181
19.2.2.11.2	Location Report procedure	181
19.2.2.11.3	Location Report Failure Indication procedure	182
19.2.2.12	Overload procedure	182
19.2.2.12.1	Overload Start procedure	182
19.2.2.12.2	Overload Stop procedure	182
19.2.2.13	Write-Replace Warning procedure	183
19.2.2.14	eNB Direct Information Transfer procedure	183
19.2.2.15	MME Direct Information Transfer procedure	184
19.2.2.16	S1 CDMA2000 Tunnelling procedures	184
19.2.2.16.1	Downlink S1 CDMA2000 Tunnelling procedure	184
19.2.2.16.2	Uplink S1 CDMA2000 Tunnelling procedure	185
19.2.2.17	Kill procedure	185
19.2.2.18	LPPa Transport procedures	185
19.2.2.18.1	Downlink UE Associated LPPa Transport procedure	186
19.2.2.18.2	Uplink UE Associated LPPa Transport procedure	186
19.2.2.18.3	Downlink Non UE Associated LPPa Transport procedure	186
19.2.2.18.4	Uplink Non UE Associated LPPa Transport procedure	187
19.2.2.19	Trace procedures	187
19.2.2.19.1	Trace Start procedure	187
19.2.2.19.2	Trace Failure Indication procedure	188
19.2.2.19.3	Deactivate Trace procedure	188
19.2.2.19.4	Cell Traffic Trace procedure	188
19.2.2.20	UE Capability Info Indication procedure	188
19.2.2.21	UE Radio Capability Match procedure	189
19.2.2.22	PWS Restart Indication procedure	189
20	X2 Interface	190
20.1	User Plane	190
20.1.1	Flow Control Functions	190
20.2	Control Plane	190
20.2.1	X2-CP Functions	191
20.2.2	X2-CP Procedures	192
20.2.2.1	Handover Preparation procedure	192
20.2.2.2	Handover Cancel procedure	192
20.2.2.2a	SeNB Addition Preparation procedure	193
20.2.2.2b	SeNB Reconfiguration Completion procedure	193
20.2.2.2c	MeNB initiated SeNB Modification Preparation procedure	194
20.2.2.2d	SeNB initiated SeNB Modification procedure	194
20.2.2.2e	MeNB initiated SeNB Release procedure	195
20.2.2.2f	SeNB initiated SeNB Release procedure	195
20.2.2.2g	SeNB Counter Check procedure	195
20.2.2.3	UE Context Release procedure	196
20.2.2.4	SN Status Transfer procedure	196
20.2.2.5	Error Indication procedure	196
20.2.2.6	Load Indication procedure	197
20.2.2.7	X2 Setup procedure	197
20.2.2.8	eNB Configuration Update procedure	198
20.2.2.9	Reset procedure	198

20.2.2.10	Resource Status Reporting Initiation procedure	199
20.2.2.11	Resource Status Reporting procedure	199
20.2.2.12	Radio Link Failure Indication procedure	199
20.2.2.13	Handover Report procedure	200
20.2.2.14	Mobility Settings Change procedure	200
20.2.2.15	Cell Activation procedure	201
20.2.2.16	X2 Release procedure	201
20.2.2.17	X2AP Message Transfer procedure	201
20.2.2.18	X2 Removal procedure	202
20.2.3	Void	202
21	Void	202
21.1	Void	202
21.2	Void	202
21.3	Void	202
22	Support for self-configuration and self-optimisation	202
22.1	Definitions	202
22.2	UE Support for self-configuration and self-optimisation	203
22.3	Self-configuration	203
22.3.1	Dynamic configuration of the S1-MME interface	203
22.3.1.1	Prerequisites	203
22.3.1.2	SCTP initialization	204
22.3.1.3	Application layer initialization	204
22.3.2	Dynamic Configuration of the X2 interface	204
22.3.2.1	Prerequisites	204
22.3.2.2	SCTP initialization	204
22.3.2.3	Application layer initialization	204
22.3.2a	Automatic Neighbour Relation Function	204
22.3.3	Intra-LTE/frequency Automatic Neighbour Relation Function	206
22.3.4	Inter-RAT/Inter-frequency Automatic Neighbour Relation Function	207
22.3.5	Framework for PCI Selection	208
22.3.6	TNL address discovery	208
22.3.6.1	TNL address discovery of candidate eNB via S1 interface	208
22.4	Self-optimisation	209
22.4.1	Support for Mobility Load Balancing	209
22.4.1.1	General	209
22.4.1.2.1	Load reporting for intra-LTE scenario	210
22.4.1.2.2	Load reporting for inter-RAT scenario	210
22.4.2	Support for Mobility Robustness Optimisation	211
22.4.2.1	General	211
22.4.2.2	Connection failure due to intra-LTE mobility	211
22.4.2.2a	Connection failure due to inter-RAT mobility	214
22.4.2.3	Unnecessary HO to another RAT	214
22.4.2.4	O&M Requirements	215
22.4.2.5	Inter-RAT ping-pong	215
22.4.3	Support for RACH Optimisation	216
22.4.4	Support for Energy Saving	216
22.4.4.1	General	216
22.4.4.2	Solution description	216
22.4.4.3	O&M requirements	217
22.4.5	Radio Link Failure report	217
22.5	Void	218
22.6	Void	218
23	Others	218
23.1	Support for real time IMS services	218
23.1.1	IMS Emergency Call	218
23.2	Subscriber and equipment trace	218
23.2.1	Signalling activation	218
23.2.2	Management activation	219
23.3	E-UTRAN Support for Warning Systems	219
23.3.1	Earthquake and Tsunami Warning System	219

23.3.2	Commercial Mobile Alert System	219
23.3.3	Korean Public Alert System.....	219
23.3.4	EU-Alert	219
23.4	Interference avoidance for in-device coexistence.....	219
23.4.1	Problems	219
23.4.2	Solutions	220
23.5	TDD Enhanced Interference Management and Traffic Adaptation (eIMTA)	221
23.6	RAN assisted WLAN interworking.....	222
23.6.1	General principles	222
23.6.2	Access network selection and traffic steering rules	222
23.7	Support of Low Complexity UEs	223
23.8	Support for Radio Interface based Synchronization	223
23.9	Network-assisted interference cancellation/suppression	223
23.10	Support for sidelink communication	223
23.10.1	General.....	223
23.10.2	Radio Protocol Architecture	224
23.10.2.1	User plane	224
23.10.2.2	Control plane.....	224
23.10.3	Radio resource allocation.....	225
23.10.3.1	Resource Pool for sidelink control information	226
23.10.3.2	Resource Pool for sidelink data.....	227
23.11	Support for sidelink discovery.....	227
23.11.1	General.....	227
23.11.2	Radio Protocol Architecture	228
23.11.3	Radio resource allocation.....	228
Annex A (informative):	NAS Overview.....	230
A.1	Services and Functions	230
A.2	NAS protocol states & state transitions.....	230
Annex B (informative):	MAC and RRC Control	231
B.1	Difference between MAC and RRC control	231
B.2	Void.....	231
Annex C (informative):	Void	232
Annex D (informative):	Void	233
Annex E (informative):	Void	234
Annex F (informative):	Void	235
Annex G (informative):	Guideline for E-UTRAN UE capabilities.....	236
Annex H (informative):	Void	238
Annex I (informative):	SPID ranges and mapping of SPID values to cell reselection and inter-RAT/inter frequency handover priorities	239
I.1	SPID ranges.....	239
I.2	Reference SPID values	239
Annex J (informative):	Carrier Aggregation	241
J.1	Deployment Scenarios.....	241
J.2	Void.....	242
J.3	Void.....	242
J.4	Void.....	242
J.5	Void.....	242
J.6	Void.....	242
Annex K (informative):	Time domain ICIC.....	243

K.1	Deployment scenarios	243
K.1.1	CSG scenario	243
K.1.2	Pico scenario.....	244
Annex L (informative):	Void	245
Annex M (informative):	Dual Connectivity	246
M.1	Dual Connectivity operation.....	246
M.2	Operation Overview	246
Annex N (informative):	Sidelink communication.....	250
N.1	Deployment Scenarios.....	250
Annex O (informative):	Change history	251
History		263

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document provides an overview and overall description of the E-UTRAN radio interface protocol architecture. Details of the radio interface protocols are specified in companion specifications of the 36 series.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TR 25.913: "Requirements for Evolved UTRA (E-UTRA) and Evolved UTRAN (E-UTRAN)".
- [3] 3GPP TS 36.201: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer; General description".
- [4] 3GPP TS 36.211: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical Channels and Modulation".
- [5] 3GPP TS 36.212: "Evolved Universal Terrestrial Radio Access (E-UTRA); Multiplexing and channel coding".
- [6] 3GPP TS 36.213: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures".
- [7] 3GPP TS 36.214: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer; Measurements".
- [8] IETF RFC 4960 (09/2007): "Stream Control Transmission Protocol".
- [9] 3GPP TS 36.302: "Evolved Universal Terrestrial Radio Access (E-UTRA); Services provided by the physical layer".
- [10] Void
- [11] 3GPP TS 36.304: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) procedures in idle mode".
- [12] 3GPP TS 36.306: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio access capabilities".
- [13] 3GPP TS 36.321: "Evolved Universal Terrestrial Radio Access (E-UTRA); Medium Access Control (MAC) protocol specification".
- [14] 3GPP TS 36.322: "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Link Control (RLC) protocol specification".
- [15] 3GPP TS 36.323: "Evolved Universal Terrestrial Radio Access (E-UTRA); Packet Data Convergence Protocol (PDCP) specification".
- [16] 3GPP TS 36.331: "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC) protocol specification".
- [17] 3GPP TS 23.401: "Technical Specification Group Services and System Aspects; GPRS enhancements for E-UTRAN access".