# ETSI TR 129 994 V14.0.0 (2017-04)



Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE;

Recommended infrastructure measures to overcome specific Mobile Station (MS) and User Equipment (UE) faults (3GPP TR 29.994 version 14.0.0 Release 14)





# Reference RTR/TSGC-0129994ve00 Keywords

GSM,LTE,UMTS

### **ETSI**

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

## Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at <a href="https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx">https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx</a>

If you find errors in the present document, please send your comment to one of the following services: <u>https://portal.etsi.org/People/CommiteeSupportStaff.aspx</u>

## Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

**DECT**<sup>™</sup>, **PLUGTESTS**<sup>™</sup>, **UMTS**<sup>™</sup> and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**<sup>™</sup> and **LTE**<sup>™</sup> are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## **Foreword**

This Technical Report (TR) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <a href="http://webapp.etsi.org/key/queryform.asp">http://webapp.etsi.org/key/queryform.asp</a>.

# Modal verbs terminology

In the present document "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights				
Forev	Foreword			
Moda	ord			
Forev				
1	Scope	6		
2	References	6		
3	Abbreviations	6		
4	General	6		
5	Specific implementation on the radio interface	7		
5.1				
5.1.1	Justification	7		
5.1.2	Solution	7		
5.2	"Directed Retry" type Handovers	7		
5.2.1	Justification	7		
5.2.2	Solution	7		
5.3	Cell broadcast and frequency hopping	8		
5.3.1	Justification	8		
5.3.2	Solution			
5.4	Handling of Phase 2 and Phase 2+ BCCH Messages	8		
5.4.1	Justification	8		
5.4.2	Solution	8		
5.5	Handling of Phase 2 and Phase 2+ SACCH Messages			
5.5.1	Justification			
5.5.2	Solution			
5.6	Handling of assignment message using Mobile Allocation IE including ARFCN=0			
5.6.1	Justification			
5.6.2	Solution			
5.7	Hopping sequence generation including ARFCN=0			
5.7.1	Justification			
5.7.2	Solution			
5.8	QoS IE length between R97 and R99 implementations			
5.8.1	Justification			
5.8.2	Solution	10		
5.9	MS unable to handle the LOCATION UPDATING ACCEPT, ATTACH ACCEPT and ROUTING			
	AREA UPDATE ACCEPT messages when the EPLMN Lists IE is included			
5.9.1	Justification			
5.9.2	Solution			
5.10	MS unable to handle messages when the truncation function is used			
5.10.1				
5.10.2				
5.11	Roaming restrictions issues with reject cause #13 and #15			
5.11.1				
5.11.2	Solution	12		
6	Use of VAD/DTX in conjunction with frequency hopping for a speech call	12		
6.1	Scope			
6.2	General			
6.3	Implementation options to reduce the occurance of undetected bad frames by utilising normal system	12		
0.3	featuresfeatures features featu	12		
6.3.1	Number of frequency hopping channels			
6.3.2	Frequency hopping type			
6.3.3				
0.5.5	Continuous SID frames on C0	13		

6.4	Implementation options to reduce the occurance of undetected bad frames by changing normal system	
	operation	
6.4.1	Changing the training sequence of the dummy burst to a new (ninth) training sequence	14
6.4.2	Using an alternative training sequence out of the eight assigned	14
6.4.3	Setting the stealing flag for the bits transmitted which are not intended to be part of the TCH	14
6.4.4	Sending partial SID frames on C0	14
6.5	Tested Combinations	14
6.5.1	"Normal" system	15
6.5.2	New training sequence	
6.5.3	Alternative training sequence from the eight assigned	15
6.5.4	Setting stealing flag for unintentionally transmitted bits	15
6.5.5	Setting stealing flag for unintentionally transmitted bits and modifying training sequence for	
	Dummy Bursts	16
6.5.6	Sending partial SID information on C0	16
Annex A	: Amendment Request 08.08 - 021 R4: Information on channel in use in HO	
	REQUEST	17
A.3.1.5.1.		
A.3.1.5.2	Handover Resource allocation	
A.3.1.5.2.		
A.3.2.1.8	HANDOVER REQUEST	
A.3.2.1.9	HANDOVER REQUIRED	
A.3.2.2.49		
Annex B	: Change History	23
History		

# **Foreword**

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

### where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

# 1 Scope

The present document clarifies recommended measures which may be adopted by 3GPP infrastructure utilising GSM or GERAN as access network to enable inter-working to be obtained between network and various User Equipment (UE) implementations of the 3GPP specification. The objective is to obtain compatibility without changing the consolidated set of specifications. The present document describes the recommended changes to the infrastructure to cater for specific faults within some types of UE.

The lifetime of the herein described measures together with their potential impact on optimal network performance is out of the scope of the present document.

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications". 3GPP TS 04.08 (Phase 1): "Mobile radio interface layer 3 specification Part 1: Generic". [2] [3] 3GPP TS 04.08 (Phase 2): "Mobile radio interface layer 3 specification". [4] 3GPP TS 04.08 (Phase 2+): "Mobile radio interface layer 3 specification". 3GPP TS 05.05 (Phase 2): "Radio Performance Aspects. [5] [6] 3GPP TS 05.05 (Phase 2+): "Radio Performance Aspects. [7] 3GPP TS 24.007: "Mobile radio interface signalling layer 3 General aspects". [8] 3GPP TS 24.008: "Mobile radio interface layer 3 specification Core Network Protocols-Stage 3". 3GPP TS 23.107: "Quality of Service, Concept and Architecture". [9] 3GPP TS 44.018: "Mobile radio interface layer 3 specification, Radio Resource Control (RRC) [10] protocol".

# 3 Abbreviations

Abbreviations used in the present document are listed in 3GPP TR 21.905 [1].

# 4 General

In the implementation of the standard it has been found that some aspects of the specifications have been misinterpreted by some MS manufacturers. These MSs require specific implementations of the Phase 1 standard in the infrastructure, to provide completely compatible interworking.

It has been assumed throughout this TR that Phase 2 and later infrastructure will interwork with Phase 1 MSs in the same way as Phase 1 infrastructure.