



**Digital cellular telecommunications system (Phase 2+) (GSM);  
Universal Mobile Telecommunications System (UMTS);  
LTE;  
Interworking between the Public Land Mobile Network (PLMN)  
supporting packet based services and  
Packet Data Networks (PDN)  
(3GPP TS 29.061 version 13.7.0 Release 13)**



---

Reference

RTS/TSGC-0329061vd70

---

Keywords

GSM,LTE,UMTS

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	8
1 Scope .....	9
2 References .....	9
3 Definitions and abbreviations.....	13
3.1 Definitions .....	13
3.2 Abbreviations .....	13
3.3 Symbols.....	15
4 Network characteristics .....	15
4.1 Key characteristics of PLMN .....	15
4.2 Key characteristics of PSDN .....	15
4.3 Key characteristics of IP Networks .....	15
5 Interworking Classifications.....	16
5.1 Service Interworking .....	16
5.2 Network Interworking .....	16
5.3 Numbering and Addressing.....	16
6 Access reference configuration .....	16
6.1 General .....	16
6.2 Access Interfaces and Reference Points for non-EPC based Packet Domain.....	16
6.3 Access Interfaces and Reference Points for EPC based Packet Domain.....	17
7 Interface to Packet Domain Bearer Services .....	17
7.1 A/Gb mode .....	17
7.2 Iu mode.....	17
7.3 Interface to EPC-based Packet Domain Bearer Services.....	18
8 Subscription checking .....	18
8A Prevention of IP spoofing.....	18
9 Message Screening .....	18
10 Interworking with PSDN (X.75/X.25) .....	18
11 Interworking with PDN (IP).....	19
11.1 General .....	19
11.2 PDN Interworking Model.....	19
11.2.1 Access to Internet, Intranet or ISP through Packet Domain .....	20
11.2.1.1 Transparent access to the Internet .....	21
11.2.1.2 Ipv4 Non Transparent access to an Intranet or ISP .....	22
11.2.1.2.1 non-EPC based Ipv4 Non Transparent access .....	22
11.2.1.2.2 EPC based Ipv4 Non Transparent access .....	25
11.2.1.3 Ipv6 Non Transparent access to an Intranet or ISP .....	27
11.2.1.3.1 Ipv6 PDP Context Activation .....	27
11.2.1.3.1a Ipv6 EPC based Bearer Activation.....	30
11.2.1.3.2 Ipv6 Stateless Address Autoconfiguration .....	32
11.2.1.3.2a Ipv6 Stateless Address Autoconfiguration for EPC .....	34
11.2.1.3.3 Ipv6 Stateful Address Autoconfiguration.....	37
11.2.1.3.4 Ipv6 Router Configuration Variables .....	37
11.2.1.3.5 Ipv6 Prefix Delegation via DHCPv6.....	38
11.2.1.4 Access to Internet, Intranet or ISP with Mobile Ipv4.....	38
11.2.1.5 IP Fragmentation Across Gi/Sgi .....	41
11.2.2 Access to networks handling Non-IP data services through Packet Domain.....	41

11.3	Numbering and Addressing .....	42
11.4	Charging .....	43
11.5	Domain Name System Server (DNS Server) .....	43
11.6	Screening .....	43
11.7	IP Multicast access .....	43
11.8	Non-IP data transferring over SGi .....	44
11.8.1	General .....	44
11.8.2	SGi PtP tunnelling based on UDP/IP .....	44
11.8.3	Other SGi PtP tunnelling mechanisms .....	45
12	Interworking with PDN (PPP) .....	46
12.1	General .....	46
12.2	PDN Interworking Model .....	46
12.2.1	Virtual dial-up- and direct Access to PDNs, or ISPs through Packet Domain .....	46
12.2.1.1	Procedural description .....	47
13	Interworking with PDN (DHCP) .....	49
13.1	General .....	49
13.2	PDN Interworking Model of GGSN for DHCP .....	50
13.2.1	Address allocation by the Intranet or ISP .....	50
13.2.1.1	Address allocation using DHCPv4 .....	51
13.2.1.2	Void .....	52
13.2.2	Other configuration by the Intranet or ISP (Ipv6 only) .....	52
13.3	PDN Interworking Model of P-GW for DHCP .....	53
13.3.1	Address allocation by the Intranet or ISP .....	54
13.3.1.1	Ipv4 Address allocation and Ipv4 parameter configuration via DHCPv4 .....	54
13.3.1.2	Ipv6 Prefix allocation via Ipv6 stateless address autoconfiguration via DHCPv6 .....	55
13.3.1.3	Ipv6 parameter configuration via stateless DHCPv6 .....	55
13a	Interworking with IMS .....	55
13a.1	General .....	55
13a.2	IMS Interworking Model .....	56
13a.2.1	IMS Specific Configuration in the GGSN/P-GW .....	56
13a.2.2	IMS Specific Procedures in the GGSN/P-GW .....	57
13a.2.2.1	Request for Signalling Server Address .....	57
13a.2.2.1a	Failure of Signalling Server Address .....	57
13a.2.2.2	Establishment of a PDP Context/EPS Bearer for Signalling .....	57
13a.2.2.3	Creation of a PDP Context/EPS Bearer for IMS Media Flows .....	58
13b	Interworking with BM-SC in EPS .....	59
13b.1	General .....	59
13b.2	BM-SC interworking model of MBMS GW .....	59
13b.3	Forwarding of user plane packets at the MBMS GW .....	60
14	Internet Hosted Octet Stream Service (IHOSS) .....	61
15	Interworking between Packet Domains .....	61
15.1	Security Agreements .....	62
15.2	Routing protocol agreements .....	62
15.3	Charging agreements .....	62
16	Usage of RADIUS on Gi/Sgi interface .....	62
16.1	RADIUS Authentication and Authorization .....	62
16.2	RADIUS Accounting .....	63
16.3	Authentication and accounting message flows on Gi interface .....	64
16.3.1	IP PDP type .....	64
16.3.2	PPP PDP type .....	66
16.3.3	Accounting Update .....	67
16.3.4	AAA-Initiated PDP context termination .....	68
16.3a	Authentication and accounting message flows on Sgi interface .....	69
16.3a.1	Authentication, Authorization and Accounting procedures .....	69
16.3a.2	Accounting Update .....	71
16.3a.3	AAA-Initiated Bearer termination .....	72
16.4	List of RADIUS attributes .....	73

16.4.1	Access-Request message (sent from GGSN/P-GW to AAA server) .....	73
16.4.2	Access-Accept (sent from AAA server to GGSN/P-GW) .....	75
16.4.3	Accounting-Request START (sent from GGSN/P-GW to AAA server) .....	76
16.4.4	Accounting Request STOP (sent from GGSN/P-GW to AAA server) .....	77
16.4.5	Accounting Request ON (optionally sent from GGSN/P-GW to AAA server) .....	79
16.4.6	Accounting Request OFF (optionally sent from GGSN/P-GW to AAA server) .....	79
16.4.7	Sub-attributes of the 3GPP Vendor-Specific attribute .....	80
16.4.7.1	Presence of the 3GPP Vendor-Specific attribute in RADIUS messages .....	80
16.4.7.2	Coding 3GPP Vendor-Specific RADIUS attributes .....	85
16.4.8	Accounting Request Interim-Update (sent from GGSN/P-GW to AAA server) .....	100
16.4.9	Disconnect Request (optionally sent from AAA server to GGSN/P-GW) .....	101
16a	Usage of Diameter on Gi/Sgi interface .....	102
16a.1	Diameter Authentication and Authorization .....	102
16a.2	Diameter Accounting .....	103
16a.3	Authentication and accounting message flows on Gi interface .....	104
16a.3.1	IP PDP type .....	104
16a.3.2	PPP PDP type .....	105
16a.3.3	Accounting Update .....	108
16a.3.4	Server-Initiated PDP context termination .....	108
16a.3a	Authentication and accounting message flows on Sgi interface .....	109
16a.3a.1	Authentication, Authorization and Accounting procedures .....	109
16a.3a.2	Accounting Update .....	111
16a.3a.3	Server-Initiated Bearer termination .....	112
16a.4	Gi/Sgi Diameter messages .....	113
16a.4.1	AAR Command .....	113
16a.4.2	AAA Command .....	114
16a.4.3	ACR Command .....	115
16a.4.4	ACA Command .....	116
16a.4.5	STR Command .....	117
16a.4.6	STA Command .....	117
16a.4.7	ASR Command .....	118
16a.4.8	ASA Command .....	118
16a.5	Gi/Sgi specific AVPs .....	119
16a.6	Gi/Sgi specific Experimental-Result-Code AVP .....	121
16a.7	Gi/Sgi re-used AVPs .....	121
17	Usage of Diameter on Gmb interface .....	121
17.1	MBMS user authorisation .....	122
17.2	MBMS service registration / de-registration .....	122
17.3	MBMS session start / update/ stop .....	122
17.4	MBMS user deactivation .....	122
17.5	Message flows .....	123
17.5.1	Service activation .....	123
17.5.2	Session start procedure .....	124
17.5.3	Session stop procedure .....	125
17.5.4	Registration procedure .....	125
17.5.5	De-registration procedure (GGSN initiated) .....	126
17.5.6	De-registration procedure (BM-SC initiated) .....	126
17.5.7	Service deactivation .....	127
17.5.7.1	BM-SC Initiated Multicast Service Deactivation .....	129
17.5.8	Trace Session Activation procedure .....	129
17.5.9	Trace Session Deactivation procedure .....	130
17.5.10	MBMS UE Context Modification Procedure .....	130
17.5.11	Session Update Procedure .....	131
17.5.12	MBMS broadcast session termination (GGSN initiated) .....	132
17.6	Gmb Messages .....	132
17.6.1	AAR Command .....	132
17.6.2	AAA Command .....	133
17.6.3	STR Command .....	134
17.6.4	STA Command .....	134
17.6.5	Re-Auth-Request Command .....	135

17.6.6	RE-Auth-Answer Command.....	136
17.6.7	Abort-Session-Request Command.....	137
17.6.8	Abort-Session-Answer Command .....	137
17.7	Gmb specific AVPs .....	137
17.7.1	3GPP-Vendor-Specific AVP .....	139
17.7.2	TMGI AVP .....	139
17.7.3	Required-MBMS-Bearer-Capabilities AVP .....	139
17.7.4	Void .....	139
17.7.5	MBMS-StartStop-Indication AVP.....	139
17.7.6	MBMS-Service-Area AVP .....	140
17.7.7	MBMS-Session-Duration AVP .....	140
17.7.8	Alternative-APN AVP .....	140
17.7.9	MBMS-Service-Type AVP.....	140
17.7.10	MBMS-2G-3G-Indicator AVP .....	141
17.7.11	MBMS-Session-Identity AVP .....	141
17.7.12	RAI AVP .....	141
17.7.13	Additional-MBMS-Trace-Info AVP.....	141
17.7.14	MBMS-Time-To-Data-Transfer AVP .....	141
17.7.15	MBMS-Session-Repetition-Number AVP.....	142
17.7.16	MBMS-Required-QoS AVP .....	142
17.7.17	MBMS-Counting-Information AVP .....	142
17.7.18	MBMS-User-Data-Mode-Indication AVP.....	142
17.7.19	MBMS-GGSN-Address AVP.....	143
17.7.20	MBMS-GGSN-Ipv6-Address AVP .....	143
17.7.21	MBMS-BMSC-SSM-IP-Address AVP.....	143
17.7.22	MBMS-BMSC-SSM-Ipv6-Address AVP.....	143
17.7.23	MBMS-Flow-Identifier AVP.....	143
17.7.24	CN-IP-Multicast-Distribution AVP.....	143
17.7.25	MBMS-HC-Indicator AVP.....	143
17.7a	Gmb re-used AVPs.....	143
17.8	Gmb specific Experimental-Result-Code AVP values.....	144
17.8.1	Success.....	144
17.8.2	Permanent Failures .....	144
17.8.3	Transient Failures .....	144
18	Usage of RADIUS at the Pk Reference Point .....	145
18.1	General .....	145
18.2	Radius Profile for Pk Reference Point.....	145
18.3	Interconnecting the Presence Network Agent and the GGSN .....	145
19	Usage of Diameter on Mz interface.....	145
19.1	Introduction .....	145
19.2	Call flows in roaming scenarios .....	146
19.2.1	Service activation.....	146
19.2.1.1	Service Provided by the BM-SC in Home PLMN .....	146
19.2.1.2	Service Provided by the BM-SC in visited PLMN .....	148
19.2.2	Service deactivation.....	149
19.2.2.1	Service Provided by the BM-SC in home PLMN .....	149
19.2.2.2	Service Provided by the BM-SC in visited PLMN .....	150
19.2.2.3	BM-SC in the home PLMN initiated multicast service deactivation .....	151
19.3	Mz messages .....	151
19.4	Mz specific AVPs.....	151
19.5	Mz specific Experimental-Result-Code AVP values .....	152
19.5.1	Success.....	152
19.5.2	Permanent Failures .....	152
19.5.3	Transient Failures .....	152
20	Usage of Diameter on SGmb interface.....	152
20.1	General .....	152
20.2	MBMS session start / update/ stop .....	153
20.2A	MBMS heartbeat .....	153
20.3	Message flows .....	153
20.3.1	Session start procedure .....	153

20.3.2	Session update procedure.....	154
20.3.3	Session stop procedure.....	155
20.3.4	MBMS session termination (MBMS GW initiated) .....	155
20.3.5	MBMS heartbeat procedure.....	156
20.4	SGmb Messages .....	157
20.4.1	Re-Auth-Request Command.....	157
20.4.2	RE-Auth-Answer Command.....	159
20.4.3	Session-Termination-Request Command .....	160
20.4.4	Session-Termination-Answer Command.....	160
20.4.5	Abort-Session-Request Command.....	160
20.4.6	Abort-Session-Answer Command .....	161
20.5	SGmb re-used AVPs .....	161
20.5a	SGmb specific AVPs.....	163
20.5a.1	MBMS-Access-Indicator AVP .....	163
20.5a.2	MBMS-GW-SSM-IP-Address AVP .....	164
20.5a.3	MBMS-GW-SSM-Ipv6-Address AVP .....	164
20.5a.4	MBMS-BMSC-SSM-UDP-Port AVP.....	164
20.5a.5	MBMS-GW-UDP-Port AVP .....	164
20.5a.6	MBMS-GW-UDP-Port-Indicator AVP.....	164
20.5a.7	MBMS-Data-Transfer-Start AVP.....	164
20.5a.8	MBMS-Data-Transfer-Stop AVP .....	164
20.5a.9	MBMS-Flags AVP .....	164
20.5a.10	Restart-Counter AVP.....	165
20.5a.11	Diagnostic-Info AVP .....	165
20.5a.12	MBMS-Cell-List AVP.....	165
20.6	SGmb specific Experimental-Result-Code AVP values.....	166
20.7	Use of the Supported-Features AVP on the SGmb reference point.....	166
<b>Annex A (informative):</b>	<b>Interworking PCS1900 with PSDNs.....</b>	<b>168</b>
<b>Annex B (normative):</b>	<b>Rate control related to Cellular Internet Of Things (CIoT)</b>	
	<b>optimisations .....</b>	<b>169</b>
B.1	General .....	169
B.2	Support of rate control of user data .....	169
B.2.0	General .....	169
B.2.1	APN Rate Control in the PGW.....	169
B.2.2	Serving PLMN Rate Control information handling in the PGW.....	170
<b>Annex C (informative):</b>	<b>Change history .....</b>	<b>171</b>
History .....		172



---

# Foreword

This Technical Specification (TS) has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The present document describes the network interworking for the Packet Domain. Interworking to various external networks is defined together with the interworking for data forwarding while subscribers roam within the 3GPP system.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- Y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# 1 Scope

The present document defines the requirements for Packet Domain interworking between a:

- a) PLMN and PDN;
- b) PLMN and PLMN.

The present document is valid for a PLMN in A/Gb mode as well as for a PLMN in Iu mode. If text applies only for one of these systems it is explicitly mentioned by using the terms "A/Gb mode" and "Iu mode". Please note, that the A interface does not play any role in the scope of the present document although the term "A/Gb mode" is used.

For inter-working between EPC PLMN and external networks, the present document is valid for both 3GPP accesses and non-3GPP accesses.

The present document also defines, in clause 17, the protocol for the Gmb interface, in clause 20, the protocol for the SGmb interface, and in clause 19, the protocol for the Mz interface.

The present document also defines, in clause 18, the usage of Radius at the Pk Reference Point between the GGSN and the Presence Network Agent.

The term "Packet Domain" includes both EPC based and non-EPC based Packet Domains.

The present document also defines the specific requirements for rate control related to CIoT optimisations.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] Void.
- [2] 3GPP TS 22.060: "General Packet Radio Service (GPRS); Service Description; Stage 1".
- [3] 3GPP TS 23.060: "General Packet Radio Service (GPRS); Service Description; Stage 2".
- [4] Void.
- [5] Void.
- [6] Void.
- [7] Void.
- [8] Void.
- [9] Void.
- [10] 3GPP TS 27.060: "Packet Domain; Mobile Station (MS) supporting Packet Switched services".
- [11] ITU-T Recommendation E.164: "The international public telecommunication numbering plan".
- [12] Void.
- [13] Void.