



BSI Standards Publication

Mechanical joining — Guidelines for fatigue testing of joints

National foreword

This Published Document is the UK implementation of ISO/TR 12998:2019.

The UK participation in its preparation was entrusted to Technical Committee WEE/29, Resistance welding.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019
Published by BSI Standards Limited 2019

ISBN 978 0 580 51639 9

ICS 25.160.40

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 May 2019.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

TECHNICAL REPORT

ISO/TR 12998

First edition
2019-04-19

Mechanical joining — Guidelines for fatigue testing of joints

*Assemblage mécanique — Lignes directrices pour les essais de fatigue
des assemblages*



Reference number
ISO/TR 12998:2019(E)

© ISO 2019



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	5
5 Specimens	6
5.1 General.....	6
5.2 Test specimen materials.....	7
5.3 Types of test specimens.....	8
5.4 Selection of suitable specimens.....	8
5.5 Test specimen fabrication.....	10
5.5.1 Coupons for specimen fabrication.....	10
5.5.2 Bending and forming.....	10
5.5.3 Joining.....	11
5.5.4 Tolerances.....	11
5.5.5 Storage.....	11
5.5.6 Inspection.....	11
5.6 Test specimen geometry.....	12
5.6.1 General.....	12
5.6.2 Specimen geometry of tensile shear and peel specimens.....	12
5.6.3 Geometry of the hat and other closed section specimens.....	18
5.6.4 Double disc and KS-2 specimen.....	22
6 Specimen clamps and alignment	23
6.1 General.....	23
6.2 Verification and adjustment of specimen clamps and alignment.....	23
6.2.1 Alignment.....	23
6.2.2 Verification of the clamping.....	23
6.3 Clamping device design.....	24
6.3.1 General.....	24
6.3.2 Example of suitable clamping device design.....	25
7 Testing procedure	26
7.1 General.....	26
7.2 Testing machine.....	26
7.3 Mounting of clamping devices/clamps.....	26
7.4 Clamping procedure.....	26
7.5 Fatigue testing.....	27
7.5.1 General.....	27
7.5.2 Setting load conditions for the fatigue testing.....	28
7.5.3 Test frequency.....	30
7.6 Test termination.....	30
7.6.1 General.....	30
7.6.2 Failure criterion and number of cycles to failure.....	31
7.6.3 Stiffness.....	32
7.6.4 Data acquisition.....	32
7.7 Re-testing.....	33
8 Test report	33
8.1 Basic information.....	33
8.1.1 General.....	33
8.1.2 Material prior to fatigue test specimen preparation.....	33
8.1.3 Mechanical properties.....	33

8.1.4	Specimen design and preparation.....	33
8.1.5	Test procedure.....	33
8.1.6	Fatigue testing machine.....	33
8.1.7	Ambient conditions during the fatigue test.....	34
8.1.8	Results of post-test examination.....	34
8.2	Presentation of fatigue test results.....	34
8.2.1	Tabular presentation.....	34
8.2.2	Graphical presentation.....	34
8.2.3	Numerical evaluation, statistics.....	35
Annex A (informative) Calibration specimen for verifying the load distribution in H-specimens.....		36
Annex B (informative) Hydraulic clamps for the fatigue testing of H-specimens.....		37
Annex C (informative) Clamps for the fatigue testing of H-specimens.....		38
Annex D (informative) Flow chart — Data acquisition.....		39
Bibliography.....		41

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 44, *Welding and allied processes*, Subcommittee SC 6, *Resistance welding and allied mechanical joining*.

Any feedback, question or request for official interpretation related to any aspect of this document should be directed to the Secretariat of ISO/TC 44/SC 6 via your national standards body. A complete listing of these bodies can be found at www.iso.org/members.html. Official interpretations, where they exist, are available from this page: <https://committee.iso.org/sites/tc44/home/interpretation.html>.

Introduction

This document gives recommendations for fatigue testing of test specimens with dimensional information for single- and multi-joint specimens for riveted, clinched and screwed mechanical joints. H-shaped, hat-shaped, double-disc and KS-2 type specimens are specified. This document is based on ISO 18592, the standard on the fatigue testing of resistance spot welds.

The fatigue tests specified in this document are conducted at room temperature, at constant load amplitudes and specified load ratios. For most of the specimens, the primary loads experienced by the joints are shear and peel loads. Some test specimens can be subjected to torsion or bending loads; the joints themselves experience non-uniform shear and peel loads.

Mechanical joining — Guidelines for fatigue testing of joints

1 Scope

This document gives recommendations for test specimens and procedures for performing constant load amplitude fatigue tests on single- and multi-joint sheet specimens in the thickness range from 0,5 mm to 6 mm at room temperature and a relative humidity of max. 80 %.

NOTE The thickness range for advanced high strength steels (AHSS) and ultra high strength steels (UHSS) is generally below 3,0 mm. Greater thicknesses apply for aluminium alloys, for example.

This document covers:

- testing of joints to evaluate materials;
- evaluation of the influence of joint type and joint size on the test results;
- evaluation of the influence of load type and load mode on the test results;
- testing of component-like specimens to evaluate their structural performance.

Depending on the specimen used, it is possible from the results to evaluate the fatigue behaviour of joints under shear-, peel-, normal-tension and combinations of loads and that of the tested specimen.

The results of fatigue testing obtained with component like specimens are suitable for deriving criteria for the selection of materials and thickness combinations for structures and components subjected to cyclic loading. This statement is especially relevant for results obtained with specimens with boundary conditions, i.e. a local stiffness, similar to that of the structure in question. The results of fatigue testing are suitable for direct application to a design only when the loading conditions in service and the stiffness of the design in the joint area are similar.

This document does not apply to civil engineering applications such as metal building and steel construction which are covered by other applicable standards.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

load

repeated load

F

applied force varying simply and periodically between constant maximum and minimum values

Note 1 to entry: Adapted from ISO 14324:2003, 3.12.