Australian Standard<sup>™</sup>

Low-voltage switchgear and controlgear

Part 6.2: Multiple function equipment— Control and protective switching devices (or equipment) (CPS)



This Australian Standard was prepared by Committee EL-006, Industrial Switchgear and Controlgear. It was approved on behalf of the Council of Standards Australia on 22 July 2004.

This Standard was published on 23 September 2004.

The following are represented on Committee EL-006:

Australasian Railway Association Australian Chamber of Commerce and Industry Australian Electrical and Electronic Manufacturers Association Bureau of Steel Manufacturers of Australia Electricity Supply Association of Australia Engineers Australia National Electrical and Communications Association National Electrical Switchboard Manufacturers Association Testing Interests (Australia)

#### Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Web Shop at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

Australian Standards<sup>™</sup> and other products and services developed by Standards Australia are published and distributed under contract by SAI Global, which operates the Standards Web Shop.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

This Standard was issued in draft form for comment as DR 04167.

Australian Standard<sup>™</sup>

# Low-voltage switchgear and controlgear

Part 6.2: Multiple function equipment— Control and protective switching devices (or equipment) (CPS)

Originated as AS 3947.6.2—1996. Previous edition AS/NZS 3947.6.2:2001. Revised and redesignated as AS 60947.6.2—2004.

#### COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 6264 6

#### PREFACE

This Standard was prepared by the Standards Australia Committee EL-006, Industrial Switchgear and Controlgear to supersede AS/NZS 3947.6.2:2001.

The objective of this Standard, in addition to that stated in Clause 1, is to bring Australian requirements into line with Edition 2.0 (2002-10) of IEC 60947-6-2.

This Standard is Part 6.2 of a series which, when complete, will consist of the following:

AS 60947 Low-voltage switchgear and controlgear

AS 60947.1*	Part 1:	General rules
AS 60947.2*	Part 2:	Circuit-breakers
AS 60947.3	Part 3:	Switches, disconnectors, switch-disconnectors and fuse- combination units
AS 60947.3 Supp1	Part 3:	Switches, disconnectors, switch-disconnectors and fuse- combination units, Supplement 1: Fuse-switch- disconnectors and switch-disconnectors for use with low- voltage aerial bundled cables
AS 60947.4.1*	Part 4.1:	Contactors and motor-starters—Electromechanical contactors and motor-starters
AS 60947.4.2*	Part 4.2:	Contactors and motor-starters—A.C. semiconductor motor controllers and starters
AS 60947.4.3	Part 4.3:	Contactors and motor-starters—A.C. semiconductor controllers and contactors for non-motor loads
AS 60947.5.1*	Part 5.1:	Control circuit devices and switching elements—Electro- mechanical control circuit devices
AS 60947.5.2*	Part 5.2:	Control circuit devices and switching elements—Proximity switches
AS 60947.5.3	Part 5.3:	Control circuit devices and switching elements— Requirements for proximity devices with defined behaviour under fault conditions
AS 60947.5.4*	Part 5.4:	Control circuit devices and switching elements—Methods of assessing the performance of low-energy contacts– Special tests
AS 60947.5.5	Part 5.5:	Control circuit devices and switching elements—Electrical emergency stop devices with mechanical latching function
AS 60947.5.6	Part 5.6:	Control circuit devices and switching elements—D.C. interface for proximity sensors and switching amplifiers (NAMUR)
AS 60947.5.7*	Part 5.7:	Control circuit devices and switching elements— Requirements for proximity devices with analogue output
AS 60947.6.1	Part 6.1:	Multiple function equipment—Automatic transfer switching equipment
AS 60947.6.2*	Part 6.2:	Multiple function equipment—Control and protective switching devices (or equipment) (CPS) (this Standard)
AS 60947.7.1*	Part 7.1:	Ancillary equipment—Terminal blocks for copper conductors
AS 60947.7.2*	Part 7.2:	Ancillary equipment—Protective conductor terminal blocks for copper conductors

AS 60947.7.3*	Part 7.3:	Ancillary equipment—Safety requirements for terminal
		blocks for the reception of cartridge fuse-links
AS 60947.8*	Part 8:	Control units for built-in thermal protection for rotating machines

It is the intention of the Committee to align the numbering of this series of Standards with that of the corresponding IEC 60947 series of Standards.

Standards from the list above that are marked with an asterisk (\*) are, at the time of publication of this document, available as a part of the AS 60947 series of Standards.

Standards that are not so marked remain as AS(/NZS) 3947 series Standards. Following the next amendment or revision of the corresponding IEC Standard, each of these Standards remaining in the AS(/NZS) 3947 series will be revised and renumbered as a part of the AS 60947 series.

This Standard is identical with and has been reproduced from Edition 2.0 (2002-10) of IEC 60947-6-2:2002, Low-voltage switchgear and controlgear – Part 6-2: Multiple function equipment—Control and protective switching devices (or equipment) (CPS).

The provisions of the general rules dealt with in AS 60947.1 (hereinafter referred to as Part 1) are applicable to this Standard, where specifically called for. Clauses and subclauses, tables, figures and appendices of the general rules thus applicable are identified by reference to Part 1, for example, 1.2.3 of Part 1, Table 4 of Part 1, or Annex A of Part 1. Where reference is made to other parts of the AS 60947 (AS/NZS 3947) series, they too are referred to as the relevant part, after the initial reference. AS/NZS 3947.6.1 is, therefore, referred to as Part 6.1.

This Standard differs from AS/NZS 3947.6.2:2001 in the following areas:

- (a) The numbering of tables has been brought into line with AS 60947.1.
- (b) Heat resistance requirements clarified for materials.
- (c) Additional safety requirements for CPS suitable for isolation have been clarified.
- (d) EMC immunity requirements have been expanded.
- (e) Tests of dielectric properties have been clarified.
- (f) EMC test requirements have been revised.
- (g) Test sequence 1 has been expanded.
- (h) Dielectric withstand requirements have been revised.
- (i) Figures 2 to 25 replace the former figures 2 to 8.
- (j) The condition and operation of the CPS following the electrical durability test of Annex A have been clarified.
- (k) Annex B has been deleted.

As this Standard is reproduced from an International Standard, the following applies:

- (i) Its number does not appear on each page of text and its identity is shown only on the cover and title page.
- (ii) In the source text 'this standard' should read 'this Australian Standard'.
- (iii) A full point should be substituted for a comma when referring to a decimal marker.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the annex to which they apply. A 'normative' annex is an integral part of a Standard, whereas an 'informative' annex is only for information and guidance.

## CONTENTS

1	Scope and object			1
2 Normative references			ferences	1
3	Defin	Definitions		
	3.1	Contro	l and protective switching device (or equipment) (CPS)	3
	3.2	CPS su	uitable for isolation	3
	3.3	CPS fo	r motor control and protection	4
		3.3.1	Direct-on-line CPS	4
		3.3.2	Reversing CPS	4
		3.3.3	Two-direction CPS	4
	3.4	Openin	ıg time	4
	3.5	Phase	loss sensitive relay or release (for motor protection)	4
4	Class	sificatior	۰	4
5	Chara	acteristi	CS	. 4
	5 1	Summa	ary of characteristics	4
	5.2		f CPS	5
	•.=	5.2.1	Number of poles	5
		522	Kind of current (a c or d c )	5
		5.2.3	Method of operation	5
		5.2.4	Method of control	5
		5.2.5	Method of resetting after overload	5
		5.2.6	Method of rearming after short-circuit	5
	5.3	Rated a	and limiting values of the main circuit	5
		5.3.1	Rated voltages	5
		5.3.2	Currents and powers	5
		5.3.3	Rated frequency	5
		5.3.4	Rated duties	6
		5.3.5	Normal load and overload characteristics	6
		5.3.6	Short circuit characteristics	6
	5.4	Utilizat	ion categories	6
		5.4.1	Standard utilization categories	6
		5.4.2	Assignment of utilization categories based on the results of tests	. 7
		5.4.3	Application of utilization categories for motor control duty	. 8
	5.5	Contro	l circuits	8
	5.6	6 Auxiliary circuits		
	5.7	Relays	or releases	8
		5.7.1	Types of relays or releases	8
		5.7.2	Characteristic values	9
		5.7.3	Designation and current setting of overload relays or releases	9
		5.7.4	Time current characteristics of over current relays or releases	9
		5.7.5	Influence of ambient air temperature 1	10
	5.8	Switchi	ing overvoltages 1	10

				Page
6	Prod	uct infor	mation	10
	6.1	Nature	of information	10
		6.1.1	Identification	10
		6.1.2	Characteristics	10
	6.2	Markin	g	11
	6.3	Instruc	tions for installation, operation and maintenance	11
7	Norm	nal servi	ce, mounting and transport conditions	11
8	Cons	struction	al and performance requirements	12
	8.1	Constr	uctional requirements	12
		8.1.1	Materials	12
		8.1.2	Current-carrying parts and their connections	12
		8.1.3	Clearances and creepage distances	12
		8.1.4	Actuator	12
		8.1.5	Indication of the contact position	12
		8.1.6	Additional safety requirements for CPS's suitable for isolation	12
		8.1.7	Terminals	12
		8.1.8	Additional requirements for CPS's provided with a neutral pole	13
		8.1.9	Provisions for protective earthing	13
		8.1.10	Enclosures for CPS's	13
	8.2	Perforr	nance requirements	13
		8.2.1	Operating conditions	13
		8.2.2	Temperature rise	16
		8.2.3	Dielectric properties	19
		8.2.4	Performance under no load, normal load and overload conditions	19
		8.2.5	Ability to make, carry and break short-circuit currents	24
		8.2.6	Switching overvoltages	24
	8.3	Electro	magnetic compatibility (EMC)	25
		8.3.1	General	25
		8.3.2	Immunity	25
		8.3.3	Emission	25
9	Test	S		26
	9.1	Kind of	tests	26
		9.1.1	General	26
		9.1.2	Type test	26
		9.1.3	Routine tests	26
		9.1.4	Sampling tests	26
		9.1.5	Special tests	26
	9.2	Compli	ance with constructional requirements	26
	9.3	Compli	ance with performance requirements	26
		9.3.1	Test sequences	27
		9.3.2	General test conditions	27
		9.3.3	Performance under no load, normal load and overload conditions	27
		9.3.4	Performance under short-circuit conditions	30
		9.3.5	EMC tests	32

0.4	Toot of		Page
9.4		Test Sequence I: Temperature rice, energing limite	42
	9.4.1	dielectric properties	44
	9.4.2	Test Sequence II: Performance under normal load and overload conditions	46
	9.4.3	Test sequence III: Operational performance before and after operating sequences at <i>I</i> <sub>cr</sub> and "r" current test	47
	9.4.4	Test Sequence IV: Operational performance before and after operating sequences at <i>I</i> <sub>cs</sub>	48
	9.4.5	Test Sequence V: Additional breaking capacity	49
	9.4.6	Test Sequence VI: Additional test sequence for four-pole CPS's	49
	9.4.7	Test Sequence VII: Additional test sequence for CPS's intended for use in an individual enclosure	50
	9.4.8	Test sequence VIII: EMC	50
9.5	Routin	e tests	50
	9.5.1	General	50
	9.5.2	Operation and operating limits	50
	9.5.3	Dielectric tests	51
9.6	Sampli	ng plans and test procedure	51
Annex A	(normat	ive) Special tests	78
Annex B	Vacan	t	81
Annex C	(normat	ive) Marking and identification of CPS terminals	82
Annex D	(informa	ative) Items subject to agreement between manufacturer and user	86
	(		
Figure 1	– Multip	le of current setting limits for ambient air temperature time-delay	<b>F</b> 4
overioad	relays c	or releases (see 8.2.1.5.1)	51
Figure 2a	ı – Eleva	ation	52
Figure 2b	) – Secti	ons A-A and B-B	53
Figure 2 ·	– EUT n	nounted in metallic enclosure – Two-phase poles in series configuration	53
Figure 3a	ı – Eleva	ation	54
Figure 3b	– Secti	ions A-A and B-B	55
Figure 3	– EUT n	nounted in metallic enclosure – Three-phase poles in series configuration	55
Figure 4a	ı – Eleva	ation	56
Figure 4b	– Sect	ions A-A and B-B	57
Figure 4	– EUT n	nounted in metallic enclosure – Three-phase configuration	57
Figure 5 - electrosta Two-phas	– Test c atic disc se poles	ircuit for emission tests, immunity to harmonics, current dips, harges and radiated electromagnetic fields – in series configuration	58
Figure 6 - electrosta Three-ph	- Test c atic disc ase pole	ircuit for emission tests, immunity to harmonics, current dips, harges and radiated electromagnetic fields – es in series configuration	59
Figure 7 - electrosta	– Test c atic disc	ircuit for emission tests, immunity to harmonics, current dips, harges and radiated electromagnetic fields – figuration	60
		at up for the verification of immunity to electrostatic discharges	00
Figure 0		et up for immunity to radiated electromagnetic fields	01
ingule 9	- rests	יפנייטף זטר וווווותווונץ נט זמטומנפט פופטנוטווומטוופנוט וופוטצ	UZ

	Page
Figure 10 – Test set-up for conducted disturbances induced by radio-frequency fields (common mode) – Two-phase poles in series configuration	63
Figure 11 – Test set-up for conducted disturbances induced by radio-frequency fields (common mode) – Three-phase poles in series configuration	64
Figure 12 – Test set-up for conducted disturbances induced by radio-frequency fields (common mode) – Three-phase configuration	65
Figure 13 – Circuit for electrical fast transients/bursts (EFT/B) immunity test – Two-phase poles in series configuration	66
Figure 14 – Circuit for electrical fast transients/bursts (EFT/B) immunity test – Three-phase poles in series configuration	67
Figure 15 – Circuit for electrical fast transients/bursts (EFT/B) immunity test – Three-phase configuration	68
Figure 16 – Test set-up for electrical fast transients/bursts (EFT/B) immunity test	69
Figure 17 – Test circuit for the verification of the influence of surges in the main circuit (line-to-earth) – Two-phase poles configuration	70
Figure 18 – Test circuit for the verification of the influence of current surges in the main circuit – Two-phase poles configuration	71
Figure 19 – Test circuit for the verification of the influence of surges in the main circuit (line-to-earth) – Three-phase poles in series configuration	72
Figure 20 – Test circuit for the verification of the influence of current surges in the main circuit – Three-phase poles in series configuration	73
Figure 21 – Test circuit for the verification of the influence of surges in the main circuit (line to earth) – Three-phase configuration	74
Figure 22 – Test circuit for the verification of the influence of current surges in the main circuit – Three-phase configuration	75
Figure 23 – Representation of test current produced by back-to-back thyristors	76
Figure 24 – Test current for the verification of the influence of the current dips and interruptions	77
Figure 25 – Radiated emission test set-up	77
Table 1 – Utilization categories	7
Table 2 – Limits of operation of inverse time-delay overload relays or releases when energized on all poles	15
Table 3 – Trip classes of inverse time-delay overload relays or releases for utilization categories AC-42, AC-43, AC-44, DC-43, DC-45	15
Table 4 – Limits of operation of three-pole inverse time-delay overload relays or releases when energized on two poles only	16
Table 5 – Temperature rise limits of terminals	17

	. •
Table 5 – Temperature rise limits of terminals	17
Table 6 – Temperature-rise limits of accessible parts	17
Table 7 – Temperature-rise limits for insulated coils in air	18
Table 8 – Intermittent duty test cycle data	18
Table 9 – Rated making and breaking capacities – Making and breaking conditions   corresponding to the utilization categories	20
Table 10 – Relationship between current broken $I_{c}$ and OFF time for the verification	
of rated making and breaking capacities	21
Table 11 – Conventional operational performance after making/breaking capacity tests	22
Table 12 – Operational performance before and after short-circuit tests at $I_{cr}$ and $I_{cs}$	23

## Page

Table 13 – Prospective conventional test current $I_{cr}$ and "r" current $(I_r)$ as a function	
of the maximum <i>I</i> <sub>e</sub> for a given construction	24
Table 14 – Acceptance criteria when EM disturbances are present	25
Table 15 – Test parameters for current dips and interruptions	41
Table 16 – Test sequences	43

#### STANDARDS AUSTRALIA

### Australian Standard

## Low-voltage switchgear and controlgear Part 6.2: Multiple function equipment—Control and protective switching devices (or equipment) (CPS)

#### 1 Scope and object

This part of IEC 60947 AS/NZS 60947 applies to control and protective switching devices (or equipment) (CPS), the main contacts of which are intended to be connected to circuits of rated voltage not exceeding 1 000 V a.c. or 1 500 V d.c.

CPSs are intended to provide both protective and control functions for circuits and are operated otherwise than by hand. They may also fulfill additional functions, such as isolation.

The object of this part is to state:

- the characteristics of CPS's;
- the conditions with which CPS's shall comply with reference to their operation and behaviour, their dielectric properties, the degree of protection provided by their enclosure where applicable;
- the tests intended to verify that these conditions have been met, and the methods to be adopted for these tests;
- the information to be marked on or given with the CPS's.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

References to international standards that are struck through in this clause are replaced by references to Australian or Australian/New Zealand Standards that are listed immediately thereafter and identified by shading. Any Australian or Australian/New Zealand Standard that is identical to the International Standard it replaces is identified as such.

IEC 60034-1:1996, Rotating electrical machines - Part 1: Rating and performance

AS 1359.101, *Rotating electrical machines—General requirements—Rating and performance* (identical to IEC 60034-1:1996)

IEC 60085:1984, Thermal evaluation and classification of electrical insulation

IEC 60410:1973, Sampling plans and procedures for inspection by attributes

IEC 60695-2-10:2000, Fire hazard testing – Part 2-10: Glowing/hot-wire based test methods – Glow-wire apparatus and common test procedure

AS/NZS 60695.2.10; Fire hazard testing, Part 2.10: Glowing/hot wire based test methods— Glow-wire apparatus and common test procedure