



TECHNICAL SPECIFICATION

**Smart Cards;
Test specification for the Host Controller Interface (HCI);
Part 1: Terminal features
(Release 10)**

Reference

RTS/SCP-00HCITva20

Keywords

smart card, terminal

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	8
Introduction	9
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definitions, symbols and abbreviations	11
3.1 Definitions	11
3.2 Symbols.....	11
3.3 Abbreviations	11
3.4 Void.....	12
3A Formats.....	12
3A.1 Format of the table of optional features.....	12
3A.2 Format of the applicability table.....	13
3A.3 Status and Notations.....	13
4 Test environment.....	14
4.1 Table of optional features.....	14
4.2 Applicability table	15
4.3 Information to be provided by the device supplier	17
4.4 Test equipment	17
4.4.0 Base Requirements	17
4.4.1 Measurement/setting uncertainties.....	18
4.4.2 Default conditions for DUT operation.....	18
4.4.2.1 General	18
4.4.2.2 Status of UICC interfaces.....	18
4.4.3 Minimum/maximum conditions for DUT operation.....	18
4.4.4 Conventions	18
4.5 Test execution	18
4.5.1 Parameter variations	18
4.5.2 Execution requirements	18
4.6 Pass criterion	19
4.6.0 Principle.....	19
4.6.1 Unanticipated behaviour from the DUT	19
5 Test cases.....	19
5.1 HCI architecture	19
5.1.1 Overview	19
5.1.2 Hosts	19
5.1.3 Gates	20
5.1.3.1 Conformance requirements	20
5.1.3.2 Test case 1: existence of gates.....	20
5.1.3.2.1 Test execution.....	20
5.1.3.2.2 Initial conditions	20
5.1.3.2.3 Test procedure	20
5.1.3.3 Void.....	20
5.1.4 Pipes.....	21
5.1.4.1 Conformance requirements	21
5.1.4.2 Test case 1: static pipe deletion.....	21
5.1.4.2.1 Test execution.....	21
5.1.4.2.2 Initial conditions	21
5.1.4.2.3 Test procedure	21
5.1.4.3 Test case 2: initial pipe state and persistence of pipe state and registry value	22

5.1.4.3.1	Test execution.....	22
5.1.4.3.2	Initial conditions.....	22
5.1.4.3.3	Test procedure.....	22
5.1.5	Registries.....	23
5.1.5.1	Conformance requirements.....	23
5.1.5.2	Test case 1: registry deletion.....	23
5.1.5.2.1	Test execution.....	23
5.1.5.2.2	Initial conditions.....	23
5.1.5.2.3	Test procedure.....	23
5.2	HCP.....	24
5.2.1	HCP packets.....	24
5.2.1.1	Conformance requirements.....	24
5.2.2	HCP message structure.....	24
5.2.2.1	Conformance requirements.....	24
5.2.2.2	Test case 1: commands/events on pipe which is not open.....	24
5.2.2.2.1	Test execution.....	24
5.2.2.2.2	Initial conditions.....	24
5.2.2.2.3	Test procedure.....	25
5.2.3	Message fragmentation.....	25
5.2.3.1	Conformance requirements.....	25
5.3	Instructions.....	25
5.3.1	Commands.....	25
5.3.1.1	Overview.....	25
5.3.1.1.1	Conformance requirements.....	25
5.3.1.2	Generic commands.....	26
5.3.1.2.1	ANY_SET_PARAMETER.....	26
5.3.1.2.2	ANY_GET_PARAMETER.....	26
5.3.1.2.3	ANY_OPEN_PIPE.....	27
5.3.1.2.4	ANY_CLOSE_PIPE.....	27
5.3.1.3	Administration commands.....	28
5.3.1.3.1	ADM_CREATE_PIPE.....	28
5.3.1.3.2	ADM_NOTIFY_PIPE_CREATED.....	28
5.3.1.3.3	ADM_DELETE_PIPE.....	29
5.3.1.3.4	ADM_NOTIFY_PIPE_DELETED.....	29
5.3.1.3.5	ADM_CLEAR_ALL_PIPE.....	29
5.3.1.3.6	ADM_NOTIFY_ALL_PIPE_CLEARED.....	29
5.3.2	Responses.....	30
5.3.2.1	Conformance requirements.....	30
5.3.2.2	Test case 1: response to unknown command.....	30
5.3.2.2.1	Test execution.....	30
5.3.2.2.2	Initial conditions.....	30
5.3.2.2.3	Test procedure.....	30
5.3.3	Events.....	30
5.3.3.1	Conformance requirements.....	30
5.3.3.2	Test case 1: reception of unknown events.....	30
5.3.3.2.1	Test execution.....	30
5.3.3.2.2	Initial conditions.....	30
5.3.3.2.3	Test procedure.....	31
5.4	GATES and subclauses.....	31
5.4.1	GATES.....	31
5.4.1.1	Conformance requirements.....	31
5.4.2	Management gates.....	31
5.4.2.1	Administration gates.....	31
5.4.2.1.1	Host controller administration gate.....	31
5.4.2.1.2	Host administration gate.....	33
5.4.2.2	Link management gate.....	34
5.4.2.2.1	Host controller link management gate.....	34
5.4.2.2.2	Host link management gate.....	34
5.4.2.3	Identity management gate.....	34
5.4.2.3.1	Local registry.....	34
5.4.2.3.2	Remote registry.....	35
5.4.2.4	Loop back gate.....	36

5.4.2.4.1	Conformance requirements.....	36
5.4.3	Generic gates	36
5.5	HCI procedures	36
5.5.1	Pipe management.....	36
5.5.1.1	Pipe creation.....	36
5.5.1.1.1	Conformance requirements.....	36
5.5.1.2	Pipe deletion.....	37
5.5.1.2.1	Conformance requirements.....	37
5.5.1.2.2	Test case 1: valid pipe deletion from host to host controller	37
5.5.1.3	Clear all Pipes	37
5.5.1.3.1	Conformance requirements.....	37
5.5.1.3.2	Test case 1: identity reference data when ETSI TS 102 613 is used	38
5.5.1.3.3	Test case 2: reception of ADM_CLEAR_ALL_PIPE - static pipes, dynamic pipes to host	38
5.5.2	Registry access.....	39
5.5.3	Host and Gate discovery	39
5.5.4	Session initialization	39
5.5.4.1	Conformance requirements	39
5.5.4.2	Test case 1: inhibited state	39
5.5.4.2.1	Test execution.....	39
5.5.4.2.2	Initial conditions	39
5.5.4.2.3	Test procedure	40
5.5.4.3	Test case 2: inhibited state, followed by subsequent successful identity check	40
5.5.4.3.1	Test execution.....	40
5.5.4.3.2	Initial conditions	40
5.5.4.3.3	Test procedure	41
5.5.4.4	Test case 3: initialization using all defined gates	41
5.5.4.4.1	Test execution.....	41
5.5.4.4.2	Initial conditions	41
5.5.4.4.3	Test procedure	41
5.5.5	Loop back testing.....	44
5.5.5.1	Conformance requirements	44
5.5.5.2	Test case 1: processing of EVT_POST_DATA	44
5.5.5.2.1	Test execution.....	44
5.5.5.2.2	Initial conditions	45
5.5.5.2.3	Test procedure	45
5.6	Contactless card emulation.....	45
5.6.1	Overview	45
5.6.1.1	Conformance requirements	45
5.6.1.2	Test case 1: RF gate of type A	45
5.6.1.2.1	Test execution.....	45
5.6.1.2.2	Initial conditions	45
5.6.1.2.3	Test procedure	46
5.6.1.3	Test case 2: RF gate of type B.....	46
5.6.1.3.1	Test execution.....	46
5.6.1.3.2	Initial conditions	46
5.6.1.3.3	Test procedure	46
5.6.1.4	Test case 3: RF gate of type F.....	47
5.6.1.4.1	Test execution.....	47
5.6.1.4.2	Initial conditions	47
5.6.1.4.3	Test procedure	47
5.6.2	Void	47
5.6.3	Gates	47
5.6.3.1	Void.....	47
5.6.3.2	Identity management gate	48
5.6.3.2.1	Conformance requirements.....	48
5.6.3.3	Card RF gates.....	48
5.6.3.3.1	Overview	48
5.6.3.3.2	Commands.....	48
5.6.3.3.3	Events and subclauses	48
5.6.3.3.4	Registry and subclauses.....	48
5.6.3.4	Card application gates	58
5.6.3.4.1	Overview	58

5.6.3.4.2	Commands.....	58
5.6.3.4.3	Events and subclauses	58
5.6.3.4.4	Registry	59
5.6.4	Procedures.....	60
5.6.4.1	Use of contactless card application	60
5.6.4.1.1	Conformance requirements.....	60
5.6.4.1.2	Test case 1: ISO/IEC 14443-3 Type A.....	60
5.6.4.1.3	Test case 2: ISO/IEC 14443-3 Type B	61
5.6.4.1.4	Test case 3: Routing EVT_FIELD_ON and EVT_FIELD_OFF to RF Gate with lowest G _{ID}	62
5.6.4.1.5	Test case 4: ISO/IEC 14443-3 Type A.....	63
5.6.4.1.6	Test case 5: ISO/IEC 14443-3 Type B	64
5.6.4.2	Non ISO/IEC 14443-4 type A.....	65
5.6.4.2.1	Conformance requirements.....	65
5.6.4.2.2	Test case 1: Non ISO/IEC 14443-4 type A.....	65
5.6.4.2.3	Test case 2: Routing EVT_FIELD_ON and EVT_FIELD_OFF to RF Gate with lowest G _{ID}	66
5.6.4.3	Type B' RF technology	67
5.6.4.3.1	Conformance requirements.....	67
5.6.4.4	Type F RF technology.....	67
5.6.4.4.1	Conformance requirements.....	67
5.6.4.4.2	Test case 1: ISO/IEC 18092 Type F.....	67
5.6.4.4.3	Test case 2: RF off during ISO/IEC 18092 Type F commands handling	68
5.6.4.4.4	Test case 3: Routing EVT_FIELD_ON and EVT_FIELD_OFF to RF Gate with lowest G _{ID}	70
5.6.4.5	Update RF technology settings	71
5.6.4.5.1	Conformance requirements.....	71
5.6.4.6	Identity check.....	71
5.6.4.6.1	Conformance requirements.....	71
5.7	Contactless reader.....	72
5.7.1	Overview	72
5.7.1.1	Conformance requirements	72
5.7.2	Reader RF gates	72
5.7.2.1	Overview.....	72
5.7.2.2	Command.....	72
5.7.2.2.1	WR_XCHG_DATA	72
5.7.2.3	Registries.....	72
5.7.2.3.1	Type A reader RF gate	72
5.7.2.3.2	Type B reader RF gate.....	76
5.7.2.4	Events and subclauses	78
5.7.2.4.1	Events	78
5.7.2.4.2	EVT_READER_REQUESTED	78
5.7.2.4.3	EVT_END_OPERATION.....	78
5.7.2.5	Responses.....	78
5.7.2.5.1	Conformance requirements.....	78
5.7.3	Reader application gates	79
5.7.3.1	Overview.....	79
5.7.3.2	Command.....	79
5.7.3.2.1	Conformance requirements.....	79
5.7.3.3	Registry	79
5.7.3.3.1	Conformance requirements.....	79
5.7.3.4	Events and subclauses	79
5.7.3.4.1	Events	79
5.7.3.4.2	EVT_TARGET_DISCOVERED	79
5.7.4	Procedures.....	80
5.7.4.1	Use of contactless reader application	80
5.7.4.1.1	Conformance requirements.....	80
5.8	Connectivity	80
5.8.1	Overview	80
5.8.2	Connectivity gate and subclauses	80
5.8.2.1	Connectivity gate	80
5.8.2.2	Commands	80
5.8.2.2.1	PRO_HOST_REQUEST	80
5.8.2.3	Events and subclauses	80
5.8.2.3.1	Events	80

5.8.2.3.2	EVT_CONNECTIVITY	81
5.8.2.3.3	Void	81
5.8.2.3.4	EVT_OPERATION_ENDED	81
5.8.2.3.5	EVT_TRANSACTION	81
5.8.2.4	Registry	81
5.8.2.4.1	Conformance requirements.....	81
5.8.3	Connectivity application gate and subclauses.....	82
5.8.3.1	Connectivity application gate.....	82
5.8.3.1.1	Conformance requirements.....	82
5.8.3.2	Commands	82
5.8.3.2.1	Conformance requirements.....	82
5.8.3.3	Events and subclauses	82
5.8.3.3.1	Events	82
5.8.3.3.2	EVT_STANDBY	82
5.8.3.4	Registry	82
5.8.3.4.1	Conformance requirements.....	82
5.8.4	Procedures.....	82
5.8.4.1	Use of connectivity gate.....	82
Annex A (informative):	Bibliography.....	83
Annex B (informative):	Core specification version information.....	84
Annex C (informative):	Change history	85
History		87

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Smart Card Platform (SCP).

The contents of the present document are subject to continuing work within TC SCP and may change following formal TC SCP approval. If TC SCP modifies the contents of the present document, it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 0 early working draft;
 - 1 presented to TC SCP for information;
 - 2 presented to TC SCP for approval;
 - 3 or greater indicates TC SCP approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

The present document is part 1 of a multi-part deliverable covering the Test specification for the Host Controller Interface (HCI), as identified below:

- Part 1:** "Terminal features";
 - Part 2: "UICC features";
 - Part 3: "Host Controller features".
-

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document defines test cases for the terminal relating to the Host Controller Interface (HCI) as specified in ETSI TS 102 622 [1].

The aim of the present document is to ensure interoperability between the terminal and the UICC independently of the respective manufacturer, card issuer or operator.

1 Scope

The present document covers the minimum characteristics which are considered necessary for the terminal in order to provide compliance to ETSI TS 102 622 [1].

The present document specifies the test cases for:

- the HCI core as described in the first part of ETSI TS 102 622 [1];
- the contactless platform as described in the second part of ETSI TS 102 622 [1].

Test cases for the UICC relating to ETSI TS 102 622 [1] and test cases for the Single Wire Protocol (SWP) covering both terminal and UICC are out of scope of the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

- In the case of a reference to a TC SCP document, a non specific reference implicitly refers to the latest version of that document in the same Release as the present document.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 102 622: "Smart Cards; UICC - Contactless Front-end (CLF) Interface; Host Controller Interface (HCI)".
- [2] ETSI TS 102 613: "Smart Cards; UICC - Contactless Front-end (CLF) Interface; Part 1: Physical and data link layer characteristics".
- [3] ETSI TS 102 223: "Smart Cards; Card Application Toolkit (CAT)".
- [4] ISO/IEC 18092: "Information technology - Telecommunications and information exchange between systems - Near Field Communication - Interface and Protocol (NFCIP-1)".
- [5] ISO/IEC 14443-2: "Identification cards - Contactless integrated circuit(s) cards - Proximity cards - Part 2: Radio frequency power and signal interface".
- [6] ISO/IEC 14443-3: "Identification cards - Contactless integrated circuit(s) cards - Proximity cards - Part 3: Initialization and anticollision".
- [7] ISO/IEC 14443-4: "Identification cards - Contactless integrated circuit(s) cards - Proximity cards - Part 4: Transmission Protocol".
- [8] ISO/IEC 7816-4: "Information technology - Identification cards - Integrated circuit(s) cards with contacts - Part 4: Interindustry commands for interchange".
- [9] ISO/IEC 9646-7: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".
- [10] ETSI TS 102 695-3: "Smart Cards; Test specification for the Host Controller Interface (HCI); Part 3: Host Controller features".