
Paints and varnishes — Wettability —
Part 7:
Measurement of the contact angle on a
tilt stage (roll-off angle)

Peintures et vernis — Mouillabilité —

Partie 7: Mesurage de l'angle de contact sur un plan incliné (angle d'écroulement)





COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Apparatus and materials	2
6 Sampling	4
7 Procedure	4
7.1 General for measuring the roll-off angle.....	4
7.1.1 Setting up the contact angle measuring system.....	4
7.1.2 Test conditions.....	5
7.1.3 Conditioning of the test panels.....	5
7.2 Measurement.....	5
7.2.1 General.....	5
7.2.2 Application of the drop.....	5
7.2.3 Determination of the roll-off angle.....	6
8 Precision	8
9 Test report	8
Annex A (informative) Notes on sampling and treatment of test specimens	10
Annex B (informative) Factors influencing the roll-off angle	11
Bibliography	13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 35, *Paints and varnishes*, Subcommittee SC 9, *General test methods for paints and varnishes*.

A list of all parts in the ISO 19403 series can be found on the ISO website.

Introduction

Dynamic contact angles describe the processes on the interface liquid/solid during volume increase (advancing angle) or volume decrease (receding angle) of a drop in horizontal position. As an alternative to the static method (see ISO 19403-2), for the advancing angle always a surface area is wetted, which was previously unwetted. For the receding angle, the contact angle during dewetting is observed. From the difference between advancing angle and receding angle, information on chemical homogeneity and roughness can be concluded. The receding angle is not suitable for the determination of the surface energy.

Paints and varnishes — Wettability —

Part 7:

Measurement of the contact angle on a tilt stage (roll-off angle)

1 Scope

This document specifies a method for the dynamic measurement of the roll-off angle of a liquid drop on a solid surface. From the dynamic measurement, the advancing and receding angles of the drop rolling off can also be determined. The roll-off angle plays a role when evaluating, for example, easy-to-clean or anti-adherent surfaces.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4618, *Paints and varnishes — Terms and definitions*

ISO 19403-1, *Paints and varnishes — Wettability — Part 1: Terminology and general principles*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4618, ISO 19403-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— IEC Electropedia: available at <http://www.electropedia.org/>

— ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

roll-off angle

α_s

tipping of the surface of the solid body, due to which a liquid drop put down onto this surface rolls off

3.2

advancing angle

θ_a

contact angle, which is measured during advancing of the three-phase point

Note 1 to entry: Generally, the advancing angle is used for the determination of the interface energy, in which case the measurement should be carried out close to the thermodynamic equilibrium. This is approximately reached if there is no influence of, for example, the dosing speed on the contact angle.

[SOURCE: ISO 19403-6:2017, 3.2]