

FINAL VERSION

VERSION FINALE



**Environmental testing –
Part 2-64: Tests – Test Fh: Vibration, broadband random and guidance**

**Essais d'environnement –
Partie 2-64: Essais – Essai Fh: Vibrations aléatoires à large bande et guide**

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	8
4 Requirements for test apparatus.....	13
4.1 General.....	13
4.2 Basic motion	14
4.3 Cross-axis motion	14
4.4 Mounting	14
4.5 Measuring systems.....	14
4.6 Vibration tolerances	15
4.6.1 ASD and r.m.s. value.....	15
4.6.2 Distribution.....	15
4.6.3 Statistical accuracy.....	16
4.6.4 Frequency resolution	17
4.7 Control strategy.....	18
4.7.1 Single/multipoint control	18
4.7.2 Multireference control.....	18
4.8 Vibration response investigation.....	18
5 Severities	19
5.1 Test frequency range	19
5.2 RMS value of acceleration.....	19
5.3 Shape of acceleration spectral density curve.....	20
5.4 Test duration	20
6 Preconditioning	20
7 Initial measurements and functional performance test	20
8 Testing	20
8.1 General.....	20
8.2 Initial vibration response investigation.....	21
8.3 Low-level excitation for equalization prior to testing.....	22
8.4 Random testing	22
8.4.1 General	22
8.4.2 Intermediate measurements and functional performance	23
8.5 Final vibration response investigation.....	23
9 Recovery.....	24
10 Final measurements and functional performance	24
11 Information to be given in the relevant specification	24
12 Information to be given in the test report	25
Annex A (informative) Standardized test spectra.....	26
Annex B (informative) Guidance.....	32
B.1 General introduction.....	32
B.2 Requirements for testing	32
B.2.1 Single-point and multipoint control.....	32

B.2.2	Distribution	33
B.2.3	Initial and final slope.....	34
B.3	Testing procedures.....	34
B.4	Equipment normally used with vibration isolators.....	35
B.4.1	Transmissibility factors for isolators.....	35
B.4.2	Temperature effect	35
B.5	Test severities.....	35
B.6	Equipment performance	35
B.7	Initial and final measurements.....	35
Annex C (informative)	Guidance on non-Gaussian distribution/high kurtosis tests.....	36
C.1	Non-Gaussian random vibration	36
C.2	Methods to generate non-Gaussian random vibration	36
C.2.1	General	36
C.2.2	Amplitude modulation technique	37
C.2.3	Phase modification technique	37
C.2.4	Non-uniform phase technique	38
C.3	Additional analysis	38
C.4	Frequency range	39
Bibliography	40
Figure 1	– Tolerance bands for acceleration spectral density; initial and final slope (see B.2.3).....	15
Figure 2	– Time history of stochastically excitation; probability density function with Gaussian (normal) distribution (example with crest factor = 3, see also 3.14 and 4.6.2).....	16
Figure 3	– Statistical accuracy of acceleration spectral density versus degrees of freedom for different confidence levels (see also 4.6.3)	17
Figure 4	– Examples of the beta distribution with different α and β values.....	13
Figure 5	– Time history of non-Gaussian excitation – Probability density function compared with Gaussian (normal) distribution.....	23
Figure A.1	– Frequency/amplitude break points – Transportation.....	26
Figure A.2	– Stationary installation spectrum – Frequency/amplitude break points.....	27
Figure A.3	– Equipment in wheeled vehicles – Frequency/amplitude break points.....	29
Figure A.4	– Equipment installed in airplanes and helicopters.....	30
Table A.1	– Categories for spectrum – Transportation	26
Table A.2	– Break points for spectrum: transportation.....	27
Table A.3	– Categories for spectrum: stationary installation	28
Table A.4	– Break points for spectrum: stationary installation	28
Table A.5	– Categories for spectrum: equipment in wheeled vehicles	29
Table A.6	– Break points for spectrum: equipment in wheeled vehicles.....	30
Table A.7	– Categories for spectrum: equipment in airplanes and helicopters	31
Table A.8	– Break points for spectrum: equipment in airplanes and helicopters	31

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ENVIRONMENTAL TESTING –

Part 2-64: Tests – Test Fh: Vibration, broadband random and guidance

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

DISCLAIMER

This Consolidated version is not an official IEC Standard and has been prepared for user convenience. Only the current versions of the standard and its amendment(s) are to be considered the official documents.

This Consolidated version of IEC 60068-2-64 bears the edition number 2.1. It consists of the second edition (2008-04) [documents 104/456/FDIS and 104/459/RVD] and its amendment 1 (2019-10) [documents 104/848/FDIS and 104/855/RVD]. The technical content is identical to the base edition and its amendment.

This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.

International Standard IEC 60068-2-64 has been prepared by IEC technical committee 104: Environmental conditions, classification and methods of test.

This second edition constitutes a technical revision.

The major changes with regard to the previous edition concern the removal of Method 1 and Method 2, replaced by a single method, and replacement of Annex A with suggested test spectra and removal of Annex C.

Also included in this revision is the testing of soft packed specimens.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

It has the status of a basic safety publication in accordance with IEC Guide 104.

A list of all the parts in the IEC 60068 series, under the general title *Environmental testing*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of IEC 60068 deals with broadband random vibration testing intended for general application to components, equipment and other products, hereinafter referred to as "specimens", that may be subjected to vibrations of a stochastic nature. The methods and techniques in this standard are based on digital control of random vibration. It permits the introduction of variations to suit individual cases if these are prescribed by the relevant specification.

Compared with most other tests, test Fh is not based on deterministic but on statistical techniques. Broad-band random vibration testing is therefore described in terms of probability and statistical averages.

It is emphasized that random testing always demands a certain degree of engineering judgement, and both supplier and purchaser should be fully aware of this fact. The writer of the relevant specification is expected to select the testing procedure and the values of severity appropriate to the specimen and its use.

The test method is based primarily on the use of an electrodynamic or a servo-hydraulic vibration generator with an associated computer based control system used as a vibration testing system.

The traditional general purpose broad-band random vibration test utilizes waveforms with a Gaussian distribution of amplitudes. However, when so specified, this test procedure can also be utilized with random vibration tests with a non-Gaussian distribution of amplitudes. Such tests are sometimes alternatively known as high kurtosis tests.

Annexes A and B are informative annexes giving examples of test spectra for different environmental conditions, a list of details to be considered for inclusion in specifications and guidance.

Annex C is an informative annex giving information on non-Gaussian distribution/high kurtosis tests.

ENVIRONMENTAL TESTING –

Part 2-64: Tests-Test Fh: Vibration, broadband random and guidance

1 Scope

This part of IEC 60068 demonstrates the adequacy of specimens to resist dynamic loads without unacceptable degradation of its functional and/or structural integrity when subjected to the specified random vibration test requirements.

Broadband random vibration may be used to identify accumulated stress effects and the resulting mechanical weakness and degradation in the specified performance. This information, in conjunction with the relevant specification, may be used to assess the acceptability of specimens.

This standard is applicable to specimens which may be subjected to vibration of a stochastic nature resulting from transportation or operational environments, for example in aircraft, space vehicles and land vehicles. It is primarily intended for unpackaged specimens, and for items in their transportation container when the latter may be considered as part of the specimen itself. However, if the item is packaged, then the item itself is referred to as a product and the item and its packaging together are referred to as a test specimen. This standard may be used in conjunction with IEC 60068-2-47:2005, for testing packaged products.

If the specimens are subjected to vibration of a combination of random and deterministic nature resulting from transportation or real life environments, for example in aircraft, space vehicles and for items in their transportation container, testing with pure random may not be sufficient. See IEC 60068-3-8:2003 for estimating the dynamic vibration environment of the specimen and based on that, selecting the appropriate test method.

Although primarily intended for electrotechnical specimens, this standard is not restricted to them and may be used in other fields where desired (see Annex A).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-300: *International Electrotechnical Vocabulary – Electrical and electronic measurements and measuring instruments – Part 311: General terms relating to measurements – Part 312: General terms relating to electrical measurements – Part 313: Types of electrical measuring instruments – Part 314: Specific terms according to the type of instrument*

IEC 60068-1: *Environmental testing – Part 1: General and guidance*

IEC 60068-2-6: *Environmental testing – Part 2-6: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60068-2-47:2005, *Environmental testing – Part 2-47: Tests – Mounting of specimens for vibration, impact and similar dynamic tests*