

FINAL VERSION

VERSION FINALE

**Cable networks for television signals, sound signals and interactive services –
Part 7-1: Hybrid Fibre Coax Outside Plant status monitoring – Physical (PHY)
layer specification**

**Réseaux de distribution par câbles pour signaux de télévision, signaux de
radiodiffusion sonore et services interactifs –
Partie 7-1: Surveillance de l'état des installations extérieures des réseaux
hybrides à fibre optique et câble coaxial – Spécification de la couche
physique (PHY)**



CONTENTS

| | |
|---|----|
| FOREWORD..... | 3 |
| INTRODUCTION..... | 5 |
| 1 Scope..... | 6 |
| 2 Normative references | 7 |
| 3 Terms, definitions and abbreviations | 7 |
| 3.10 Abbreviated terms | 8 |
| 4 HMS reference architecture forward and return channel specifications | 8 |
| 4.1 HMS specification documents..... | 9 |
| 4.2 Functional assumptions | 9 |
| 5 Physical layer specification..... | 10 |
| 5.1 Separate forward and return channels | 10 |
| 5.2 Single forward and return path channels | 10 |
| 5.3 Byte-based transmission | 11 |
| 5.4 Byte formats and transmission order | 11 |
| 5.5 Packet-based transmission..... | 11 |
| 5.6 Duplex operation | 11 |
| 5.7 Forward and return channel specifications..... | 11 |
| 5.8 Media access control layer interface..... | 18 |
| 5.9 RF cut-off | 18 |
| Bibliography..... | 19 |
| | |
| Figure 1 – HMS reference architecture diagram | 9 |
| Figure 2 – Bit transmission order | 11 |
| | |
| Table 1 – Transponder type classifications | 6 |
| Table 2 – HMS document family | 9 |
| Table 3 – Spectral limits by geographical area (North America and Europe) | 10 |
| Table 4 – HMS PHY channel RF and modulation specifications | 12 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 7-1: Hybrid Fibre Coax Outside Plant status monitoring – Physical (PHY) layer specification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

DISCLAIMER

This Consolidated version is not an official IEC Standard and has been prepared for user convenience. Only the current versions of the standard and its amendment(s) are to be considered the official documents.

This Consolidated version of IEC 60728-7-1 bears the edition number 1.1. It consists of the first edition (2003-10) [documents 100/576/CDV and 100/683/RVC] and its amendment 1 (2015-04) [documents 100/2417/FDIS and 100/2481/RVD]. The technical content is identical to the base edition and its amendment.

This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.

International Standard IEC 60728-7-1 has been prepared by technical area 5: Cable networks for television signals, sound signals and interactive services, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

The following differences exist in some countries:

The Japanese *de facto* standard (NCTEA S-006) concerning requirements for the HFC outside plant management, which was published in 1995, has already been available in Japan. The purpose of this standard is to support the design and implementation of interoperable management systems for HFC cable networks used in Japan. (see Table 4)

INTRODUCTION

Standards and other deliverables of the IEC 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television and sound signals and for processing, interfacing and transmitting all kinds of data signals for interactive services using all applicable transmission media. These signals are typically transmitted in networks by frequency-multiplexing techniques.

This includes for instance

- regional and local broadband cable networks,
- extended satellite and terrestrial television distribution systems,
- individual satellite and terrestrial television receiving systems,

and all kinds of equipment, systems and installations used in such cable networks, distribution and receiving systems.

The extent of this standardization work is from the antennas and/or special signal source inputs to the headend or other interface points to the network up to the terminal input of the customer premises equipment.

The standardization work will consider coexistence with users of the RF spectrum in wired and wireless transmission systems.

The standardization of any user terminals (i.e. tuners, receivers, decoders, multimedia terminals, etc.) as well as of any coaxial and optical cables and accessories thereof is excluded.

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 7-1: Hybrid Fibre Coax Outside Plant status monitoring – Physical (PHY) layer specification

1 Scope

This part of IEC 60728 specifies requirements for The Hybrid Fibre Coax (HFC) Outside Plant (OSP) Physical (PHY) Layer Specification and is part of the series of specifications developed by the Hybrid Management Sub-Layer (HMS) subcommittee under the SCTE. The purpose of the HMS specification is to support the design and implementation of interoperable management systems for evolving HFC cable networks. The HMS Physical (PHY) Layer Specification describes the physical layer portion of the protocol stack used for communication between HMS-compliant transponders interfacing to managed outside plant network elements (NE) and a centralized head-end element (HE).

This standard describes the PHY layer requirements that must be implemented by all *Type 2* and *Type 3* compliant OSP HMS transponders on the HFC plant and the controlling equipment in the head-end. Any exceptions to compliance with this standard will be specifically noted herein as necessary. Refer to Table 1 for a full definition of the type classifications.

Electromagnetic Compatibility (EMC) is not specified in this standard and is left to the vendor to ensure compliance with local EMC regulatory requirements. Other than operating temperature, physical parameters such as shock, vibration, humidity, etc., are also not specified and left to the vendor's discretion.

Transponder type classifications referenced within the HMS series of standards are defined in Table 1.

Table 1 – Transponder type classifications

| Type | Description | Application |
|--------|---|--|
| Type 0 | Refers to legacy transponder equipment, which is incapable of supporting the HMS specifications | This transponder interfaces with legacy network equipment through proprietary means. This transponder could be managed through the same management applications as the other types through proxies or other means at the head-end |
| Type 1 | Refers to stand-alone transponder equipment (legacy or new) which can be upgraded to support the HMS specifications | This transponder interfaces with legacy network equipment through proprietary means. Type 1 is a standards-compliant transponder (either manufactured to the standard or upgraded) that connects to legacy network equipment via a proprietary interface |
| Type 2 | Refers to a stand-alone, HMS-compliant transponder | This transponder interfaces with network equipment designed to support the electrical and physical specifications defined in the HMS standards. It can be factory or field-installed. Its RF connection is independent of the monitored NE |
| Type 3 | Refers to a stand-alone or embedded, HMS-compliant transponder | This transponder interfaces with network equipment designed to support the electrical specifications defined in the HMS standards. It may or may not support the physical specifications defined in the HMS standards. It can be factory-installed. It may or may not be field-installed. Its RF connection is through the monitored NE |