

FINAL VERSION

VERSION FINALE



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE
COMITÉ INTERNATIONAL SPÉCIAL DES PERTURBATIONS RADIOÉLECTRIQUES

**Specification for radio disturbance and immunity measuring apparatus
and methods –**

**Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas
and test sites for radiated disturbance measurements**

**Spécifications des méthodes et des appareils de mesure des perturbations
radioélectriques et de l'immunité aux perturbations radioélectriques –**

**Partie 1-4: Appareils de mesure des perturbations radioélectriques et de
l'immunité aux perturbations radioélectriques – Antennes et emplacements
d'essai pour les mesures des perturbations rayonnées**

CONTENTS

FOREWORD	8
1 Scope	10
2 Normative references	10
3 Terms, definitions and abbreviated terms	11
3.1 Terms and definitions.....	11
3.2 Abbreviated terms.....	15
4 Antennas for measurement of radiated radio disturbance	16
4.1 General.....	16
4.2 Physical parameter (measurand) for radiated disturbance measurements	16
4.3 Antennas for the frequency range 9 kHz to 150 kHz.....	17
4.3.1 General.....	17
4.3.2 Magnetic field antenna.....	17
4.3.3 Shielding of loop antenna	17
4.4 Antennas for the frequency range 150 kHz to 30 MHz.....	17
4.4.1 Electric field antenna	17
4.4.2 Magnetic field antenna.....	18
4.4.3 Balance and electric field discrimination of antennas	18
4.5 Antennas for the frequency range 30 MHz to 1 000 MHz.....	18
4.5.1 General.....	18
4.5.2 Low-uncertainty antenna for use if there is an alleged non-compliance to the electric disturbance field strength limit	18
4.5.3 Antenna characteristics.....	18
4.5.4 Balance of antenna	20
4.5.5 Cross-polar response of antenna	22
4.6 Antennas for the frequency range 1 GHz to 18 GHz.....	23
4.6.1 General.....	23
4.6.2 Receive antenna	23
4.7 Special antenna arrangements – large-loop antenna system.....	25
5 Test sites for measurement of radio disturbance field strength for the frequency range of 9 kHz to 30 MHz	26
6 Test sites for measurement of radio disturbance field strength for the frequency range of 30 MHz to 1 000 MHz	26
6.1 General.....	26
6.2 OATS.....	26
6.2.1 General.....	26
6.2.2 Weather-protection enclosure	26
6.2.3 Obstruction-free area	26
6.2.4 Radio-frequency ambient environment of a test site	28
6.2.5 Ground plane.....	28
6.3 Suitability of other test sites	28
6.3.1 Other ground-plane test sites.....	28
6.3.2 Test sites without ground plane (FAR)	29
6.4 Test site validations	29
6.4.1 General.....	29
6.4.2 Overview of test site validations.....	30
6.5 Basic parameters of the NSA method for OATS and SAC.....	30

6.5.1	General equation and table of theoretical NSA values.....	30
6.5.2	Antenna calibration	34
6.6	Reference site method for OATS and SAC	34
6.6.1	General.....	34
6.6.2	Antennas not permitted for RSM measurements	35
6.6.3	Determination of the antenna pair reference site attenuation on a REFTS	35
6.6.4	Determination of the antenna pair reference site attenuation using an averaging technique on a large OATS.....	36
6.7	Validation of an OATS by the NSA method	39
6.7.1	Discrete frequency method	39
6.7.2	Swept frequency method.....	40
6.8	Validation of a weather-protection-enclosed OATS or a SAC	41
6.9	Possible causes for exceeding site acceptability limits	43
6.10	Site validation for FARs	44
6.10.1	General.....	44
6.10.2	RSM for FAR sites	48
6.10.3	NSA method for FAR sites	50
6.10.4	Site validation criteria for FAR sites	52
6.11	Evaluation of set-up table and antenna tower.....	52
6.11.1	General.....	52
6.11.2	Evaluation procedure for set-up table influences	53
7	Test sites for measurement of radio disturbance field strength for the frequency range 1 GHz to 18 GHz	54
7.1	General.....	54
7.2	Reference test site.....	55
7.3	Test site validation.....	55
7.3.1	General.....	55
7.3.2	Acceptance criterion for site validation.....	56
7.4	Antenna requirements for S_{VSWR} standard test procedure	56
7.4.1	General.....	56
7.4.2	Transmit antenna	57
7.4.3	Antennas and test equipment for the S_{VSWR} reciprocal test procedure	59
7.5	Required positions for site validation testing	60
7.5.1	General.....	60
7.5.2	Descriptions of S_{VSWR} measurement positions in a horizontal plane (Figure 23).....	60
7.5.3	Descriptions of S_{VSWR} additional measurement positions (Figure 24).....	61
7.5.4	Summary of S_{VSWR} measurement positions.....	62
7.6	S_{VSWR} site validation – standard test procedure	65
7.7	S_{VSWR} site validation – reciprocal test procedure using an isotropic field probe	66
7.8	S_{VSWR} conditional measurement position requirements	67
7.9	S_{VSWR} site validation test report.....	68
7.10	Limitations of the S_{VSWR} site validation method.....	68
7.11	Alternative test sites	69
8	Common mode absorption devices	69
8.1	General.....	69
8.2	CMAD S -parameter measurements	69
8.3	CMAD test jig.....	69

8.4	Measurement method using the TRL calibration.....	70
8.5	Specification of ferrite clamp-type CMAD	72
8.6	CMAD performance (degradation) check using spectrum analyzer and tracking generator.....	73
9	Reverberating chamber for total radiated power measurement	75
9.1	General.....	75
9.2	Chamber.....	75
9.2.1	Chamber size and shape	75
9.2.2	Door, openings in walls, and mounting brackets.....	75
9.2.3	Stirrers	76
9.2.4	Test for the efficiency of the stirrers.....	76
9.2.5	Coupling attenuation.....	77
10	TEM cells for immunity to radiated disturbance measurement.....	78
Annex A (normative) Parameters of antennas		79
A.1	General.....	79
A.2	Preferred antennas	79
A.2.1	General.....	79
A.2.2	Calculable antenna	79
A.2.3	Low-uncertainty antennas	79
A.3	Simple dipole antennas.....	80
A.3.1	General.....	80
A.3.2	Tuned dipole.....	81
A.3.3	Shortened dipole.....	81
A.4	Broadband antenna parameters	82
A.4.1	General.....	82
A.4.2	Antenna type	83
A.4.3	Specification of the antenna.....	83
A.4.4	Antenna calibration	84
A.4.5	Antenna user information	84
Annex B (XXX) (Void)		85
Annex C (normative) Large-loop antenna system for magnetic field induced-current measurements in the frequency range of 9 kHz to 30 MHz.....		86
C.1	General.....	86
C.2	Construction of an LLAS	86
C.3	Construction of a large-loop antenna (LLA).....	86
C.4	Validation of an LLAS	91
C.5	Construction of the LLAS verification dipole antenna.....	93
C.6	Conversion factors	94
C.6.1	General.....	94
C.6.2	Current conversion factors for an LLAS with non-standard diameter	95
C.6.3	Conversion of LLAS measured current to magnetic field strength.....	96
C.7	Examples	98
Annex D (normative) Construction details for open area test sites in the frequency range of 30 MHz to 1 000 MHz (see Clause 6).....		100
D.1	General.....	100
D.2	Ground plane construction	100
D.2.1	Material	100
D.2.2	Roughness	100
D.3	Services to EUT.....	101

D.4	Weather-protection enclosure construction	101
D.4.1	Materials and fasteners.....	101
D.4.2	Internal arrangements.....	102
D.4.3	Size	102
D.4.4	Uniformity with time and weather	102
D.5	Turntable and set-up table	102
D.6	Receive antenna mast installation.....	103
Annex E (xxx)	(Void).....	104
Annex F (informative)	Basis for ± 4 dB site acceptability criterion (see Clause 6).....	105
F.1	General.....	105
F.2	Error analysis.....	105
Annex G (informative)	Examples of uncertainty budgets for site validation of a COMTS using RSM with a calibrated antenna pair (see 6.6)	107
G.1	Quantities to be considered for antenna pair reference site attenuation calibration using the averaging technique	107
G.2	Quantities to be considered for antenna pair reference site attenuation calibration using a REFTS	108
G.3	Quantities to be considered for COMTS validation using an antenna pair reference site attenuation	109
Annex H (informative)	Definition of uncertainty in cross-polar response measurement	110
H.1	General.....	110
H.2	Example uncertainty estimate	112
H.3	Rationale for the estimates of input quantities in Table H.1 and Table H.3	113
H.4	Measurement of XPR below 100 MHz at an OATS	114
Bibliography	116
Figure 1	– Schematic of radiation from EUT reaching an LPDA antenna directly and via ground reflection at a 3 m site, showing the beamwidth half-angle, φ , at the reflected ray.....	19
Figure 2	– RX antenna E-plane radiation pattern example, with limit area shaded for 3 m distance and 2 m EUT width.....	24
Figure 3	– Determination of maximum useable EUT width using half-power beamwidth	24
Figure 4	– Determination of maximum useable EUT height using half-power beamwidth	25
Figure 5	– Obstruction-free area of a test site with a turntable	27
Figure 6	– Obstruction-free area with stationary EUT	27
Figure 7	– Test point locations for 3 m and 10 m test distances	36
Figure 8	– Paired test point locations for all test distances.....	38
Figure 9	– Example of paired test point selection for a test distance of 10 m.....	38
Figure 10	– Illustration of an investigation of influence of antenna mast on A_{APR}	39
Figure 11	– Typical antenna positions for a weather-protected OATS or a SAC – vertical polarization validation measurements	42
Figure 12	– Typical antenna positions for a weather-protected OATS or a SAC – horizontal polarization validation measurements	42
Figure 13	– Typical antenna positions for a weather-protected OATS or a SAC – vertical polarization validation measurements for a smaller EUT	43
Figure 14	– Typical antenna positions for a weather-protected OATS or a SAC – horizontal polarization validation measurements for a smaller EUT	43
Figure 15	– Measurement positions for FAR site validation	46

Figure 16 – Example of one measurement position and antenna tilt for FAR site validation	48
Figure 17 – Typical quasi free-space test site reference SA measurement set-up	50
Figure 18 – Theoretical free-space NSA as a function of frequency for different measurement distances [see Equation (16)].....	52
Figure 19 – Position of the antenna relative to the edge above a rectangle set-up table (top view).....	54
Figure 20 – Antenna position above the set-up table (side view).....	54
Figure 21 – Transmit antenna E-plane radiation pattern example (this example is for informative purposes only).....	58
Figure 22 – Transmit antenna H-plane radiation pattern (this example is for informative purposes only).....	59
Figure 23 – S_{VSWR} measurement positions in a horizontal plane (see 7.5.2 for description).....	60
Figure 24 – S_{VSWR} positions (height requirements)	62
Figure 25 – S_{VSWR} conditional measurement position requirements	68
Figure 26 – Definition of the reference planes inside the test jig	70
Figure 27 – The four configurations for the TRL calibration	72
Figure 28 – Limits for the magnitude of S_{11} , measured according to the provisions of 8.1 to 8.3	73
Figure 29 – Example of a 50 Ω adaptor construction in the vertical flange of the jig	74
Figure 30 – Example of a matching adaptor with balun or transformer	74
Figure 31 – Example of a matching adaptor with resistive matching network.....	75
Figure 32 – Example of a typical paddle stirrer	76
Figure 33 – Range of coupling attenuation as a function of frequency for a chamber using the stirrer shown in Figure 32	77
Figure A.1 – Short dipole antenna factors for $R_L = 50 \Omega$	82
Figure C.1 – The LLAS, consisting of three mutually perpendicular large-loop antennas	88
Figure C.2 – An LLA containing two opposite slits, positioned symmetrically with respect to the current probe C	89
Figure C.3 – Construction of an LLA slit.....	89
Figure C.4 – Example of an LLA slit construction using a strap of printed circuit board to obtain a rigid construction	90
Figure C.5 – Construction of the metal box containing the current probe.....	90
Figure C.6 – Example showing the routing of several cables from an EUT to minimize capacitive coupling from the leads to the LLAS	91
Figure C.7 – The eight positions of the LLAS verification dipole during validation of an LLA	92
Figure C.8 – Reference validation factors for loops of 2 m, 3 m, and 4 m diameters.....	92
Figure C.9 – Construction of the LLAS verification dipole antenna	94
Figure C.10 – Sensitivity S_D of an LLA with diameter D relative to an LLA with 2 m diameter	95
Figure C.11 – Conversion factor C_{dA} [for conversion into dB(μ A/m)] for three standard measurement distances d	97
Figure D.1 – The Rayleigh criterion for roughness in the ground plane	101
Table 1 – Site validation methods applicable for OATS, OATS-based, SAC, and FAR site types	30

Table 2 – Theoretical normalized site attenuation, A_N – recommended geometries for broadband antennas ^a (1 of 2)	32
Table 3 – Example template for A_{APR} data sets	35
Table 4 – RSM frequency steps	35
Table 5 – Maximum dimensions of test volume versus test distance	44
Table 6 – Frequency ranges and step sizes for FAR site validation	48
Table 7 – S_{VSWR} measurement position designations (1 of 3)	63
Table 8 – S_{VSWR} reporting requirements	68
Table C.1 – Reference validation factors of Figure C.8 for loops of 2 m, 3 m, and 4 m diameters	93
Table C.2 – Sensitivity S_D of an LLA with diameter D relative to an LLA with 2 m diameter (Figure C.10)	96
Table C.3 – Magnetic field strength conversion factor C_{dA} for three measurement distances (Figure C.11)	98
Table D.1 – Maximum roughness for 3 m, 10 m and 30 m measurement distances	101
Table F.1 – Error budget	105
Table G.1 – Antenna pair reference site attenuation calibration using the large-OATS averaging technique	107
Table G.2 – Antenna pair reference site attenuation calibration using REFTS	108
Table G.3 – COMTS validation using an antenna pair reference site attenuation	109
Table H.1 – Example uncertainty estimate for XPR measurement in a FAR and assumed $a_{xpT} = 22$ dB, $a_{xpR} = 34$ dB	113
Table H.2 – Uncertainties depending on other values of A_{xpT} (other assumptions as in Table H.1)	114
Table H.3 – Example uncertainty estimate for XPR measurement at an OATS and assumed $a_{xpT} = 22$ dB, $a_{xpR} = 34$ dB	115

INTERNATIONAL ELECTROTECHNICAL COMMISSION
INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

**SPECIFICATION FOR RADIO DISTURBANCE AND
IMMUNITY MEASURING APPARATUS AND METHODS –**

**Part 1-4: Radio disturbance and immunity measuring apparatus –
Antennas and test sites for radiated disturbance measurements**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

CISPR 16-1-4 edition 4.1 contains the fourth edition (2019-01) [documents CIS/A/1262/FDIS and CIS/A/1275/RVD] and its amendment 1 (2020-06) [documents CIS/A/1316/FDIS and CIS/A/1320/RVD].

This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.

This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- provisions are added to address test site validation in the frequency range from 30 MHz to 1000 MHz using the reference site method, to take into account the receive antenna radiation pattern in the frequency range from 1 GHz to 18 GHz, and further details on test site validation using the NSA method with broadband antennas in the frequency range from 30 MHz to 1 000 MHz.

International Standard CISPR 16-1-4 has been prepared by CISPR subcommittee A: Radio-interference measurements and statistical methods.

It has the status of a basic EMC publication in accordance with IEC Guide 107, *Electromagnetic compatibility – Guide to the drafting of electromagnetic compatibility publications*.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of CISPR 16 series, under the general title *Specification for radio disturbance and immunity measuring apparatus and methods*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

SPECIFICATION FOR RADIO DISTURBANCE AND IMMUNITY MEASURING APPARATUS AND METHODS –

Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas and test sites for radiated disturbance measurements

1 Scope

This part of CISPR 16 specifies the characteristics and performance of equipment for the measurement of radiated disturbances in the frequency range 9 kHz to 18 GHz. Specifications for antennas and test sites are included.

NOTE In accordance with IEC Guide 107, CISPR 16-1-4 is a basic EMC publication for use by product committees of the IEC. As stated in Guide 107, product committees are responsible for determining the applicability of the EMC standard. CISPR and its sub-committees are prepared to cooperate with product committees in the evaluation of the value of particular EMC tests for specific products.

The requirements of this publication apply at all frequencies and for all levels of radiated disturbances within the CISPR indicating range of the measuring equipment.

Methods of measurement are covered in Part 2-3, further information on radio disturbance is given in Part 3, and uncertainties, statistics and limit modelling are covered in Part 4 of CISPR 16.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CISPR 16-1-1, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus*

CISPR 16-1-5:2014, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-5: Radio disturbance and immunity measuring apparatus – Antenna calibration sites and reference test sites for 5 MHz to 18 GHz*
CISPR 16-1-5:2014/AMD1:2016

CISPR 16-1-6:2014, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-6: Radio disturbance and immunity measuring apparatus – EMC antenna calibration*
CISPR 16-1-6:2014/AMD1:2017

CISPR 16-2-3:2016, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 2-3: Methods of measurement of disturbances and immunity – Radiated disturbance measurements*

CISPR TR 16-3, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 3: CISPR technical reports*