

GUIDELINE

ASHRAE Guideline 24-2015 (Supersedes ASHRAE Guideline 24-2008)

Ventilation and Indoor Air Quality in Low-Rise Residential Buildings

Approved by the ASHRAE Standards Committee on June 27, 2015, and by the ASHRAE Technology Council on July 1, 2015.

ASHRAE Guidelines are scheduled to be updated on a five-year cycle; the date following the Guideline number is the year of ASHRAE Board of Directors approval. The latest edition of an ASHRAE Guideline may be purchased on the ASHRAE website (www.ashrae.org) or from ASHRAE Customer Service, 1791 Tullie Circle, NE, Atlanta, GA 30329-2305. E-mail: orders@ashrae.org. Fax: 678-539-2129. Telephone: 404-636-8400 (worldwide) or toll free 1-800-527-4723 (for orders in US and Canada). For reprint permission, go to www.ashrae.org/permissions.

© 2015 ASHRAE ISSN 1049-894X

ASHRAE Standing Standard Project Committee 62.2 Cognizant TC: 4.3, Ventilation Requirements and Infiltration SPLS Liaison: John F. Dunlap

Paul Francisco,*† *Chair* lain S. Walker,* *Vice-Chair* Paul H. Raymer,*† *Secretary* David A. Baylon* Terry M. Brennan* Roy R. Crawford* S. Craig Drumheller* Philip W. Fairey, III* Mark C. Jackson*† Richard J. Karg*† Joseph W. Lstiburek*

Michael R. Lubliner* Stephany I. Mason*† Darren B. Meyers* James C. Moore, III* Amy B. Musser* Mary Opalka* John P. Proctor* Don T. Stevens* Thomas R. Stroud* Eric D. Werling* Bruce A. Wilcox*

Ted A. Williams* Gary Craw Henry T. Greist Sanjeev K. Hingorani Glenn P. Langan Wayne E. Morris Armin Rudd Max H. Sherman Sarany Singer Christine Q. Sun Steven Welty†

* Denotes members of voting status when the document was approved for publication † Denotes members of the Guideline 24-2008 revision subcommittee

ASHRAE STANDARDS COMMITTEE 2014–2015

Richard L. Hall, *Chair* Douglass T. Reindl, *Vice-Chair* Joseph R. Anderson James Dale Aswegan Charles S. Barnaby Donald M. Brundage John A. Clark Waller S. Clements David R. Conover John F. Dunlap James W. Earley, Jr. Steven J. Emmerich Patricia T. Graef Rita M. Harrold Adam W. Hinge Srinivas Katipamula Debra H. Kennoy Malcolm D. Knight Rick A. Larson Arsen K. Melkov Mark P. Modera Cyrus H. Nasseri Heather L. Platt Peter Simmonds Wayne H. Stoppelmoor, Jr. Jack H. Zarour Julia A. Keen, *BOD ExO* Bjarne Wilkens Olesen, *CO*

Stephanie C. Reiniche, Senior Manager of Standards

SPECIAL NOTE

This Guideline was developed under the auspices of ASHRAE. ASHRAE Guidelines are developed under a review process, identifying a Guideline for the design, testing, application, or evaluation of a specific product, concept, or practice. As a Guideline it is not definitive but encompasses areas where there may be a variety of approaches, none of which must be precisely correct. ASHRAE Guidelines are written to assist professionals in the area of concern and expertise of ASHRAE's Technical Committees and Task Groups.

ASHRAE Guidelines are prepared by Project Committees appointed specifically for the purpose of writing Guidelines. The Project Committee Chair and Vice-Chair must be members of ASHRAE; while other committee members may or may not be ASHRAE members, all must be technically qualified in the subject area of the Guideline.

Development of ASHRAE Guidelines follows procedures similar to those for ASHRAE Standards except that (a) committee balance is desired but not required, (b) an effort is made to achieve consensus but consensus is not required, (c) Guidelines are not appealable, and (d) Guidelines are not submitted to ANSI for approval.

The Senior Manager of Standards of ASHRAE should be contacted for

a. interpretation of the contents of this Guideline,

b. participation in the next review of the Guideline,

- c. offering constructive criticism for improving the Guideline, or
- d. permission to reprint portions of the Guideline.

DISCLAIMER

ASHRAE uses its best efforts to promulgate Standards and Guidelines for the benefit of the public in light of available information and accepted industry practices. However, ASHRAE does not guarantee, certify, or assure the safety or performance of any products, components, or systems tested, installed, or operated in accordance with ASHRAE's Standards or Guidelines or that any tests conducted under its Standards or Guidelines will be nonhazardous or free from risk.

ASHRAE INDUSTRIAL ADVERTISING POLICY ON STANDARDS

ASHRAE Standards and Guidelines are established to assist industry and the public by offering a uniform method of testing for rating purposes, by suggesting safe practices in designing and installing equipment, by providing proper definitions of this equipment, and by providing other information that may serve to guide the industry. The creation of ASHRAE Standards and Guidelines is determined by the need for them, and conformance to them is completely voluntary.

In referring to this Standard or Guideline and in marking of equipment and in advertising, no claim shall be made, either stated or implied, that the product has been approved by ASHRAE.

CONTENTS

ASHRAE Guideline 24-2015, Ventilation and Indoor Air Quality in Low-Rise Residential Buildings

SECT	ΓΙΟΝ	PAGE
Foreword		2
1	Purpose	2
2	Scope	2
3	Definitions	2
4	Indoor Contaminants	4
5	Building Airflow Fundamentals	11
6	Outdoor Air	14
7	Moisture	17
8	Contaminant Generation and Transport	19
9	Indoor Air Quality Control	23
10	Mechanical Ventilation System Design	
11	Natural Ventilation	
12	Verification of Equipment Performance	35
13	Operations and Maintenance Documentation	
14	References	40
15	Abbreviations	44

NOTE

Approved addenda, errata, or interpretations for this guideline can be downloaded free of charge from the ASHRAE Web site at www.ashrae.org/technology.

© 2015 ASHRAE

1791 Tullie Circle NE · Atlanta, GA 30329 · www.ashrae.org · All rights reserved. ASHRAE is a registered trademark of the American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc. (This foreword is not part of this standard. It is merely informative and does not contain requirements necessary for conformance to the standard. It has not been processed according to the ANSI requirements for a standard and may contain material that has not been subject to public review or a consensus process. Unresolved objectors on informative material are not offered the right to appeal at ASHRAE or ANSI.)

FOREWORD

In 2003, ASHRAE published Standard 62.2, Ventilation and Acceptable Indoor Air Quality in Low-Rise Residential Buildings, the first stand-alone ventilation and indoor air quality (IAQ) standard specifically written for low-rise residential buildings. Although Standard 62.2 provides far more detailed residential ventilation requirements than were contained in the previous versions of Standard 62, the 62.2 project committee felt that the new standard by itself did not adequately address the need to provide information on achieving better IAQ in low-rise residential buildings. In writing Guideline 24, the committee was able to address IAQ and ventilation issues where consensus could not be achieved in Standard 62.2 and to provide explanatory and educational material that would be inappropriate in a document intended for code adoption.

While the title of Guideline 24—Ventilation and Acceptable Indoor Air Quality in Low-Rise Residential Buildings is nearly identical to that of Standard 62.2, this guideline's purpose and scope contain many significant differences with Standard 62.2. The purpose of the standard is limited to defining the roles of and minimum requirements for mechanical and natural ventilation systems and the building envelope intended to provide acceptable IAQ in low-rise residential buildings. While these roles and requirements are written with the intent of providing acceptable IAQ in low-rise residential buildings, the much broader purpose of this guideline is to provide information on achieving better IAQ in all types of dwelling units.

The scope of this guideline is also broader than that of Standard 62.2. Both scopes specify that the documents apply to residential buildings three stories or fewer in height above grade, including manufactured and modular houses. However, Standard 62.2's scope specifically excludes unvented combustion space heaters and provides a list of reasons that may prevent acceptable IAQ from being achieved, despite meeting all of the minimum requirements. Given its broader scope addressing topics not included in the standard, Guideline 24 goes beyond Standard 62.2's baseline objective of acceptable IAQ in providing information aimed at helping to achieve better IAQ.

Thus, in addition to providing informative background material on residential IAQ, this guideline addresses important residential IAQ issues that were not addressed in Standard 62.2 due to a lack of consensus or other reasons. Some of these issues were addressed in prepublication draft versions of Standard 62.2 and include carbon monoxide (CO) alarms, air distribution, better air filtration, and unvented combustion appliances. This guideline also provides useful information on topics such as verification of ventilation equipment performance and operations and maintenance, which, though important, are not easily addressed in a standard intended for code adoption.

1. PURPOSE

1.1 This guideline provides information on achieving indoor air quality (IAQ) that may go beyond minimum requirements, i.e., better IAQ.

1.2 This guideline provides information relevant to ventilation and IAQ with regard to envelope and system design, material selection, commissioning and installation, and operation and maintenance.

2. SCOPE

This guideline primarily applies to ventilation and IAQ for human occupancy in residential buildings three stories or fewer in height above grade, including manufactured and modular houses.

3. DEFINITIONS

When the following terms are used in this guideline, the definitions provided in this section apply.

acceptable indoor air quality: air toward which a substantial majority of occupants express no dissatisfaction with respect to odor and sensory irritation and in which there are not likely to be contaminants at concentrations that are known to pose a health risk.

air cleaning: the use of equipment that removes particulate, microbial, or gaseous contaminants (including odors) from air.

air, exhaust: air discharged from any space to the outside by an exhaust system.

air, indoor: air in an occupiable space.

air, outdoor: air from outside the building that is taken into a ventilation system or that enters a space through infiltration or natural ventilation openings.

air, transfer: air that is moved from one occupiable space to another, usually through doorways or grilles.

air, ventilation: outdoor air that is delivered to a space to dilute airborne contaminants.

air change rate: airflow in volume units per hour divided by the volume of the space on which the air change rate is based in identical units (normally expressed in air changes per hour [ach]).

balanced system: one or more fans that supply outdoor air and exhaust building air at essentially equal rates.

bathroom: any room containing a bathtub, a shower, a spa, or a similar source of moisture.

better IAQ: air that not only meets the definition of "acceptable indoor air quality," but also is expected to have reduced levels of contaminants of concern recommended by the selected cognizant authority.

breathing zone: the region within an occupied space between planes 3 and 72 in. (75 and 1800 mm) above the floor and