



BSI Standards Publication

**Maritime navigation and
radiocommunication
equipment and systems —
Shipborne radar —
Performance requirements,
methods of testing and
required test results**

National foreword

This British Standard is the UK implementation of EN 62388:2013. It is identical to IEC 62388:2013, incorporating corrigendum February 2014. It supersedes BS EN 62388:2008, which will be withdrawn on 31 July 2016.

IEC corrigendum February 2014 corrects elements of subclause 16.1.7.2 and Table H.1.

The UK participation in its preparation was entrusted to Technical Committee EPL/80, Maritime navigation and radiocommunication equipment and systems.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014.
Published by BSI Standards Limited 2014

ISBN 978 0 580 74694 9

ICS 33.060; 47.020.70

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 May 2014.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 62388

October 2013

ICS 33.060; 47.020.70

English version

**Maritime navigation and radiocommunication equipment and systems -
Shipborne radar -
Performance requirements, methods of testing and required test results
(IEC 62388:2013)**

Matériels et systèmes de navigation et de
radiocommunication maritimes -
Radars de bord -
Exigences de performance, méthodes
d'essai et résultats exigés
(CEI 62388:2013)

Navigations- und
Funkkommunikationsgeräte und -systeme
für die Seeschifffahrt -
Radar für Schiffe -
Leistungsanforderungen, Prüfverfahren
und geforderte Prüfergebnisse
(IEC 62388:2013)

This European Standard was approved by CENELEC on 2013-07-31. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 80/696/FDIS, future edition 2 of IEC 62388, prepared by IEC TC 80 "Maritime navigation and radiocommunication equipment and systems" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62388:2013.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2014-04-30
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2016-07-31

This document supersedes EN 62388:2008.

EN 62388:2013 includes the following significant technical changes with respect to EN 62388:2008:

- In 6.2 (Transmission and interference) reference is now made to a revised Annex B (Unwanted emissions) where the mask has been tightened from 20 dB/decade to 30 dB/decade in line with ITU requirements and a new informative Annex J has been added concerning interference from emissions in adjacent frequency bands;
- Clause 7 (Display presentation) has been simplified (and the previous Annexes J and K deleted) with reference made instead to EN 62288 with associated changes throughout the standard;
- In 9.9.2 (PI lines and positioning) the requirements for parallel index lines have been revised;
- In 10.4.4 (Display orientation) a new mode of display orientation "head-up stabilised" has been added;
- In 11.5 (Automatic Identification System) new requirements and tests have been added for types of AIS targets, AIS repeater stations and filtering of AIS targets;
- In Clause 12 (Chart radar) a new subclause 12.3 has been added for ECDIS backup requirements;
- In Clause 13 (Ergonomic criteria) a new subclause 13.5 has been added giving requirements for default control settings;
- 14.3 (Output interfacing) has been revised together with the associated Annex H to update the requirements particularly with regard to interfaces to the VDR;
- Clause 16 (Alerts and failures) has been revised to update the requirements to align with bridge alert management and new requirements added for an alert management interface with associated changes throughout the standard;
- In Clause 18 (Equipment familiarisation and documentation) a new subclause 18.3 has been added for maintenance information and equipment update.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62388:2013 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 62616	NOTE	Harmonised as EN 62616.
ISO 9000	NOTE	Harmonised as EN ISO 9000.
ISO 9241-8	NOTE	Harmonised as EN ISO 9241-8.
ISO 9241-12	NOTE	Harmonised as EN ISO 9241-12.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60945	-	Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results	EN 60945	-
IEC 61162	series	Maritime navigation and radiocommunication equipment and systems - Digital interfaces	EN 61162	series
IEC 61174	-	Maritime navigation and radiocommunication equipment and systems - Electronic chart display and information system (ECDIS) - Operational and performance requirements, methods of testing and required test results	EN 61174	-
IEC 61924-2	2012	Maritime navigation and radiocommunication equipment and systems - Integrated navigation systems - Part 2: Modular structure for INS - Operational and performance requirements, methods of testing and required test results	EN 61924-2	2013
IEC 61996-1	2013	Maritime navigation and radiocommunication equipment and systems - Shipborne voyage data recorder (VDR) - Part 1: Performance requirements, methods of testing and required test results	EN 61996-1	2013
IEC 62288	-	Maritime navigation and radiocommunication equipment and systems - Presentation of navigation-related information on shipborne navigational displays - General requirements, methods of testing and required test results	EN 62288	-
ITU-R Recommendation M.628	-	Technical characteristics for search and rescue radar transponders	-	-
ITU-R Recommendation M.824	-	Technical parameters of radar beacons (racons)	-	-

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
ITU-R Recommendation M.1176	-	Technical parameters of radar target enhancers	-	-
IHO S-52	-	Specifications for chart content and display aspects of ECDIS	-	-
IHO S-52, Appendix 2, Annex A	-	IHO ECDIS Presentation Library	-	-
IMO Resolution A.424(IX)	-	Performance standards for gyro- compasses	-	-
IMO Resolution A.694(17)	-	General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids	-	-
IMO Resolution A.821(19)	-	Performance standards for gyro- compasses for high-speed craft	-	-
IMO Resolution MSC.96(72)	-	Amendments to performance standards for devices to indicate speed and distance (resolution A.824(19))	-	-
IMO Resolution MSC.116(73)	-	Performance standards for marine transmitting heading devices (THDs)	-	-
IMO Resolution MSC.191(79)	-	Performance standards for the presentation of navigation-related information on shipborne navigational displays	-	-
IMO Resolution MSC.192(79)	-	Adoption of the revised performance standards for radar equipment	-	-
IMO Resolution MSC.232(82)	-	Revised performance standards for electronic chart display and information systems (ECDIS)	-	-
IMO Resolution MSC.302(87)	-	Adoption of performance standards for Bridge Alert Management	-	-
IMO MSC.1/Circ.1389	-	Guidance on procedures for updating shipborne navigation and communication equipment	-	-
VESA-2007-5	2007	Industry Standards and Guidelines for Computer Display Monitor Timing (DMT) Standard	-	-
DDWG DVI	1999	Digital Visual Interface (DVI) Revision 1.0, Digital Display Working Group (DDWG)	-	-

CONTENTS

1	Scope.....	14
2	Normative references.....	14
3	Terms and definitions.....	15
4	General	27
4.1	Overview.....	27
4.2	Purpose	28
4.3	Application of these standards.....	28
4.4	Equipment categories.....	28
4.5	Establishing equipment type and status.....	29
4.6	Conditions of measurement and related definitions.....	30
4.7	Quality requirements	30
5	Tests.....	30
5.1	Test sites and simulation	30
5.1.1	Environmental and RF testing.....	30
5.1.2	Over-sea radar performance tests.....	30
5.1.3	Test targets and target simulation for performance tests	31
5.2	Test terminology and format.....	31
5.2.1	General.....	31
5.2.2	Test requirement terminology	31
5.2.3	Testing method terminology	32
6	Radar performance.....	32
6.1	General.....	32
6.2	Transmission and interference.....	32
6.2.1	Transmission frequency.....	32
6.2.2	Interference.....	33
6.3	Performance optimisation and monitoring	33
6.3.1	General.....	33
6.3.2	Optimum performance	33
6.4	Gain and anti-clutter functions.....	34
6.4.1	General.....	34
6.4.2	Gain function	34
6.4.3	Manual and automatic sea anti-clutter	34
6.4.4	Rain anti-clutter	35
6.5	Signal processing.....	35
6.5.1	General.....	35
6.5.2	Target enhancement.....	35
6.5.3	Radar signal correlation.....	36
6.5.4	Signal processing and radar image latency	36
6.5.5	Second-time-around echoes.....	36
6.5.6	Transmission format	37
6.5.7	Picture update	37
6.5.8	Additional processing	37
6.5.9	Signal processing description	37
6.6	Operation with SARTs, target enhancers (RTEs) and beacons.....	38
6.6.1	General.....	38

6.6.2	Radar beacons, SARTs and enhancers	38
6.7	Minimum range and range compensation.....	38
6.7.1	General.....	38
6.7.2	Range compensation.....	39
6.7.3	Minimum range	39
6.8	Range and bearing discrimination	40
6.8.1	General.....	40
6.8.2	Measurement conditions	40
6.8.3	Range discrimination	40
6.8.4	Bearing discrimination	40
6.8.5	Fundamental radar accuracy	41
6.9	Target detection performance assessment.....	41
6.9.1	General.....	41
6.9.2	Range of first detection in minimal clutter	42
6.9.3	Assessment of target detection with clutter	44
6.9.4	Radar performance documentation.....	49
6.10	Radar antenna (including pitch and roll)	50
6.10.1	General.....	50
6.10.2	Vertical radiation pattern/pitch and roll	50
6.10.3	Antenna horizontal pattern	51
6.10.4	Antenna side lobes.....	51
6.11	Radar availability – Standby and transmit	52
6.11.1	Requirements	52
6.11.2	Methods of test and required results	52
7	Display presentation	53
7.1	General.....	53
7.1.1	Requirements	53
7.1.2	Methods of test and required results	53
7.2	Linearity and index delay	53
7.2.1	Requirements	53
7.2.2	Methods of test and required results	53
7.3	Use and discrimination of colour.....	53
7.3.1	Requirements	53
7.3.2	Methods of test and required results	53
8	CCRP and own ship.....	54
8.1	Consistent common reference point (CCRP).....	54
8.1.1	CCRP	54
8.1.2	CCRP position	54
8.1.3	Measurements	54
8.1.4	Antenna offset	55
8.2	Own ship.....	55
8.2.1	General.....	55
8.2.2	Own ship's outline and minimised symbol	55
8.2.3	Heading line	55
8.2.4	Stern line	56
9	Navigation tools.....	56
9.1	General.....	56
9.2	Units of measurement.....	56
9.2.1	Requirements	56

9.2.2	Methods of test and required results	57
9.3	Presentation	57
9.3.1	Requirements	57
9.3.2	Methods of test and required results	57
9.4	Display range scales	57
9.4.1	Mandatory range scales	57
9.5	Variable range marker (VRM)	58
9.5.1	General	58
9.5.2	VRM measurements	58
9.6	Electronic bearing line (EBL)	59
9.6.1	General	59
9.6.2	EBL measurements	59
9.6.3	EBL origin position	60
9.7	Cursor	60
9.7.1	General	60
9.7.2	Cursor measurement	60
9.7.3	Selection by cursor	61
9.8	Offset measurement of range and bearing	61
9.8.1	General	61
9.8.2	Electronic range and bearing line (ERBL)	61
9.9	Parallel index lines (PI)	62
9.9.1	General	62
9.9.2	PI lines and positioning	62
9.10	Bearing scale	63
9.10.1	General	63
9.10.2	Bearing scale presentation	63
9.11	Range rings	64
9.11.1	General	64
9.11.2	Range ring presentation and measurement	64
9.12	Radar maps	65
9.12.1	General	65
9.12.2	Map functions and display simple user-defined maps	65
9.12.3	Map memory and transfer	65
9.12.4	Map presentation properties	66
9.13	Navigation routes	66
9.13.1	General	66
9.13.2	Route display and monitoring	67
10	Orientation, motion and stabilisation	67
10.1	General	67
10.2	Azimuth orientation	67
10.2.1	Accuracy of alignment	67
10.2.2	Heading readout and reference	68
10.2.3	Azimuth stabilisation update	69
10.3	Motion and orientation modes	69
10.3.1	General	69
10.3.2	True and relative motion	69
10.4	Off-centring	70
10.4.1	General	70
10.4.2	Manual and automatic off-centring	70

10.4.3	Automatic reset	70
10.4.4	Display orientation	71
10.5	Ground and sea stabilisation	72
10.5.1	Mode and source	72
10.5.2	Ground stabilisation	72
10.5.3	Sea stabilisation	73
11	Aids for collision avoidance	73
11.1	General	73
11.2	Target trails and past positions	73
11.2.1	General	73
11.2.2	Time and plot requirements	74
11.2.3	Trails/past position availability	74
11.3	Target tracking (TT)	75
11.3.1	General	75
11.3.2	Presentation of targets	75
11.3.3	Tracking calculations	76
11.3.4	Target tracking availability	76
11.3.5	Classification and tracked target capacity	77
11.3.6	Manual acquisition	78
11.3.7	Automatic acquisition	78
11.3.8	Motion trend	78
11.3.9	Visibility of 50 %	79
11.3.10	Tracking algorithm	79
11.3.11	Target swap	79
11.3.12	Cease tracking	79
11.3.13	Target tracking scenarios	79
11.3.14	Target motion and tracking accuracy	80
11.3.15	Tracker range and bearing accuracy	88
11.3.16	Reference target	89
11.4	Tracking limitations	89
11.4.1	Tracking warnings	89
11.4.2	Documentation	90
11.4.3	Requirements	90
11.4.4	Methods of test and required results	90
11.5	Automatic identification system	90
11.5.1	General	90
11.5.2	AIS targets and data report capacity	90
11.5.3	AIS target filtering	92
11.5.4	Activation and deactivation of AIS targets	92
11.5.5	AIS functionality and presentation	93
11.6	Radar and AIS target data	95
11.6.1	Requirements	95
11.6.2	Methods of test and required results	95
11.6.3	Bow crossing range and time (BCR/BCT)	96
11.7	Operational target alerts	96
11.7.1	CPA and TCPA	96
11.7.2	New target warning	97
11.7.3	Lost tracked radar target	97
11.7.4	Lost AIS target criteria	98

11.8	Target association.....	99
11.8.1	General.....	99
11.8.2	Association and priority.....	99
11.9	Trial manoeuvre.....	103
11.9.1	General.....	103
11.9.2	Trial functions.....	103
12	Chart radar (optional classification).....	104
12.1	General requirements.....	104
12.1.1	General.....	104
12.1.2	Chart operation and source.....	104
12.1.3	Chart elements and availability.....	105
12.1.4	Chart reference.....	106
12.1.5	Primary chart information set.....	106
12.1.6	Chart stabilisation and chart redraw.....	107
12.1.7	Chart position and latency.....	108
12.1.8	Matching and adjustment.....	108
12.1.9	Chart symbols, colours, and size.....	109
12.1.10	Chart display size.....	110
12.1.11	Chart alerts and indications.....	110
12.1.12	Chart malfunction.....	111
12.1.13	Chart radar malfunction.....	111
12.2	Additional requirements for standalone radar with chart facilities.....	111
12.2.1	General.....	111
12.2.2	Provision and updating of chart information.....	111
12.2.3	Content and structure of chart data.....	112
12.3	Additional requirements for ECDIS back-up (optional).....	112
12.3.1	General.....	112
12.3.2	Requirements.....	112
12.3.3	Test Methods and required results.....	112
13	Ergonomic criteria (control functions and display).....	112
13.1	General.....	112
13.2	Operational controls.....	112
13.2.1	Requirements.....	112
13.2.2	Methods of test and required results.....	113
13.3	Primary controls.....	113
13.3.1	Requirements.....	113
13.3.2	Methods of test and required results.....	113
13.4	Control properties.....	114
13.4.1	Requirements.....	114
13.4.2	Methods of test and required results.....	114
13.5	Default control setting and saved user control settings.....	114
13.5.1	Requirements.....	114
13.5.2	Test methods and required results.....	115
14	Interfacing.....	116
14.1	General.....	116
14.2	Input interfacing.....	116
14.2.1	Input data.....	116
14.2.2	Input quality, integrity and latency.....	117
14.3	Output interfacing.....	117

14.3.1	Output format	117
14.3.2	Output target data	117
14.3.3	VDR interface	118
15	Design, servicing and installation	119
15.1	General.....	119
15.2	Fault diagnosis and servicing	119
15.2.1	Requirements	119
15.2.2	Methods of test and required results	120
15.3	Display design	120
15.3.1	Requirements	120
15.3.2	Methods of test and required results	120
15.4	Transceiver design.....	120
15.4.1	General.....	120
15.4.2	Sector blanking.....	121
15.5	Antenna design.....	121
15.5.1	Requirements	121
15.5.2	Methods of test and required results	121
15.6	Inter-switched and multiple radars	122
15.6.1	General.....	122
15.6.2	System safeguards.....	122
15.6.3	Combining radar	122
15.6.4	Multiple radar system status.....	123
15.7	Multiple operational displays	123
15.7.1	Additional information and conformity.....	123
15.7.2	Requirements	123
15.7.3	Methods of test and required results	124
15.8	Safety – antenna and radiation	124
15.8.1	General.....	124
15.8.2	Antenna radiation and rotation.....	124
15.8.3	Microwave radiation levels	124
16	Alerts and failures.....	125
16.1	General.....	125
16.1.1	Priority of alerts	125
16.1.2	Alerts and indications	125
16.1.3	Alarm contact outputs.....	125
16.1.4	Alert management interface.....	125
16.1.5	Unacknowledged warnings.....	126
16.1.6	Unacknowledged alarms	127
16.1.7	Remote acknowledgement and silencing of alerts.....	127
16.1.8	Picture freeze	128
16.1.9	Sensor failure alert.....	128
16.2	Backup and fallback arrangements	128
16.2.1	Requirements	128
16.2.2	Failure of heading information (azimuth stabilisation).....	128
16.2.3	Failure of speed through the water information.....	129
16.2.4	Failure of course and speed over ground information	129
16.2.5	Failure of position input information	129
16.2.6	Failure of radar video input information	130
16.2.7	Failure of AIS input information.....	130

16.2.8	Failure of an integrated or networked system	130
17	Environmental testing	130
17.1	General.....	130
17.2	Testing to IEC 60945.....	131
17.2.1	Requirements	131
17.2.2	Methods of test and required results	131
17.3	Additional environmental tests.....	131
17.3.1	General.....	131
17.3.2	Antenna shock test.....	132
18	Equipment familiarisation and documentation	132
18.1	Familiarisation simulator	132
18.1.1	General.....	132
18.1.2	Requirements	132
18.1.3	Methods of test and required results	132
18.2	Instructions and documentation	133
18.2.1	General.....	133
18.2.2	Documentation.....	133
18.2.3	Operating instructions.....	133
18.3	Radar system installation.....	134
18.3.1	Requirements	134
18.3.2	Methods of test and required results	134
18.4	Maintenance information for equipment update	135
18.4.1	Requirements	135
18.4.2	Methods of test and required results	135
Annex A (informative)	Guidelines for radar functionality on navigation displays.....	136
Annex B (normative)	Unwanted emissions of radar systems.....	137
Annex C (informative)	Radar target size (RCS) and detection range calculations	142
Annex D (informative)	Factors that influence target detection.....	146
Annex E (normative)	Sensor errors.....	155
Annex F (informative)	Target scenario simulator/reported target simulator.....	157
Annex G (informative)	Tracked and reported target states	158
Annex H (normative)	IEC 61162 sentence formats	159
Annex I (normative)	Radar control function/indication grouping	168
Annex J (informative)	Interference to shipborne radar from emissions in adjacent frequency bands.....	172
Bibliography	175
Figure 1	– Reduction of range to first detection due to rain at S-band	45
Figure 2	– Reduction of range to first detection due to rain at X-band	45
Figure 3	– TT scenario 1	82
Figure 4	– TT scenario 2	83
Figure 5	– TT scenario 3	84
Figure 6	– TT scenario 4	85
Figure 7	– TT scenario 5	86
Figure B.1	– B ₄₀ falls within the allocated band	140
Figure B.2	– B ₄₀ falls outside the allocated band.....	141

Figure C.1 – Enhancement by reflection (dB) over free-space (9,41 GHz)	145
Figure C.2 – Enhancement by reflection (dB) over free-space (3,05 GHz)	145
Figure D.1 – Effect of sea spikes on target detection.....	148
Figure D.2 – Multi-path plots for S-band.....	150
Figure D.3 – Multi-path plot for X-band	150
Figure G.1 – Tracked target states	158
Figure G.2 – AIS target state	158
Table 1 – Performance requirements for categories of ship/craft for SOLAS V	29
Table 2 – Range of first detection in clutter-free conditions	42
Table 3 – X-band pass/fail assessment criteria	48
Table 4 – S-band pass/fail assessment criteria	48
Table 5 – Pass/fail assessment.....	49
Table 6 – Douglas sea state parameters	49
Table 7 – Main horizontal beam pattern	51
Table 8 – Effective side-lobes.....	52
Table 9 – Features and colours to be used for radar maps.....	66
Table 10 – Tracked target capacity (subset of Table 1).....	77
Table 11 – Typical tracked target accuracy (95 % probability figures)	80
Table 12 – TT scenario 1, with sensor errors applied	81
Table 13 – TT scenario 1, times of measurement task.....	81
Table 14 – TT scenario 1, accuracies after 1 min and 3 min (all values)	82
Table 15 – TT scenario 2, own ship turning through 180°	83
Table 16 – TT scenario 3, initial target data.....	84
Table 17 – TT scenario 4, initial target data for fast targets (standard speed ships).....	84
Table 18 – TT scenario 4, initial target data for fast targets (HSC).....	85
Table 19 – TT scenario 5: initial target data for standard craft.....	86
Table 20 – TT scenario 5: initial target data for collision scenario for HSC.....	86
Table 21 – Measurement points and results at 3 min and 6 min for HSC	87
Table 22 – Measurement points and results at 11 min and 14 min for HSC.....	87
Table 23 – Measurement points and results at 3 min and 6 min for standard craft	87
Table 24 – Measurement points and results at 11 min and 14 min for standard craft.....	88
Table 25 – Measurement of tracked target accuracy.....	88
Table 26 – AIS display capacity (subset of Table 1)	91
Table 27 – AIS reporting rates	98
Table 28 – Association scenario 1, initial TT and AIS target position and data	100
Table 29 – Association scenario 1, AIS target data for diverging and converging tracks	101
Table 30 – Association scenario 2, initial TT and AIS target position and data	101
Table 31 – Association scenario 2, AIS target data for changing speed	102
Table 32 – Association scenario 3, TT and AIS target start position and data.....	102
Table 33 – Association scenario 4, initial TT and AIS target position and data	103
Table 34 – Association scenario 4, TT and AIS target with the same course and speed	103
Table 35 – Control settings configured in response to 'Default' selection.....	115

Table 36 – Antenna shock test severity (half sine pulse).....	132
Table B.1 – Measurement frequency ranges.....	138
Table D.1 – Spread of RCS values for typical ships.....	147
Table D.2 – S-band performance predictions for ranges of 0,2, 0,4, 0,7 NM.....	149
Table D.3 – X-band performance predictions for ranges of 0,2, 0,7 NM	149
Table D.4 – Parameters for attenuation in uniform rain conditions	151
Table D.5 – Typical values for attenuation and backscatter in uniform rain conditions.....	151
Table D.6 – Additional radar system parameters (X/S-band)	151
Table D.7 – Target size, height and RCS values	152
Table D.8 – S-band radar parameters (LP).....	153
Table D.9 – X-band radar parameters (LP).....	154
Table H.1 – Mandatory IEC 61162-1 sentences	159
Table H.2 – Optional IEC 61162-3 messages	160
Table H.3 – Description of terms	161
Table H.4 – Header format (1 of 2).....	162
Table H.5 – Package data format	164
Table I.1 – Top-level grouping of data and control functions for radar applications	168
Table I.2 – Icons for common function controls (1 of 2).....	169

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS –

Shipborne radar – Performance requirements, methods of testing and required test results

1 Scope

This International Standard specifies the minimum operational and performance requirements, methods of testing and required test results conforming to performance standards not inferior to those adopted by the IMO in Resolution MSC.192(79).

(MSC.192/2) The radar installation, in addition to meeting the general requirements as set out in resolution A.694(17) and the related standard IEC 60945, should comply with the performance standards of MSC.192(79). When a requirement of this standard is different from IEC 60945, the requirement in this standard takes precedence.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61162 (all parts), *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*

IEC 61174, *Maritime navigation and radiocommunication equipment and systems – Electronic chart display and information systems (ECDIS) – Operational and performance requirements, methods of testing and required test results*

IEC 61924-2:2012, *Maritime navigation and radiocommunication equipment and systems – Part 2 Modular Structure for INS - Operational and performance requirements, methods of testing and required test results*

IEC 61996-1:2012, *Maritime navigation and radiocommunication equipment and systems – Shipborne voyage data recorder (VDR) – Part 1: Voyage data recorder (VDR) - Performance requirements – Methods of testing and required test results*

IEC 62288, *Maritime navigation and radiocommunication equipment and systems – Presentation of navigation-related information on shipborne navigational displays – General requirements, methods of testing and required results*

ITU-R Recommendation M.628, *Technical characteristics for search and rescue radar transponders*

ITU-R Recommendation M.824, *Technical parameters of radar beacons (racons)*

ITU-R Recommendation M.1176, *Technical parameters of radar target enhancers*