

ETSI EN 300 296 V2.1.1 (2016-03)



**Land Mobile Service;
Radio equipment using integral antennas
intended primarily for analogue speech;
Harmonised Standard covering the essential requirements
of article 3.2 of the Directive 2014/53/EU**

Reference

REN/ERM-TGDMR-348

Keywords

analogue, mobile, PMR, radio, regulation, speech

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	9
3.1 Definitions.....	9
3.2 Symbols.....	10
3.3 Abbreviations	11
4 General and operational requirements.....	11
4.1 General	11
4.1.1 Environmental profile	11
4.1.2 Choice of model for testing	11
4.1.3 Auxiliary test equipment.....	12
4.2 Mechanical and electrical design.....	12
4.2.1 General.....	12
4.2.2 Controls	12
4.2.3 Transmitter shut-off facility.....	12
4.3 Marking.....	12
5 Test conditions, power sources and ambient temperatures	12
5.1 Normal and extreme test conditions	12
5.2 Test power source.....	12
5.3 Normal test conditions.....	13
5.3.1 Normal temperature and humidity	13
5.3.2 Normal test power source	13
5.3.2.1 Mains voltage.....	13
5.3.2.2 Regulated lead-acid battery power sources used on vehicles.....	13
5.3.2.3 Other power sources.....	13
5.4 Extreme test conditions	13
5.4.1 Extreme temperatures	13
5.4.2 Extreme test source voltages.....	13
5.4.2.1 Mains voltage.....	13
5.4.2.2 Regulated lead-acid battery power sources used on vehicles.....	14
5.4.2.3 Power sources using other types of batteries.....	14
5.4.2.4 Other power sources.....	14
5.5 Procedure for tests at extreme temperatures.....	14
5.5.0 Thermal balance.....	14
5.5.1 Procedure for equipment designed for continuous transmission.....	14
5.5.2 Procedure for equipment designed for intermittent transmission	14
6 General conditions of measurement	15
6.1 Test signals.....	15
6.2 Receiver mute or squelch facility	15
6.3 Artificial antenna.....	15
6.4 Test sites and general arrangements for radiated measurements	15
6.5 Arrangement for test signals at the input of the transmitter	15
6.6 Receiver rated audio output power.....	16
6.7 Reference for degradation measurements.....	16
6.7.1 Definition.....	16
6.7.2 Procedures for measurements using the test fixture.....	16
6.7.3 Procedures for measurements using the test site.....	16
7 Technical characteristics of the transmitter	17

7.1	Frequency error	17
7.1.1	Definition	17
7.1.2	Method of measurement	17
7.1.3	Limits	17
7.2	Effective radiated power	17
7.2.1	Definition	17
7.2.2	Method of measurement	18
7.2.2.0	General	18
7.2.2.1	Maximum effective radiated power under normal test conditions	18
7.2.2.2	Average effective radiated power under normal test conditions	19
7.2.2.3	Method of measurements of maximum and average effective radiated power under extreme test conditions	20
7.2.3	Limits	20
7.3	Maximum permissible frequency deviation	21
7.3.1	Definition	21
7.3.2	Method of measurement	21
7.3.2.0	General arrangements	21
7.3.2.1	Maximum permissible frequency deviation	21
7.3.2.2	Response of the transmitter to modulation frequencies above 3 kHz	22
7.3.3	Limits	22
7.3.3.1	Maximum permissible frequency deviation	22
7.3.3.2	Response of the transmitter to modulation frequencies above 3 kHz	22
7.4	Adjacent and alternate channel power	23
7.4.1	Definition	23
7.4.2	Method of measurement	23
7.4.3	Limits	25
7.5	Radiated unwanted emissions in the spurious domain	25
7.5.1	Definition	25
7.5.2	Method of measurement	25
7.5.3	Limits	27
7.6	Voice Operated Transmitter	27
7.6.1	Definition	27
7.6.2	Method of measurement	28
7.6.3	Limits	28
7.7	Maximum transmission time	28
7.7.1	Definition	28
7.7.2	Method of measurement	28
7.7.3	Limits	29
8	Technical characteristics of the receiver	29
8.1	Average usable sensitivity (field strength, speech)	29
8.1.1	Definition	29
8.1.2	Methods of measurement	29
8.1.2.1	Method of measurement under normal test conditions	29
8.1.2.2	Method of measurement under extreme test conditions	31
8.1.3	Limits	31
8.2	Spurious radiations	32
8.2.1	Definition	32
8.2.2	Method of measurement	33
8.2.3	Limits	34
8.3	Co-channel rejection	35
8.3.1	Definition	35
8.3.2	Method of measurement	35
8.3.3	Limits	36
8.4	Adjacent channel selectivity	36
8.4.1	Definition	36
8.4.2	Method of measurement	36
8.4.3	Limits	37
8.5	Spurious response rejection	37
8.5.1	Definition	37
8.5.2	Method of measurement	37
8.5.2.1	Introduction to the method of measurement	37

8.5.2.2	Measurement arrangement	39
8.5.2.3	Method of the search	39
8.5.2.4	Measurement	40
8.5.3	Limits	41
8.6	Intermodulation response rejection	41
8.6.1	Definition	41
8.6.2	Method of measurement	41
8.6.3	Limits	42
8.6.3.1	Limits for low power equipment	42
8.6.3.2	Limits for other equipment	42
8.7	Blocking or desensitization	43
8.7.1	Definition	43
8.7.2	Method of measurement	43
8.7.3	Limits	44
9	Testing for compliance with technical requirements	44
9.1	Test conditions, power supply and ambient temperatures	44
9.2	Interpretation of the measurement results	45

Annex A (normative): Radiated measurement.....46

A.1	Test sites and general arrangements for measurements involving the use of radiated fields	46
A.1.0	General	46
A.1.1	Anechoic chamber	46
A.1.2	Anechoic chamber with a conductive ground plane	47
A.1.3	Open Area Test Site (OATS)	48
A.1.4	Test antenna	49
A.1.5	Substitution antenna	49
A.1.6	Measuring antenna	50
A.2	Guidance on the use of radiation test sites	50
A.2.0	General	50
A.2.1	Verification of the test site	50
A.2.2	Preparation of the EUT	50
A.2.3	Power supplies to the EUT	50
A.2.4	Volume control setting for analogue speech tests	50
A.2.5	Range length	51
A.2.6	Site preparation	51
A.3	Coupling of signals	52
A.3.1	General	52
A.3.2	Data signals	52
A.3.3	Speech and analogue signals	52
A.3.3.0	General	52
A.3.3.1	Acoustic coupler description	52
A.3.3.2	Calibration	53
A.4	Test fixture	53
A.4.1	Description	53
A.4.2	Calibration	54
A.4.3	Mode of use	54

Annex B (normative): Specification for some particular measurement arrangements.....55

B.1	Power measuring receiver specification	55
B.1.0	General	55
B.1.1	IF filter	55
B.1.2	Attenuation indicator	57
B.1.3	RMS value indicator	57
B.1.4	Oscillator and amplifier	57
B.2	Spectrum analyser specification	57
B.2.1	Adjacent and alternate channel power measurement	57
B.2.2	Unwanted emissions measurement	58

B.3	Integrating and power summing device	58
Annex C (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	59
Annex D (normative):	Band-stop filter (for SINAD meter)	61
History		62

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.9] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.8].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table C.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

National transposition dates	
Date of adoption of this EN:	21 March 2016
Date of latest announcement of this EN (doa):	30 June 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 December 2016
Date of withdrawal of any conflicting National Standard (dow):	31 December 2017

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document covers the minimum characteristics considered necessary in order to avoid harmful interference and to make acceptable use of the available frequencies.

The present document applies to equipment with integral antennas, used in angle modulation systems in the land mobile service, operating on radio frequencies between 30 MHz and 1 000 MHz, with channel separations of 12,5 kHz, 20 kHz and 25 kHz, and is intended primarily for analogue speech.

In the present document different requirements are given for the different radio frequency bands, channel separations, environmental conditions and types of equipment, where appropriate.

The present document is complementary to ETSI EN 300 086 [i.6], which covers radio equipment with an internal or external RF connector, for use in the land mobile service.

The present document may apply to PMR446 equipment as defined in [i.7]. Note that PMR446 equipment has a requirement to incorporate a receiver and may have requirements for 180 s maximum transmission time and VOX.

Table 1: Radiocommunications service frequency bands

Radiocommunications service frequency bands	
Transmit	30 MHz to 1 000 MHz
Receive	30 MHz to 1 000 MHz

The present document contains requirements to demonstrate that "... *Radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference*" and that "....*radio equipment supports certain features ensuring access to emergency services*" [i.8].

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Radio Equipment Directive [i.8] may apply to equipment within the scope of the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TR 100 028 (V1.4.1) (12-2001) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [2] ANSI C63.5 (2006): "American National Standard for Calibration of Antennas Used for Radiated Emission Measurements in Electro Magnetic Interference".
- [3] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".