

ETSI TS 129 163 V12.12.0 (2016-08)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
Interworking between the IP Multimedia (IM) Core Network (CN)
subsystem and Circuit Switched (CS) networks
(3GPP TS 29.163 version 12.12.0 Release 12)**



Reference

RTS/TSGC-0329163vcc0

Keywords

GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	15
1 Scope	16
2 References	16
3 Definitions and abbreviations.....	22
3.1 Definitions	22
3.2 Abbreviations	22
4 General	24
4.1 General interworking overview	24
5 Network characteristics	25
5.1 Key characteristics of ISUP/BICC based CS networks.....	25
5.2 Key characteristics of IM CN subsystem	25
6 Interworking with CS networks	26
6.1 Interworking reference model	26
6.1.1 Interworking reference points and interfaces.....	26
6.1.2 Interworking functional entities	26
6.1.2.1 Signalling Gateway Function (SGW)	26
6.1.2.2 Media Gateway Control Function (MGCF)	27
6.1.2.3 IP Multimedia – Media Gateway Function (IM-MGW)	27
6.2 Control plane interworking model.....	27
6.3 User plane interworking model	27
7 Control plane interworking	27
7.1 General	27
7.2 Interworking between CS networks supporting ISUP and the IM CN subsystem	28
7.2.1 Services performed by network entities in the control plane	29
7.2.1.1 Services performed by the SS7 signalling function	29
7.2.1.2 Services of the SGW	29
7.2.1.3 Services of the MGCF	29
7.2.1.4 Services of the SIP signalling function	29
7.2.2 Signalling interactions between network entities in the control plane	29
7.2.2.1 Signalling between the SS7 signalling function and MGCF	29
7.2.2.1.1 Signalling from MGCF to SS7 signalling function	29
7.2.2.1.2 Signalling from SS7 signalling function to MGCF	29
7.2.2.1.3 Services offered by SCTP and M3UA.....	29
7.2.2.2 Signalling between the MGCF and SIP signalling function.....	30
7.2.3 SIP-ISUP protocol interworking.....	30
7.2.3.1 Incoming call interworking from SIP to ISUP at I-MGCF	30
7.2.3.1.1 Sending of IAM	30
7.2.3.1.2 Coding of the IAM	31
7.2.3.1.2A Coding of the IAM when Number Portability is supported.....	46
7.2.3.1.2B Coding of the IAM for Carrier Routeing	49
7.2.3.1.3 Sending of COT	49
7.2.3.1.3A Sending of SAM	50
7.2.3.1.4 Sending of 180 ringing	51
7.2.3.1.4A Sending of 183 Session Progress for early media scenarios	54
7.2.3.1.4B Sending of 181Call is being forwarded	57
7.2.3.1.4C Sending of 183 Session Progress for overlap signalling using the in-dialog method	58
7.2.3.1.4D Sending of 183 Session Progress to carry ISUP Cause	58
7.2.3.1.4E Sending of 183 Session Progress for ICS call	58
7.2.3.1.5 Sending of the 200 OK (INVITE)	59

7.2.3.1.6	Sending of the Release message (REL).....	61
7.2.3.1.7	Coding of the REL.....	61
7.2.3.1.8	Receipt of the Release Message	62
7.2.3.1.9	Receipt of RSC, GRS or CGB (H/W oriented)	64
7.2.3.1.9a	Receipt of REFER	65
7.2.3.1.10	Autonomous Release at I-MGCF	65
7.2.3.1.11	Internal through connection of the bearer path.....	66
7.2.3.2	Outgoing Call Interworking from ISUP to SIP at O-MGCF.....	66
7.2.3.2.1	Sending of INVITE	66
7.2.3.2.1a	Sending of INVITE without determining the end of address signalling.....	69
7.2.3.2.2	Coding of the INVITE.....	71
7.2.3.2.2A	Coding of the INVITE when Number Portability is supported	82
7.2.3.2.2B	Coding of the INVITE for Carrier Routeing	84
7.2.3.2.2C	Coding of INVITE with instance-id in form of IMEI URN	84
7.2.3.2.3	Receipt of CONTINUITY	85
7.2.3.2.4	Sending of ACM and awaiting answer indication	86
7.2.3.2.5	Coding of the ACM	88
7.2.3.2.6	Sending of the Call Progress message (CPG).....	91
7.2.3.2.7	Coding of the CPG	93
7.2.3.2.7a	Receipt of 200 OK(INVITE).....	95
7.2.3.2.7b	Internal through connection of the bearer path.....	95
7.2.3.2.8	Sending of the Answer Message (ANM).....	95
7.2.3.2.9	Coding of the ANM.....	95
7.2.3.2.10	Sending of the Connect message (CON)	97
7.2.3.2.11	Coding of the CON.....	97
7.2.3.2.11A	Receipt of a reINVITE request	97
7.2.3.2.12	Receipt of Status Codes 4xx, 5xx or 6xx.....	97
7.2.3.2.13	Receipt of a BYE.....	100
7.2.3.2.14	Receipt of the Release Message	100
7.2.3.2.15	Receipt of RSC, GRS or CGB (H/W oriented)	100
7.2.3.2.16	Autonomous Release at O-MGCF.....	100
7.2.3.2.17	Special handling of 580 precondition failure received in response to either an INVITE or UPDATE	101
7.2.3.2.18	Sending of CANCEL.....	101
7.2.3.2.19	Receipt of SIP redirect (3xx) response	102
7.2.3.2.20	Sending of INFO for overlap signalling using the in-dialog method	102
7.2.3.3	Timers	103
7.3	Interworking between CS networks supporting BICC and the IM CN subsystem.....	103
7.3.1	Services performed by network entities in the control plane	104
7.3.2	Signalling interactions between network entities in the control plane	104
7.3.2.1	Signalling between the SS7 signalling function and MGCF.....	104
7.3.2.1.1	Signalling from MGCF to SS7 signalling function	104
7.3.2.1.2	Signalling from SS7 signalling function to MGCF	104
7.3.2.1.3	Services offered by STC, SCTP and M3UA	105
7.3.2.2	Signalling between the MGCF and SIP signalling function.....	105
7.3.3	SIP-BICC protocol interworking	105
7.3.3.1	Incoming call interworking from SIP to BICC at I-MGCF.....	105
7.3.3.1.1	Sending of IAM	105
7.3.3.1.2	Coding of IAM	105
7.3.3.1.2A	Coding of the IAM when Number Portability is supported.....	106
7.3.3.1.2B	Coding of the IAM for Carrier Routeing	106
7.3.3.1.3	Sending of COT.....	107
7.3.3.1.3A	Sending of SAM	107
7.3.3.1.4	Sending of 180 Ringing	107
7.3.3.1.4A	Sending of 183 Session Progress for early media scenarios	107
7.3.3.1.4B	Sending of 181 Call is being forwarded	107
7.3.3.1.4C	Sending of 183 Session Progress for overlap signalling using the in-dialog method	107
7.3.3.1.4D	Sending of 183 Session Progress to carry ISUP Cause	107
7.3.3.1.4E	Sending of 183 Session Progress for ICS call	107
7.3.3.1.5	Sending of the 200 OK (INVITE)	108
7.3.3.1.6	Sending of the Release message (REL).....	108
7.3.3.1.7	Coding of the REL.....	108

7.3.3.1.8	Receipt of the Release Message	108
7.3.3.1.9	Receipt of RSC, GRS or CGB (H/W oriented)	108
7.3.3.1.9a	Receipt of REFER	108
7.3.3.1.9b	Autonomous Release at I-MGCF	108
7.3.3.1.10	Internal through connection of the bearer path	108
7.3.3.1.11	Out of Band DTMF	108
7.3.3.2	Outgoing Call Interworking from BICC to SIP at O-MGCF	108
7.3.3.2.1	Sending of INVITE	108
7.3.3.2.1a	Sending of INVITE without determining the end of address signalling	109
7.3.3.2.2	Coding of the INVITE	109
7.3.3.2.2A	Coding of the INVITE when number portability is supported	110
7.3.3.2.2B	Coding of the INVITE for Carrier Routeing	110
7.3.3.2.2C	Coding of INVITE with instance-id in form of IMEI URN	110
7.3.3.2.3	Sending of UPDATE	110
7.3.3.2.4	Sending of ACM and Awaiting Answer indication	111
7.3.3.2.5	Coding of the ACM	111
7.3.3.2.6	Sending of the Call Progress message (CPG)	111
7.3.3.2.7	Coding of the CPG	111
7.3.3.2.7a	Receipt of 200 OK (INVITE)	111
7.3.3.2.7b	Internal through connection of the bearer path	111
7.3.3.2.8	Sending of the Answer Message (ANM)	111
7.3.3.2.9	Coding of the ANM	111
7.3.3.2.10	Sending of the Connect message (CON)	111
7.3.3.2.11	Coding of the CON	111
7.3.3.2.11A	Receipt of re-INVITE requests	112
7.3.3.2.12	Receipt of Status Codes 4xx, 5xx or 6xx	112
7.3.3.2.13	Receipt of a BYE	112
7.3.3.2.14	Receipt of the Release Message	112
7.3.3.2.15	Receipt of RSC, GRS or CGB (H/W oriented)	112
7.3.3.2.16	Out of Band DTMF	112
7.3.3.2.17	Sending of CANCEL	112
7.3.3.2.18	Autonomous Release at O-MGCF	112
7.3.3.2.19	Special handling of 580 precondition failure received in response to either an INVITE or UPDATE	112
7.3.3.2.20	Receipt of SIP redirect (3xx) response	112
7.3.3.2.21	Sending of INFO for overlap signalling using the in-dialog method	112
7.3.3.3	Timers	113
7.4	Supplementary Services	113
7.4.1	Calling line identification presentation/restriction (CLIP/CLIR)	113
7.4.2	Connected line presentation and restriction (COLP/COLR)	113
7.4.2.0	General	113
7.4.2.1	Incoming Call Interworking from SIP to BICC/ISUP at the I-MGCF	113
7.4.2.1.1	INVITE to IAM interworking (SIP to ISUP/BICC calls)	113
7.4.2.1.2	ANM/CON to 200 OK (INVITE)	113
7.4.2.2	Outgoing Call Interworking from BICC/ISUP to SIP at O-MGCF	114
7.4.2.2.1	IAM to INVITE interworking (ISUP to SIP calls)	114
7.4.2.2.2	1XX to ANM or CON interworking	115
7.4.2.2.3	200 OK (INVITE) to ANM/CON interworking	115
7.4.3	Direct Dialling In (DDI)	116
7.4.4	Malicious call identification	116
7.4.5	Subaddressing (SUB)	116
7.4.5.1	General	116
7.4.5.2	Interworking at I-MGCF	117
7.4.5.3	Interworking at O-MGCF	118
7.4.6	Call Forwarding Busy (CFB)/ Call Forwarding No Reply (CFNR) / Call Forwarding Unconditional (CFU) / Call Deflection (CD)	119
7.4.6.1	General	119
7.4.6.2	Interworking at the O-MGCF	119
7.4.6.2.1	General	119
7.4.6.2.2	Interworking SIP to ISUP	119
7.4.6.2.3	Interworking ISUP to SIP	123
7.4.6.3	Interworking at the I-MGCF	126

7.4.6.3.1	General	126
7.4.6.3.2	Interworking from SIP to ISUP	126
7.4.6.3.3	Interworking from ISUP to SIP	129
7.4.7	Void	133
7.4.8	Explicit Call Transfer (ECT)	133
7.4.9	Call Waiting.....	133
7.4.10	Call Hold.....	133
7.4.10.1	Session hold initiated from the IM CN subsystem side.....	133
7.4.10.2	Session hold initiated from the CS network side.....	134
7.4.11	Call Completion on busy subscriber.....	136
7.4.12	Completion of Calls on No Reply (CCNR)	136
7.4.13	Terminal Portability (TP).....	136
7.4.14	Conference calling (CONF) / Three-Party Service (3PTY).....	136
7.4.15	Void	137
7.4.16	Closed User Group (CUG)	137
7.4.17	Multi-Level Precedence and Pre-emption (MLPP).....	137
7.4.18	Global Virtual Network Service (GVNS).....	137
7.4.19	International telecommunication charge card (ITCC)	137
7.4.20	Reverse charging (REV)	137
7.4.21	User-to-User Signalling (UUS).....	137
7.4.21.0	General	137
7.4.21.1	User-to-User Signalling (UUS) service 1 (implicit).....	137
7.4.21.1.0	General	137
7.4.21.1.1	Void.....	138
7.4.21.1.2	User-to-user information Interworking from SIP to ISUP	138
7.4.21.1.3	User-to-user information Interworking from ISUP to SIP	138
7.4.21.2	User-to-User Signalling (UUS) service 1 (explicit)	138
7.4.21.3	User-to-User Signalling (UUS) service 2 (explicit)	138
7.4.21.4	User-to-User Signalling (UUS) service 3 (explicit)	138
7.4.22	Multiple Subscriber Number (MSN)	139
7.4.23	Anonymous Call rejection	139
7.4.23.0	General	139
7.4.23.1	ISUP-SIP protocol interworking at the I-MGCF.....	139
7.4.23.2	SIP-ISUP protocol interworking at the O-MGCF	139
7.4.24	Customized Alerting Tones (CAT) in the 3GPP CS domain.....	139
7.5	IMS Supplementary Services	139
7.5.1	Originating Identification Presentation (OIP) and Originating Identification Restriction (OIR).....	139
7.5.2	Terminating Identification Presentation (TIP) and Terminating Identification Restriction (TIR).....	139
7.5.2.1	General	139
7.5.2.2	Interworking at the O-MGCF.....	139
7.5.2.3	Interworking at the I-MGCF	141
7.5.2.4	Timer.....	142
7.5.3	void	142
7.5.4	Communication Diversion (CDIV).....	142
7.5.4.1	General	142
7.5.4.2	Interworking at the O-MGCF.....	143
7.5.4.2.1	General	143
7.5.4.2.2	Call forwarding within the ISUP Network appeared	148
7.5.4.3	Interworking at the I-MGCF	151
7.5.5	Communication Hold (HOLD).....	158
7.5.6	Conference call (CONF)	158
7.5.6.1	General	158
7.5.6.2	Subscribing for the conference event package	158
7.5.6.3	Interworking the notification.....	159
7.5.7	Anonymous Communication Rejection (ACR) and Communication Barring (CB).....	159
7.5.8	Message Waiting Indication (MWI)	160
7.5.9	Malicious Communication Identification (MCID)	160
7.5.9.0	General	160
7.5.9.1	Interworking at the O-MGCF.....	160
7.5.9.1.0	General	160
7.5.9.1.1	Interworking of the MCID XML Request schema with the ISUP MCID request indicators	160
7.5.9.1.2	Interworking of the ISUP MCID response indicators with the MCID XML Response schema ...	161

7.5.9.1.3	Interworking of the ISUP Calling Party Number in an Identification Response with the OrigPartyIdentity within the MCID XML Response schema.....	161
7.5.9.1.4	Interworking of the ISUP Generic Number in an Identification Response with the GenericNumber within the MCID XML Response schema	161
7.5.9.2	Interworking at the I-MGCF	161
7.5.9.2.1	General	161
7.5.9.2.2	Interworking of identification Request	161
7.5.9.2.3	Interworking of identification Response.....	162
7.5.10	Closed User Group (CUG)	162
7.5.10.0	General	162
7.5.10.1	Interworking at the I-MGCF	162
7.5.10.2	Interworking at the O-MGCF.....	163
7.5.11	CCBS/CCNR	164
7.5.11.0	General	164
7.5.11.1	Interworking at the I-MGCF	164
7.5.11.2	Interworking at the O-MGCF.....	166
7.5.12	Communication Waiting (CW).....	168
7.5.12.0	General	168
7.5.12.1	Interworking at the I-MGCF	168
7.5.12.2	Interworking at the O-MGCF.....	168
7.5.13	Customized Alerting Tones (CAT).....	168
7.5.13.1	General	168
7.5.13.2	Early session model.....	168
7.5.13.2.1	Interworking at the O-MGCF	168
7.5.13.2.2	MGCF – IM-MGW Interaction for CAT service	169
7.5.13.3	Forking model	173
7.5.13.4	Gateway model	173
8	User plane interworking	173
8.1	Interworking between IM CN subsystem and bearer independent CS network	173
8.1.1	Transcoder-less Mb to Nb Interworking	174
8.1.1.1	Initialisation	174
8.1.1.2	Time alignment	174
8.1.1.3	Rate control	174
8.1.1.4	Frame quality indication	175
8.1.1.5	Framing	175
8.1.1.6	Transcoding.....	175
8.1.1.7	Discontinuous transmission	175
8.1.1.8	Timing and sequence information.....	175
8.2	Interworking between IM CN subsystem and TDM-based CS network	176
8.3	Transcoding requirements	176
8.4	Diffserv code point requirements	176
8.5	DTMF handling	176
9	MGCF – IM-MGW Interaction	177
9.1	Overview	177
9.2	Mn signalling interactions	177
9.2.1	Network model	177
9.2.2	Basic IM CN subsystem originated session	178
9.2.2.1	BICC forward bearer establishment	178
9.2.2.1.1	IM-MGW selection	178
9.2.2.1.2	CS network side bearer establishment	178
9.2.2.1.3	IM CN subsystem side termination reservation.....	178
9.2.2.1.4	IM CN subsystem side session establishment	178
9.2.2.1.5	Through-connection	179
9.2.2.1.6	Codec handling.....	179
9.2.2.1.7	Failure handling in MGCF	179
9.2.2.1.8	Message sequence chart.....	179
9.2.2.2	BICC backward bearer establishment	180
9.2.2.2.1	IM-MGW selection	180
9.2.2.2.2	IM CN subsystem side termination reservation.....	181
9.2.2.2.3	IM CN subsystem side session establishment	181

9.2.2.2.4	CS network side bearer establishment	181
9.2.2.2.5	Through-connection	182
9.2.2.2.6	Codec handling	182
9.2.2.2.7	Failure handling in MGCF	182
9.2.2.2.8	Message sequence chart.....	182
9.2.2.3	ISUP	183
9.2.2.3.1	IM-MGW selection	183
9.2.2.3.2	IM CN subsystem side termination reservation.....	183
9.2.2.3.3	IM CN subsystem side session establishment	184
9.2.2.3.4	CS network side circuit reservation.....	184
9.2.2.3.5	Through-connection	184
9.2.2.3.6	Continuity check.....	185
9.2.2.3.7	Codec handling.....	185
9.2.2.3.8	Voice processing function	185
9.2.2.3.9	Failure handling in MGCF	185
9.2.2.3.10	Message sequence chart.....	185
9.2.3	Basic CS network originated session	187
9.2.3.1	BICC forward bearer establishment	187
9.2.3.1.1	IM-MGW selection	187
9.2.3.1.2	IM CN subsystem side termination reservation.....	187
9.2.3.1.3	IM CN subsystem side session establishment	187
9.2.3.1.4	CS network side bearer establishment.....	187
9.2.3.1.5	Called party alerting	188
9.2.3.1.6	Called party answer	188
9.2.3.1.7	Through-Connection.....	188
9.2.3.1.8	Codec handling.....	188
9.2.3.1.9	Failure handling in MGCF	188
9.2.3.1.10	Message sequence chart.....	188
9.2.3.2	BICC Backward bearer establishment	190
9.2.3.2.1	IM-MGW selection	190
9.2.3.2.2	CS network side bearer establishment.....	190
9.2.3.2.3	IM CN subsystem side termination reservation.....	190
9.2.3.2.4	IM CN subsystem side session establishment	191
9.2.3.2.5	Called party alerting	191
9.2.3.2.6	Called party answer	191
9.2.3.2.7	Through-Connection.....	191
9.2.3.2.8	Codec handling.....	191
9.2.3.2.9	Failure handling in MGCF	192
9.2.3.2.10	Message sequence chart.....	192
9.2.3.3	ISUP	194
9.2.3.3.1	IM-MGW selection	194
9.2.3.3.2	CS network side circuit reservation.....	194
9.2.3.3.3	IM CN subsystem side termination reservation.....	194
9.2.3.3.4	IM CN subsystem side session establishment	194
9.2.3.3.5	Called party alerting	195
9.2.3.3.6	Called party answer	195
9.2.3.3.7	Through-Connection.....	195
9.2.3.3.8	Continuity Check.....	195
9.2.3.3.9	Codec handling	195
9.2.3.3.10	Voice Processing function.....	196
9.2.3.3.11	Failure handling in MGCF	196
9.2.3.3.12	Message sequence chart.....	196
9.2.3.4	Handling of Forking.....	198
9.2.3.4.1	Detection of Forking.....	198
9.2.3.4.2	IM CN subsystem side session establishment	198
9.2.3.4.3	IM CN subsystem side session establishment completion	199
9.2.3.4.4	Message sequence chart.....	199
9.2.4	Session release initiated from IM CN subsystem side	202
9.2.4.1	BICC	202
9.2.4.1.1	Session release in the IM CN subsystem side.....	202
9.2.4.1.2	Session release in the CS network side.....	202
9.2.4.1.3	Message sequence chart.....	202

9.2.4.2	ISUP	203
9.2.4.2.1	Session release in the IM CN subsystem side.....	203
9.2.4.2.2	Session release in the CS network side.....	203
9.2.4.2.3	Message sequence chart.....	203
9.2.5	Session release initiated from CS network side	203
9.2.5.1	BICC	203
9.2.5.1.1	Session release in the CS network side.....	203
9.2.5.1.2	Session release in the IM CN subsystem side.....	204
9.2.5.1.3	Message sequence chart.....	204
9.2.5.2	ISUP	204
9.2.5.2.1	Session release in the CS network side.....	204
9.2.5.2.2	Session release in the IM CN subsystem side.....	204
9.2.5.2.3	Message sequence chart.....	205
9.2.6	Session release initiated by MGCF.....	205
9.2.6.1	BICC	205
9.2.6.1.1	Session release in the CS network side.....	205
9.2.6.1.2	Session release in the IM CN subsystem side.....	205
9.2.6.1.3	Message sequence chart.....	205
9.2.6.2	ISUP	206
9.2.6.2.1	Session release in the CS network side.....	206
9.2.6.2.2	Session release in the IM CN subsystem side.....	206
9.2.6.2.3	Message sequence chart.....	206
9.2.7	Session release initiated by IM-MGW	207
9.2.7.1	BICC	207
9.2.7.1.1	Session release in the CS network side.....	207
9.2.7.1.2	Session release in the IM CN subsystem side.....	207
9.2.7.1.3	Message sequence chart.....	207
9.2.7.2	ISUP	208
9.2.7.2.1	Session release in the CS network side.....	208
9.2.7.2.2	Session release in the IM CN subsystem side.....	208
9.2.7.2.3	Message sequence chart.....	209
9.2.8	Handling of RTP telephone events	209
9.2.8.1	Sending DTMF digits out-of-band to CS CN (BICC).....	210
9.2.8.2	Sending and receiving DTMF digits inband to/from CS CN (ISUP or BICC)	212
9.2.8.3	Receiving DTMF digits out-of-band from CS CN (BICC)	213
9.2.9	Session hold initiated from IM CN subsystem	214
9.2.10	Session hold initiated from CS network	216
9.2.11	Explicit Congestion Notification Support.....	218
9.2.11.1	General.....	218
9.2.11.1a	Incoming Call Interworking from SIP to ISUP/BICC at I-MGCF.....	218
9.2.11.1b	Outgoing Call Interworking from ISUP/BICC to SIP at O-MGCF	219
9.2.11.1c	Detection of ECN failures by IM-MGW	219
9.2.11.2	Message sequence chart	219
9.2.12	Interactive Connectivity Establishment Support.....	220
9.2.12.1	General	220
9.2.12.2	ICE lite	220
9.2.12.3	Full ICE.....	221
9.2.12.4	Procedures for Interactive Connectivity Establishment (ICE)	223
9.2.12.4.1	ICE lite	223
9.2.12.4.2	Full ICE	224
9.2.12.4.3	Connectivity check result notification (full ICE)	225
9.2.12.4.4	New peer reflexive candidate notification (full ICE)	225
9.2.13	Codec Parameters Handling.....	226
9.2.13.1	Handling of common codec parameters	226
9.2.13.2	EVS speech codec	227
9.3	Mn Signalling procedures	236
9.3.1	Procedures related to terminations towards the IM CN Subsystem	236
9.3.1.1	Reserve IMS connection point	237
9.3.1.2	Configure IMS resources	238
9.3.1.3	Reserve IMS Connection point and configure remote resources	239
9.3.1.4	Release IMS termination.....	241
9.3.1.5	Detect IMS RTP Tel event.....	242

9.3.1.6	Notify IMS RTP Tel event	242
9.3.1.7	Void.....	242
9.3.1.8	Send IMS RTP Tel event	242
9.3.1.9	Stop IMS RTP Tel event	242
9.3.1.10	Termination heartbeat indication	243
9.3.1.11	IMS Bearer Released.....	243
9.3.1.12	End IMS RTP Tel event.....	243
9.3.1.13	IMS Send Tone	243
9.3.1.14	IMS Stop Tone	243
9.3.1.15	IMS Tone Completed.....	243
9.3.1.16	ECN Failure Indication	244
9.3.1.17	ICE Connectivity Check Result Notification	244
9.3.1.18	ICE New Peer Reflexive Candidate Notification.....	245
9.3.2	Procedures related to a termination towards an ISUP network.....	245
9.3.2.1	Reserve TDM circuit.....	245
9.3.2.2	Change TDM through-connection	246
9.3.2.3	Activate TDM voice-processing function	246
9.3.2.4	Send TDM tone	246
9.3.2.5	Stop TDM tone.....	246
9.3.2.6	Play TDM announcement	246
9.3.2.7	TDM announcement completed	246
9.3.2.8	Stop TDM announcement	246
9.3.2.9	Continuity check	246
9.3.2.10	Continuity check verify.....	247
9.3.2.11	Continuity check response	247
9.3.2.12	Release TDM termination	247
9.3.2.13	Termination Out-of-Service	248
9.3.2.14	Termination heartbeat indication	248
9.3.2.15	Bearer Released.....	248
9.3.2.16	TDM tone completed	248
9.3.3	Procedures related to a termination towards a BICC network	248
9.3.4	Non-call related procedures	249
9.3.5	Multiple IP Realms	250
9.4	Multimedia Priority Service (MPS) Support.....	251
9.4.1	General.....	251
9.4.2	IM-MGW Resource Congestion in ADD response, request is queued	251
9.4.3	IM-MGW Resource Congestion in ADD response, MGCF seizes new IM-MGW	252
9.4.4	IM-MGW Priority Resource Allocation	252
9.4.5	IM-MGW Priority User Data marking.....	253

Annex A (informative):	Void	254
-------------------------------	-------------------	------------

Annex B (normative):	Codec Negotiation between a BICC CS network and the IM CN subsystem.....	255
-----------------------------	---	------------

B.1	Introduction	255
B.2	Control plane interworking	255
B.2.1	Incoming call interworking from SIP to BICC at I-MGCF.....	255
B.2.1.1	Sending of IAM	255
B.2.1.2	Sending of SDP answer	255
B.2.2	Outgoing call interworking from BICC to SIP at O-MGCF	255
B.2.2.1	Sending of INVITE.....	255
B.2.2.2	Responding to serving node initiating codec negotiation	256
B.2.3	Mid-call interworking from SIP to BICC at I-MGCF or O-MGCF	256
B.2.3.1	Receipt of SDP offer.....	256
B.2.3.2	Generating SDP answer	257
B.2.4	Mid-call interworking from BICC to SIP at I-MGCF or O-MGCF	257
B.2.4.1	Receipt of mid-call codec negotiation request	257
B.2.4.2	Responding to serving node initiating mid-call codec negotiation	257
B.2.4.3	Receipt of codec modification request.....	258
B.2.5	Codec parameter translation between BICC CS network and the IM CN subsystem	258
B.2.5.1	Codec parameters for 3GPP AMR-NB codecs	259

B.2.5.2	Codec parameters for 3GPP AMR-WB codecs	260
B.2.5.3	Codec parameters for 3GPP non-AMR codecs.....	262
B.2.5.4	Codec parameters for ITU-T codecs.....	262
B.3	MGCF – IM-MGW interaction during interworking of codec negotiation.....	263
B.3.1	Basic IM CN subsystem originated session	263
B.3.1.1	BICC forward bearer establishment	264
B.3.1.1.1	IM-MGW selection	264
B.3.1.1.2	CS network side bearer establishment.....	264
B.3.1.1.3	IM CN subsystem side session establishment	264
B.3.1.1.4	Through-connection	264
B.3.1.1.5	Codec handling	265
B.3.1.1.6	Failure handling in MGCF	265
B.3.1.1.7	Message sequence chart	265
B.3.2	Basic CS network originated session.....	267
B.3.2.1	BICC forward bearer establishment.....	267
B.3.2.1.1	IM-MGW selection	267
B.3.2.1.2	IM CN subsystem side termination reservation	267
B.3.2.1.3	IM CN subsystem side session establishment.....	267
B.3.2.1.4	CS network side bearer establishment.....	267
B.3.2.1.5	Called party alerting.....	268
B.3.2.1.6	Called party answer.....	268
B.3.2.1.7	Through-Connection	268
B.3.2.1.8	Codec handling	268
B.3.2.1.9	Failure handling in MGCF	268
B.3.2.1.10	Message sequence chart	268
B.3.3	CS network initiated mid-call codec negotiation.....	271
B.3.4	IM CN subsystem initiated mid-call codec negotiation.....	272
Annex C (normative):	Interworking of CPC parameter	273
C.1	Interworking SIP to ISUP.....	273
C.2	Interworking ISUP to SIP.....	274
Annex D:	Void	275
Annex E (normative):	Multimedia interworking between the IP Multimedia Core Network (CN) Subsystem (IMS) and Circuit Switched (CS) networks	276
E.1	Basic Multimedia calls interworking between the IMS and CS Networks scenarios	276
E.2	Control plane interworking	276
E.2.1	General	276
E.2.2	Functionalities required in the MGCF for multimedia calls support.....	277
E.2.3	IM CN subsystem originated session	277
E.2.3.1	Preconditions used at IMS side.....	277
E.2.3.1.1	Interactions between H.245 or MONA and SIP/SDP	277
E.2.3.2	Preconditions not used at IMS side.....	279
E.2.3.2.1	Interactions between H.245 or MONA and SIP/SDP	279
E.2.3.3	Fallback to speech at session establishment	281
E.2.4	CS network originated session	281
E.2.4.1	Interactions between SIP/SDP and H.245 or MONA	281
E.2.4.1.1	Normal Call setup	281
E.2.4.1.2	Call setup if multimedia call can not be recognized in an unambiguous manner.....	283
E.2.4.1.3	Fallback to speech during call setup	283
E.2.4.2	CS originated – IM CN transit – CS terminated	284
E.2.5	Service change.....	285
E.2.5.2.1	SCUDIF	285
E.2.5.2.1.0	General	285
E.2.5.2.1.1	IM CN subsystem originated change.....	285
E.2.5.2.1.2	CS network originated change.....	287
E.2.5.2.2	Non-SCUDIF case (ISUP or BICC without SCUDIF)	288
E.2.5.2.2.1	Change from multimedia to audio	288

E.2.5.2.2.2	Change from speech to multimedia	289
E.2.6	Call release	289
E.2.6.1	Call release initiated from the IM CN subsystem side	289
E.2.6.2	Call release initiated from the CS network side	290
E.2.6.3	Call release initiated from the interworking node	291
E.3	User plane interworking	292
E.3.1	Functionalities required in the IM-MGW for multimedia calls support	292
E.4	MGCF and IM-MGW interactions	292
E.4.1	Introduction	292
E.4.2	Mn signalling interactions	293
E.4.2.1	Introduction	293
E.4.2.2	H.248 Context Model	293
E.4.2.3	Transport of H.245 messages between the MGCF and IM-MGW	293
E.4.2.3.1	General	293
E.4.2.3.2	Transport from MGCF to IM-MGW	294
E.4.2.3.3	Transport from IM-MGW to MGCF	294
E.4.2.4	Call establishment procedure	294
E.4.2.5	Handling of H.245 indication message	297
E.4.2.5.1	Overview	297
E.4.2.5.2	Function Not Understood / Function Not Supported message	297
E.4.2.5.3	User Input Indication message	298
E.4.2.6	Handling of H.245 Command message	298
E.4.2.6.1	Overview	298
E.4.2.6.2	Flow control command	298
E.4.2.6.3	End Session Command	299
E.4.2.6.4	videoFastUpdatePicture	299
E.4.2.7	Mn Signalling Interactions to support the Media Oriented Negotiation Acceleration (MONA)	300
E.4.2.7.1	Overview	300
E.4.2.7.2	Mn Interactions for MONA preference messages	302
E.4.2.7.3	Mn Interactions for MONA MPCs	304
E.4.2.7.4	Mn Interactions for MONA SPCs	306
E.4.2.7.4.1	General	306
E.4.2.7.4.2	Transport from MGCF to IM-MGW	306
E.4.2.7.4.3	Transport from IM-MGW to MGCF	307
E.4.2.7.4.4	Termination of SPC procedure	307
E.4.2.7.5	Mn Interactions for fallback from MONA procedures to standard H.324 setup	308
E.4.2.8	Interworking between RTCP messages and H.245 messages	309
E.4.2.8.1	Overview	309
E.4.2.8.2	IM CN subsystem originated RTCP messages	309
E.4.2.8.3	CS network originated H.245 messages	310
E.4.3	Mn Signalling procedures	311
E.4.3.1	Overview	311
E.4.3.2	Add Multiplex Termination	312
E.4.3.3	Configure Multiplex Termination	313
E.4.3.4	Signal H245 Message	314
E.4.3.5	Notify H245 Message	314
E.4.3.6	Notify MONA Preference Reception	315
E.4.3.7	Notify MONA Preference Completed	315
E.4.3.8	Signal SPC	316
E.4.3.9	Notify SPC	316
E.4.3.10	Notify MPC	317
E.4.3.11	Notify Detection of Legacy Interworking	317
E.4.3.12	Request RTCP-Interworking	318
E.4.3.13	Notify RTCP-Interworking	318
E.4.3.14	Signal-H.245-Interworking	319
E.4.3.15	Stop MPC	319
E.4.3.16	Stop SPC	319
E.4.3.17	Stop MONA Negotiation	320
Annex F (normative):	PSTN XML Scheme	322

F.1	Scope	322
F.2	MIME type	322
F.3	XML Schema definition.....	322
F.4	IANA registration template	327
Annex G (informative):	Void	330
Annex H (normative):	Interworking of Originating Line Information (OLI) parameter (network option).....	331
H.1	Interworking SIP to ISUP.....	331
H.2	Interworking ISUP to SIP.....	331
Annex I (normative):	GTT interworking between the IP Multimedia Core Network (CN) Subsystem (IMS) and Circuit Switched (CS) networks	332
I.1	Overview of GTT interworking between the IMS and Circuit Switched (CS) networks	332
I.2	Control plane interworking	333
I.2.1	General	333
I.2.2	Functionalities required in the MGCF for GTT calls support	333
I.2.3	IM CN subsystem originated session	333
I.2.3.1	Initial INVITE with an SDP offer including a text media line	333
I.2.4	CS network originated session	334
I.2.4.1	General.....	334
I.2.4.2	Initial INVITE with an SDP offer including audio only	334
I.2.5	Subsequent SDP offer/answer exchange adding text to an audio session	335
I.3	User plane interworking	335
I.3.1	Functionalities required in the IM-MGW for GTT support	335
I.3.2	Monitoring of text/modem signals on the CS side	335
I.3.3	Multiplexing between the CS and IMS streams	336
I.3.4	Conversion between text/modem and Real-Time Text over RTP	336
I.4	MGCF and IM-MGW interactions.....	336
I.4.1	Introduction	336
I.4.2	Mn signalling interactions	336
I.4.2.1	Introduction.....	336
I.4.2.2	H.248 Context Model	337
I.4.2.3	Specific Mn signalling for GTT.....	337
I.4.2.4	IM CN subsystem originated session between the MGCF and IM-MGW	338
I.4.2.4.1	Initial INVITE with an SDP offer including Real-Time Text.....	338
I.4.2.5	CS network originated session.....	340
I.4.2.5.1	Initial INVITE with an SDP offer only including audio	340
I.4.3	Mn Signalling procedures	341
I.4.3.1	Overview	341
Annex J (informative):	Call Flow for Customized Alerting Tone (CAT) interworking between CS network and IMS	342
J.1	Introduction	342
J.2	IMS CAT provided by the terminating IMS user using gateway model towards user served in CS networks	342
J.2.1	Callflow without using precondition mechanism	342
Annex K (normative):	T.38 interworking between the IP Multimedia Core Network (CN) Subsystem (IMS) and Circuit Switched (CS) networks	344
K.1	General	344
K.2	Recommend T.38 configuration.....	344

K.3	Handling T.38 SDP attributes at the I-MGCF.....	345
K.4	Handling T.38 SDP attributes at the O-MGCF	346
K.5	Applicable T.38 SDP attributes at the Mn Interface	347
Annex L (informative):	Change history	348
History		350

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies the principles of interworking between the 3GPP IM CN subsystem and BICC/ISUP based legacy CS networks, in order to support IM basic voice, data and multimedia calls.

The present document addresses the areas of control and user plane interworking between the IM CN subsystem and CS networks through the network functions, which include the MGCF and IM-MGW. For the specification of control plane interworking, areas such as the interworking between SIP and BICC or ISUP are detailed in terms of the processes and protocol mappings required for the support of both IM originated and terminated voice and multimedia calls.

Other areas addressed encompass the transport protocol and signalling issues for negotiation and mapping of bearer capabilities and QoS information.

The present document specifies the interworking between 3GPP profile of SIP (as detailed according to 3GPP TS 24.229 [9]) and BICC or ISUP, as specified in ITU-T Recommendations Q.1902.1 to Q.1902.6 [30] and ITU-T Q761 to Q764 [4] respectively.

The present document also specifies the interworking between circuit switched multimedia telephony service, as described in 3GPP TS 26.110 [78], 3GPP TS 26.111 [79], and ITU-T Recommendation H.324 [81] and packet switched multimedia services, as described in 3GPP TS 26.235 [80] and 3GPP TS 26.236 [32], in particular and the interworking between the 3GPP profile of SIP and the inband control protocols for multimedia communication as specified in ITU-T Recommendations H.245 [82] and H.324 Annex K [81].

The present document addresses two interworking scenarios with respect to the properties of the CS network:

- The CS network does not use any 3GPP specific additions.
- The CS network uses 3GPP specific additions.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] ITU-T Recommendation G.711 (11/88): "Pulse Code Modulation (PCM) of voice frequencies".
- [2] ITU-T Recommendation H.248.1 (05/02): "Gateway control protocol: Version 2".
- [3] ITU-T Recommendation Q.701 (03/93), Q.702 (11/88), Q.703 (07/96), Q.704 (07/96), Q.705 (03/93), Q.706 (03/93), Q.707 (11/88), Q.708 (03/99), Q.709 (03/93): "Functional description of the message transfer part (MTP) of Signalling System No. 7".
- [4] ITU-T Recommendations Q.761 to Q.764 (12/99): "Specifications of Signalling System No.7 ISDN User Part (ISUP)".
- [5] Void.
- [6] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [7] Void.
- [8] 3GPP TS 24.228: "Signalling flows for the IP multimedia call control based on SIP and SDP".