

# ETSI TS 136 300 V12.9.0 (2016-04)



**LTE;  
Evolved Universal Terrestrial Radio Access (E-UTRA)  
and Evolved Universal Terrestrial  
Radio Access Network (E-UTRAN);  
Overall description;  
Stage 2  
(3GPP TS 36.300 version 12.9.0 Release 12)**



---

Reference

RTS/TSGR-0236300vc90

---

Keywords

LTE

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at  
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	14
1 Scope .....	15
2 References .....	15
3 Definitions, symbols and abbreviations .....	17
3.1 Definitions .....	17
3.2 Abbreviations .....	19
4 Overall architecture .....	23
4.1 Functional Split .....	23
4.2 Void.....	26
4.2.1 Void .....	26
4.2.2 Void .....	26
4.3 Radio Protocol architecture .....	26
4.3.1 User plane .....	26
4.3.2 Control plane .....	26
4.4 Synchronization.....	27
4.5 IP fragmentation.....	27
4.6 Support of HeNBs .....	27
4.6.1 Architecture .....	27
4.6.2 Functional Split.....	29
4.6.3 Interfaces.....	31
4.6.3.1 Protocol Stack for S1 User Plane .....	31
4.6.3.2 Protocol Stacks for S1 Control Plane .....	32
4.6.3.3 Protocol Stack for S5 interface.....	33
4.6.3.4 Protocol Stack for SGi interface.....	33
4.6.3.5 Protocol Stack for X2 User Plane and X2 Control Plane .....	33
4.6.4 Void .....	33
4.6.5 Support of LIPA with HeNB .....	33
4.6.6 Support of X2 GW.....	35
4.6.6.1 Enhanced TNL Address Discovery.....	36
4.6.6.2 Routing of X2AP messages .....	36
4.6.6.3 (H)eNB unavailability.....	36
4.6.6.4 (H)eNB registration.....	36
4.7 Support for relaying.....	36
4.7.1 General.....	36
4.7.2 Architecture .....	37
4.7.3 S1 and X2 user plane aspects.....	37
4.7.4 S1 and X2 control plane aspects .....	38
4.7.5 Radio protocol aspects .....	39
4.7.6 Signalling procedures .....	40
4.7.6.1 RN attach procedure.....	40
4.7.6.2 E-RAB activation/modification.....	41
4.7.6.3 RN startup procedure .....	41
4.7.6.4 RN detach procedure.....	42
4.7.6.5 Neighbouring Information Transfer .....	43
4.7.6.6 Mobility to or from RN .....	43
4.7.7 Relay Node OAM Aspects .....	43
4.7.7.1 Architecture.....	43
4.7.7.2 OAM Traffic QoS Requirements .....	44
4.7.7.3 Security Aspects.....	44
4.7.7.4 Void.....	44

4.7.7.5	OAM Requirements for Configuration Parameters.....	44
4.7.7.5.1	Parameters Associated with Relay Bearer Mapping.....	44
4.8	Support of SIPTO at the Local Network .....	44
4.8.1	General.....	44
4.8.2	SIPTO at the Local Network with collocated L-GW .....	45
4.8.3	Support for SIPTO@LN with Stand-Alone Gateway .....	46
4.9	Support for Dual Connectivity .....	46
4.9.1	General.....	46
4.9.2	Radio Protocol Architecture .....	46
4.9.3	Network Interfaces.....	47
4.9.3.1	E-UTRAN Control Plane for Dual Connectivity .....	47
4.9.3.2	E-UTRAN User Plane for Dual Connectivity .....	47
5	Physical Layer for E-UTRA.....	48
5.1	Downlink Transmission Scheme.....	50
5.1.1	Basic transmission scheme based on OFDM.....	50
5.1.2	Physical-layer processing .....	51
5.1.3	Physical downlink control channels.....	51
5.1.4	Downlink Reference signal and synchronization signals.....	52
5.1.5	Downlink multi-antenna transmission .....	52
5.1.6	MBSFN transmission.....	52
5.1.7	Physical layer procedure .....	53
5.1.7.1	Link adaptation .....	53
5.1.7.2	Power Control .....	53
5.1.7.3	Cell search.....	53
5.1.8	Physical layer measurements definition.....	53
5.1.9	Coordinated Multi-Point transmission.....	53
5.2	Uplink Transmission Scheme.....	54
5.2.1	Basic transmission scheme .....	54
5.2.2	Physical-layer processing .....	54
5.2.3	Physical uplink control channel.....	54
5.2.4	Uplink Reference signal.....	55
5.2.5	Random access preamble .....	55
5.2.6	Uplink multi-antenna transmission .....	55
5.2.7	Physical channel procedure.....	55
5.2.7.1	Link adaptation .....	55
5.2.7.2	Uplink Power control .....	56
5.2.7.3	Uplink timing control.....	56
5.2.8	Coordinated Multi-Point reception .....	56
5.3	Transport Channels.....	56
5.3.1	Mapping between transport channels and physical channels.....	58
5.4	E-UTRA physical layer model .....	58
5.4.1	Void .....	58
5.4.2	Void .....	58
5.5	Carrier Aggregation.....	58
5.6	Sidelink .....	59
5.6.1	Basic transmission scheme .....	59
5.6.2	Physical-layer processing .....	59
5.6.3	Physical Sidelink control channel.....	60
5.6.4	Sidelink reference signals .....	60
5.6.5	Physical channel procedure.....	60
5.6.5.1	Sidelink power control .....	60
5.6.6	Physical layer measurements definition.....	60
6	Layer 2.....	60
6.1	MAC Sublayer.....	62
6.1.1	Services and Functions .....	62
6.1.2	Logical Channels .....	63
6.1.2.1	Control Channels.....	63
6.1.2.2	Traffic Channels.....	63
6.1.3	Mapping between logical channels and transport channels .....	64
6.1.3.1	Mapping in Uplink .....	64

6.1.3.2	Mapping in Downlink .....	64
6.1.3.3	Mapping in Sidelink .....	65
6.2	RLC Sublayer .....	65
6.2.1	Services and Functions .....	65
6.2.2	PDU Structure .....	65
6.3	PDCP Sublayer .....	66
6.3.1	Services and Functions .....	66
6.3.2	PDU Structure .....	67
6.4	Carrier Aggregation .....	67
6.5	Dual Connectivity .....	68
7	RRC .....	70
7.1	Services and Functions .....	70
7.2	RRC protocol states & state transitions .....	71
7.3	Transport of NAS messages .....	72
7.4	System Information .....	72
7.5	Carrier Aggregation .....	73
7.6	Dual Connectivity .....	74
8	E-UTRAN identities .....	75
8.1	E-UTRAN related UE identities .....	75
8.2	Network entity related Identities .....	75
8.3	Sidelink communication related identities .....	76
9	ARQ and HARQ .....	76
9.1	HARQ principles .....	76
9.2	ARQ principles .....	77
9.3	Void .....	77
10	Mobility .....	77
10.1	Intra E-UTRAN .....	78
10.1.1	Mobility Management in ECM-IDLE .....	78
10.1.1.1	Cell selection .....	78
10.1.1.2	Cell reselection .....	79
10.1.1.3	Void .....	80
10.1.1.4	Void .....	80
10.1.1.5	Void .....	80
10.1.2	Mobility Management in ECM-CONNECTED .....	80
10.1.2.1	Handover .....	80
10.1.2.1.1	C-plane handling .....	81
10.1.2.1.2	U-plane handling .....	84
10.1.2.2	Path Switch .....	85
10.1.2.2.1	Path Switch upon handover .....	85
10.1.2.2.2	Path Update upon Dual Connectivity specific activities .....	85
10.1.2.3	Data forwarding .....	86
10.1.2.3.1	For RLC-AM DRBs .....	86
10.1.2.3.2	For RLC-UM DRBs .....	86
10.1.2.3.3	SRB handling .....	87
10.1.2.3.4	User data forwarding for Dual Connectivity .....	87
10.1.2.4	Void .....	87
10.1.2.5	Void .....	87
10.1.2.6	Void .....	87
10.1.2.7	Timing Advance .....	87
10.1.2.8	Dual Connectivity operation .....	88
10.1.2.8.1	SeNB Addition .....	88
10.1.2.8.2	SeNB Modification .....	89
10.1.2.8.2.1	Intra-MeNB handover involving SCG change .....	92
10.1.2.8.3	SeNB Release .....	93
10.1.2.8.4	Change of SeNB .....	94
10.1.2.8.5	MeNB to eNB Change .....	95
10.1.2.8.6	SCG change .....	96
10.1.3	Measurements .....	97
10.1.3.1	Intra-frequency neighbour (cell) measurements .....	98

10.1.3.2	Inter-frequency neighbour (cell) measurements.....	99
10.1.4	Paging and C-plane establishment .....	99
10.1.5	Random Access Procedure .....	99
10.1.5.1	Contention based random access procedure.....	100
10.1.5.2	Non-contention based random access procedure .....	101
10.1.5.3	Interaction model between L1 and L2/3 for Random Access Procedure .....	103
10.1.6	Radio Link Failure .....	103
10.1.7	Radio Access Network Sharing .....	104
10.1.8	Handling of Roaming and Area Restrictions for UEs in ECM-CONNECTED.....	105
10.1.8a	Handling of Roaming and Access Restrictions for UEs in ECM-CONNECTED .....	105
10.2	Inter RAT .....	105
10.2.1	Cell reselection .....	105
10.2.2	Handover .....	106
10.2.2a	Inter-RAT cell change order to GERAN with NACC .....	106
10.2.2b	Inter-RAT handovers from E-UTRAN .....	107
10.2.2b.1	Data forwarding .....	107
10.2.2b.1.1	For RLC-AM bearers .....	107
10.2.2b.1.2	For RLC-UM bearers .....	107
10.2.3	Measurements .....	107
10.2.3.1	Inter-RAT handovers from E-UTRAN .....	107
10.2.3.2	Inter-RAT handovers to E-UTRAN.....	108
10.2.3.3	Inter-RAT cell reselection from E-UTRAN.....	108
10.2.3.4	Limiting measurement load at UE .....	108
10.2.4	Network Aspects.....	108
10.2.5	CS fallback.....	108
10.3	Mobility between E-UTRAN and Non-3GPP radio technologies.....	109
10.3.1	UE Capability Configuration .....	109
10.3.2	Mobility between E-UTRAN and cdma2000 network .....	109
10.3.2.1	Tunnelling of cdma2000 Messages over E-UTRAN between UE and cdma2000 Access Nodes .....	110
10.3.2.2	Mobility between E-UTRAN and HRPD.....	111
10.3.2.2.1	Mobility from E-UTRAN to HRPD .....	111
10.3.2.2.1.1	HRPD System Information Transmission in E-UTRAN .....	111
10.3.2.2.1.2	Measuring HRPD from E-UTRAN.....	111
10.3.2.2.1.2.1	Idle Mode Measurement Control .....	111
10.3.2.2.1.2.2	Active Mode Measurement Control.....	111
10.3.2.2.1.2.3	Active Mode Measurement .....	111
10.3.2.2.1.3	Pre-registration to HRPD Procedure.....	111
10.3.2.2.1.4	E-UTRAN to HRPD Cell Re-selection.....	112
10.3.2.2.1.5	E-UTRAN to HRPD Handover.....	112
10.3.2.2.2	Mobility from HRPD to E-UTRAN .....	112
10.3.2.3	Mobility between E-UTRAN and cdma2000 1xRTT .....	112
10.3.2.3.1	Mobility from E-UTRAN to cdma2000 1xRTT.....	112
10.3.2.3.1.1	cdma2000 1xRTT System Information Transmission in E-UTRAN.....	112
10.3.2.3.1.2	Measuring cdma2000 1xRTT from E-UTRAN .....	112
10.3.2.3.1.2.1	Idle Mode Measurement Control .....	112
10.3.2.3.1.2.2	Active Mode Measurement Control.....	113
10.3.2.3.1.2.3	Active Mode Measurement.....	113
10.3.2.3.1.3	E-UTRAN to cdma2000 1xRTT Cell Re-selection.....	113
10.3.2.3.1.4	E-UTRAN to cdma2000 1xRTT Handover .....	113
10.3.2.3.2	Mobility from cdma2000 1xRTT to E-UTRAN.....	113
10.3.2.3.3	1xRTT CS Fallback.....	113
10.3.3	CDMA2000 interworking in LTE shared networks.....	115
10.4	Area Restrictions .....	115
10.4a	Roaming and Access Restrictions .....	116
10.5	Mobility to and from CSG and Hybrid cells .....	116
10.5.0	Principles for idle-mode mobility with CSG cells .....	116
10.5.0.1	Intra-frequency mobility .....	116
10.5.0.2	Inter-frequency mobility .....	116
10.5.0.3	Inter-RAT Mobility.....	116
10.5.1	Inbound mobility to CSG cells .....	116
10.5.1.1	RRC_IDLE.....	116
10.5.1.2	RRC_CONNECTED.....	117

10.5.2	Outbound mobility from CSG cells .....	119
10.5.2.1	RRC_IDLE.....	119
10.5.2.2	RRC_CONNECTED.....	119
10.6	Measurement Model.....	120
10.7	Hybrid Cells .....	120
10.7.1	RRC_IDLE .....	120
10.7.2	RRC_CONNECTED .....	121
10.7.2.1	Inbound Mobility .....	121
10.7.2.2	Outbound Mobility.....	121
11	Scheduling and Rate Control.....	121
11.1	Basic Scheduler Operation .....	121
11.1.1	Downlink Scheduling .....	122
11.1.2	Uplink Scheduling .....	122
11.2	Activation/Deactivation Mechanism .....	123
11.3	Measurements to Support Scheduler Operation .....	123
11.4	Rate Control of GBR, MBR and UE-AMBR .....	123
11.4.1	Downlink .....	123
11.4.2	Uplink .....	124
11.4.3	UE-AMBR for Dual Connectivity .....	124
11.5	CQI reporting for Scheduling.....	124
11.6	Explicit Congestion Notification.....	125
12	DRX in RRC_CONNECTED .....	125
13	QoS.....	126
13.1	Bearer service architecture .....	126
13.2	QoS parameters .....	127
13.3	QoS support in Hybrid Cells .....	128
14	Security.....	128
14.1	Overview and Principles .....	128
14.2	Security termination points.....	131
14.3	State Transitions and Mobility .....	131
14.3.1	RRC_IDLE to RRC_CONNECTED .....	131
14.3.2	RRC_CONNECTED to RRC_IDLE .....	132
14.3.3	Intra E-UTRAN Mobility .....	132
14.3.4	SeNB Removal .....	132
14.4	AS Key Change in RRC_CONNECTED .....	132
14.5	Security Interworking.....	132
14.6	RN integrity protection for DRB(s).....	133
15	MBMS.....	133
15.1	General .....	134
15.1.1	E-MBMS Logical Architecture.....	134
15.1.2	E-MBMS User Plane Protocol Architecture .....	136
15.1.3	E-MBMS Control Plane Protocol Architecture .....	136
15.2	MBMS Cells.....	137
15.2.1	MBMS-dedicated cell .....	137
15.2.2	MBMS/Unicast-mixed cell .....	137
15.3	MBMS Transmission.....	137
15.3.1	General.....	137
15.3.2	Single-cell transmission .....	137
15.3.3	Multi-cell transmission .....	137
15.3.4	MBMS Reception States.....	139
15.3.5	MCCH Structure .....	139
15.3.6	MBMS signalling on BCCH.....	139
15.3.7	MBMS User Data flow synchronisation.....	140
15.3.8	Synchronisation of MCCH Update Signalling via M2 .....	141
15.3.9	IP Multicast Distribution .....	141
15.4	Service Continuity .....	141
15.5	Network sharing .....	143
15.6	Network Functions for Support of Multiplexing .....	143
15.7	Procedures .....	143

15.7.1	Procedures for Broadcast mode .....	143
15.7.1.1	Session Start procedure .....	143
15.7.1.2	Session Stop procedure .....	145
15.7a	M1 Interface .....	145
15.7a.1	M1 User Plane .....	145
15.8	M2 Interface .....	146
15.8.1	M2 Control Plane .....	146
15.8.2	M2 Interface Functions .....	147
15.8.2.1	General .....	147
15.8.2.2	MBMS Session Handling Function.....	147
15.8.2.3	MBMS Scheduling Information Provision Function .....	147
15.8.2.4	M2 Interface Management Function .....	147
15.8.2.5	M2 Configuration Function.....	147
15.8.2.6	MBMS Service Counting Function.....	147
15.8.2.7	MBMS Service Suspension and Resumption Function.....	148
15.8.2.8	MBMS Overload Notification Function.....	148
15.8.3	M2 Interface Signalling Procedures.....	148
15.8.3.1	General .....	148
15.8.3.2	MBMS Session signalling procedure .....	148
15.8.3.3	MBMS Scheduling Information procedure .....	148
15.8.3.4	M2 Interface Management procedures .....	148
15.8.3.4.1	Reset procedure .....	148
15.8.3.4.2	Error Indication procedure.....	148
15.8.3.5	M2 Configuration procedures .....	148
15.8.3.5.1	M2 Setup procedure .....	148
15.8.3.5.2	eNB Configuration Update procedure .....	149
15.8.3.5.3	MCE Configuration Update procedure.....	149
15.8.3.6	MBMS Service Counting procedures .....	149
15.8.3.6.1	MBMS Service Counting procedure .....	149
15.8.3.6.2	MBMS Service Counting Results Report procedure.....	149
15.8.3.7	MBMS Overload Notification procedure.....	149
15.9	M3 Interface .....	149
15.9.1	M3 Control Plane.....	149
15.9.2	M3 Interface Functions .....	150
15.9.2.1	General .....	150
15.9.2.2	MBMS Session Handling Function.....	150
15.9.2.3	M3 Interface Management Function .....	150
15.9.2.4	M3 Configuration Function.....	150
15.9.3	M3 Interface Signalling Procedures.....	150
15.9.3.1	General .....	150
15.9.3.2	MBMS Session signalling procedure .....	150
15.9.3.3	M3 Interface Management procedures .....	151
15.9.3.3.1	Reset procedure .....	151
15.9.3.3.2	Error Indication procedure.....	151
15.9.3.4	M3 Configuration procedures .....	151
15.9.3.4.1	M3 Setup procedure .....	151
15.9.3.4.2	MCE Configuration Update procedure.....	151
15.10	MBMS Counting .....	151
15.10.1	General.....	151
15.10.2	Counting Procedure .....	151
16	Radio Resource Management aspects .....	152
16.1	RRM functions .....	152
16.1.1	Radio Bearer Control (RBC) .....	152
16.1.2	Radio Admission Control (RAC).....	152
16.1.3	Connection Mobility Control (CMC) .....	152
16.1.4	Dynamic Resource Allocation (DRA) - Packet Scheduling (PS) .....	153
16.1.5	Inter-cell Interference Coordination (ICIC).....	153
16.1.5.1	UE configurations for time domain ICIC.....	153
16.1.5.2	OAM requirements for time domain ICIC .....	154
16.1.5.2.1	Configuration for CSG cell.....	154
16.1.5.2.2	Configuration for interfering non-CSG cell.....	154

16.1.6	Load Balancing (LB) .....	154
16.1.7	Inter-RAT Radio Resource Management .....	154
16.1.8	Subscriber Profile ID for RAT/Frequency Priority .....	155
16.1.9	Inter-eNB CoMP .....	155
16.1.10	Cell on/off and cell discovery .....	155
16.2	RRM architecture .....	155
16.2.1	Centralised Handling of certain RRM Functions .....	155
16.2.2	De-Centralised RRM .....	155
16.2.2.1	UE History Information .....	155
16.2.3	Void .....	156
16.3	UE assistance information for RRM and UE power optimisations .....	156
17	Void .....	156
17.1	Void .....	156
18	UE capabilities .....	156
19	S1 Interface .....	158
19.1	S1 User plane .....	158
19.2	S1 Control Plane .....	158
19.2.1	S1 Interface Functions .....	159
19.2.1.1	S1 Paging function .....	160
19.2.1.2	S1 UE Context Management function .....	160
19.2.1.3	Initial Context Setup Function .....	160
19.2.1.3a	UE Context Modification Function .....	160
19.2.1.4	Mobility Functions for UEs in ECM-CONNECTED .....	160
19.2.1.4.1	Intra-LTE Handover .....	160
19.2.1.4.2	Inter-3GPP-RAT Handover .....	160
19.2.1.5	E-RAB Service Management function .....	160
19.2.1.6	NAS Signalling Transport function .....	160
19.2.1.7	NAS Node Selection Function (NNSF) .....	161
19.2.1.8	S1-interface management functions .....	161
19.2.1.9	MME Load balancing Function .....	161
19.2.1.10	Location Reporting Function .....	161
19.2.1.11	Warning Message Transmission function .....	161
19.2.1.12	Overload Function .....	161
19.2.1.13	RAN Information Management Function .....	162
19.2.1.14	S1 CDMA2000 Tunnelling function .....	162
19.2.1.15	Configuration Transfer Function .....	162
19.2.1.16	LPPa Signalling Transport function .....	162
19.2.1.17	Trace Function .....	162
19.2.1.18	UE Radio Capability Match .....	162
19.2.2	S1 Interface Signalling Procedures .....	162
19.2.2.1	Paging procedure .....	162
19.2.2.2	S1 UE Context Release procedure .....	163
19.2.2.2.1	S1 UE Context Release (EPC triggered) .....	163
19.2.2.2.2	S1 UE Context Release Request (eNB triggered) .....	163
19.2.2.3	Initial Context Setup procedure .....	164
19.2.2.3a	UE Context Modification procedure .....	165
19.2.2.4	E-RAB signalling procedures .....	165
19.2.2.4.1	E-RAB Setup procedure .....	165
19.2.2.4.2	E-RAB Modification procedure .....	166
19.2.2.4.3	E-RAB Release procedure .....	167
19.2.2.4.4	E-RAB Release Indication procedure .....	168
19.2.2.4.5	E-RAB Modification Indication procedure .....	168
19.2.2.5	Handover signalling procedures .....	168
19.2.2.5.1	Handover Preparation procedure .....	169
19.2.2.5.2	Handover Resource Allocation procedure .....	169
19.2.2.5.3	Handover Notification procedure .....	170
19.2.2.5.4	Handover Cancellation .....	170
19.2.2.5.5	Path Switch procedure .....	171
19.2.2.5.6	Message sequence diagrams .....	171
19.2.2.5.7	eNB Status Transfer procedure .....	179

19.2.2.5.8	MME Status Transfer procedure .....	180
19.2.2.6	NAS transport procedures .....	180
19.2.2.7	S1 interface Management procedures .....	182
19.2.2.7.1	Reset procedure .....	182
19.2.2.7.1a	eNB initiated Reset procedure .....	182
19.2.2.7.1b	MME initiated Reset procedure .....	183
19.2.2.7.2	Error Indication functions and procedures .....	183
19.2.2.7.2a	eNB initiated error indication .....	183
19.2.2.7.2b	MME initiated error indication .....	183
19.2.2.8	S1 Setup procedure .....	184
19.2.2.9	eNB Configuration Update procedure .....	184
19.2.2.9a	eNB Configuration Transfer procedure .....	185
19.2.2.10	MME Configuration Update procedure .....	185
19.2.2.10a	MME Configuration Transfer procedure .....	186
19.2.2.11	Location Reporting procedures .....	186
19.2.2.11.1	Location Reporting Control procedure .....	186
19.2.2.11.2	Location Report procedure .....	187
19.2.2.11.3	Location Report Failure Indication procedure .....	187
19.2.2.12	Overload procedure .....	187
19.2.2.12.1	Overload Start procedure .....	187
19.2.2.12.2	Overload Stop procedure .....	188
19.2.2.13	Write-Replace Warning procedure .....	188
19.2.2.14	eNB Direct Information Transfer procedure .....	189
19.2.2.15	MME Direct Information Transfer procedure .....	189
19.2.2.16	S1 CDMA2000 Tunnelling procedures .....	190
19.2.2.16.1	Downlink S1 CDMA2000 Tunnelling procedure .....	190
19.2.2.16.2	Uplink S1 CDMA2000 Tunnelling procedure .....	190
19.2.2.17	Kill procedure .....	191
19.2.2.18	LPPa Transport procedures .....	191
19.2.2.18.1	Downlink UE Associated LPPa Transport procedure .....	191
19.2.2.18.2	Uplink UE Associated LPPa Transport procedure .....	192
19.2.2.18.3	Downlink Non UE Associated LPPa Transport procedure .....	192
19.2.2.18.4	Uplink Non UE Associated LPPa Transport procedure .....	192
19.2.2.19	Trace procedures .....	193
19.2.2.19.1	Trace Start procedure .....	193
19.2.2.19.2	Trace Failure Indication procedure .....	193
19.2.2.19.3	Deactivate Trace procedure .....	194
19.2.2.19.4	Cell Traffic Trace procedure .....	194
19.2.2.20	UE Capability Info Indication procedure .....	194
19.2.2.21	UE Radio Capability Match procedure .....	195
19.2.2.22	PWS Restart Indication procedure .....	195
20	X2 Interface .....	195
20.1	User Plane .....	195
20.1.1	Flow Control Functions .....	196
20.2	Control Plane .....	196
20.2.1	X2-CP Functions .....	197
20.2.2	X2-CP Procedures .....	197
20.2.2.1	Handover Preparation procedure .....	197
20.2.2.2	Handover Cancel procedure .....	198
20.2.2.2a	SeNB Addition Preparation procedure .....	198
20.2.2.2b	SeNB Reconfiguration Completion procedure .....	199
20.2.2.2c	MeNB initiated SeNB Modification Preparation procedure .....	199
20.2.2.2d	SeNB initiated SeNB Modification procedure .....	200
20.2.2.2e	MeNB initiated SeNB Release procedure .....	200
20.2.2.2f	SeNB initiated SeNB Release procedure .....	201
20.2.2.2g	SeNB Counter Check procedure .....	201
20.2.2.3	UE Context Release procedure .....	201
20.2.2.4	SN Status Transfer procedure .....	202
20.2.2.5	Error Indication procedure .....	202
20.2.2.6	Load Indication procedure .....	203
20.2.2.7	X2 Setup procedure .....	203

20.2.2.8	eNB Configuration Update procedure.....	203
20.2.2.9	Reset procedure.....	204
20.2.2.10	Resource Status Reporting Initiation procedure.....	204
20.2.2.11	Resource Status Reporting procedure.....	205
20.2.2.12	Radio Link Failure Indication procedure.....	205
20.2.2.13	Handover Report procedure.....	205
20.2.2.14	Mobility Settings Change procedure.....	206
20.2.2.15	Cell Activation procedure.....	206
20.2.2.16	X2 Release procedure.....	207
20.2.2.17	X2AP Message Transfer procedure.....	207
20.2.2.18	X2 Removal procedure.....	207
20.2.3	Void.....	208
21	Void.....	208
21.1	Void.....	208
21.2	Void.....	208
21.3	Void.....	208
22	Support for self-configuration and self-optimisation.....	208
22.1	Definitions.....	208
22.2	UE Support for self-configuration and self-optimisation.....	209
22.3	Self-configuration.....	209
22.3.1	Dynamic configuration of the S1-MME interface.....	209
22.3.1.1	Prerequisites.....	209
22.3.1.2	SCTP initialization.....	209
22.3.1.3	Application layer initialization.....	210
22.3.2	Dynamic Configuration of the X2 interface.....	210
22.3.2.1	Prerequisites.....	210
22.3.2.2	SCTP initialization.....	210
22.3.2.3	Application layer initialization.....	210
22.3.2a	Automatic Neighbour Relation Function.....	210
22.3.3	Intra-LTE/frequency Automatic Neighbour Relation Function.....	212
22.3.4	Inter-RAT/Inter-frequency Automatic Neighbour Relation Function.....	213
22.3.5	Framework for PCI Selection.....	214
22.3.6	TNL address discovery.....	214
22.3.6.1	TNL address discovery of candidate eNB via S1 interface.....	214
22.4	Self-optimisation.....	215
22.4.1	Support for Mobility Load Balancing.....	215
22.4.1.1	General.....	215
22.4.1.2.1	Load reporting for intra-LTE scenario.....	216
22.4.1.2.2	Load reporting for inter-RAT scenario.....	217
22.4.2	Support for Mobility Robustness Optimisation.....	217
22.4.2.1	General.....	217
22.4.2.2	Connection failure due to intra-LTE mobility.....	217
22.4.2.2a	Connection failure due to inter-RAT mobility.....	220
22.4.2.3	Unnecessary HO to another RAT.....	221
22.4.2.4	O&M Requirements.....	222
22.4.2.5	Inter-RAT ping-pong.....	222
22.4.3	Support for RACH Optimisation.....	223
22.4.4	Support for Energy Saving.....	223
22.4.4.1	General.....	223
22.4.4.2	Solution description.....	223
22.4.4.3	O&M requirements.....	224
22.4.5	Radio Link Failure report.....	224
22.5	Void.....	224
22.6	Void.....	224
23	Others.....	224
23.1	Support for real time IMS services.....	224
23.1.1	IMS Emergency Call.....	224
23.2	Subscriber and equipment trace.....	225
23.2.1	Signalling activation.....	225
23.2.2	Management activation.....	225

23.3	E-UTRAN Support for Warning Systems .....	225
23.3.1	Earthquake and Tsunami Warning System .....	225
23.3.2	Commercial Mobile Alert System .....	226
23.3.3	Korean Public Alert System.....	226
23.3.4	EU-Alert .....	226
23.4	Interference avoidance for in-device coexistence.....	226
23.4.1	Problems .....	226
23.4.2	Solutions .....	226
23.5	TDD Enhanced Interference Management and Traffic Adaptation (eIMTA) .....	228
23.6	RAN assisted WLAN interworking.....	229
23.6.1	General principles.....	229
23.6.2	Access network selection and traffic steering rules .....	229
23.7	Support of Low Complexity UEs .....	229
23.8	Support for Radio Interface based Synchronization .....	230
23.9	Network-assisted interference cancellation/suppression .....	230
23.10	Support for sidelink communication .....	230
23.10.1	General.....	230
23.10.2	Radio Protocol Architecture .....	231
23.10.2.1	User plane .....	231
23.10.2.2	Control plane.....	231
23.10.3	Radio resource allocation.....	232
23.10.3.1	Resource Pool for sidelink control information .....	233
23.10.3.2	Resource Pool for sidelink data.....	234
23.11	Support for sidelink discovery.....	234
23.11.1	General.....	234
23.11.2	Radio Protocol Architecture .....	235
23.11.3	Radio resource allocation.....	235
<b>Annex A (informative):    NAS Overview .....</b>		<b>237</b>
A.1	Services and Functions.....	237
A.2	NAS protocol states & state transitions.....	237
<b>Annex B (informative):    MAC and RRC Control .....</b>		<b>238</b>
B.1	Difference between MAC and RRC control .....	238
B.2	Void.....	238
<b>Annex C (informative):    Void .....</b>		<b>239</b>
<b>Annex D (informative):    Void .....</b>		<b>240</b>
<b>Annex E (informative):    Void .....</b>		<b>241</b>
<b>Annex F (informative):    Void .....</b>		<b>242</b>
<b>Annex G (informative):    Guideline for E-UTRAN UE capabilities.....</b>		<b>243</b>
<b>Annex H (informative):    Void .....</b>		<b>245</b>
<b>Annex I (informative):    SPID ranges and mapping of SPID values to cell reselection and inter-RAT/inter frequency handover priorities .....</b>		<b>246</b>
I.1	SPID ranges.....	246
I.2	Reference SPID values .....	246
<b>Annex J (informative):    Carrier Aggregation .....</b>		<b>248</b>
J.1	Deployment Scenarios.....	248
J.2	Void.....	249
J.3	Void.....	249
J.4	Void.....	249
J.5	Void.....	249
J.6	Void.....	249

<b>Annex K (informative):</b>	<b>Time domain ICIC</b> .....	<b>250</b>
K.1	Deployment scenarios .....	250
K.1.1	CSG scenario .....	250
K.1.2	Pico scenario .....	251
<b>Annex L (informative):</b>	<b>Void</b> .....	<b>252</b>
<b>Annex M (informative):</b>	<b>Dual Connectivity</b> .....	<b>253</b>
M.1	Dual Connectivity operation.....	253
M.2	Operation Overview .....	253
<b>Annex N (informative):</b>	<b>Sidelink communication</b> .....	<b>256</b>
N.1	Deployment Scenarios.....	256
<b>Annex O (informative):</b>	<b>Change history</b> .....	<b>257</b>
History	.....	267

---

# Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# 1 Scope

The present document provides an overview and overall description of the E-UTRAN radio interface protocol architecture. Details of the radio interface protocols are specified in companion specifications of the 36 series.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TR 25.913: "Requirements for Evolved UTRA (E-UTRA) and Evolved UTRAN (E-UTRAN)".
- [3] 3GPP TS 36.201: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer; General description".
- [4] 3GPP TS 36.211: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical Channels and Modulation".
- [5] 3GPP TS 36.212: "Evolved Universal Terrestrial Radio Access (E-UTRA); Multiplexing and channel coding".
- [6] 3GPP TS 36.213: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures".
- [7] 3GPP TS 36.214: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer; Measurements".
- [8] IETF RFC 4960 (09/2007): "Stream Control Transmission Protocol".
- [9] 3GPP TS 36.302: "Evolved Universal Terrestrial Radio Access (E-UTRA); Services provided by the physical layer".
- [10] Void
- [11] 3GPP TS 36.304: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) procedures in idle mode".
- [12] 3GPP TS 36.306: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio access capabilities".
- [13] 3GPP TS 36.321: "Evolved Universal Terrestrial Radio Access (E-UTRA); Medium Access Control (MAC) protocol specification".
- [14] 3GPP TS 36.322: "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Link Control (RLC) protocol specification".
- [15] 3GPP TS 36.323: "Evolved Universal Terrestrial Radio Access (E-UTRA); Packet Data Convergence Protocol (PDCP) specification".
- [16] 3GPP TS 36.331: "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC) protocol specification".