



**VHF air-ground Digital Link (VDL) Mode 2;  
Technical characteristics and  
methods of measurement  
for ground-based equipment;  
Part 1: Physical layer and MAC sub-layer**

Reference
REN/AERO-00010
Keywords
aeronautical, radio, testing, VHF

***ETSI***

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

***Important notice***

---

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.  
Information on the current status of this and other ETSI documents is available at  
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

***Copyright Notification***

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.  
The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.  
All rights reserved.

**DECT™, PLUGTESTS™, UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and  
of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

---

## Contents

Intellectual Property Rights .....	6
Foreword.....	6
Modal verbs terminology.....	6
Introduction .....	6
1    Scope .....	7
2    References .....	7
2.1    Normative references .....	7
2.2    Informative references.....	7
3    Definitions and abbreviations.....	8
3.1    Definitions.....	8
3.1.1    Basic reference model definitions.....	8
3.1.2    Service conventions definitions .....	8
3.1.3    General definitions.....	9
3.2    Abbreviations .....	9
4    General architecture of VDL Mode 2.....	10
5    Physical layer protocols and services functional specifications.....	11
5.1    Overview .....	11
5.1.1    Functions .....	11
5.1.2    Data reception by the receiver .....	12
5.1.3    Data transmission.....	12
5.2    Transmission procedure .....	12
5.3    Modulation scheme .....	13
5.4    Training sequence.....	13
5.4.1    RF power rise time definition .....	13
5.5    Physical layer Service Access Point.....	14
5.6    Tuning range and channel increments .....	14
6    VDL MODE 2 equipment requirements .....	14
6.1    Transmitter requirements .....	14
6.1.1    Frequency Tolerance.....	14
6.1.2    Manufacturer's declared output power.....	14
6.1.3    Adjacent channel power.....	15
6.1.3.1    16 kHz channel bandwidth.....	15
6.1.3.2    25 kHz channel bandwidth.....	15
6.1.4    Conducted Spurious emissions .....	16
6.1.5    Cabinet radiation.....	16
6.1.6    Modulation rate.....	16
6.1.7    Intermodulation attenuation .....	16
6.1.8    RF power rise time.....	16
6.1.9    RF power release time .....	16
6.1.10    Transceiver timing requirements .....	17
6.1.10.1    Receiver to transmitter turn-around time .....	17
6.1.10.2    Transmitter to receiver turn-around time .....	17
6.1.11    Symbol constellation error.....	17
6.1.12    Protection of the transmitter.....	17
6.1.13    Load VSWR capability .....	17
6.2    Receiver requirements .....	17
6.2.1    Sensitivity .....	17
6.2.2    Co-channel interference .....	17
6.2.3    First Adjacent Channel Rejection .....	17
6.2.4    Rejection of signals within the VHF Aeronautical band.....	18
6.2.5    Rejection of signals outside the VHF Aeronautical band .....	18
6.2.6    In-band Intermodulation .....	18
6.2.7    Desired signal dynamic range.....	19

6.2.8	Conducted spurious emission .....	19
6.2.9	Cabinet radiation.....	19
6.2.10	Symbol rate capture range .....	19
6.2.11	Frequency capture range .....	19
6.3	Void.....	19
6.4	MAC sub-layer requirements .....	19
6.4.1	MAC services .....	19
6.4.1.1	Multiple Access.....	19
6.4.1.2	Channel Congestion.....	19
6.4.2	MAC System Parameters.....	19
6.4.2.1	Timer TM1 (inter-access delay timer).....	19
6.4.2.2	Timer TM2 (channel busy timer) .....	20
6.4.2.3	Parameter p (persistence) .....	20
6.4.2.4	Counter M1 (maximum access attempts) .....	20
6.4.3	Description of MAC Layer Procedures .....	20
6.4.3.1	Channel Sensing.....	20
6.4.3.2	Access Attempt .....	20
6.4.3.3	Signal Quality Parameter .....	20
6.4.4	Services (Part of DLS).....	20
6.4.4.1	Error Detection.....	20
6.4.4.2	Station Identification.....	20
7	General requirements .....	21
7.1	General .....	21
7.2	Controls and indicators.....	21
7.3	Class of emission and modulation characteristics .....	21
7.4	Warm up.....	21
8	Test conditions, power sources and ambient temperatures .....	21
8.1	Test power source.....	21
8.2	Normal and extreme test conditions .....	21
8.2.1	Normal test conditions .....	21
8.2.1.1	Normal temperature and humidity .....	21
8.2.1.2	Normal power sources.....	22
8.2.1.2.1	Mains voltage and frequency.....	22
8.2.1.2.2	Other power sources .....	22
8.2.2	Extreme test conditions.....	22
8.2.2.1	Extreme temperatures.....	22
8.2.2.2	Procedure for tests at extreme temperatures.....	22
8.2.2.2.1	General .....	22
8.2.2.2.2	High temperature .....	22
8.2.2.2.3	Low temperature.....	22
8.2.2.3	Extreme values of test power sources .....	23
8.2.2.4	Other power sources .....	23
8.3	Test channels .....	23
8.4	General conditions of measurement .....	23
8.4.1	Receiver test signal arrangement .....	23
8.4.2	Receiver BER test.....	23
8.4.3	Performance check.....	24
9	Detailed Test Procedures for the physical layer .....	25
9.1	Transmitter .....	25
9.1.1	Frequency Error .....	25
9.1.1.1	Definition .....	25
9.1.1.2	Method of measurement.....	25
9.1.1.3	Limits .....	25
9.1.2	Manufacturer's declared output power .....	25
9.1.3	Adjacent channel power.....	26
9.1.3.1	Method of measurement for the first adjacent channel .....	26
9.1.3.2	Method of measurement for the second adjacent channel.....	27
9.1.3.3	Method of measurement for the fourth adjacent channel .....	27
9.1.3.4	Wideband noise .....	29
9.1.4	Spurious emissions .....	30

9.1.5	Cabinet Radiation .....	30
9.1.6	Void .....	30
9.1.7	Inter-modulation attenuation.....	30
9.1.8	RF power rise time.....	31
9.1.9	RF power release time .....	33
9.1.10	Physical layer, system parameters .....	34
9.1.10.1	Receiver to Transmitter turn-around time .....	34
9.1.10.2	Transmitter to Receiver turn-around time .....	35
9.1.11	Symbol Constellation Error .....	36
9.1.12	Protection of the transmitter.....	37
9.1.12.1	Method of measurement.....	37
9.1.12.2	Requirement .....	37
9.1.13	Load VSWR capability .....	37
9.2	Receiver.....	38
9.2.1	Sensitivity .....	38
9.2.2	Co-channel interference.....	38
9.2.3	First Adjacent Channel Rejection .....	39
9.2.4	Rejection of signals within the VHF Aeronautical band.....	40
9.2.5	Rejection of signals outside the VHF Aeronautical band .....	41
9.2.6	In-band Intermodulation .....	41
9.2.7	Desired Signal dynamic range .....	42
9.2.8	Conducted spurious emission .....	43
9.2.9	Cabinet Radiation .....	43
9.2.10	Symbol rate capture range .....	43
9.2.11	Frequency capture range .....	44
9.3	Void.....	44
9.4	MAC sub-layer .....	44
9.4.1	MAC services .....	45
9.4.1.1	Multiple Access.....	45
9.4.1.2	Channel Congestion .....	45
9.4.2	MAC System Parameters.....	45
9.4.2.1	Timer TM1 (inter-access delay timer).....	45
9.4.2.2	Timer TM2 (channel busy timer) .....	46
9.4.2.3	Parameter p (persistence) .....	46
9.4.2.4	Counter M1 (maximum access attempts) .....	47
9.4.3	Description of MAC Layer Procedures .....	48
9.4.3.1	Channel Sensing.....	48
9.4.3.2	Access Attempt .....	48
9.4.3.3	Signal Quality Parameter .....	49
9.4.4	Services (Part of DLS).....	49
9.4.4.1	Error Detection.....	49
9.4.4.2	Station Identification .....	50
	<b>Annex A (informative): Bibliography.....</b>	<b>51</b>
	History .....	52

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Aeronautics (AERO).

The present document is part 1 of a multi-part deliverable covering VHF air-ground Digital Link (VDL) Mode 2; Technical characteristics and methods of measurement for ground-based equipment, as identified below:

**Part 1: "Physical layer and MAC sub-layer";**

Part 2: "Upper layers";

Part 3: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

<b>National transposition dates</b>	
Date of adoption of this EN:	21 April 2015
Date of latest announcement of this EN (doa):	31 July 2015
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2016
Date of withdrawal of any conflicting National Standard (dow):	31 January 2016

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

## Introduction

The present document states the technical specifications for ground-based equipment implementing Very High Frequency (VHF) Digital Link (VDL) Mode 2 air interface, operating in the VHF band (117,975 MHz to 137,000 MHz) with 25 kHz channel spacing.

Manufacturers should note that in the future, all or part of the frequency band 108,000 MHz to 117,975 MHz may become available for aeronautical communications.

The VDL Mode 2 system is designed to be a Ground/Air sub-system of the Aeronautical Telecommunication Network (ATN) using the AM(R)S band and it is organized according to the Open Systems Interconnection (OSI) model (defined by ISO). It will provide reliable subnetwork services to the ATN system.

The present document may be used to produce tests for the assessment of the performance of the equipment.

---

# 1 Scope

The present document applies to VDL Mode 2 ground-air digital communications using Differential Eight Phase Shift Keying (D8PSK), intended for channel increments of 25 kHz. The VDL Mode 2 system provides data communication exchanges between aircraft and ground-based systems. The scope of the present document is limited to ground-based stations.

The present document provides functional specifications for ground-based radio equipment intended to be used for ground-air data communications. The present document is derived from the following documents:

- Annex 10 of the ICAO Convention on International Civil Aviation [1].
- ED 92B [i.2]: "MOPS for an Airborne VDL Mode-2 Transceiver Operating in the frequency range 118-136.975 MHz" (2012), which specifies the airborne transceiver.

The present document consists of two parts:

- the first part provides functional specifications and test procedures for physical layer and MAC sub-layer;
  - the second part provides functional specifications and test procedures for link and sub-network access layers.
- 

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ICAO Convention on International Civil Aviation: "Annex 10 - Aeronautical Telecommunications, Volume III - Communication Systems, Part I - Digital Data Communication Systems, Second Edition, July 2007, incorporating Amendments up to 88A (applicable 14/11/13). Chapter 6 - VHF Air-ground Digital Link (VDL)".
- [2] ICAO Convention on International Civil Aviation: "Annex 10 - Aeronautical Telecommunications, Volume V - Aeronautical Radio Frequency Spectrum Utilization", Third Edition, July 2013 incorporating Amendments up to 88A.
- [3] ETSI EN 300 113-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 1: Technical characteristics and methods of measurement".
- [4] ICAO Document 9776/AN970 (first edition, 2001): "Manual on VHF Digital Link (VDL) mode 2".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.