



Digital cellular telecommunications system (Phase 2+) (GSM); Background for Radio Frequency (RF) requirements (3GPP TR 45.050 version 13.1.0 Release 13)



Reference

RTR/TSGG-0145050vd10

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Report (TR) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	22
1 Scope	23
1.1 General	23
1.2 References	23
2 Information available	23
3 DCS1800 system scenarios	23
4 GSM900 small cell system scenarios	24
5 GSM900 and DCS1800 microcell system scenarios.....	24
6 Conversion factors.....	25
7 Repeaters	26
8 Error Patterns for Speech Coder Developments.....	26
9 Simulations of Performance	26
10 GSM900 railway system scenarios	26
11 Simulation results for GPRS receiver performance	27
12 Pico BTS RF scenarios.....	27
13 CTS system scenarios.....	27
14 GSM400 system scenarios	27
15 MXM system scenarios	28
16 LCS scenarios.....	28
17 8-PSK Scenarios.....	28
18 T-GSM 900 System Scenarios	28
19 MBMS System Scenarios.....	28
20 T-GSM 810 System Scenarios	28
21 Multicarrier BTS Class.....	28
22 ER-GSM band introduction.....	28
23 Extended Training Sequence Code Sets.....	29
23.1 Background	29
23.2 Extended TSC Sets	29
23.2.1 Scope	29
23.2.2 Design criteria.....	29
23.2.3 Design methodology	29
23.2.4 Evaluation methodology	30
23.2.5 Performance evaluation	30
24 Machine-type-communication (MTC) deployment, including EC-GSM-IoT, in a reduced BCCH spectrum allocation.....	30
24.1 Introduction	30
24.2 Simulation campaign.....	31

24.2.1	Introduction.....	31
24.2.2	Idle mode procedures.....	32
24.2.2.1	General	32
24.2.2.1.1	Simulator support	32
24.2.2.1.2	Performance metrics	32
24.2.2.1.3	Simulation assumptions	33
24.2.2.2	PLMN selection	33
24.2.2.3	Cell selection.....	33
24.2.2.3.1	General	33
24.2.2.3.2	GPRS/EGPRS	34
24.2.2.3.3	EC-GSM-IoT.....	35
24.2.2.4	Cell reconfirmation	35
24.2.2.4.1	GPRS/EGPRS	35
24.2.2.4.2	EC-GSM-IoT	37
24.2.3	Common control channel performance.....	39
24.2.3.1	General	39
24.2.3.2	GPRS/EGPRS	39
24.2.3.2.1	Resource usage	39
24.2.3.2.2	Common control signaling delay.....	40
24.2.3.2.3	Failed attempts	40
24.2.3.3	EC-GSM-IoT	40
24.2.3.3.1	Resource usage	40
24.2.3.3.2	Common control signaling delay.....	41
24.2.3.3.3	Failed attempts	41
24.2.3.3.4	Coverage class distribution.....	41
24.2.4	Data traffic and control channel performance.....	42
24.2.4.1	General	42
24.2.4.2	GPRS/EGPRS	42
24.2.4.2.1	PDCH resource usage.....	42
24.2.4.2.2	Latency	42
24.2.4.2.4	Failed Attempts	43
24.2.4.2.5	Capacity.....	43
24.2.4.3	EC-GSM-IoT	43
24.2.4.3.1	PDCH resource usage.....	43
24.2.4.3.2	Latency of MAR periodic reports.....	44
24.2.4.3.3	Latency of Downlink Application Ack.....	44
24.2.4.3.3	Failed attempts	44
24.2.4.3.4	Capacity.....	44
24.2.4.3.5	Coverage Class Distribution.....	45
24.3	Conclusion.....	45

Annex A: DCS1800 System scenarios.....47

A.0	INTRODUCTION.....	47
A.1	SCENARIO 1 - SINGLE BTS AND MS.....	47
A.1.1	Constraints.....	47
A.1.1.1	Frequency Bands and Channel Arrangement (Clause 2 of GSM 05.05)	47
A.1.1.2	Proximity	48
A.1.1.3	Range	48
A.1.3	Inputs needed.....	49
A.2	SCENARIO 2 - MULTIPLE MS AND BTS, COORDINATED	49
A.2.1	Constraints.....	49
A.2.3	Inputs needed.....	50
A.3	SCENARIO 3 - MULTIPLE MS AND BTS, UNCOORDINATED.....	51
A.3.1	Constraints.....	51
A.3.3	Inputs needed.....	51
A.4	SCENARIO 4 - COLOCATED MS.....	52
A.4.1	Constraints.....	52
A.4.3	Inputs needed.....	53

A.5	SCENARIO 5 - COLOCATED BTS	53
A.5.1	Constraints.....	53
A.5.3	Inputs needed.....	53
A.6	SCENARIO 6 - COLOCATION WITH OTHER SYSTEMS	54
A.6.1	Constraints.....	54
A.6.3	Inputs needed.....	54
A.7	Title: Justifications for the proposed Rec. 05.05_DCS	55
A.7.1	Transmitter	56
A.7.1.1	Modulation, Spurs and Noise.....	56
A.7.1.1.1	Co-ordinated, BTS -> MS (Scenario 2, figure 2.1)	56
A.7.1.1.2	Uncoordinated, BTS -> MS (Scenario 3, figure 3.1)	56
A.7.1.1.3	Co-ordinated & Uncoordinated MS -> BTS (Scenarios 2 and 3, figures 2.1 and 3.1).....	56
A.7.1.1.4	Co-ordinated & Uncoordinated MS->MS (Scenario 4)	56
A.7.1.1.5	Co-ordinated & Uncoordinated BTS->BTS (Scenario 5)	56
A.7.1.2	Switching Transients.....	56
A.7.1.2.1	Uncoordinated MS -> BTS (Scenario 3, figure 3.1)	56
A.7.1.2.2	Uncoordinated BTS -> MS (Scenario 3, figure 3.1)	56
A.7.1.3	Intermodulation.....	57
A.7.1.3.1	Co-ordinated, BTS -> MS (Scenario 2, figures 2.2 and 2.3).....	57
A.7.1.3.2	Uncoordinated, BTS ->MS (Scenario 3, figure 3.2 top)	57
A.7.1.3.3	Uncoordinated, MS&MS-> BTS (Scenario 4, figure 4.1 bottom)	57
A.7.1.3.4	Uncoordinated MS&MS-> MS (Scenario 4, figure 4.1 top)	57
A.7.2	Receiver.....	57
A.7.2.1	Blocking.....	57
A.7.2.1.1	Co-ordinated & Uncoordinated BTS-> MS (Scenarios 2 and 3, figures 2.1 and 3.1).....	57
A.7.2.1.2	Co-ordinated MS-> BTS (Scenario 2, figure 2.1)	57
A.7.2.1.3	Uncoordinated MS-> BTS (Scenario 3, figure 3.1)	57
A.7.2.1.4	Co-ordinated & Uncoordinated MS-> MS (Scenario 4)	57
A.7.2.1.5	Co-ordinated & Uncoordinated BTS-> BTS (Scenario 5)	57
A.7.2.2	Intermodulation.....	58
A.7.2.2.1	Co-ordinated & Uncoordinated BTS-> MS (Scenarios 2 and 3, figure 3.2 middle)	58
A.7.2.2.2	Co-ordinated MS & MS -> BTS (Scenario 4).....	58
A.7.2.2.3	Uncoordinated MS & MS -> BTS (Scenario 4, figure 3.2 lower).....	58
A.7.2.3	Maximum level	58
A.7.2.3.1	Co-ordinated MS -> BTS (Scenario 1).....	58
A.7.2.3.2	Co-ordinated BTS -> MS (Scenario 1).....	58
A.8.1	SCOPE	58
A.8.2	FREQUENCY BANDS AND CHANNEL ARRANGEMENT	58
A.8.3	REFERENCE CONFIGURATION	58
A.8.4	TRANSMITTER CHARACTERISTICS.....	59
A.8.4.1	Output power	59
A.8.4.1.1	Mobile Station.....	59
A.8.4.1.2	Base Station.....	59
A.8.4.2	Output RF spectrum.....	59
A.8.4.2.1	Spectrum due to the modulation.....	59
A.8.4.2.2	Spectrum due to switching transients.....	60
A.8.4.3	Spurious emissions	60
A.8.4.3.1	Principle of the specification.....	60
A.8.4.3.2	Base Station.....	60
A.8.4.3.3	Mobile Station.....	60
A.8.4.4	Radio frequency tolerance	61
A.8.4.5	Output level dynamic operation.....	61
A.8.4.5.1	Base station	61
A.8.4.5.2	Mobile station:	61
A.8.4.6	Phase accuracy	61
A.8.4.7	Intermodulation attenuation	61
A.8.4.7.1	Base transceiver station.....	61
A.8.4.7.2	Intra BTS intermodulation attenuation.....	61
A.8.4.7.3	Intermodulation between MS	61
A.8.5	RECEIVER CHARACTERISTICS	62

A.8.5.1	Blocking characteristics	62
A.8.5.2	Intermodulation characteristics	63
A.8.5.3	Spurious response rejection	63
A.8.5.4	Spurious emissions	63
A.8.6	TRANSMITTER/RECEIVER PERFORMANCE	63
A.8.6.1	Nominal error rates (NER)	63
A.8.6.2	Reference sensitivity level	63
A.8.6.3	Reference interference level	64
A.8.6.4	Erroneous frame indication performance	64

Annex B: GSM900 Small Cell System scenarios.....65

B.1	Transmitter	66
B.1.1	Modulation, Spurs and Noise	66
B.1.1.1	Co-ordinated, BTS -> MS	66
B.1.1.2	Uncoordinated, BTS -> MS	66
B.1.1.3	Co-ordinated & Uncoordinated MS -> BTS	66
B.1.1.4	Co-ordinated & Uncoordinated MS -> MS	66
B.1.1.5	Co-ordinated & Uncoordinated BTS -> BTS	67
B.1.2	Switching Transients	67
B.1.2.1	Uncoordinated MS -> BTS	67
B.1.2.2	Uncoordinated BTS -> MS	67
B.1.3	Intermodulation	67
B.1.3.1	Coordinated, BTS -> MS	67
B.1.3.2	Uncoordinated, BTS -> MS	67
B.1.3.3	Uncoordinated, MS&MS -> BTS	67
B.1.3.4	Uncoordinated MS&MS -> MS	67
B.2	Receiver	67
B.2.1	Blocking	67
B.2.1.1	Co-ordinated & Uncoordinated BTS -> MS	67
B.2.1.2	Co-ordinated MS -> BTS	67
B.2.1.3	Uncoordinated MS -> BTS	68
B.2.1.4	Co-ordinated & Uncoordinated MS -> MS	68
B.2.1.5	Co-ordinated and Uncoordinated BTS -> BTS	68
B.2.2	Intermodulation	68
B.2.2.1	Co-ordinated & Uncoordinated BTS -> MS	68
B.2.2.2	Co-ordinated MS & MS -> BTS	68
B.2.2.3	Uncoordinated MS & MS -> BTS	68
B.2.3	Maximum level	68
B.2.3.1	Co-ordinated MS -> BTS	68
B.2.3.2	Co-ordinated BTS -> MS	68
B.3.1	Transmitter	69
B.3.1.1	Modulation, Spurs and Noise	69
B.3.1.1.1	Co-ordinated, BTS -> MS	69
B.3.1.1.2	Uncoordinated, BTS -> MS	69
B.3.1.1.3	Co-ordinated & Uncoordinated MS -> BTS	69
B.3.1.1.4	Co-ordinated & Uncoordinated MS -> MS	69
B.3.1.1.5	Co-ordinated & Uncoordinated BTS -> BTS	69
B.3.1.2	Switching Transients	69
B.3.1.2.1	Uncoordinated MS -> BTS	69
B.3.1.2.2	Uncoordinated BTS -> MS	69
B.3.1.3	Intermodulation	70
B.3.1.3.1	Coordinated, BTS -> MS	70
B.3.1.3.2	Uncoordinated, BTS -> MS	70
B.3.1.3.3	Uncoordinated, MS&MS -> BTS	70
B.3.1.3.4	Uncoordinated MS&MS -> MS	70
B.3.2	Receiver	70
B.3.2.1	Blocking	70
B.3.2.1.1	Co-ordinated & Uncoordinated BTS -> MS	70
B.3.2.1.2	Co-ordinated MS -> BTS	70
B.3.2.1.3	Uncoordinated MS -> BTS	70
B.3.2.1.4	Co-ordinated & Uncoordinated MS -> MS	70

B.3.2.1.5	Co-ordinated and Uncoordinated BTS -> BTS	70
B.3.2.2	Intermodulation.....	70
B.3.2.2.1	Co-ordinated & Uncoordinated BTS -> MS	70
B.3.2.2.2	Co-ordinated MS & MS -> BTS	71
B.3.2.2.3	Uncoordinated MS & MS -> BTS.....	71
B.3.2.3	Maximum level.....	71
B.3.2.3.1	Co-ordinated MS -> BTS	71
B.3.2.3.2	Co-ordinated BTS -> MS	71
Annex C:	Microcell System Scenarios.....	72
Annex D:	Conversion factors	85
Annex E:	Repeater Scenarios.....	89
E.1	INTRODUCTION.....	89
E.2	REPEATER APPLICATIONS - OUTDOOR AND INDOOR	89
E.3	OUTDOOR REPEATER SCENARIO	89
E.4	OUTDOOR REPEATER PERFORMANCE Requirements.....	90
E.4.1	Wideband Noise	90
E.4.2	Intermodulation Products and Spurious Emissions	91
E.4.3	Output Power.....	91
E.4.4	Blocking by Uncoordinated BTS	91
E.4.5	Summary of Outdoor Repeater Requirements.....	92
E.5	INDOOR REPEATER SCENARIO	92
E.6	INDOOR REPEATER PERFORMANCE REQUIREMENTS	92
E.6.1	Wideband Noise	92
E.6.2	Intermodulation Products and Spurious Emissions	93
E.6.3	Output Power.....	93
E.6.4	Blocking by Uncoordinated BTS	94
E.6.5	Summary of Indoor Repeater Requirements	94
E.7	Title: Repeater Scenarios.....	95
E.7.1	Introduction	95
E.7.2	Repeater performance.....	95
E.7.2.1	Link Equations	95
E.7.2.2	Co-ordinated Scenario	96
E.7.2.3	Uncoordinated Scenario.....	97
E.7.2.4	Wideband Noise.....	97
E.7.2.5	3rd order Intermodulation (IM3) performance/Spurious emissions:	97
E.7.3	Repeater scenarios	97
E.7.3.1	Rural scenario	98
E.7.3.2	Urban Scenario	98
E.7.4	Summary	99
E.7.4.1	Repeater Specification	99
E.7.4.2	Planning considerations	99
E.7.5	Out of band Gain	100
E.7.6	Planning guidelines for repeaters.....	100
E.7.7	Indoor Repeater Scenario	100
Annex F:	Error Patterns for Speech Coder Development.....	104
F.0	Introduction	104
F.1	Channel Conditions	104
F.1.1	Simulation Conditions	104
F.1.2	Available Error Patterns	104
F.2	Test Data for the half rate speech coder	105
F.2.1	File description.....	105
F.2.2	Soft decision values and chip error patterns	105

F.2.3	Error patterns of corresponding TCH/FS	106
Annex G:	Simulation of Performance	108
G.1	Implementation Losses and Noise Figure	108
G.1.1	Assumed Equalizer.....	108
G.1.2	Accuracy of Simulations	108
G.1.3	Simulation Results.....	108
G.2	Reference Structure	117
G.2.1	Error Concealment	118
G.2.2	Implementation Losses and Noise Figure	118
G.2.3	Assumed Equalizer.....	118
G.2.4	Simulation Results.....	118
G.2.5	Proposed Values for Recommendation GSM 05.05.....	118
G.3	Simulation of performance for AMR	119
G.3.1	System Configuration.....	119
G.3.2	Error Concealment	119
G.3.3	Implementation Losses and Noise Figure	120
G.3.4	Assumed Equalizer.....	120
G.3.5	Simulation Methods	120
G.3.5.1	Simulation for speech	120
G.3.5.2	Simulation for DTX.....	120
G.3.5.3	Simulation for inband channel	120
G.3.6	Remarks to the Data in GSM 05.05.....	121
Annex H:	GSM900 Railway System Scenarios.....	122
H.1	Scope	122
H.1.1	List of some abbreviations.....	122
H.2	Constraints.....	122
H.2.1	GSM based systems in the 900 MHz band.....	122
H.2.2	Other systems	123
H.2.3	UIC systems outline	123
H.2.4	Fixed UIC RF parameters.....	123
H.3	Methodology	123
H.3.1	Scenarios	124
H.3.2	Format of calculations	125
H.3.3	GSM900 systems parameters	125
H.3.4	Minimum Coupling Loss.....	126
H.3.5	Interference margins.....	127
H.3.6	Differences between E- and P-GSM	127
H4	Transmitter requirements	127
H.4.1	Transmitter requirements summary.....	128
H.5	Receiver requirements	128
H.5.1	Receiver requirements summary	129
H.6	Wanted signals levels	129
H.6.1	Maximum wanted signal level.....	130
H.6.2	Dynamic range of wanted signals.....	130
Annex I:	Void	131
Annex J:	GSM900 Railway System Scenarios.....	132
J.1	Introduction	132
J.2	Basic considerations	132
J.2.1	Types of equipment and frequency ranges	132
J.3	Discussion of the individual sections in GSM 05.05	133
J.3.1	Scope	133

J.3.2	Frequency bands and channel arrangement	133
J.3.3	Reference configuration	134
J.3.4	Transmitter characteristics.....	134
J.3.4.1	Output power	134
J.3.4.2	Void	134
J.3.4.2.1	Spectrum due to the modulation and wide band noise	134
J.3.4.2.2a	MS spectrum due to switching transients.....	134
J.3.4.2.2b	BTS spectrum due to switching transients	135
J.3.4.3.1	Spurious emissions.....	135
J.3.4.3.2	BTS spurious emissions	136
J.3.4.3.3	MS spurious emissions.....	136
J.3.4.3.4	MS spurious emissions onto downlinks	137
J.3.4.4	Radio frequency tolerance	138
J.3.4.5	Output level dynamic operation.....	138
J.3.4.5.1	BTS output level dynamic operation.....	138
J.3.4.5.2	MS output level dynamic operation	139
J.3.4.6	Phase accuracy.....	139
J.3.4.7.1	Intra BTS intermod attenuation.....	139
J.3.4.7.2	Intermodulation between MS (DCS1800 only).....	139
J.3.4.7.3	Mobile PBX	139
J.3.5	Receiver characteristics	140
J.3.5.1	Blocking characteristics	140
J.3.5.2	Blocking characteristics (in-band).....	140
J.3.5.3	Blocking characteristics (out-of-band).....	141
J.3.5.4	AM suppression characteristics	141
J.3.5.5	Intermodulation characteristics	141
J.3.5.6	Spurious emissions	141
J.3.6	Transmitter/receiver performance	141
J.3.6.1	Nominal error rates	141
J.3.6.2	Reference sensitivity level	141

Annex K: Block Erasure Rate Performance for GPRS143

K.1	Introduction	143
K.2	Simulation Model.....	143
K.3	Results	143
K.4	Conclusions	144

Annex L: Proposal on how to report GPRS performance into GSM 05.05.....145

L.1	Introduction	145
L.2	GPRS BLER performance.....	145
L.3	GPRS throughput analyses.....	146
L.3.1	TU50 ideal FH.....	147
L.3.2	TU3 no FH	148
L.4	Proposals for GPRS performance in GSM 05.05	148
L.4.1	TU50 ideal FH.....	148
L.4.2	TU3 no FH	149
L.5	Conclusions	149

Annex M: GPRS simulation results in TU 3 and TU 50 no FH.....150

M.1	Introduction	150
M.2	Simulation Model.....	150
M.3	Maximum GPRS throughput.....	152
M.4	Conclusion.....	153

M.5	References	153
Annex N:	C/I_c and E_b/N₀ Radio Performance for the GPRS Coding Schemes.....	154
N.1	Introduction	154
N.2	C/I simulation results.....	154
N.3	E _b /N ₀ performance.....	156
N.4	Conclusions	158
N.5	References	158
Annex O:	Void	159
Annex P:	Block Error Rate and USF Error Rate for GPRS	160
P.1	Introduction	160
P.2	Simulation Assumptions.....	160
P.3	Simulation Results.....	161
P.3.1	Interference Simulations.....	161
P.3.1.1	TU50 Ideal Frequency Hopping	161
P.3.1.2	TU50 No Frequency Hopping	162
P.3.1.3	TU3 Ideal Frequency Hopping	163
P.3.1.4	TU3 No Frequency Hopping	164
P.3.1.5	RA250 No Frequency Hopping	165
P.3.2	Sensitivity Simulations.....	166
P.3.2.1	TU50 Ideal Frequency Hopping	166
P.3.2.2	TU50 No Frequency Hopping	167
P.3.2.3	HT100 No Frequency Hopping	168
P.3.2.4	RA250 No Frequency Hopping	169
P.3.2.5	Static Channel	170
Annex Q:	Block Error Rate and USF Error Rate for GPRS, 1800 MHz.....	171
Q.1	Introduction	171
Q.2	Simulation Assumptions.....	171
Q.3	Simulation Results.....	172
Q.3.1	Interference Simulations, 1 800 MHz.....	172
Q.3.1.2	TU50, Ideal Frequency Hopping	172
Q.3.1.3	TU50 No Frequency Hopping	173
Q.3.2	Sensitivity Simulations, 1800 MHz.....	174
Q.3.2.1	TU50 Ideal Frequency Hopping	174
Q.3.2.2	TU50 No Frequency Hopping	175
Q.3.2.3	HT100 No Frequency Hopping	176
Annex R:	Pico BTS RF Scenarios.....	177
R.1	Introduction	177
R.2	Fixed parameters	177
R.3	Maximum BTS Output Power.....	178
R.4	BTS Receiver Sensitivity	179
R.4.1	Balanced link (zero interference scenario)	179
R.4.2	Interferer at MCL scenario	179
R.4.3	Power control (zero interference scenario).....	180
R.4.4	Sensitivity overview	180
R.5	BTS Power Control Range	180
R.6	BTS Spectrum due to modulation and wideband noise.....	180

R.7	Spurious Emissions	181
R.8	Radio Frequency Tolerance.....	181
R.9	Blocking Characteristics.....	182
R.10	pico- BTS AM suppression characteristics	183
R.10.1	Modulation sidebands.....	184
R.10.1.1	Uncoordinated BTS->MS	184
R.10.1.2	Uncoordinated MS->BTS	184
R.10.2	Switching transients	184
R.10.2.1	Uncoordinated BTS->MS	184
R.10.2.2	Uncoordinated MS->BTS	184
R.10.3	Blocking	185
R.10.3.1	Uncoordinated BTS->MS	185
R.10.3.2	Uncoordinated MS->BTS	185
R.10.4	The AM suppression requirement	185
R.10.4.1	Downlink, BTS->MS.....	185
R.10.4.2	Uplink, MS->BTS.....	185
R.10.4.3	Interference levels.....	186
R.11	intermodulation	186
R.11.1	co-ordinated and uncoordinated BTS -> MS (scenarios 2 & 3, figure 3.2 middle).....	186
R.11.2	coordinated MS&MS -> BTS (scenario 4).....	186
R.11.3	uncoordinated MS&MS -> BTS (scenario 4, figure 3.2 lower)	186
R.11.4	MCL relaxation	187
R.12	Pico BTS TI1.5 performance requirements.....	187
R.12.1	Nominal Error Rates for Pico-BTS	187
R.13	timing and synchronisation	188
R.13.1	Steady state timing advance error.....	188
R.13.2	Conventional BTS	189
R.13.3	Pico-BTS	189
R.13.3.1	Pico-BTS relaxation.....	189
R.13.3.2	MS impact of Pico-BTS relaxation.....	189
Annex S:	CTS system scenarios	191
S.1	Introduction	191
S.1.1	Parameter Set.....	191
S.1.1.1	Transmitter Parameter.....	191
S.1.1.2	Receiver Parameter	192
S.1.1.3	Minimum coupling loss values	192
S.1.1.4	Path loss models	192
S.1.1.5	Margins	193
S.2	Transmitter characteristics	193
S.2.1	Maximum CTS-FP Transmit Power limited by MS blocking.....	193
S.2.2	Maximum CTS-FP Transmit Power limited by Spectrum due to Modulation and WBN	194
S.2.3	Specification of max. CTS-FP Transmit Power and CTS-FP Spectrum due to modulation and wide band noise	195
S.2.3.1	Maximum CTS-FP transmit power.....	195
S.2.3.2	Spectrum due to modulation and wide band noise.....	196
S.2.4	Balanced link for zero interference scenario (Interferer at MCL scenario)	197
S.2.5	Range of Coverage for CTS:	197
S.2.6	Minimum CTS-FP transmit power	198
S.2.7	Power Level Distribution	199
S.2.8	Spurious Emission.....	199
S.3	Receiver characteristics	200
S.3.1	Blocking	200
S.3.2	AM suppression.....	201
S.3.2.1	Spectrum due to modulation	201
S.3.2.2	Switching transients.....	202

S.3.2.3	Blocking.....	203
S.3.2.4	Specification of AM Suppression.....	203
S.3.3	Intermodulation	204
S.3.3.1	uncoordinated CTS-MSs -> GSM-BTS.....	204
S.3.3.2	uncoordinated CTS-FPs -> MS.....	204
S.3.3.3	uncoordinated GSM-MSs -> CTS-FP.....	205
S.4	CTS-FP TI5 performance requirements	205
S.4.1	Nominal Error Rates for the CTS-FP	205
S.5	Conclusion.....	206
Annex T:	GSM400 system scenarios	207
T.0	Introduction	207
T.1	Frequency bands and channel arrangement.....	207
T.2	System Scenario Calculations for GSM400 systems	208
T.2.1	Worst case proximity scenarios.....	208
T.3	Worst Case Scenario Requirements	210
T.3.1	Transmitter	210
T.3.1.1	Modulation, Spurs and noise.....	210
T.3.1.1.1	Co-ordinated BTS -> MS	210
T.3.1.1.2	Uncoordinated BTS -> MS	210
T.3.1.1.3	Coordinated & Uncoordinated MS -> BTS.....	210
T.3.1.1.4	Coordinated & Uncoordinated MS -> MS	210
T.3.1.1.5	Coordinated & Uncoordinated BTS -> BTS	210
T.3.1.2	Switching transients.....	210
T.3.1.2.1	Uncoordinated MS -> BTS	210
T.3.1.2.2	Uncoordinated BTS -> MS	210
T.3.1.3	Intermodulation.....	211
T.3.1.3.1	Coordinated BTS -> MS	211
T.3.1.3.2	Uncoordinated BTS -> MS	211
T.3.1.3.3	Uncoordinated MSs -> BTS.....	211
T.3.1.3.4	Uncoordinated MS & MS -> MS	211
T.3.2	Receiver.....	211
T.3.2.1	Blocking.....	211
T.3.2.1.1	Coordinated & Uncoordinated BTS -> MS.....	211
T.3.2.1.2	Coordinated MS -> BTS	211
T.3.2.1.3	Uncoordinated MS -> BTS	211
T.3.2.1.4	Coordinated & Uncoordinated MS -> MS	211
T.3.2.1.5	Coordinated & Uncoordinated BTS -> BTS	211
T.3.2.2	Intermodulation.....	211
T.3.2.2.1	Coordinated & Uncoordinated BTS -> MS.....	211
T.3.2.2.2	Coordinated MS -> BTS	212
T.3.2.2.3	Uncoordinated MS -> BTS	212
T.3.2.3	Maximum level.....	212
T.3.2.3.1	Coordinated MS -> BTS	212
T.3.2.3.2	Coordinated BTS -> MS	212
T.4	Transmitter characteristics	212
T.4.1	Output power.....	212
T.4.1.1	Mobile Station	212
T.4.1.2	Base Station	212
T.4.2	Output RF Spectrum.....	212
T.4.2.1	Spectrum due to the modulation and wideband noise.....	212
T.4.2.2	Spectrum due to switching transients	213
T.4.3	Spurious emissions	213
T.4.3.1	Principle of the specification	213
T.4.3.2	Base transceiver station	214
T.4.3.3	Mobile station	214
T.4.4	Radio frequency tolerance	214

T.4.5	Output level dynamic operation	214
T.4.5.1	Base station.....	214
T.4.5.2	Mobile station	215
T.4.6	Phase accuracy	215
T.4.7	Intermodulation attenuation.....	215
T.5	Receiver characteristics.....	215
T.5.1	Blocking characteristics	215
T.5.2	AM suppression characteristics.....	217
T.5.3	Intermodulation Characteristics.....	218
T.5.4	Spurious emissions	218
T.6	Receiver performance.....	218
Annex U:	850 MHz and 1 900 MHz Mixed-Mode Scenarios	219
U.1	Introduction	219
U.2	BTS Wide Band Noise and Intra BTS Intermodulation Attenuation	219
U.2.1	Overview	219
U.2.1.1	TIA/EIA-136.....	219
U.2.1.2	ETSI GSM	220
U.2.2	Scenario - Mixed-Mode Multi-Carrier BTS in FCC Regulated Environment.....	220
U.2.3	BTS Wide Band Noise and Intra BTS Intermodulation Attenuation Analysis.....	221
U.3	BTS Blocking and AM Suppression Characteristics.....	223
U.3.1	Overview	223
U.3.1.1	TIA/EIA-136.....	223
U.3.1.2	ETSI GSM	223
U.3.2	Scenario - Mixed-Mode Multiple MS and BTS, Uncoordinated Close Proximity.....	223
U.3.3	Blocking Analysis	224
U.3.3.1	Definition.....	224
U.3.3.2	Calculation.....	224
U.3.4	AM Suppression Analysis	225
Annex V:	LCS scenarios	226
V.1	Introduction	226
V.2	TOA Type A LMU in a Co-Located Deployment	226
V.2.1	Constraints.....	226
V.2.2	Frequency Bands and Channel Arrangement (clause 2 of GSM 05.05).....	226
V.2.3	Proximity for DCS1800/PCS1900	226
V.2.4	Inputs needed.....	227
V.2.5	Conclusion.....	227
V.3	Discussion of TOA LMU RF Specification	227
V.3.1	Introduction	227
V.3.2	Analysis Model	228
V.3.3	Results	228
V.3.4	Conclusions	229
V.4	Simulation results for TOA-LMU performance	229
V.4.1	Introduction and requirements.....	229
V.4.2	Simulation model	232
V.4.3	Assumed TOA estimation algorithm.....	232
V.4.4	Simulation results	233
V.4.4.1	Sensitivity performance	233
V.4.4.2	Interference performance	233
V.4.4.3	Multipath performance	234
V.4.4.4	Positioning Performance	235
V.5	Discussion of RIT measurement performance of TOA LMU	236
V.6	Simulations Results for E-OTD LMUs and E-OTD Capable MSs	237
V.6.1	Introduction	237

V.6.2	E-OTD Measurement Accuracy	237
V.6.2.1	Sensitivity Performance	237
V.6.2.2	Interference Performance	238
V.6.2.3	Multipath performance	240
V.6.3	Location accuracy	241
V.6.3.1	Network parameters	241
V.6.3.2	Simulation results	241
V.7	BTS Frequency Source Stability, E-OTD reporting periods and E-OTD Location Accuracy	242
V.7.1	Factors determining E-OTD stability	242
V.7.2	Relationship between range errors and location error	243

Annex V.A: Evaluation of Positioning Measurement Systems244

1	Introduction	244
2	Positioning Simulator	244
3	System Simulator	245
3.1	Initiation	246
3.2	Path loss calculations	246
3.3	Channel allocation	246
3.4	C and I calculations	246
3.5	Dropping calls with too low C/I	247
3.6	System simulator parameters	247
4	Radio Link Level Simulator	248
5	Channel Model	248
5.1	Channel model requirements	248
5.2	Channel model	248
5.3	Delay spread	249
5.4	Average power delay profile	250
5.5	Matching the delay spread of the channel model to the delay spread model	250
5.6	Short-term fading	250
5.7	Diversity	251
5.8	Limitations	251
5.9	Summary of the channel model	251
6	GSM Adaptation	252
6.1	FIR Filter Implementation	252
6.2	Sampling in Time Domain	253
6.3	Frequency Hopping	253
7	Position Calculation and Statistical Evaluation	253
8	References	254

Annex V.B: Simulations on Co-Existence of EDGE and GSM Modulated Signals.....255

1	Introduction	255
2	Simulations	256
3	Simulation Results	257
4	Conclusions	259

Annex W: Update of GPRS background information260

W.1	Introduction	260
W.2	References	260
W.3	Simulation assumptions	260
W.4	Co-channel interference simulations with varying C/I	261
W.5	Co-channel interference simulations with varying Eb/N0	262

W.6 Effect on the MS receiver Noise Factor	264
W.7 Conclusion.....	265
Annex X: 8-PSK Scenarios.....	266
X.1 Assumptions	266
X.2 Closest Approach	266
X.2.1 Closest Approach, Coordinated.....	266
X.2.1.1 Closest Approach BTS Transmitting, Coordinated	266
X.2.1.1.1 Nominal Error Rate Requirement at High Input Levels.....	266
X.2.1.1.2 MS Receiver Intermodulation Characteristics.....	266
X.2.1.2 Closest Approach MS Transmitting, Coordinated	267
X.2.1.2.1 Nominal Error Rate at High Input Levels	267
X.2.1.2.1.1 GSM900 BTS	267
X.2.1.2.1.2 DCS1800 BTS	268
X.2.1.2.2 BTS Receiver Intermodulation Characteristics	268
X.2.1.3 Minimum Coupling for Coordinated Case.....	269
X.2.1.3.1 Downlink Power Control Enabled	269
X.2.1.3.2 No Downlink Power Control.....	269
X.2.2 Closest Approach, Uncoordinated.....	269
X.2.2.1 Closest Approach BTS Transmitting, Uncoordinated	269
X.2.2.1.1 Noise Masking	269
X.2.2.1.2 MS Receiver Intermodulation Characteristics.....	269
X.2.2.1.3 BTS Tx Inter/Intra Modulation Masking	270
X.2.2.2 Minimum Coupling for Uncoordinated Case.....	270
X.3 Analysis of Specifications.....	270
X.3.1 Scenario 1: Single BTS and MS	270
X.3.1.1 Specifications Affected (GSM 05.05).....	270
X.3.1.2 Maximum Receiver Levels	270
X.3.1.3 Reference Sensitivity Level	270
X.3.1.3.1 Coverage Limit	270
X.3.1.3.2 Link Balance	271
X.3.2 Scenario 2: Multiple MS and BTS, Coordinated.....	271
X.3.2.1 Specifications Affected (GSM 05.05).....	272
X.3.2.2 Adaptive Power Control (GSM 05.05, subclause 4.1).....	272
X.3.2.3 Output RF Spectrum (GSM 05.05, subclause 4.1).....	272
X.3.2.4 Inter/Intra Modulation Attenuation, BTS (GSM 05.05, subclauses 4.7.1 and 4.7.2).....	273
X.3.2.5 Blocking (GSM 05.05, subclause 5.1)	273
X.3.2.6 Reference Interference Level	273
X.3.3 Scenario 3: Multiple MS and BTS, Uncoordinated.....	274
X.3.3.1 Specifications Affected (GSM 05.05).....	274
X.3.3.2 Output RF Spectrum (GSM 05.05, subclause 4.2).....	274
X.3.3.3 Transmit Intermodulation (GSM 05.05, subclause 4.7).....	275
X.3.3.4 Blocking, In-Band Up and Down Links (GSM 05.05, subclause 5.1).....	275
X.3.3.5 BTS Receiver Intermodulation (GSM 05.05, subclause 5.3).....	276
X.4 C/I Limited Coordinated MS and BTS.....	276
X.4.1 N=4/12 Reuse Pattern, Geometric C/I.....	276
X.4.2 N=4/12 Reuse Pattern, C/I CDF	277
X.4.3 Adjacent Channel Interference	278
X.5 BTS Inter and Intra Modulation	278
X.5.1 Simplified Analysis	278
X.5.2 Normal BTS to Normal BTS (Same EIRP).....	280
X.5.3 Normal to Micro (Micro BTS EIRP is 20 dB less than Normal BTS)	282
Annex Y: T-GSM 900 system scenarios	285
Y.0 Introduction	285
Y.1 Frequency bands and channel arrangement.....	285

Y.2	System Scenario Calculations for T-GSM 900 systems.....	285
Y.2.1	Worst case proximity scenarios.....	285
Y.3	Worst Case Scenario Requirements	287
Y.3.1	Transmitter	287
Y.3.1.1	Modulation, Spurs and noise.....	287
Y.3.1.1.1	Co-ordinated BTS -> MS	287
Y.3.1.1.2	Uncoordinated BTS -> MS	287
Y.3.1.1.3	Coordinated & Uncoordinated MS -> BTS.....	288
Y.3.1.1.4	Coordinated & Uncoordinated MS -> MS	288
Y.3.1.1.5	Coordinated & Uncoordinated BTS -> BTS	288
Y.3.1.2	Switching transients.....	288
Y.3.1.2.1	Uncoordinated MS -> BTS	288
Y.3.1.2.2	Uncoordinated BTS -> MS	288
Y.3.1.3	Intermodulation.....	288
Y.3.1.3.1	Coordinated BTS -> MS	288
Y.3.1.3.2	Uncoordinated BTS -> MS	288
Y.3.1.3.3	Uncoordinated MSs -> BTS.....	288
Y.3.1.3.4	Uncoordinated MS & MS -> MS	288
Y.3.2	Receiver.....	289
Y.3.2.1	Blocking.....	289
Y.3.2.1.1	Coordinated & Uncoordinated BTS -> MS.....	289
Y.3.2.1.2	Coordinated MS -> BTS	289
Y.3.2.1.3	Uncoordinated MS -> BTS	289
Y.3.2.1.4	Coordinated & Uncoordinated MS -> MS	289
Y.3.2.1.5	Coordinated & Uncoordinated BTS -> BTS	289
Y.3.2.2	Intermodulation.....	289
Y.3.2.2.1	Coordinated & Uncoordinated BTS -> MS.....	289
Y.3.2.2.2	Coordinated MS -> BTS	289
Y.3.2.2.3	Uncoordinated MS -> BTS	289
Y.3.2.3	Maximum level	290
Y.3.2.3.1	Coordinated MS -> BTS	290
Y.3.2.3.2	Coordinated BTS -> MS	290
Y.4	Transmitter characteristics	290
Y.4.1	Output power.....	290
Y.4.1.1	Mobile Station	290
Y.4.1.2	Base Station	290
Y.4.2	Output RF Spectrum.....	290
Y.4.2.1	Spectrum due to the modulation and wideband noise.....	290
Y.4.2.2	Spectrum due to switching transients	291
Y.4.3	Spurious emissions	291
Y.4.3.1	Principle of the specification	291
Y.4.3.2	Base transceiver station	291
Y.4.3.3	Mobile station	292
Y.4.4	Radio frequency tolerance	292
Y.4.5	Output level dynamic operation	292
Y.4.5.1	Base station.....	292
Y.4.5.2	Mobile station	292
Y.4.6	Phase accuracy	292
Y.4.7	Intermodulation attenuation.....	292
Y.5	Receiver characteristics	293
Y.5.1	Blocking characteristics	293
Y.5.2	AM suppression characteristics.....	294
Y.5.3	Intermodulation Characteristics.....	294
Y.5.4	Spurious emissions	294
Y.6	Receiver performance.....	294
Annex Z:	MBMS system scenarios.....	295
Annex ZA:	T-GSM 810 system scenarios	301

ZA.1	Introduction	301
ZA.2	Coexistence scenario study	302
ZA.2.1	T-GSM 810-iDEN TM	302
ZA.2.1.1	Downlink study.....	302
ZA.2.1.2	Uplink study.....	302
ZA.2.2	T-GSM 810-TETRA	303
ZA.2.2.1	Downlink study.....	303
ZA.2.2.2	Uplink study.....	303
ZA.2.3	T-GSM 810-T-CDMA	304
ZA.2.3.1	Downlink study.....	304
ZA.2.3.2	Uplink study.....	305
ZA.3	Conclusion.....	305
ZA.4	System parameters.....	305
ZA.5	References	306
Annex ZB:	Introduction of multicarrier BTS class.....	307
ZB.1	Introduction	307
ZB.2	Transmitter	307
ZB.2.1	Introduction	307
ZB.2.2	Proposal for relaxation and change	308
ZB.2.2.1	Introduction of MCBTS class 1 and class 2.....	308
ZB.2.2.2	Spectrum due to modulation and wideband noise.....	308
ZB.2.2.3	Spurious emission	308
ZB.2.2.4	BSS Intermodulation attenuation.....	309
ZB.2.3	Simulation results	309
ZB.2.4	Impact to GSM-R due to relaxation	317
ZB.3	Receiver.....	317
ZB.3.1	Proposal for the relaxation.....	317
ZB.3.2	Treatment of receive levels exceeding the new blocking limit.....	318
ZB.3.2.1	Simulation results	318
ZB.3.2.2	Conclusion	320
ZB.3.2.3	Discussion.....	321
Annex ZC:	Introduction of Medium Range and Local Area multicarrier BTS classes	322
ZC.1	Introduction	322
ZC.2	Transmitter	322
ZC.3	Receiver.....	322
ZC.4	References	323
Annex ZD:	ER-GSM band introduction.....	324
ZD.1	Introduction	324
ZD.2	Generalities on Working assumption and methodology	324
ZD.2.1	Evaluation on impacted requirements	324
ZD.2.2	Assumptions	325
ZD.2.2.1	RF performances.....	325
ZD.2.2.2	Blocker rejection by victim public base station	325
ZD.2.2.3	Blocking and Intermodulation reminders	326
ZD.2.2.4	Desensitization computing method.....	326
ZD.2.2.5	Coordinated and uncoordinated deployment	327
ZD.2.2.6	Exception to blocking requirement for ER-GSM mobiles.....	327
ZD.3	Victim receiver performance for lowest frequency offset of ER-GSM interferer.....	327
ZD.3.1	GSM BTS as victim receiver.....	327
ZD.3.2	UTRA/E-UTRA BS as victim receiver	328

ZD.4 Victim receiver performance in the ER-GSM frequency range	328
ZD.4.1 GSM BTS as victim receiver.....	329
ZD.4.2 UTRA/E-UTRA BS as victim receiver	329
ZD.5 Specified requirement based on co-existence analysis.....	329
ZD.5.1 Uncoordinated deployment	330
ZD.5.2 Coordinated deployment	330
ZD.6 References	330
Annex ZE: Extended TSC Sets.....	331
ZE.1 Extended TSC Sets Design.....	331
ZE.1.1 Introduction	331
ZE.1.2 Training Sequence Design.....	331
ZE.1.2.1 Initial Search.....	331
ZE.1.2.2 Building the Cost Function	332
ZE.1.2.2.1 Auto Correlation Cost	332
ZE.1.2.2.2 Cross Correlation Cost	333
ZE.1.2.2.2.1 Basic Principle.....	333
ZE.1.2.2.2.2 Used Model	334
ZE.1.2.3 Performing the search	337
ZE.1.3 Proposed Training Sequence Code Set.....	337
ZE.1.4 Equivalence of rotational approaches	338
ZE.2 Performance framework for design of Extended TSC Sets.....	340
ZE.2.1 Working Assumptions for performance framework	340
ZE.3 Delay statistics for design of Extended TSC Sets	342
ZE.3.1 Background	342
ZE.3.2 Simulations.....	343
ZE.3.2.1 Simulation assumptions	343
ZE.3.2.2 Non-ideal network synchronization.....	343
ZE.3.2.3 Collection of results	344
ZE.3.2.4 Delay distribution	344
ZE.4 NewToN – Performance evaluation	344
ZE.4.1 Introduction	345
ZE.4.2 Impact of co-TSC interference	345
ZE.4.2.1 Introduction.....	345
ZE.4.2.2 System model of co-TSC interference	346
ZE.4.2.2.1 Network configuration.....	346
ZE.4.2.2.2 Interferer strength	347
ZE.4.2.2.3 Co-TSC probability	348
ZE.4.2.3 Link level simulations.....	349
ZE.4.2.3.1 Interference model	349
ZE.4.2.3.2 Other simulation parameters.....	350
ZE.4.2.3.3 Results and discussion	350
ZE.4.3 System level simulations	350
ZE.4.3.1 Introduction.....	350
ZE.4.3.2 Simulation assumptions	351
ZE.4.3.3 Results – non-VAMOS	351
ZE.4.3.4 Results – VAMOS	352
ZE.4.4 Performance comparison according to NewToN framework	353
ZE.4.5 Conclusions	354
ZE.4.6: Performance comparison according to NewToN performance framework	355
ZE.4.7 Detailed link level performance	356
Annex ZF: Machine-type-communication (MTC) deployment, including EC-GSM-IoT, in a reduced BCCH spectrum allocation.....	357
ZF.1 Common simulation assumption framework.....	357
ZF.1.1 Tdoc reference.....	357
ZF.1.2 Working assumptions for network simulations	358

ZF.2 Simulator for Network synchronization evaluation	359
ZF.2.1 Tdoc reference	359
ZF.2.2 Introduction	359
ZF.2.3 Simulator description	360
ZF.2.3.1 General.....	360
ZF.2.3.2 Network configuration and plan	360
ZF.2.3.3 Mapping and timing of logical channels.....	361
ZF.2.3.4 Relevant range of coupling loss.....	361
ZF.2.3.5 Realistic interference model	361
ZF.2.3.6 Receiver model	364
ZF.2.4 Discussion and conclusions.....	365
ZF.3 Simulator for Common control channel evaluation	365
ZF.3.1 Tdoc reference.....	365
ZF.3.2 General	366
ZF.3.3 Minimizing execution time.....	366
ZF.3.3.1 General.....	366
ZF.3.3.2 Interferers.....	366
ZF.3.3.2.1 Interferer types	366
ZF.3.3.2.2 Minimum number of interferers.....	366
ZF.3.3.2.3 Requirement on modeled energy level.....	367
ZF.3.3.2.4 Conservation of energy	367
ZF.3.3.3 Oversampling.....	367
ZF.3.3.4 Pre-generation of bursts	367
ZF.3.3.5 Verification.....	367
ZF.3.3.5.1 General	367
ZF.3.3.5.2 Sensitivity limited performance	368
ZF.3.3.5.3 Interference limited performance	368
ZF.4 Simulator for Data traffic and control channel performance.....	369
ZF.4.1 Tdoc reference.....	369
ZF.4.2 Model	369
ZF.4.2.1 General.....	369
ZF.4.2.2 Mapping tables.....	370
ZF.4.2.2.1 First stage mapping (SINR → BER).....	370
ZF.4.2.2.2 Second stage mapping (BER → BLEP).....	370
ZF.4.2.2.3 Mapping choice.....	370
ZF.4.2.3 SINR handling	371
ZF.4.2.3.1 Blind repetition	371
ZF.4.2.3.2 MRC (uplink only).....	372
ZF.4.3 Verification.....	372
ZF.4.3.1 Sensitivity	372
ZF.4.3.2 Multi-interference (DTS-2).....	373
ZF.5 Results for Network synchronization evaluation	373
ZF.5.1 GPRS/EGPRS	373
ZF.5.1.0 Tdoc reference	373
ZF.5.1.1 Simulator configuration	374
ZF.5.1.2 Results	374
ZF.5.1.3 Discussion and conclusions	377
ZF.5.2 EC-GSM-IoT.....	377
ZF.5.2.1 Tdoc reference	377
ZF.5.2.2 Simulator configuration	377
ZF.5.2.3 Results	377
ZF.5.2.4 Conclusions.....	380
ZF.6 Results for Common control channel evaluation	380
ZF.6.1 GPRS/EGPRS	380
ZF.6.1.1 Tdoc reference	380
ZF.6.1.2 Assumptions	380
ZF.6.1.2.1 General	380
ZF.6.1.2.2 Network synchronization	380
ZF.6.1.2.3 BCCH Power Savings	380

ZF.6.1.3.4	Frequency planning	380
ZF.6.1.4	Simulations	381
ZF.6.1.4.1	Simulation assumptions	381
ZF.6.1.4.1.1	System parameters.....	381
ZF.6.1.5	Results	381
ZF.6.1.5.1	Resource Usage.....	381
ZF.6.1.5.2	Common control channel delay.....	382
ZF.6.1.5.3	Failed Attempts	382
ZF.6.1.6	Discussion.....	382
ZF.6.1.7	Conclusions.....	382
ZF.6.2	EC-GSM-IoT.....	382
ZF.6.2.1	Tdoc reference	382
ZF.6.2.2	Assumptions	383
ZF.6.2.2.1	Link model	383
ZF.6.2.2.2	Blind transmissions	383
ZF.6.2.2.3	Network synchronization	383
ZF.6.2.2.4	Coverage class adaptation	383
ZF.6.2.2.5	BCCH Power Savings	383
ZF.6.2.2.6	Frequency planning	383
ZF.6.2.3	Simulations	383
ZF.6.2.3.1	Simulation assumptions	383
ZF.6.2.3.2	System parameters	384
ZF.6.2.4	Results	384
ZF.6.2.4.1	General	384
ZF.6.2.4.2	Resource Usage	384
ZF.6.2.4.3	Common control channel delay.....	386
ZF.6.2.4.4	Failed Attempts	386
ZF.6.2.4.5	Coverage class distribution	386
ZF.6.2.5	Discussion.....	387
ZF.6.2.6	Conclusions.....	387
ZF.7	Results for Data traffic and control channel evaluation	387
ZF.7.1	GPRS/EGPRS	387
ZF.7.1.1	Tdoc reference	387
ZF.7.1.2	Assumptions	387
ZF.7.1.2.1	Traffic generation.....	387
ZF.7.1.2.2	RACH interference.....	387
ZF.7.1.2.3	BCCH Power Savings	388
ZF.7.1.3	Simulations	388
ZF.7.1.3.1	Simulation assumptions	388
ZF.7.1.3.1.1	System parameters.....	389
ZF.7.1.3.1.2	Cell selection and coding scheme selection.....	389
ZF.7.1.3.1.3	Control signaling	389
ZF.7.1.3.1.4	Simulated scenarios	390
ZF.7.1.3.2	Results.....	390
ZF.7.1.3.2.1	Time Slot Usage	390
ZF.7.1.3.2.2	Latency of Uplink Transmissions	391
ZF.7.1.3.2.3	Latency of Downlink Transmissions	391
ZF.7.1.3.2.4	Failed Attempts	392
ZF.7.1.3.2.5	Capacity	392
ZF.7.1.4	Discussion and conclusions	392
ZF.7.2	EC-GSM-IoT.....	392
ZF.7.2.1	Assumptions	392
ZF.7.2.1.1	Traffic generation.....	392
ZF.7.2.1.2	EC-RACH interference	393
ZF.7.2.1.3	BCCH Power Savings	393
ZF.7.2.1.4	Uplink Power Backoff.....	393
ZF.7.2.2	Simulations	393
ZF.7.2.2.1	Simulation assumptions	393
ZF.7.2.2.1.1	System parameters.....	394
ZF.7.2.2.1.2	Cell selection and uplink coverage class selection	394
ZF.7.2.2.1.3	Downlink coverage class selection and coding scheme selection	395

ZF.7.2.2.1.4	Control signaling	395
ZF.7.2.2.1.5	Simulated scenarios	395
ZF.7.2.2.2	Results	395
ZF.7.2.2.2.1	TS Usage	396
ZF.7.2.2.2.2	Latency of MAR periodic reports	397
ZF.7.2.2.2.3	Latency of Downlink Application Ack	397
ZF.7.2.2.2.4	Failed Attempts	397
ZF.7.2.2.2.5	Capacity	397
ZF.7.2.2.3	DL and UL Coverage Class Distribution	398
ZF.7.2.3	Discussion and conclusions	399
ZF.7.2.3.1	Impact from frequency re-use	399
ZF.7.2.3.2	SINR vs carrier based measurements	399
ZF.7.2.3.2.1	General	399
ZF.7.2.3.2.2	Coverage class distribution	399
ZF.7.2.3.2.3	BLER	400
ZF.7.2.4	Conclusion	401
ZF.8	Traffic model for legacy GPRS MTC	401
ZF.8.1	Tdoc reference	401
ZF.8.2	Legacy GRPS MTC uses cases and scenarios	401
ZF.8.3	Aggregated traffic model of MTC over Legacy GPRS	402
ZF.9	Simulator model for wanted signal level and SINR estimation error	403
ZF.9.1	Tdoc reference	403
ZF.9.2	Model	403
ZF.9.3	Noise-limited case	404
ZF.9.4	Interference-limited case	405
ZF.9.5	Discussion and conclusions	406
Annex ZG:	Change history	407
History	408	

Foreword

This Technical Report has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

1.1 General

The present document gives background information on how the RF requirements of GSM400, GSM900 and DCS 1800 systems have been derived.

1.2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- | | |
|-----|--|
| [1] | 3GPP TR 45.820, 'Cellular System Support for Ultra Low Complexity and Low Throughput Internet of Things' |
| [2] | 3GPP TS 45.001, 'Physical layer on the radio path;General description' |
| [3] | 3GPP TS 45.003, 'Channel coding' |
| [4] | 3GPP TS 45.004, 'Modulation' |

2 Information available

The present document collects together temporary documents of ETSI SMG and STC SMG2 and 3GPP GERAN which can be seen as base line material for the RF requirements in GSM 05.05. The documents are divided into several clauses

In each clause there is a short description of the documents. The documents themselves are annexed to this report.

A list of phase 2 change requests to SMG2 related documents are annexed to the SMG meeting reports.

3 DCS1800 system scenarios

There are two documents describing the basis of the DCS1800 RF requirements. They are:

- DCS1800 System scenarios (TDoc SMG 259/90, reproduced as TDoc SMG 60/91).
- Justifications for the DCS1800 05.05 (TDoc SMG 260/90, revised as TDoc SMG 60/91)).

These documents have been derived first by the UK PCN operators and later by GSM2 ad hoc group working on DCS 1800 requirements during 1990. The documents were presented to TC SMG in October 1990.

DCS1800 System Scenarios describes six scenarios which are considered to be the relevant cases for DCS1800. The six scenarios described are:

- Single MS - Single BTS.
- Multiple MSs - Multiple co-ordinated BTSSs.