

ETSI TS 101 270-2 V1.2.1 (2003-07)

Technical Specification

Transmission and Multiplexing (TM); Access transmission systems on metallic access cables; Very High Speed Digital Subscriber Line (VDSL); Part 2: Transceiver specification



Reference

RTS/TM-06023

Keywords

access, ATM, B-ISDN, IP, network, transmission,
VDSL, XDSL

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2003.
All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members.
TIPHONTM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	9
Foreword.....	9
1 Scope	9
2 References	10
3 Definitions and abbreviations.....	10
3.1 Definitions	10
3.2 Abbreviations	12
4 Reference models	14
4.1 Interface model.....	14
4.2 Protocol model	14
4.2.1 Protocol layer model.....	14
4.2.2 Functional decomposition.....	14
4.3 Reference points	15
4.3.1 V reference point	15
4.3.2 U reference points.....	15
4.3.3 S and T reference points	15
4.4 Deployment configurations	15
5 Physical Medium Dependent (PMD) layer	17
5.1 Multi-carrier PMD sub-layer specification.....	17
5.1.1 PMD functional model.....	17
5.1.2 VTU-O and VTU-R functional characteristics	18
5.1.2.1 Modulation	18
5.1.2.1.1 Sub-carriers	18
5.1.2.1.2 Data sub-carriers.....	18
5.1.2.1.3 Modulation by the Inverse Discrete Fourier Transform (IDFT).....	18
5.1.2.2 Cyclic extension.....	18
5.1.2.3 Synchronisation.....	19
5.1.2.3.1 Pilot tone.....	19
5.1.2.3.2 Loop timing	20
5.1.2.3.3 Timing advance	20
5.1.2.3.4 Synchronous mode (optional).....	20
5.1.2.4 Power back-off in the upstream direction	20
5.1.2.5 Constellation encoder.....	20
5.1.2.5.1 Even values of b	21
5.1.2.5.2 Odd values of b , $b = 1$ or $b = 3$	21
5.1.2.5.3 Odd values of b , $b > 3$	22
5.1.2.6 Gain scaling.....	23
5.1.2.7 Tone ordering.....	23
5.1.2.8 U_1 -interface characteristics	24
5.1.2.8.1 Egress	24
5.1.2.8.2 Power Spectral Density of all signals	24
5.1.2.8.3 Wideband launch power	24
5.2 Single carrier PMD sub-layer specification.....	24
5.2.1 Basic principles.....	24
5.2.1.1 Functional model.....	24
5.2.1.2 Timing.....	25
5.2.2 Transmit functionality.....	25
5.2.2.1 Frame splitting	25
5.2.2.2 Coding and modulation.....	27
5.2.2.2.1 Constellation encoder	27
5.2.2.2.2 Modulator	31
5.2.2.3 Carrier spectral shaping.....	32
5.2.3 Receive functionality	33

5.2.4	Interface specification.....	34
5.2.4.1	I-interface.....	34
5.2.4.2	U1-interface (Transmission Media Interface).....	34
5.2.4.2.1	Transmit signal power.....	34
5.2.4.2.2	Transmit signal Power Spectral Density.....	34
5.2.4.2.3	Transmit PSD control.....	34
5.2.4.2.4	Return Loss.....	35
5.2.4.2.5	Output Signal Balance (OSB).....	35
5.2.5	Transmission profiles.....	36
5.2.5.1	Transmission profile specification.....	36
5.2.5.1.1	Profile code.....	36
5.2.5.1.2	Bit Rates.....	36
5.2.5.1.3	Spectral allocation of the Transmit Signal.....	37
5.2.5.2	Standard Transmission Profiles.....	37
5.2.5.2.1	Standard Transmission Profiles - VDSL Band Allocation.....	38
5.2.5.2.2	Standard Transmission Profiles - Optional Regional Specific Band Allocation.....	39
6	Transmission Convergence (TC) layer.....	40
6.1	TC layer functionality.....	40
6.1.1	Generic functional model.....	40
6.1.2	ATM transport.....	42
6.1.2.1	Functional model of ATM transport.....	42
6.1.2.2	Transport of ATM data.....	42
6.1.3	STM transport.....	43
6.1.3.1	Functional model of STM transport.....	43
6.1.3.2	Transport of STM data.....	43
6.1.4	Packets Transport Mode (PTM).....	44
6.1.4.1	Functional Model of PTM transport.....	44
6.1.4.2	Transport of PTM Data.....	44
6.1.5	Network timing reference transport.....	45
6.2	Transport Protocol Specific TC (TPS-TC) sub-layer.....	45
6.2.1	ATM Transport Protocol Specific TC (ATM_TC).....	45
6.2.1.1	Application interface description.....	45
6.2.1.1.1	Data flow.....	45
6.2.1.1.2	Synchronisation flow.....	46
6.2.1.1.3	Control flow.....	46
6.2.1.1.4	OAM flow.....	47
6.2.1.2	ATM_TC functionality.....	47
6.2.1.2.1	Cell rate de-coupling.....	47
6.2.1.2.2	HEC generation and verification.....	47
6.2.1.2.3	Cell payload randomisation and de-randomisation.....	47
6.2.1.2.4	Cell delineation.....	48
6.2.2	SDH Transport Protocol Specific TC (SDH_TC).....	48
6.2.2.1	Application interface description.....	48
6.2.2.1.1	Data flow.....	48
6.2.2.1.2	Synchronisation flow.....	48
6.2.2.1.3	OAM flow.....	48
6.2.2.2	SDH TPS-TC functionality.....	49
6.2.3	Overhead channel TPS-TC (OC_TC).....	49
6.2.3.1	Application interface description.....	49
6.2.3.1.1	Data flow.....	49
6.2.3.1.2	Synchronisation flow.....	49
6.2.3.2	Single Carrier OC_TC functionality.....	49
6.2.3.2.1	VOC and eoc multiplexing.....	50
6.2.3.2.2	De-multiplexing.....	50
6.2.4	PTM transport protocol specific TC (PTM-TC).....	50
6.2.4.1	Application Interface Description.....	50
6.2.4.1.1	Data Flow.....	51
6.2.4.1.2	Synchronization Flow.....	51
6.2.4.1.3	Control Flow.....	51
6.2.4.1.4	OAM Flow.....	52
6.2.4.2	PTM TPS-TC Functionality.....	52

6.2.4.2.1	Packet encapsulation	52
6.2.4.2.2	Frame structure	52
6.2.4.2.3	Octet transparency	53
6.2.4.2.4	Frame Check Sequence (FCS)	54
6.2.4.2.5	Packet error monitoring	54
6.2.4.3	Data rate decoupling	55
6.2.4.4	Frame delineation	55
6.3	Physical Medium-Specific TC (PMS-TC) sub-layer	55
6.3.1	Functional model	55
6.3.2	Interface specification	56
6.3.2.1	$\alpha(\beta)$ - Interface	56
6.3.2.1.1	Data flow	56
6.3.2.1.2	Synchronisation flow	56
6.3.2.1.3	OAM flow	57
6.3.2.2	I-Interface	57
6.3.2.2.1	Data flow	57
6.3.2.2.2	Synchronisation flow	58
6.4	PMS-TC functions for multi-carrier modulation	58
6.4.1	Scrambler	59
6.4.2	Forward error correction	59
6.4.3	Interleaving	59
6.4.3.1	General	59
6.4.3.2	Triangular implementation	60
6.4.4	Framing	60
6.4.4.1	Frame description	60
6.4.4.2	Payload adaptation	61
6.4.4.3	Reed-Solomon encoding	62
6.4.4.4	Superframe description and contents of fast and slow octets	63
6.4.4.4.1	Cyclic redundancy check	63
6.4.4.4.2	Synchronisation octet	63
6.4.4.4.3	Indicator bits (IB)	64
6.4.4.4.4	Network Timing Reference (NTR)	64
6.4.4.5	Convergence of fast and interleaved buffers	65
6.5	PMS-TC for single carrier modulation	65
6.5.1	Transmission frame format	65
6.5.1.1	Fast codeword structure	66
6.5.1.2	Slow codeword structure	66
6.5.1.3	Frame header octet definition	67
6.5.1.3.1	Syncword octets	67
6.5.1.3.2	Control 1 octet	68
6.5.1.3.3	Control 2 octet	68
6.5.1.3.4	Control 3 octet	69
6.5.1.3.5	CRC-bits	69
6.5.1.3.6	NTR transport and NTR marker generation	69
6.5.1.4	Frame transport classes	69
6.5.1.5	Frame delineation algorithm	70
6.5.2	Data randomisation and de-randomisation	70
6.5.3	Forward error correction	70
6.5.4	Interleaving	71
7	Operations and maintenance	72
7.1	OAM reference model	72
7.1.1	OAM framework	72
7.1.2	Components of the OAM framework	72
7.1.3	OAM functionality	73
7.1.4	Fault and performance monitoring process	74
7.2	OAM entities	75
7.2.1	OAM functional model	75
7.2.2	OAM communication channels	76
7.2.2.1	Indicator Bits (IB)	77
7.2.2.2	VDSL Overhead Control (VOC)	77
7.2.2.3	Embedded operation channel (eoc)	77

7.2.3	Partitioning of OAM data	78
7.3	OAM primitives and parameters	78
7.3.1	Line-related primitives.....	78
7.3.1.1	Near-end anomalies.....	79
7.3.1.2	Far-end anomalies	79
7.3.1.3	Near-end defects	79
7.3.1.4	Far-end defects	79
7.3.1.5	Near-end failures.....	80
7.3.1.6	Far-end failures	80
7.3.2	Path-related primitives.....	80
7.3.2.1	Anomalies, defects and failures for ATM transport.....	80
7.3.2.1.1	Near-end anomalies	81
7.3.2.1.2	Far-end anomalies	81
7.3.2.1.3	Near-end defects	81
7.3.2.1.4	Far-end defects	81
7.3.2.1.5	Near-end failures	81
7.3.2.1.6	Far-end failures.....	82
7.3.2.2	Anomalies, defects and failures for STM transport.....	82
7.3.3	Power-related primitives.....	82
7.3.3.1	Near-end primitives.....	82
7.3.3.2	Far-end primitives	82
7.3.4	Far-end indicators	83
7.3.5	Performance parameters	83
7.3.5.1	Defect and failure counters	83
7.3.5.2	Line-related performance parameters.....	83
7.3.5.3	Path-related performance parameters.....	83
7.3.5.3.1	ATM path-related performance parameters.....	84
7.3.5.3.2	SDH path-related performance parameters.....	84
7.3.6	Test parameters	84
7.3.6.1	Near-end test parameters.....	84
7.3.6.2	Far-end test parameters	84
7.3.6.3	Self-test results	84
7.4	Multi-carrier VDSL overhead channel (VOC).....	84
7.4.1	VOC bandwidth.....	84
7.4.2	VOC protocol.....	85
7.4.3	High-level on-line adaptation	85
7.4.3.1	Bit-swapping	85
7.4.3.2	Bit-swap channel.....	85
7.4.3.3	Bit-swap co-ordination.....	85
7.4.3.4	Bit-swap request.....	85
7.4.3.5	Bit-swap acknowledge	86
7.4.3.6	Bit-swap - Receiver.....	86
7.4.3.7	Bit-swap - Transmitter	87
7.4.3.8	Express swapping.....	87
7.4.3.9	Express swap request	87
7.4.4	Dynamic rate adaptation	88
7.5	Single carrier VDSL overhead control (VOC) channel.....	88
7.5.1	VOC message types	88
7.5.2	VOC message transport	88
7.5.2.1	VOC handshake	89
7.5.2.2	VOC handshake flow charts.....	89
7.5.2.3	Multiple word communication	91
7.5.3	VOC message set.....	91
7.5.3.1	Status messages.....	91
7.5.3.2	Performance-monitoring messages	92
7.5.3.3	Configuration messages	93
7.5.3.3.1	Parameter setting messages	94
7.5.3.3.2	Trigger messages.....	96
7.5.3.4	Control messages	97
7.6	VDSL embedded operations channel (eoc).....	98
7.6.1	eoc functional model.....	99
7.6.2	VME functionality	99

7.6.3	eoc protocol format	100
7.6.3.1	External message format	100
7.6.3.2	Internal message format	100
7.6.3.3	eoc organisation and message types	100
7.6.3.3.1	<i>eoc</i> message structure	101
7.6.3.3.2	eoc Message Set	102
7.6.3.3.3	Bi-directional <i>eoc</i> messages	103
7.6.3.3.4	Downstream messages	103
7.6.3.3.5	Upstream messages	104
7.6.3.4	VTU-R Data Registers	104
7.6.3.5	eoc protocol states	105
7.6.3.5.1	Message/echo-response protocol state (idle state)	105
7.6.3.5.2	Message/unable-to-comply response protocol state (UTC state)	105
7.6.3.5.3	Message/data-response protocol state	105
7.7	Single carrier specific OAM objects	106
7.7.1	Line related primitives	106
7.7.1.1	Near-end defects	106
7.7.1.2	Far-end defects	106
7.7.2	VTU-R configuration register	107
7.7.3	VTU-R performance registers	108
7.7.4	VTU transmit filter register	108
8	Link activation and de-activation	109
8.1	Link state and timing diagram	109
8.1.1	Overview	109
8.1.2	Activation procedures	109
8.1.2.1	Cold start	109
8.1.2.3	Warm start	110
8.1.2.4	Resume on error	110
8.1.2.5	Warm resume	110
8.1.3	Steady-state transmission	110
8.1.4	De-activation procedures	110
8.1.4.1	Introduction	110
8.1.4.2	Void	110
8.1.4.3	Power-down procedure	110
8.1.4.4	Hot resume procedure	110
8.1.5	De-activated power-saving state	111
8.1.6	Power-down state	111
8.1.7	Dynamic power-save state	111
8.2	Multi-carrier activation/de-activation	111
8.2.1	Overview	111
8.2.2	SOC protocol	112
8.2.2.1	Message Format	112
8.2.2.2	O/R IDLE	112
8.2.2.3	O/R REPEAT_REQUEST	112
8.2.2.4	Message codes	113
8.2.2.5	Message fields	113
8.2.2.6	Segmentation of messages	113
8.2.3	Handshake procedure	114
8.2.3.1	Message coding format	114
8.2.3.1.1	Identification field (I)	114
8.2.3.1.2	Standard information field (S)	115
8.2.3.2	Handshake procedures and Message field settings	116
8.2.3.2.1	Handshake - VTU-O	116
8.2.3.2.2	Handshake - VTU-R	117
8.2.4	Training state	120
8.2.4.1	Sequence of messages and symbols during training	120
8.2.4.2	Messages and symbols sent by the VTU-O	121
8.2.4.2.1	SOC messages	121
8.2.4.2.2	Symbol types transmitted by the VTU-O	123
8.2.4.3	Messages and symbols sent by the VTU-R	124
8.2.4.3.1	SOC messages	124

8.2.4.3.2	Symbol types transmitted by the VTU-R	125
8.2.5	Echo canceller training state (optional)	126
8.2.6	Channel analysis and exchange	127
8.2.6.1	Sequence of messages and symbols during channel analysis and exchange	127
8.2.6.2	Messages and symbols send by the VTU-O	128
8.2.6.2.1	SOC messages	128
8.2.6.2.2	Symbol types transmitted by the VTU-O	131
8.2.6.3	Messages and symbols sent by the VTU-R	131
8.2.6.3.1	SOC messages	131
8.2.6.3.2	Symbol types transmitted by the VTU-R	134
8.3	Single carrier activation/deactivation	135
8.3.1	Link states and timing	135
8.3.1.1	States	135
8.3.1.2	Activation	136
8.3.1.3	De-activation	136
8.3.2	Set of transmission parameters	137
8.3.2.1	Current STP	137
8.3.2.2	Standard STPs	137
8.3.3	Transmission parameters modification	138
8.3.3.1	Adjustment of standard STP values	138
8.3.3.2	CR_STP adjustment	138
8.3.3.3	STP adjustment summary	139
8.3.4	VTU activation/deactivation	140
8.3.5	Control signals	140
8.3.6	Flags and indicators	141
8.3.7	Transmit signals	141
8.3.8	Timers	142
8.3.9	VTU-O state machine	143
8.3.10	VTU-R state machine	146
8.3.11	Two-step activation	149
Annex A (informative):	UTOPIA Implementation of the ATM-TC Interface	150
Annex B (informative):	TC Example Algorithms	152
B.1	Frame Delineation Algorithm	152
B.2	Convolutional Interleaver	152
B.2.1	Implementation Example	152
B.2.2	Interleaving Parameters - Example	153
Annex C (informative):	Provisional handshake parameters	154
Annex D (informative):	MCM Duplexing	155
D.1	Introduction	155
D.2	MCM duplexing technique	155
D.2.1	Cyclic Suffix (CS)	155
D.2.2	Timing Advance (TA)	156
D.3	Synchronous versus asynchronous operation	156
Annex E (informative):	Bibliography	157
History	158

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Transmission and Multiplexing (TM).

The present document is part 2 of a multi-part deliverable covering the Transmission and Multiplexing (TM); Access transmission systems on metallic access cables; Very High Speed Digital Subscriber Line (VDSL), as identified below:

Part 1: "Functional requirements";

Part 2: "Transceiver specification issue 2".

1 Scope

The present document specifies requirements for transceivers that provide very high bit-rate digital transmission on metallic, unshielded, access network wire pairs. The technology is referred to as Very high speed Digital Subscriber Line (VDSL).

This present document is part 2 of the specification for VDSL and is applicable to metallic access transmission systems designed to provide multi-megabit/s digital access over part of the existing, unshielded, metallic access network. It is concerned with the specification of the line-code and duplex method which enable the requirements stated in TS 101 270-1 to be met.

The present document allows the VDSL transceiver to be implemented using either Single Carrier or Multi-Carrier modulation schemes.