

American National Standard

ASSE 1060-2017(R2021)



Performance Requirements for
**Outdoor Enclosures for
Fluid Conveying Components**

ASSE Board Approved: April 2021

ANSI Approved: September 2021

ICS Codes: 23 060 99



General Information

Neither this standard, nor any portion thereof, may be reproduced without the written consent of ASSE International.

No product may be said to be listed by ASSE International unless the manufacturer has applied to ASSE International, has had its product tested according to the applicable standards, and when the product has passed the tests, displays the ASSE Seal on the product.

Instructions for receiving the authorization to display the seal are available from the ASSE International Office. Organizations wishing to adopt or list any ASSE International standard should print the ASSE International standard number on the cover page first and in equal or larger type to that of the adopting or listing organization.

ASSE International
Mokena, Illinois
Copyright © 2021, 2017, 2006, 1996
All rights reserved.

Foreword

This foreword shall not be considered a part of the standard; however, it is offered to provide background information.

ASSE International standards are developed in the interest of consumer safety.

This standard focuses on devices that provide a range of protection for fluid conveying components that are mounted outside and above ground so that they may avoid damage from freezing, vandalism, and tampering.

The title and scope of this standard was changed during the 2005 revision to, *Performance Requirements for Outdoor Enclosures for Fluid Conveying Components*. Fluid conveying components include backflow prevention assemblies and devices, water meters, control valves, pressure reducing valves, air release valves, pumps, and other components installed outdoors and above ground that require protection from freezing, or require system security protection.

Class I and I-V enclosures provide equal or greater protection than Class II or II-V enclosures, or Class III or III-V enclosures. Class II and II-V enclosures provide an equal or greater protection than Class III or III-V enclosures.

Recognition is made of the time volunteered by members of this working group and of the support of manufacturers, who also participated in developing this standard.

This standard does not imply ASSE International's endorsement of a product that conforms to these requirements.

Compliance with this standard does not imply acceptance by any code body.

It is recommended that enclosures be installed consistent with local codes by qualified and trained professionals.

This standard was promulgated in accordance with procedures developed by ASSE International and approved by the American National Standards Institute (ANSI).

2021 Product Standards Committee

Tsan-Liang Su, PhD, Chairperson

*Stevens Institute of Technology
Hoboken, NJ*

Karl Abrahamson

*Saint Paul Department of Safety
and Inspections
Cottage Grove, MN*

Brian Andersen

*Plumbers' JAC LU130
Chicago, IL*

William Briggs Jr.

*TSF Engineering
New York, NY*

Terry Burger (non-voting)

*ASSE International
Cleveland, OH*

William Chapin

*Professional Code Consulting, LLC
Cullman, AL*

Mark E. Fish

*Zurn Industries, LLC
Cary, NC*

Ron George

*Plumb-Tech Design & Consulting Services LLC
Newport, MI*

Mark Gibeault

*Kohler Company
Kohler, WI*

Daniel Gleiberman

*Sloan Valve Company
Los Angeles, CA*

Brandon Gunnell

*Precision Plumbing Products
Portland, OR*

Chris Haldiman

*Watts Water Technologies
Springfield, MO*

John F. Higdon, P.E.

*Supply Source Products
Matthews, NC*

Jim Kendzel

*American Supply Association
Minneapolis, MN*

Ramiro Mata

*ASPE
Mentor, OH*

Bob Neff

*Delta Faucet
Pendleton, IN*

David Orton

*NSF International
Ann Arbor, MI*

Thomas Pitcherello

*State of New Jersey
Bordentown, NJ*

Daniel Rademacher

*Viega, LLC
Butte, MT*

Shabbir Rawalpindiwala

*Kohler Company
Kohler, WI*

Billy Smith

*ASPE
Montgomery, AL*

Chris White (non-voting)

*ASSE International
Mokena, IL*

1060 Working Group (2017)

Conrad L. Jahrling, Chairperson

*ASSE International
Chicago, IL*

Sonny Griffin

*G & C Enclosures
Mount Juliet, TN*

Al Adams

*Safe-T-Cover
Nashville, TN*

Gerald Pruitt

*Safe-T-Cover
Nashville, TN*

Craig Birchfield

*BF Products
Charlotte, NC*

Eric Slater

*Hubbell
Lenoir City, TN*

Ronnie Cox

*Aquashield Enclosures
N Little Rock, AR*

Tony Zhao

*IAPMO EGS
Ontario, CA*

Table of Contents

Section I	1
1.0 General	1
1.1 Application	1
1.2 Scope	1
1.3 Free Span Structural Design	2
1.4 Design Type	3
1.5 Reference Standards	3
Section II	4
2.0 Test Specimens	4
2.1 Samples Submitted for Test	4
2.2 Drawings and Technical Data (All Classes).....	4
Section III	6
3.0 Performance Requirements and Compliance Testing	6
3.1 Air Vent Requirement (Class I-V, II-V and III-V)	6
3.2 Structural Test (All Classes)	6
3.3 Access for Testing and Maintenance (All Classes)	7
Figure 1 – Access Opening for Handling Internal Components	7
3.4 Hinged Access Panel Restraints Test (All Classes)	8
3.5 Drainage Performance Test (All Classes)	8
Figure 2 – Drainage Performance Test Fixture	9
Table 1 – Relief Discharge Design	10
3.6 Freeze Protection Capability Test (Class I and I-V)	10
Figure 3 – Thermocouple Placement	11
3.7 Security/Locking Mechanism Test (All Classes)	11
Figure 4	12
Section IV	13
4.0 Detailed Requirements.....	13
4.1 Materials.....	13
4.2 Markings	13
4.3 Installation Instructions	14
Section V	15
5.0 Definitions.....	15
Appendix A	16

Performance Requirements for Outdoor Enclosures for Fluid Conveying Components

Section I

1.0 General

1.1 Application

This standard details the requirements of outdoor enclosures for fluid conveying components (herein referred to as the “enclosure”). It includes enclosure types for freezing and non-freezing locations.

These enclosures are designed to protect backflow prevention assemblies and devices, water/gas meters, control valves, pressure reducing valves, air release valves, pumps, and other components installed outdoors requiring protection from freezing and/or for system security.

1.2 Scope

1.2.1 Description

The enclosures incorporate features to provide for positive drainage, security, and accessibility for monitoring, testing, repairing, and replacing of the components. The enclosures shall provide freeze protection, freeze retardation or non-freeze protection of the components, and be vandal-resistant.

1.2.2 Classes

1.2.2.1 Freeze Protection Enclosures (Heated)

Freeze protection enclosures (Class I and I-V) shall have a minimum thermal resistance value of eight (R8), and a positive means of heat. These enclosures shall be designed and constructed to maintain a minimum internal temperature of 40.0 °F (4.4 °C) using the empirical data obtained in Section 3.6, which is based on an external temperature of -30.0 °F (-34.4 °C). Class I enclosures are designed for components that do not generate positive and/or negative air pressures. Class I-V enclosures are designed for components that generate positive and/or negative air pressures, and include an air inlet and/or outlet.

1.2.2.2 Freeze Retardant Enclosures (Non-Heated)

Freeze retardant enclosures (Class II and II-V) shall have a minimum thermal resistance value of eight (R8).

These enclosures shall be designed and constructed to be installed in climates where the ambient temperature does not go below 33.0 °F (0.6 °C) for long periods of time. These enclosures offer no guarantee of freeze protection and are for indeterminable temporary freeze protection when the ambient temperature drops below freezing for a short period of time. Class II enclosures are designed for components that do not generate positive and/or negative air pressures. Class II-V enclosures are designed for components that generate positive and/or negative air pressures, and include an air inlet and/or outlet.