

ETSI TS 125 202 V14.0.0 (2017-04)



**Universal Mobile Telecommunications System (UMTS);
7.68 Mcps Time Division Duplex (TDD) option;
Overall description: Stage 2
(3GPP TS 25.202 version 14.0.0 Release 14)**



Reference

RTS/TSGR-0125202ve00

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	5
1 Scope	6
2 References	6
3 Definitions, symbols and abbreviations	6
3.1 Definitions	6
3.2 Symbols.....	7
3.3 Abbreviations	7
4 Background and introduction	7
5 Requirements.....	8
6 Physical layer structure	8
6.0 Services offered to higher layers	8
6.1 Frame structure.....	8
6.2 Burst structure	8
6.3 Midambles.....	9
6.4 Coding and Modulation.....	12
6.5 Scrambling Codes.....	12
6.6 Synchronisation Codes	13
6.7 Transmit diversity.....	13
6.9 Indicator Channels.....	13
6.9.1 Paging Indicator Channel (PICH).....	13
6.9.2 MBMS Indicator Channel (MICH).....	13
6.10 Mapping of transport channels to physical channels.....	13
7 Physical layer procedures	14
7.1 Power Control	14
7.2 Timing Advance	15
7.3 HSDPA procedures	15
7.4 Synchronisation procedures.....	15
7.5 RACH procedures	15
7.6 Discontinuous transmission (DTX) procedure	15
7.7 Downlink transmit diversity procedure	15
7.8 DSCH procedure	15
7.9 Macrodiversity procedure.....	15
7.10 IPDL procedure	15
7.11 E-DCH procedures	15
8 UE capabilities	16
9 Layer 2/3 protocol aspects.....	16
9.1 Protocol architecture.....	16
9.2 Signalling	16
9.2.1 General.....	16
9.2.2 L2/MAC differences	16
9.2.3 L2/RRC differences	16
9.3 HSDPA related issues	17
9.4 Mobility.....	17
9.5 Idle Mode Procedures.....	17
9.6 E-DCH related issues	17
10 Iub/Iur aspects	17
10.1 Impacts on Iub/Iur interfaces – general aspects.....	17

10.1.1	Timing advance and Rx Timing Deviation.....	17
10.1.2	Paging	18
10.1.3	DSCH Power Control from the RNC.....	18
10.2	Impacts on Iub/Iur control plane protocols.....	18
10.3	Impacts on Iub/Iur user plane protocols	18
11	Radio aspects.....	18
11.1	UE radio transmission and reception.....	18
11.1.1	Transmitter characteristics	18
11.1.1.1	Transmit power	18
11.1.1.2	Output RF spectrum emissions	19
11.1.1.2.1	Occupied bandwidth	19
11.1.1.2.2	Out of band emission	19
11.1.1.2.2.1	Spectrum emission mask.....	19
11.1.1.2.2.2	Adjacent Channel Leakage power Ratio (ACLR).....	19
11.1.1.2.2.3	Spurious emissions	20
11.1.2	Receiver characteristics	20
11.1.2.1	Reference sensitivity level	20
11.1.2.1.1	Minimum Requirement	20
11.1.2.2	Adjacent Channel Selectivity (ACS).....	20
11.1.2.2.1	Minimum Requirement	20
11.1.2.3	Blocking characteristics	21
11.1.2.3.1	Minimum Requirement	21
11.1.2.4	Spurious response	22
11.1.2.4.1	Minimum Requirement	22
11.1.2.5	Spurious emissions.....	22
11.1.2.5.1	Minimum Requirement	23
11.2	Base station radio transmission and reception.....	23
11.2.1	Transmitter characteristics	23
11.2.1.1	Base station output power	23
11.2.1.2	Output RF spectrum emissions	23
11.2.1.2.1	Occupied bandwidth.....	23
11.2.1.2.2	Out of band emission	23
11.2.1.2.2.1	Spectrum emission mask.....	23
11.2.1.2.2.2	Adjacent Channel Leakage power Ratio (ACLR).....	25
11.2.1.2.2.2.1	Minimum requirement.....	25
11.2.1.2.2.3	Spurious emissions	26
11.2.2	Receiver characteristics	26
11.2.2.1	Reference sensitivity level	26
11.2.2.1.1	Minimum requirement	26
11.2.2.2	Adjacent Channel Selectivity (ACS).....	26
11.2.2.2.1	Minimum requirement.....	26
11.2.2.3	Blocking characteristics	27
11.2.2.3.1	Minimum requirement.....	27
11.2.2.3.2	Collocation with GSM900 and/or DCS 1800.....	28
11.2.2.4	Spurious emissions.....	28
11.2.2.4.1	Minimum requirement.....	29
Annex A (informative):	Change history	30
History		31

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document is the overall technical specification for the support of the 7.68Mcps TDD option in UTRA.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 25.895 (V6.0.0): "Analysis of higher chip rates for UTRA TDD evolution".
- [2] 3GPP TS 25.221: "Physical channels and mapping of transport channels onto physical channels (TDD)".
- [3] 3GPP TS 25.222: "Multiplexing and channel coding (TDD)".
- [4] 3GPP TS 25.223: "Spreading and modulation (TDD)".
- [5] 3GPP TS 25.224: "Physical layer procedures (TDD)".
- [6] 3GPP TS 25.225: "Physical layer; Measurements (TDD)".
- [7] 3GPP TS 25.301: "Radio Interface Protocol Architecture".
- [8] 3GPP TS 25.306: "UE Radio Access capabilities".
- [9] 3GPP TS 25.321: "Medium Access Control (MAC) protocol specification".
- [10] 3GPP TS 25.102: "User Equipment (UE) radio transmission and reception (TDD)".
- [11] 3GPP TS 25.105 "UTRAN (BS) TDD; Radio transmission and reception".
- [12] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [12] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [12].

(void)