

ETSI TS 136 300 V14.2.0 (2017-04)



**LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA) and
Evolved Universal Terrestrial Radio
Access Network (E-UTRAN);
Overall description;
Stage 2
(3GPP TS 36.300 version 14.2.0 Release 14)**



Reference

RTS/TSGR-0236300ve20

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSI/DeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	16
1 Scope	17
2 References	17
3 Definitions, symbols and abbreviations	20
3.1 Definitions	20
3.2 Abbreviations	22
4 Overall architecture	27
4.1 Functional Split	28
4.2 Void.....	30
4.2.1 Void	30
4.2.2 Void	30
4.3 Radio Protocol architecture	30
4.3.1 User plane	30
4.3.2 Control plane	31
4.4 Synchronization.....	32
4.5 IP fragmentation.....	32
4.6 Support of HeNBs	32
4.6.1 Architecture	32
4.6.2 Functional Split.....	34
4.6.3 Interfaces.....	36
4.6.3.1 Protocol Stack for S1 User Plane	36
4.6.3.2 Protocol Stacks for S1 Control Plane	37
4.6.3.3 Protocol Stack for S5 interface.....	37
4.6.3.4 Protocol Stack for SGi interface.....	37
4.6.3.5 Protocol Stack for X2 User Plane and X2 Control Plane	38
4.6.4 Void	38
4.6.5 Support of LIPA with HeNB	38
4.6.6 Support of X2 GW.....	39
4.6.6.1 Enhanced TNL Address Discovery.....	40
4.6.6.2 Routing of X2AP messages	40
4.6.6.3 (H)eNB unavailability.....	40
4.6.6.4 (H)eNB registration.....	40
4.7 Support for relaying.....	40
4.7.1 General.....	40
4.7.2 Architecture	41
4.7.3 S1 and X2 user plane aspects.....	41
4.7.4 S1 and X2 control plane aspects	42
4.7.5 Radio protocol aspects	43
4.7.6 Signalling procedures	44
4.7.6.1 RN attach procedure.....	44
4.7.6.2 E-RAB activation/modification.....	45
4.7.6.3 RN startup procedure	46
4.7.6.4 RN detach procedure.....	47
4.7.6.5 Neighbouring Information Transfer	48
4.7.6.6 Mobility to or from RN	48
4.7.7 Relay Node OAM Aspects	48
4.7.7.1 Architecture.....	48
4.7.7.2 OAM Traffic QoS Requirements	49
4.7.7.3 Security Aspects.....	49
4.7.7.4 Void.....	49
4.7.7.5 OAM Requirements for Configuration Parameters.....	49

4.7.7.5.1	Parameters Associated with Relay Bearer Mapping.....	49
4.8	Support of SIPTO at the Local Network	49
4.8.1	General.....	49
4.8.2	SIPTO at the Local Network with collocated L-GW.....	50
4.8.3	Support for SIPTO@LN with Stand-Alone Gateway.....	51
4.9	Support for Dual Connectivity	51
4.9.1	General.....	51
4.9.2	Radio Protocol Architecture	51
4.9.3	Network Interfaces.....	52
4.9.3.1	E-UTRAN Control Plane for Dual Connectivity	52
4.9.3.2	E-UTRAN User Plane for Dual Connectivity.....	52
4.9.3.3	Support of HeNBs for Dual Connectivity.....	53
4.9.3.4	Support of SIPTO@LN and LIPA for Dual Connectivity	53
4.10	NB-IoT	55
5	Physical Layer for E-UTRA.....	55
5.1	Downlink Transmission Scheme.....	58
5.1.1	Basic transmission scheme based on OFDM.....	58
5.1.1a	Basic transmission scheme based on OFDM for NB-IoT.....	58
5.1.2	Physical-layer processing	58
5.1.3	Physical downlink control channels.....	59
5.1.4	Downlink Reference signal and synchronization signals.....	60
5.1.4a	Downlink Reference signal and synchronization signals for NB-IoT	60
5.1.5	Downlink multi-antenna transmission	60
5.1.5a	Downlink multi-antenna transmission for NB-IoT	61
5.1.6	MBSFN transmission.....	61
5.1.7	Physical layer procedure	61
5.1.7.1	Link adaptation	61
5.1.7.2	Power Control	61
5.1.7.3	Cell search.....	61
5.1.7.3a	Cell search for NB-IoT.....	61
5.1.8	Physical layer measurements definition.....	61
5.1.9	Coordinated Multi-Point transmission.....	62
5.2	Uplink Transmission Scheme.....	62
5.2.1	Basic transmission scheme	62
5.2.1a	Basic transmission scheme for NB-IoT	63
5.2.2	Physical-layer processing	63
5.2.3	Physical uplink control channel	63
5.2.3a	Uplink control information for NB-IoT	64
5.2.4	Uplink Reference signal.....	64
5.2.4a	Uplink Reference signal for NB-IoT	64
5.2.5	Random access preamble.....	65
5.2.5a	Random access preamble for NB-IoT.....	65
5.2.6	Uplink multi-antenna transmission	65
5.2.7	Physical channel procedure.....	65
5.2.7.1	Link adaptation	65
5.2.7.2	Uplink Power control	65
5.2.7.3	Uplink timing control.....	65
5.2.8	Coordinated Multi-Point reception	66
5.3	Transport Channels.....	66
5.3.1	Mapping between transport channels and physical channels.....	67
5.3.1a	Mapping between transport channels and narrowband physical channels.....	68
5.4	E-UTRA physical layer model	69
5.4.1	Void	69
5.4.2	Void	69
5.5	Carrier Aggregation.....	69
5.5a	Multi-carrier operation for NB-IoT.....	70
5.5.1	SRS switching between component carriers	70
5.6	Sidelink	70
5.6.1	Basic transmission scheme	70
5.6.2	Physical-layer processing	71
5.6.3	Physical Sidelink control channel.....	71

5.6.4	Sidelink reference signals	71
5.6.5	Physical channel procedure.....	71
5.6.5.1	Sidelink power control	71
5.6.6	Physical layer measurements definition.....	71
5.7	Licensed-Assisted Access	71
5.7.1	Channel Access Priority Classes.....	72
5.7.2	Multiplexing of data.....	72
6	Layer 2.....	73
6.1	MAC Sublayer.....	75
6.1.1	Services and Functions	75
6.1.2	Logical Channels	75
6.1.2.1	Control Channels.....	75
6.1.2.2	Traffic Channels.....	76
6.1.3	Mapping between logical channels and transport channels	76
6.1.3.1	Mapping in Uplink	76
6.1.3.2	Mapping in Downlink	77
6.1.3.3	Mapping in Sidelink.....	78
6.2	RLC Sublayer.....	78
6.2.1	Services and Functions	78
6.2.2	PDU Structure.....	78
6.3	PDCP Sublayer.....	79
6.3.1	Services and Functions	79
6.3.2	PDU Structure.....	80
6.4	Carrier Aggregation.....	80
6.5	Dual Connectivity.....	81
7	RRC.....	83
7.1	Services and Functions	83
7.2	RRC protocol states & state transitions	83
7.3	Transport of NAS messages	84
7.3a	CIoT signalling reduction optimizations	85
7.3a.1	General.....	85
7.3a.2	Control Plane CIoT EPS optimizations	85
7.3a.3	User Plane CIoT EPS optimizations	86
7.4	System Information	88
7.5	Carrier Aggregation.....	90
7.6	Dual Connectivity.....	91
8	E-UTRAN identities.....	92
8.1	E-UTRAN related UE identities.....	92
8.2	Network entity related Identities	93
8.3	Sidelink communication and V2X Sidelink Communication related identities	93
8.4	MBMS related identities	94
9	ARQ and HARQ	94
9.1	HARQ principles.....	94
9.2	ARQ principles.....	95
9.3	Void.....	96
10	Mobility.....	96
10.1	Intra E-UTRAN.....	96
10.1.1	Mobility Management in ECM-IDLE	97
10.1.1.1	Cell selection.....	97
10.1.1.2	Cell reselection.....	97
10.1.1.3	Void.....	98
10.1.1.4	Void.....	98
10.1.1.5	Void.....	98
10.1.2	Mobility Management in ECM-CONNECTED.....	98
10.1.2.1	Handover.....	99
10.1.2.1.1	C-plane handling	99
10.1.2.1.2	U-plane handling	102
10.1.2.2	Path Switch	103
10.1.2.2.1	Path Switch upon handover	103

10.1.2.2.2	Path Update upon Dual Connectivity specific activities.....	104
10.1.2.2.3	Path Switch upon UE context resume	104
10.1.2.3	Data forwarding	104
10.1.2.3.1	For RLC-AM DRBs	104
10.1.2.3.2	For RLC-UM DRBs	105
10.1.2.3.3	SRB handling	105
10.1.2.3.4	User data forwarding for Dual Connectivity	105
10.1.2.4	Void.....	105
10.1.2.5	Void.....	105
10.1.2.6	Void.....	105
10.1.2.7	Timing Advance.....	105
10.1.2.8	Dual Connectivity operation	106
10.1.2.8.1	SeNB Addition	106
10.1.2.8.2	SeNB Modification.....	108
10.1.2.8.2.1	Intra-MeNB handover involving SCG change.....	110
10.1.2.8.3	SeNB Release	111
10.1.2.8.4	Change of SeNB	112
10.1.2.8.5	MeNB to eNB Change.....	114
10.1.2.8.6	SCG change	115
10.1.2.8.7	eNB to MeNB change	115
10.1.2.8.8	Inter-MeNB handover without SeNB change.....	116
10.1.2.9	LWA mobility	119
10.1.2.9.1	Inter-eNB handover without WT change.....	119
10.1.3	Measurements	120
10.1.3.1	Intra-frequency neighbour (cell) measurements.....	123
10.1.3.2	Inter-frequency neighbour (cell) measurements.....	123
10.1.4	Paging and C-plane establishment	123
10.1.5	Random Access Procedure	124
10.1.5.1	Contention based random access procedure.....	124
10.1.5.2	Non-contention based random access procedure	126
10.1.5.3	Interaction model between L1 and L2/3 for Random Access Procedure	128
10.1.6	Radio Link Failure	128
10.1.7	Radio Access Network Sharing	129
10.1.8	Handling of Roaming and Area Restrictions for UEs in ECM-CONNECTED.....	130
10.1.8a	Handling of Roaming and Access Restrictions for UEs in ECM-CONNECTED	130
10.2	Inter RAT	130
10.2.1	Cell reselection	130
10.2.2	Handover	131
10.2.2a	Inter-RAT cell change order to GERAN with NACC	131
10.2.2b	Inter-RAT handovers from E-UTRAN.....	132
10.2.2b.1	Data forwarding	132
10.2.2b.1.1	For RLC-AM bearers	132
10.2.2b.1.2	For RLC-UM bearers	132
10.2.3	Measurements	132
10.2.3.1	Inter-RAT handovers from E-UTRAN	132
10.2.3.2	Inter-RAT handovers to E-UTRAN	133
10.2.3.3	Inter-RAT cell reselection from E-UTRAN.....	133
10.2.3.4	Limiting measurement load at UE	133
10.2.4	Network Aspects.....	133
10.2.5	CS fallback.....	133
10.3	Mobility between E-UTRAN and Non-3GPP radio technologies.....	134
10.3.1	UE Capability Configuration	134
10.3.2	Mobility between E-UTRAN and cdma2000 network	134
10.3.2.1	Tunnelling of cdma2000 Messages over E-UTRAN between UE and cdma2000 Access Nodes	135
10.3.2.2	Mobility between E-UTRAN and HRPD.....	136
10.3.2.2.1	Mobility from E-UTRAN to HRPD	136
10.3.2.2.1.1	HRPD System Information Transmission in E-UTRAN	136
10.3.2.2.1.2	Measuring HRPD from E-UTRAN.....	136
10.3.2.2.1.2.1	Idle Mode Measurement Control	136
10.3.2.2.1.2.2	Active Mode Measurement Control	136
10.3.2.2.1.2.3	Active Mode Measurement	136
10.3.2.2.1.3	Pre-registration to HRPD Procedure.....	136

10.3.2.2.1.4	E-UTRAN to HRPD Cell Re-selection.....	137
10.3.2.2.1.5	E-UTRAN to HRPD Handover.....	137
10.3.2.2.2	Mobility from HRPD to E-UTRAN	137
10.3.2.3	Mobility between E-UTRAN and cdma2000 1xRTT	137
10.3.2.3.1	Mobility from E-UTRAN to cdma2000 1xRTT.....	137
10.3.2.3.1.1	cdma2000 1xRTT System Information Transmission in E-UTRAN.....	137
10.3.2.3.1.2	Measuring cdma2000 1xRTT from E-UTRAN	137
10.3.2.3.1.2.1	Idle Mode Measurement Control	138
10.3.2.3.1.2.2	Active Mode Measurement Control.....	138
10.3.2.3.1.2.3	Active Mode Measurement.....	138
10.3.2.3.1.3	E-UTRAN to cdma2000 1xRTT Cell Re-selection.....	138
10.3.2.3.1.4	E-UTRAN to cdma2000 1xRTT Handover	138
10.3.2.3.2	Mobility from cdma2000 1xRTT to E-UTRAN.....	138
10.3.2.3.3	1xRTT CS Fallback.....	139
10.3.3	CDMA2000 interworking in LTE shared networks.....	140
10.4	Area Restrictions	140
10.4a	Roaming and Access Restrictions	141
10.5	Mobility to and from CSG and Hybrid cells	141
10.5.0	Principles for idle-mode mobility with CSG cells	141
10.5.0.1	Intra-frequency mobility	141
10.5.0.2	Inter-frequency mobility	141
10.5.0.3	Inter-RAT Mobility.....	141
10.5.1	Inbound mobility to CSG cells	141
10.5.1.1	RRC_IDLE.....	141
10.5.1.2	RRC_CONNECTED.....	142
10.5.2	Outbound mobility from CSG cells	144
10.5.2.1	RRC_IDLE.....	144
10.5.2.2	RRC_CONNECTED.....	144
10.6	Measurement Model.....	145
10.7	Hybrid Cells	145
10.7.1	RRC_IDLE	145
10.7.2	RRC_CONNECTED	146
10.7.2.1	Inbound Mobility	146
10.7.2.2	Outbound Mobility.....	146
11	Scheduling and Rate Control.....	146
11.1	Basic Scheduler Operation	146
11.1.1	Downlink Scheduling	147
11.1.2	Uplink Scheduling	148
11.2	Activation/Deactivation Mechanism	148
11.3	Measurements to Support Scheduler Operation	149
11.4	Rate Control of GBR, MBR and UE-AMBR	149
11.4.1	Downlink	149
11.4.2	Uplink	149
11.4.3	UE-AMBR for Dual Connectivity.....	150
11.5	CQI reporting for Scheduling.....	150
11.6	Explicit Congestion Notification.....	150
12	DRX in RRC_CONNECTED	151
13	QoS.....	152
13.1	Bearer service architecture	152
13.2	QoS parameters	153
13.3	QoS support in Hybrid Cells	154
14	Security.....	154
14.1	Overview and Principles	154
14.2	Security termination points.....	157
14.3	State Transitions and Mobility	158
14.3.1	RRC_IDLE to RRC_CONNECTED	158
14.3.2	RRC_CONNECTED to RRC_IDLE	158
14.3.3	Intra E-UTRAN Mobility	158
14.3.4	SeNB Removal	158

14.4	AS Key Change in RRC_CONNECTED	159
14.5	Security Interworking.....	159
14.6	RN integrity protection for DRB(s).....	159
15	MBMS.....	159
15.1	General	160
15.1.1	E-MBMS Logical Architecture.....	161
15.1.2	E-MBMS User Plane Protocol Architecture	163
15.1.3	E-MBMS Control Plane Protocol Architecture	163
15.2	MBMS Cells.....	164
15.2.1	MBMS-dedicated cell	164
15.2.2	MBMS/Unicast-mixed cell	164
15.2.2.1	FeMBMS/Unicast-mixed cell	164
15.3	MBMS Transmission.....	164
15.3.1	General.....	164
15.3.2	Single-cell transmission	164
15.3.3	Multi-cell transmission	165
15.3.4	MBMS Reception States.....	167
15.3.5	MCCH Structure.....	167
15.3.5a	SC-MCCH structure	168
15.3.6	MBMS signalling on BCCH.....	168
15.3.7	MBMS User Data flow synchronisation.....	169
15.3.8	Synchronisation of MCCH Update Signalling via M2	170
15.3.9	IP Multicast Distribution	170
15.4	Service Continuity.....	170
15.5	Network sharing	172
15.6	Network Functions for Support of Multiplexing	172
15.7	Procedures	173
15.7.1	Procedures for Broadcast mode	173
15.7.1.1	Session Start procedure	173
15.7.1.2	Session Stop procedure	174
15.7a	M1 Interface	175
15.7a.1	M1 User Plane	175
15.8	M2 Interface	176
15.8.1	M2 Control Plane.....	176
15.8.2	M2 Interface Functions	177
15.8.2.1	General	177
15.8.2.2	MBMS Session Handling Function.....	177
15.8.2.3	MBMS Scheduling Information Provision Function	177
15.8.2.4	M2 Interface Management Function	177
15.8.2.5	M2 Configuration Function.....	177
15.8.2.6	MBMS Service Counting Function.....	177
15.8.2.7	MBMS Service Suspension and Resumption Function.....	177
15.8.2.8	MBMS Overload Notification Function.....	178
15.8.3	M2 Interface Signalling Procedures.....	178
15.8.3.1	General	178
15.8.3.2	MBMS Session signalling procedure	178
15.8.3.3	MBMS Scheduling Information procedure.....	178
15.8.3.4	M2 Interface Management procedures.....	178
15.8.3.4.1	Reset procedure	178
15.8.3.4.2	Error Indication procedure.....	178
15.8.3.5	M2 Configuration procedures	178
15.8.3.5.1	M2 Setup procedure	178
15.8.3.5.2	eNB Configuration Update procedure	178
15.8.3.5.3	MCE Configuration Update procedure.....	179
15.8.3.6	MBMS Service Counting procedures	179
15.8.3.6.1	MBMS Service Counting procedure	179
15.8.3.6.2	MBMS Service Counting Results Report procedure.....	179
15.8.3.7	MBMS Overload Notification procedure.....	179
15.9	M3 Interface	179
15.9.1	M3 Control Plane.....	179
15.9.2	M3 Interface Functions	180

15.9.2.1	General	180
15.9.2.2	MBMS Session Handling Function.....	180
15.9.2.3	M3 Interface Management Function	180
15.9.2.4	M3 Configuration Function.....	180
15.9.3	M3 Interface Signalling Procedures.....	180
15.9.3.1	General	180
15.9.3.2	MBMS Session signalling procedure	180
15.9.3.3	M3 Interface Management procedures	181
15.9.3.3.1	Reset procedure	181
15.9.3.3.2	Error Indication procedure.....	181
15.9.3.4	M3 Configuration procedures	181
15.9.3.4.1	M3 Setup procedure	181
15.9.3.4.2	MCE Configuration Update procedure.....	181
15.10	MBMS Counting	181
15.10.1	General.....	181
15.10.2	Counting Procedure	181
16	Radio Resource Management aspects	182
16.1	RRM functions	182
16.1.1	Radio Bearer Control (RBC)	182
16.1.2	Radio Admission Control (RAC).....	182
16.1.3	Connection Mobility Control (CMC)	182
16.1.4	Dynamic Resource Allocation (DRA) - Packet Scheduling (PS)	183
16.1.5	Inter-cell Interference Coordination (ICIC).....	183
16.1.5.1	UE configurations for time domain ICIC.....	183
16.1.5.2	OAM requirements for time domain ICIC.....	184
16.1.5.2.1	Configuration for CSG cell.....	184
16.1.5.2.2	Configuration for interfering non-CSG cell.....	184
16.1.6	Load Balancing (LB)	184
16.1.7	Inter-RAT Radio Resource Management	184
16.1.8	Subscriber Profile ID for RAT/Frequency Priority.....	185
16.1.9	Inter-eNB CoMP.....	185
16.1.10	Cell on/off and cell discovery	185
16.2	RRM architecture	185
16.2.1	Centralised Handling of certain RRM Functions.....	185
16.2.2	De-Centralised RRM	185
16.2.2.1	UE History Information	185
16.2.3	Void	186
16.3	UE assistance information for RRM and UE power optimisations	186
17	Void.....	186
17.1	Void.....	186
18	UE capabilities	186
19	S1 Interface	188
19.1	S1 User plane	188
19.2	S1 Control Plane.....	188
19.2.1	S1 Interface Functions	189
19.2.1.1	S1 Paging function	190
19.2.1.2	S1 UE Context Management function.....	190
19.2.1.3	Initial Context Setup Function	191
19.2.1.3a	UE Context Modification Function.....	191
19.2.1.3b	UE Context Resume Function.....	191
19.2.1.4	Mobility Functions for UEs in ECM-CONNECTED	191
19.2.1.4.1	Intra-LTE Handover	191
19.2.1.4.2	Inter-3GPP-RAT Handover	191
19.2.1.5	E-RAB Service Management function.....	191
19.2.1.6	NAS Signalling Transport function.....	191
19.2.1.7	NAS Node Selection Function (NNSF)	191
19.2.1.8	S1-interface management functions	192
19.2.1.9	MME Load balancing Function	192
19.2.1.10	Location Reporting Function	192

19.2.1.11	Warning Message Transmission function.....	192
19.2.1.12	Overload Function.....	192
19.2.1.13	RAN Information Management Function	192
19.2.1.14	S1 CDMA2000 Tunnelling function.....	193
19.2.1.15	Configuration Transfer Function.....	193
19.2.1.16	LPPa Signalling Transport function.....	193
19.2.1.17	Trace Function	193
19.2.1.18	UE Radio Capability Match.....	193
19.2.1.19	Retrieve UE Information Function.....	193
19.2.1.20	UE Information Transfer Function.....	193
19.2.2	S1 Interface Signalling Procedures.....	193
19.2.2.1	Paging procedure.....	193
19.2.2.2	S1 UE Context Release procedure	194
19.2.2.2.1	S1 UE Context Release (EPC triggered)	194
19.2.2.2.2	S1 UE Context Release Request (eNB triggered).....	194
19.2.2.3	Initial Context Setup procedure.....	195
19.2.2.3a	UE Context Modification procedure.....	196
19.2.2.4	E-RAB signalling procedures.....	196
19.2.2.4.1	E-RAB Setup procedure	196
19.2.2.4.2	E-RAB Modification procedure	197
19.2.2.4.3	E-RAB Release procedure.....	198
19.2.2.4.4	E-RAB Release Indication procedure.....	199
19.2.2.4.5	E-RAB Modification Indication procedure	199
19.2.2.5	Handover signalling procedures.....	199
19.2.2.5.1	Handover Preparation procedure	200
19.2.2.5.2	Handover Resource Allocation procedure.....	200
19.2.2.5.3	Handover Notification procedure	201
19.2.2.5.4	Handover Cancellation	201
19.2.2.5.5	Path Switch procedure	202
19.2.2.5.6	Message sequence diagrams	202
19.2.2.5.7	eNB Status Transfer procedure.....	210
19.2.2.5.8	MME Status Transfer procedure	211
19.2.2.6	NAS transport procedures	211
19.2.2.7	S1 interface Management procedures	214
19.2.2.7.1	Reset procedure	214
19.2.2.7.1a	eNB initiated Reset procedure.....	214
19.2.2.7.1b	MME initiated Reset procedure.....	215
19.2.2.7.2	Error Indication functions and procedures.....	215
19.2.2.7.2a	eNB initiated error indication	215
19.2.2.7.2b	MME initiated error indication.....	215
19.2.2.8	S1 Setup procedure	216
19.2.2.9	eNB Configuration Update procedure.....	216
19.2.2.9a	eNB Configuration Transfer procedure.....	217
19.2.2.10	MME Configuration Update procedure	217
19.2.2.10a	MME Configuration Transfer procedure	218
19.2.2.11	Location Reporting procedures	218
19.2.2.11.1	Location Reporting Control procedure.....	219
19.2.2.11.2	Location Report procedure	219
19.2.2.11.3	Location Report Failure Indication procedure.....	219
19.2.2.12	Overload procedure.....	220
19.2.2.12.1	Overload Start procedure.....	220
19.2.2.12.2	Overload Stop procedure.....	220
19.2.2.13	Write-Replace Warning procedure.....	221
19.2.2.14	eNB Direct Information Transfer procedure.....	221
19.2.2.15	MME Direct Information Transfer procedure.....	222
19.2.2.16	S1 CDMA2000 Tunnelling procedures.....	222
19.2.2.16.1	Downlink S1 CDMA2000 Tunnelling procedure.....	222
19.2.2.16.2	Uplink S1 CDMA2000 Tunnelling procedure.....	222
19.2.2.17	Kill procedure	223
19.2.2.18	LPPa Transport procedures	223
19.2.2.18.1	Downlink UE Associated LPPa Transport procedure	224
19.2.2.18.2	Uplink UE Associated LPPa Transport procedure	224

19.2.2.18.3	Downlink Non UE Associated LPPa Transport procedure.....	224
19.2.2.18.4	Uplink Non UE Associated LPPa Transport procedure	225
19.2.2.19	Trace procedures	225
19.2.2.19.1	Trace Start procedure	225
19.2.2.19.2	Trace Failure Indication procedure.....	226
19.2.2.19.3	Deactivate Trace procedure	226
19.2.2.19.4	Cell Traffic Trace procedure	226
19.2.2.20	UE Capability Info Indication procedure	226
19.2.2.21	UE Radio Capability Match procedure	227
19.2.2.22	PWS Restart Indication procedure	227
19.2.2.23	PWS Failure Indication procedure	228
19.2.2.24	UE Context Modification Indication procedure.....	228
19.2.2.25	Connection Establishment Indication procedure.....	229
19.2.2.26	UE Context Suspend procedure	229
19.2.2.27	UE Context Resume procedure.....	230
19.2.2.28	Retrieve UE Information procedure.....	230
19.2.2.29	UE Information Transfer procedure.....	230
20	X2 Interface.....	231
20.1	User Plane	231
20.1.1	Flow Control Functions	231
20.2	Control Plane.....	231
20.2.1	X2-CP Functions	232
20.2.2	X2-CP Procedures	233
20.2.2.1	Handover Preparation procedure.....	233
20.2.2.2	Handover Cancel procedure	233
20.2.2.2a	SeNB Addition Preparation procedure.....	234
20.2.2.2b	SeNB Reconfiguration Completion procedure.....	234
20.2.2.2c	MeNB initiated SeNB Modification Preparation procedure	235
20.2.2.2d	SeNB initiated SeNB Modification procedure	235
20.2.2.2e	MeNB initiated SeNB Release procedure	236
20.2.2.2f	SeNB initiated SeNB Release procedure	236
20.2.2.2g	SeNB Counter Check procedure	236
20.2.2.3	UE Context Release procedure	237
20.2.2.4	SN Status Transfer procedure	237
20.2.2.5	Error Indication procedure	238
20.2.2.6	Load Indication procedure	238
20.2.2.7	X2 Setup procedure.....	238
20.2.2.8	eNB Configuration Update procedure.....	239
20.2.2.9	Reset procedure.....	239
20.2.2.10	Resource Status Reporting Initiation procedure.....	240
20.2.2.11	Resource Status Reporting procedure	240
20.2.2.12	Radio Link Failure Indication procedure	240
20.2.2.13	Handover Report procedure	241
20.2.2.14	Mobility Settings Change procedure.....	241
20.2.2.15	Cell Activation procedure	242
20.2.2.16	X2 Release procedure	242
20.2.2.17	X2AP Message Transfer procedure	243
20.2.2.18	X2 Removal procedure	243
20.2.2.19	Retrieve UE Context	244
20.2.3	Void	245
21	Void.....	245
21.1	Void.....	245
21.2	Void.....	245
21.3	Void.....	245
22	Support for self-configuration and self-optimisation	245
22.1	Definitions	245
22.2	UE Support for self-configuration and self-optimisation	246
22.3	Self-configuration.....	246
22.3.1	Dynamic configuration of the S1-MME interface	246
22.3.1.1	Prerequisites	246

22.3.1.2	SCTP initialization	246
22.3.1.3	Application layer initialization	247
22.3.2	Dynamic Configuration of the X2 interface	247
22.3.2.1	Prerequisites	247
22.3.2.2	SCTP initialization	247
22.3.2.3	Application layer initialization	247
22.3.2a	Automatic Neighbour Relation Function	247
22.3.3	Intra-LTE/frequency Automatic Neighbour Relation Function	249
22.3.4	Inter-RAT/Inter-frequency Automatic Neighbour Relation Function	250
22.3.5	Framework for PCI Selection	251
22.3.6	TNL address discovery	251
22.3.6.1	TNL address discovery of candidate eNB via S1 interface	251
22.3.7	Dynamic configuration of the Xw-C interface	252
22.3.7.1	Prerequisites	252
22.3.7.2	SCTP initialization	252
22.3.7.3	Application layer initialization	252
22.4	Self-optimisation	252
22.4.1	Support for Mobility Load Balancing	252
22.4.1.1	General	252
22.4.1.2.1	Load reporting for intra-LTE scenario	253
22.4.1.2.2	Load reporting for inter-RAT scenario	254
22.4.2	Support for Mobility Robustness Optimisation	254
22.4.2.1	General	254
22.4.2.2	Connection failure due to intra-LTE mobility	254
22.4.2.2a	Connection failure due to inter-RAT mobility	257
22.4.2.3	Unnecessary HO to another RAT	258
22.4.2.4	O&M Requirements	259
22.4.2.5	Inter-RAT ping-pong	259
22.4.2.6	Dynamic coverage configuration changes	260
22.4.3	Support for RACH Optimisation	260
22.4.4	Support for Energy Saving	260
22.4.4.1	General	260
22.4.4.2	Solution description	260
22.4.4.3	O&M requirements	261
22.4.5	Radio Link Failure report	261
22.5	Void	262
22.6	Void	262
22A	LTE-WLAN Aggregation and RAN Controlled LTE-WLAN Interworking	262
22A.1	LTE-WLAN Aggregation	262
22A.1.1	General	262
22A.1.2	Radio Protocol Architecture	262
22A.1.3	Network Interfaces	264
22A.1.3.1	General	264
22A.1.3.2	User Plane	264
22A.1.3.3	Control Plane	264
22A.1.4	Mobility	265
22A.1.5	WLAN Measurements	265
22A.1.6	Procedure for WLAN Connection Status Reporting	266
22A.1.7	LTE-WLAN Aggregation Operation	266
22A.1.7.1	WT Addition	266
22A.1.7.2	WT Modification	267
22A.1.7.3	WT Release	269
22A.1.7.4	Change of WT	271
22A.1.8	WLAN Authentication	271
22A.2	RAN Controlled LTE WLAN Interworking	271
22A.2.1	General	271
22A.2.2	Network Interfaces	272
22A.2.2.1	General	272
22A.2.2.2	User Plane Plane	272
22A.2.2.3	Control Plane	272
22A.2.3	Mobility	272

22A.2.4	WLAN Measurements	272
22A.2.5	Procedure for WLAN Connection Status Reporting.....	272
22A.2.6	Traffic Steering Operation.....	272
22A.2.6.1	Traffic Steering from E-UTRAN to WLAN.....	272
22A.2.6.2	Traffic Steering from WLAN to E-UTRAN.....	273
22A.3	LTE/WLAN Radio Level Integration with IPsec Tunnel.....	273
22A.3.1	LWIP Operation.....	276
22A.3.1.1	LWIP Tunnel Setup and Data Bearer Configuration.....	276
22A.3.1.2	Reconfiguration to Remove WLAN Resources from Data Bearer	277
22A.3.1.3	LWIP Tunnel Release	277
22A.3.2	Network Interfaces.....	278
22A.3.2.1	General.....	278
22A.3.2.2	User Plane	278
22A.3.2.3	Control Plane.....	278
22B	Xw Interface.....	279
22B.1	User Plane	279
22B.2	Control Plane.....	279
22B.2.1	Xw-CP Functions.....	280
22B.2.2	Xw-CP Procedures.....	280
22B.2.2.1	WT Addition Preparation procedure	280
22B.2.2.2	WT Association Confirmation procedure	280
22B.2.2.3	eNB initiated WT Modification Preparation procedure	281
22B.2.2.4	WT initiated WT Modification procedure.....	281
22B.2.2.5	eNB initiated WT Release procedure.....	282
22B.2.2.6	WT initiated WT Release procedure.....	282
22B.2.2.7	WT Status Reporting Initiation	283
22B.2.2.8	WT Status Reporting	283
22B.2.2.9	Xw Setup procedure.....	283
22B.2.2.10	WT Configuration Update procedure.....	284
22B.2.2.11	Error Indication procedure	284
22B.2.2.11.1	WT initiated error indication	285
22B.2.2.11.2	eNB initiated error indication	285
22B.2.2.12	Reset procedure.....	285
22B.2.2.12.1	WT initiated reset	285
22B.2.2.12.2	eNB initiated reset	286
23	Others	288
23.1	Support for real time IMS services.....	288
23.1.1	IMS Emergency Call	288
23.2	Subscriber and equipment trace.....	288
23.2.1	Signalling activation	288
23.2.2	Management activation.....	289
23.3	E-UTRAN Support for Warning Systems.....	289
23.3.1	Earthquake and Tsunami Warning System.....	289
23.3.2	Commercial Mobile Alert System	289
23.3.3	Korean Public Alert System.....	289
23.3.4	EU-Alert	289
23.4	Interference avoidance for in-device coexistence.....	289
23.4.1	Problems	289
23.4.2	Solutions	290
23.5	TDD Enhanced Interference Management and Traffic Adaptation (eIMTA)	291
23.6	RAN assisted WLAN interworking.....	292
23.6.1	General principles.....	292
23.6.2	Access network selection and traffic steering rules	293
23.7	Support of Low Complexity UEs	293
23.7a	Support of Bandwidth Reduced Low Complexity UEs.....	293
23.7b	Support of UEs in Enhanced Coverage	294
23.8	Support for Radio Interface based Synchronization	294
23.9	Network-assisted interference cancellation/suppression	295
23.10	Support for sidelink communication	295
23.10.1	General.....	295

23.10.2	Radio Protocol Architecture	296
23.10.2.1	User plane	296
23.10.2.2	Control plane.....	296
23.10.3	Radio resource allocation.....	297
23.10.3.1	Resource Pool for sidelink control information	299
23.10.3.2	Resource Pool for sidelink data.....	299
23.10.4	Sidelink Communication via ProSe UE-to-Network Relay	299
23.11	Support for sidelink discovery.....	301
23.11.1	General.....	301
23.11.2	Radio Protocol Architecture	301
23.11.3	Radio resource allocation.....	302
23.12	Resource usage reporting for shared networks.....	304
23.13	Optimising signalling load and resource usage for paging.....	304
23.13.1	General paging optimisation	304
23.13.2	Paging optimisation for UEs in enhanced coverage	305
23.14	Support for V2X services	305
23.14.1	General.....	305
23.14.1.1	Support for V2X sidelink communication	305
23.15	Support for MMTEL voice and video enhancements.....	308
23.15.1	RAN-assisted codec adaptation	308
23.15.2	MMTEL signalling optimization	309
23.15.3	MMTEL voice quality/coverage enhancements	309
Annex A (informative): NAS Overview.....		311
A.1	Services and Functions.....	311
A.2	NAS protocol states & state transitions.....	311
Annex B (informative): MAC and RRC Control		312
B.1	Difference between MAC and RRC control	312
B.2	Void.....	312
Annex C (informative): Void		313
Annex D (informative): Void		314
Annex E (informative): Void		315
Annex F (informative): Void		316
Annex G (informative): Guideline for E-UTRAN UE capabilities.....		317
Annex H (informative): Void		319
Annex I (informative): SPID ranges and mapping of SPID values to cell reselection and inter-RAT/inter frequency handover priorities		320
I.1	SPID ranges.....	320
I.2	Reference SPID values	320
Annex J (informative): Carrier Aggregation		322
J.1	Deployment Scenarios.....	322
J.2	Void.....	323
J.3	Void.....	323
J.4	Void.....	323
J.5	Void.....	323
J.6	Void.....	323
Annex K (informative): Time domain ICIC.....		324
K.1	Deployment scenarios	324
K.1.1	CSG scenario	324
K.1.2	Pico scenario.....	325

Annex L (informative):	Void	326
Annex M (informative):	Dual Connectivity	327
M.1	Dual Connectivity operation.....	327
M.2	Operation Overview	327
Annex N (informative):	Sidelink communication	331
N.1	Deployment Scenarios.....	331
Annex O (informative):	Change history	332
History		345

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document provides an overview and overall description of the E-UTRAN radio interface protocol architecture. Details of the radio interface protocols are specified in companion specifications of the 36 series.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TR 25.913: "Requirements for Evolved UTRA (E-UTRA) and Evolved UTRAN (E-UTRAN)".
- [3] 3GPP TS 36.201: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer; General description".
- [4] 3GPP TS 36.211: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical Channels and Modulation".
- [5] 3GPP TS 36.212: "Evolved Universal Terrestrial Radio Access (E-UTRA); Multiplexing and channel coding".
- [6] 3GPP TS 36.213: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures".
- [7] 3GPP TS 36.214: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer; Measurements".
- [8] IETF RFC 4960 (09/2007): "Stream Control Transmission Protocol".
- [9] 3GPP TS 36.302: "Evolved Universal Terrestrial Radio Access (E-UTRA); Services provided by the physical layer".
- [10] Void
- [11] 3GPP TS 36.304: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) procedures in idle mode".
- [12] 3GPP TS 36.306: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio access capabilities".
- [13] 3GPP TS 36.321: "Evolved Universal Terrestrial Radio Access (E-UTRA); Medium Access Control (MAC) protocol specification".
- [14] 3GPP TS 36.322: "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Link Control (RLC) protocol specification".
- [15] 3GPP TS 36.323: "Evolved Universal Terrestrial Radio Access (E-UTRA); Packet Data Convergence Protocol (PDCP) specification".
- [16] 3GPP TS 36.331: "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC) protocol specification".
- [17] 3GPP TS 23.401: "Technical Specification Group Services and System Aspects; GPRS enhancements for E-UTRAN access".