

ETSI TS 136 523-3 v14.0.0 (2017-08)



**LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA) and
Evolved Packet Core (EPC);
User Equipment (UE) conformance specification;
Part 3: Test suites
(3GPP TS 36.523-3 version 14.0.0 Release 14)**



Reference

RTS/TSGR-0536523-3ve00

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	14
Introduction	14
1 Scope	15
2 References	15
3 Definitions and abbreviations.....	18
3.1 Definitions	18
3.2 Abbreviations	18
4 E-UTRAN/SAE system architecture and test models.....	18
4.1 Test system architecture	18
4.1.1 General system architecture.....	18
4.1.2 Component architecture.....	19
4.2 E-UTRAN test models	21
4.2.1 Layer 2 test models	21
4.2.1.1 MAC test model.....	21
4.2.1.2 RLC test model	23
4.2.1.3 PDCP test model	24
4.2.1.3.1 PDCP ROHC test model	24
4.2.1.3.2 PDCP test model (Non ROHC).....	25
4.2.2 RRC test model.....	26
4.2.3 DRB test model.....	27
4.2.4 IP Test Model	27
4.2.4.1 IP user data.....	28
4.2.4.2 Configuration of Sockets.....	29
4.2.4.2.1 Socket Establishment.....	29
4.2.4.2.2 Socket Release.....	30
4.2.4.3 Handling of IP data	30
4.2.4.4 Routing of IP Data	31
4.2.4.5 Multiple PDNs	31
4.2.4.6 IP Addresses Guidelines	32
4.2.4.6.1 Common Structure of IP Addresses	32
4.2.4.6.2 Common Requirements regarding IP Addresses	33
4.2.4.6.3 Network Entities and their IP addresses	33
4.2.4.7 User Plane Signalling for Address Allocation.....	34
4.2.4.7.1 DHCP	34
4.2.4.7.2 DHCPv6	37
4.2.4.7.3 ICMPv6	37
4.2.4.7.4 DNS	38
4.2.4A LTE-Carrier Aggregation test Models	41
4.2.4A.1 CA-MAC test model	41
4.2.4A.2 CA-RRC test model	43
4.2.4A.3 LAA-MAC test model.....	44
4.2.4A.4 LAA-RRC test model.....	45
4.2.4B Dual Connectivity test models	46
4.2.4B.1 DC MAC test model.....	46
4.2.4B.2 DC PDCP test model.....	47
4.2.4B.3 DC RRC test model.....	48
4.2.5 IP model extension for IMS	49
4.2.5.1 IPsec	50
4.2.5.1.1 Security Association	50
4.2.5.1.2 SAD and SPD	51

4.2.5.2	Signalling Compression (SigComp)	52
4.2.5.3	SIP TTCN-3 Codec	52
4.2.6	Support of DSMIPv6	52
4.2.7	MBMS test model.....	53
4.2.8	OCNG test model	53
4.2.9	Device-to-Device Proximity Services test model	55
4.2.9.1	ProSe Function test model	56
4.2.9.2	Direct Discovery test model.....	56
4.2.9.3	Direct Communication test model.....	57
4.2.10	SC-PTM test model	58
4.3	SAE Test Model.....	59
4.3.1	NAS Test Model	59
4.4	Inter RAT Test Model	60
4.4.1	E-UTRAN-UTRAN Inter RAT Test Model	60
4.4.1.1	User data over UTRAN.....	60
4.4.1.1.1	Raw user data over UTRAN.....	61
4.4.1.1.2	IP data over UTRAN	61
4.4.1.1.3	Routing IP data.....	62
4.4.2	E-UTRAN-GERAN Inter RAT Test Model	63
4.4.2.1	User data over GERAN.....	63
4.4.2.1.1	Raw user data over GERAN.....	64
4.4.2.1.2	IP data over GERAN	64
4.4.2.1.3	Routing IP data.....	65
4.4.3	E-UTRAN-CDMA2000 Inter RAT Test Model	66
4.4.3.1	E-UTRAN-CDMA2000 HRPD Inter RAT Test Model.....	66
4.4.3.2	E-UTRAN-CDMA2000 1xRTT Inter RAT test model.....	68
4.4.4	E-UTRAN FDD-TDD Inter RAT Test Model.....	71
4.4.5	E-UTRAN-UTRAN-GERAN Inter RAT Test Model	72
4.4.6	3GPP-WLAN Inter working Test Model.....	73
4.4.6.1	E-UTRAN-WLAN Inter working Test Model.....	73
4.4.6.2	UTRAN-WLAN Inter working Test Model.....	75
4.5	Generic WLAN Test Model	76
4.5.1	WLAN Access Point.....	76
4.5.2	ePDG/AAA-Server Emulation.....	76
4A	NB-IoT system architecture and test models.....	79
4A.1	Test system architecture	79
4A.2	NB-IoT test models	79
4A.2.1	Layer 2 test models	79
4A.2.1.1	Layer 2 loopback mode for CP mode.....	79
4A.2.1.2	MAC test model (CP mode).....	81
4A.2.1.3	RLC test model (CP mode)	82
4A.2.1.4	PDCP test model	83
4A.2.2	RRC / NAS test model.....	84
5	Upper Tester Interface.....	85
5.1	Definitions	85
5.2	Upper Tester ASPs	85
6	ASP specifications.....	91
6.1	General Requirements and Assumptions.....	91
6.1.1	IP ASP requirements.....	91
6.1.2	Enhancement of IP ASP for handling IMS signalling	91
6.2	E-UTRAN ASP Definitions	92
6.2.1	Configuration Primitives.....	92
6.2.2	Signalling Primitives.....	92
6.2.3	Co-ordination Messages between NAS Emulation PTC and EUTRA PTC	93
6.3	UTRAN ASP Definitions	94
6.3.1	Void	95
6.3.2	ASPs for Data Transmission and Reception	95
6.4	GERAN ASP Definitions	96
6.4.1	ASPs for Control Primitive Transmission	96
6.4.2	ASPs for Data Transmission and Reception	98

6.5	NB-IoT ASP Definitions	101
6.5.1	Configuration Primitives.....	101
6.5.2	Signalling Primitives.....	101
6.5.3	Co-ordination Messages between NAS Emulation PTC and NBIOT PTC	102
7	E-UTRAN/SAE Test Methods and Design Considerations	104
7.1	Channel Mapping	104
7.1.1	PDCCH Candidate Selection	104
7.1.1.1	FDD candidates selection.....	105
7.1.1.2	TDD candidates selection	109
7.1.1.2.1	TDD candidates selection in special subframes	112
7.1.2	ePDCCH Candidate Selection	112
7.1.2.1	FDD candidates selection.....	112
7.1.2.2	TDD candidates selection	113
7.1.3	MPDCCH Candidate Selection.....	113
7.2	Uplink Grant.....	114
7.2.1	Exception TC list	117
7.3	Downlink Resource Allocation	117
7.3.1	PDCCH DCI default formats	118
7.3.1.1	Default DCI Format to be used in test cases configuring MIMO.....	118
7.3.2	Radio parameters configured	118
7.3.2.1	HARQ Retransmission when MIMO is configured.....	119
7.3.3	General DL scheduling scheme	119
7.3.3.1	Additional rules for BCCH scheduling scheme	119
7.3.3.1.1	BCCH with DCI combination 1	120
7.3.3.1.2	BCCH with DCI combination 2	120
7.3.3.2	Additional rules for PCCH specific scheduling scheme	120
7.3.3.2.1	PCCH with DCI combination 1.....	120
7.3.3.2.2	PCCH with DCI combination 2.....	120
7.3.3.3	Additional rules for RAR specific scheduling scheme.....	121
7.3.3.3.1	RAR with DCI combination 1	121
7.3.3.3.2	RAR with DCI combination 2	121
7.3.3.4	Additional rules for UE-dedicated scheduling scheme in normal mode	121
7.3.3.5	DL Resource allocation bitmaps	123
7.3.3.5.1	DCI combination 1	123
7.3.3.5.2	DCI combination 2	125
7.3.3.6	UE-dedicated scheduling scheme in explicit mode.....	128
7.3.3.6.1	DL Scheduling in Transport Block Size Selection Test Cases	129
7.3.3.7	Resource allocation sheets	129
7.3.3.8	MPDCCH DL DCI formats	130
7.3.3.8.1	BCCH	130
7.3.3.8.2	PCCH	131
7.3.3.8.3	RAR.....	131
7.3.3.8.4	UE-dedicated scheduling.....	131
7.3.3.9	DL Resource allocation bitmaps for BL/CE UE	132
7.3.3.9.1	DCI combination 1	132
7.4	Cell Configurations	134
7.4.1	Cell Configuration Types.....	134
7.4.2	Cell Power Change	134
7.4.3	E-UTRAN cell identity	134
7.4.3.1	Timing parameters of cells	134
7.4.4	Cell configurations for NAS test cases	136
7.4.5	Configuration of Multi-Cell Environment	137
7.5	TDD Considerations.....	137
7.5.1	FDD vs. TDD implementation.....	137
7.5.2	Guideline for FDD vs. TDD verification	137
7.6	Special RLC Modes.....	138
7.6.1	Suppression of RLC Acknowledgements	138
7.6.2	Modification of VT(S).....	138
7.7	System information	138
7.7.1	System information broadcasting	138
7.7.2	Scheduling information.....	139

7.7.2a	Scheduling information for BR System information	142
7.7.3	System information modification	153
7.7.3.1	Non-PWS System Information modification	153
7.7.3.1.1	UE in Idle_mode.....	153
7.7.3.1.2	UE in connected mode.....	154
7.7.3.2	PWS System Information modification	155
7.8	Timers and Timing Restrictions	155
7.8.1	Auxiliary timers	156
7.8.2	RRC timers reconfiguration	156
7.8.3	MAC TA timer reconfiguration	156
7.8.4	Non-protocol timers	156
7.9	Error Indication	156
7.10	Race Conditions	157
7.11	Radio Link Failure.....	157
7.12	Test method for RRC signalling latency	157
7.12.1	Procedure delays in PUCCH synchronized state	157
7.12.2	Procedure delays when RACH procedure required	159
7.13	RLC test method for scheduled data.....	159
7.14	IP packets for Loopback Mode.....	160
7.14.1	IP packets used for Loopback Mode A	160
7.14.2	IP packets used for Loopback Mode B	160
7.15	Connected Mode DRX	161
7.16	Handover Sequences	162
7.16.1	Sequence of inter-cell handover.....	162
7.16.1a	Sequence of inter-cell CA handover (more than one CC before and after handover).....	163
7.16.2	Sequence of intra-cell handover.....	164
7.16.3	UL Grants used in RA procedure during handover	165
7.17	Simulation of PDCP MAC-I Failure in UE.....	165
7.17.1	Integrity and ciphering not yet activated.....	165
7.17.2	Integrity and/or ciphering already activated	166
7.18	RRC Connection Release Sequence	166
7.18a	RRC Connection Release Sequence for BL/CE UE	166
7.19	DL CCCH Message and Contention Resolution MAC Control Element transmission in one MAC PDU or in separate MAC PDUs.....	167
7.20	RRC Connection Reconfiguration Sequence (Measurement Control)	167
7.21	Inter-RAT - GERAN special issues.....	168
7.21.1	Timeslot assigned for GERAN CS traffic.....	168
7.21.2	Subchannel used in GERAN L2 access message.....	168
7.21.3	Paging in GERAN	168
7.22	EUTRAN RSRQ Calculations	168
7.22.1	Assumptions	168
7.22.2	The Ideal Calculation.....	168
7.22.3	Additional RSRQ Calculations For Fixing Boundary Values	169
7.23	Test method for eICIC and feICIC	169
7.24	Carrier Aggregation Signalling Sequences.....	170
7.24.1	Initial configuration of Pcell	170
7.24.2	Initial configuration of SCell	170
7.24.3	Scell Addition and/or release	171
7.25	Test method for MBMS	171
7.25.1	Schedule transmission of MCCH messages.....	171
7.25.2	MCCH change notification	172
7.25.3	MTCH data scheduling	172
7.26	Type B FDD Half-Duplex Considerations	172
7.27	Test method for Device-to-Device Proximity Services	173
7.27.1	Direct Discovery test method.....	173
7.27.2	Direct Communication test method	174
7.27.2.1	Synchronisation and SBCCH transmission.....	174
7.27.2.2	Sidelink data transmission/reception.....	174
7.28	Test method for SC-PTM	174
7.28.1	Schedule transmission of SC-MCCH messages	174
7.28.2	SC-MCCH information change	175
7.28.3	SC-MTCH data scheduling	175

7A	NB-IoT Test Methods and Design Considerations	175
7A.1	Physical signals and channels.....	175
7A.2	System information	176
7A.2.1	System information broadcasting in general.....	176
7A.2.2	System information scheduling and synchronisation signals.....	176
7A.2.2.1	MIB-NB, NPSS, NSSS	176
7A.2.2.2	SIB1-NB	176
7A.2.2.3	SI-messages containing SIB3-NB, SIB4-NB, SIB5-NB, SIB14-NB, SIB16-NB	177
7A.2.2.3.1	SI combination 1 scheduling	177
7A.2.2.3.2	SI combination 2/3/4 scheduling	178
7A.2.3	System information modification	179
7A.3	Search space configurations	179
7A.3.1	Type1CSS - Paging.....	180
7A.3.2	Type2CSS – Random access	180
7A.3.3	UESS	180
7A.4	Timing considerations	181
7A.4.1	Random access procedure.....	181
7A.4.2	Uplink transmissions.....	182
7A.4.3	Downlink transmissions.....	183
7A.4.4	Half-duplex mode	183
7A.4.5	Conclusions.....	184
7A.5	Scheduling requests and scheduling of UL grants.....	184
7A.5.1	RACH procedure mode	184
7A.5.2	Polling mode	184
7A.6	Scheduling requirements	184
7A.6.1	Random access procedure.....	185
7A.6.2	Downlink transmissions.....	185
7A.6.3	Periodic uplink grants	186
7A.6.4	HARQ re-transmissions	187
7A.6.4.1	Uplink	187
7A.6.4.2	Downlink.....	187
7A.6.5	Timing info for UL messages	188
7A.6.6	Uplink time alignment	188
7A.7	RRC Connection Release Sequence	188
7A.8	DL CCCH Message and Contention Resolution MAC Control Element transmission in one MAC PDU or in separate MAC PDUs.....	189
7A.9	Cell Configuration.....	189
7A.9.1	Cell Power Change	189
7A.9.2	Timing Parameters of Cells	189
7A.9.3	Configuration of Multi-Cell Environment	190
7A.10	Timers and Timing Restrictions	190
7A.11	Error Indication	190
7A.12	NBIOT RSRQ Calculations	190
8	External Function Definitions	190
9	IXIT Proforma.....	193
9.1	E-UTRAN PIXIT	193
9.2	MultiRAT PIXIT	197
9.3	NB-IoT PIXIT	201
10	Postambles.....	201
10.1	Postambles for E-UTRA to UTRA tests.....	201
10.1.1	UE postamble states and procedures for E-UTRA to UTRA.....	201
10.1.2	Switch/Power off procedure	203
10.1.2.1	Procedure	203
10.1.3	CC disconnect procedure	205
10.1.3.1	Procedure	205
10.1.4	PS Routing Area Update procedure	206
10.1.4.1	Procedure	206
10.1.5	CS fallback procedure.....	207
10.1.5.1	Procedure	207
10.2	Postambles for E-UTRAN to GERAN tests.....	209

10.2.1	UE postamble states and procedures for E-UTRA to GERAN test cases	209
10.2.2	Switch/Power off procedure	211
10.2.2.1	Procedure	211
10.2.3	PS Handover procedure	212
10.2.3.1	Procedure	212
10.2.4	CC disconnect procedure	213
10.2.4.1	Procedure	213
10.2.5	CS fallback procedure	213
10.2.5.1	Procedure	213
10.3	Postambles for E-UTRA test cases	214
10.3.1	UE postamble states and procedures for E-UTRA test cases	214
10.3.2	Switch/Power off procedure in State E1	215
10.3.2.1	Procedure	215
10.3.3	Switch/Power off procedure in State E2 and E3	216
10.3.3.1	Procedure for E2 and E3	216
10.3.3.2	Procedure for E2_T3440	217
10.3.4	Switch/Power off procedure in State E4	218
10.3.4.1	Procedure	218
10.3.5	Automatic selection mode procedure in State E5 (current cell, neighbour cell)	218
10.3.5.1	Procedure	218
10.4	Postambles for E-UTRA to HRPD test cases	218
10.4.1	UE postamble procedures for E-UTRA to HRPD (No Pre-Registration)	218
10.4.1.1	Registration on HRPD Cell	218
10.4.1.2	Detach on HRPD Cell	220
10.5	Postambles for NB-IoT test cases	220
10.5.1	UE postamble states and procedures for NB-IoT test cases	220
10.5.2	Switch/Power off procedure in State N1	221
10.5.2.1	Procedure	221
10.5.3	Switch/Power off procedure in State N2 and N3	221
10.5.3.1	Procedure for N2 and N3	221
10.5.4	Switch/Power off procedure in State N4	221
10.5.4.1	Procedure	221
10.5.5	Automatic selection mode procedure in State N5 (current cell, neighbour cell)	222
10.5.5.1	Procedure	222
11	Guidelines on test execution	222
11.1	EUTRA single technology	222
11.1.1	Replacement of test case execution	223
11.2	EUTRA - UTRA - GERAN	224
11.2.1	UTRA configured – GERAN not configured	224
11.2.1.1	EUTRA band overlapping UTRA band	224
11.2.1.2	EUTRA band not overlapping UTRA band	225
11.2.2	GERAN configured - UTRA not configured	226
11.2.3	Neither UTRA nor GERAN configured	227
11.2.4	Both UTRA and GERAN configured	227
11.2.4.1	EUTRA band overlapping UTRA band	227
11.2.4.2	EUTRA band not overlapping UTRA band	228
11.2.5	Replacement of test case execution	228
11.3	EUTRA inter-band	228
11.3.1	Primary operating band	229
11.3.2	Secondary operating band for inter-band cells	229
11.3.3	Replacement of test case execution	229
11.4	EUTRA CA	229
11.4.1	CA contiguous Intra-band operation	229
11.4.2	CA Inter-band operation	230
11.4.3	CA non-contiguous Intra-band operation	233
11.5	EUTRA MFBI	233
11.6	EUTRA DC	234
Annex A (normative):	Test Suites	236
A.1	Baseline of specifications	236

A.2	E-UTRA Test Suites.....	236
Annex B (informative):	Style Guides.....	256
B.1	Introduction	256
B.2	General Requirements for TTCN-3 Implementations	256
B.3	Naming Conventions	257
B.3.1	Prefixes and Restrictions for TTCN-3 Objects.....	257
B.3.2	Void.....	258
B.3.3	Void.....	258
B.3.4	Identifiers consisting of more than one Name	258
B.4	Implementation Issues.....	258
B.4.1	Control part	258
B.4.2	Top Level Test Case Definitions	258
B.4.3	Inter Component Communication	259
B.4.4	Encoding Information.....	259
B.4.5	Verdict Assignment.....	259
B.4.5.1	PASS verdict assignment.....	260
B.4.5.2	FAIL or INCONC verdict assignment	260
B.4.5.3	Verdict assignment in default behaviour	261
B.4.6	Default Behaviour	261
B.4.7	Templates for Sending and Receiving.....	262
B.4.8	Logging	262
B.4.8.1	Prose Step Numbers.....	262
B.4.9	Top level comments	263
B.4.10	Mapping of DRBs	263
B.5	Modularisation	263
Annex C (informative):	Design Principles.....	265
C.1	ASP Design	265
C.2	SS State Model	266
Annex D (informative)	TTCN-3 Definitions	269
D.1	EUTRA_ASP_TypeDefs.....	269
D.1.1	ASN1_Container	269
D.1.2	System_Configuration.....	278
D.1.3	Cell_Configuration.....	281
D.1.3.1	Cell_Configuration_Common.....	282
D.1.3.2	Downlink_Physical_Layer_Configuration	286
D.1.3.2.1	Antenna_Configuration.....	287
D.1.3.2.2	Physical_Channels	288
D.1.3.2.3	Physical_Signals	290
D.1.3.3	Uplink_Physical_Layer_Configuration	291
D.1.3.4	Common_MAC_Configuration	292
D.1.3.5	Random_Access_Procedure	299
D.1.3.6	System_Information_Control	304
D.1.3.7	Paging_Control	309
D.1.3.8	UE_Specific_Channel_Configuration	309
D.1.3.8.1	UE_Specific_Channel_Configuration_DL	309
D.1.3.8.2	UE_Specific_Channel_Configuration_UL	310
D.1.3.9	Carrier_Aggregation	313
D.1.3.10	OCNG_Config	315
D.1.3.11	EIMTA_Config	316
D.1.4	Cell_Power_Attenuation	316
D.1.5	Radio_Bearer_Configuration	317
D.1.5.1	PDCP_Configuration	317
D.1.5.2	RLC_Configuration	318
D.1.5.3	MAC_Configuration.....	320

D.1.6	AS_Security	323
D.1.7	Semi_Persistent_Scheduling	325
D.1.8	Paging_Trigger	327
D.1.9	L1_MAC_Indication_Control	327
D.1.10	Rlc_Indication_Control	328
D.1.11	PDCP_Count	329
D.1.12	PDCP_Handover	330
D.1.13	L1_MAC_Test_Mode	330
D.1.14	PDCCH_Order	331
D.1.15	System_Indications	331
D.1.16	System_Interface	334
D.1.17	MBMS_Configuration	335
D.1.18	SCPTM_Configuration	338
D.1.19	DirectIndicationInfo_Trigger	340
D.2	EUTRA_ASP_DrbDefs	340
D.2.1	MBMS_MR_B_Primitive_Definitions	340
D.2.2	System_Interface	341
D.3	EUTRA_NB_ASP_L2DataDefs	342
D.3.1	PDU_TypeDefs	342
D.3.1.1	MAC_PDU	342
D.3.1.2	RLC_PDU	345
D.3.1.2.1	Common	345
D.3.1.2.2	TM_Data	346
D.3.1.2.3	UM_Data	346
D.3.1.2.4	AM_Data	348
D.3.1.2.5	AM_Status	350
D.3.1.3	PDCP	353
D.3.2	DRB_Primitive_Definitions	359
D.3.2.1	DRB_Common	359
D.3.2.2	Downlink	360
D.3.2.3	Uplink	361
D.4	EUTRA_ASP_SrbDefs	362
D.4.1	SRB_DATA_ASPs	362
D.4.2	Port_Definitions	364
D.5	IP_ASP_TypeDefs	364
D.5.1	IP_Common	364
D.5.2	IP_Config	366
D.5.3	IPsec_Config	367
D.5.4	IP_SocketHandling	369
D.5.4.1	Socket_Common	369
D.5.4.2	Socket Datagram	370
D.5.4.3	TCP_Socket	371
D.5.4.4	UDP_Socket	376
D.5.4.5	ICMP_Socket	378
D.5.4.6	Socket_Primitives	380
D.5.5	System_Interface	381
D.6	NasEmu_AspTypes_EUTRA	383
D.6.1	System_Interface	384
D.7	EUTRA_CommonDefs	385
D.7.1	Common_Types	385
D.7.2	Common_Constants	385
D.7.3	RRC_Nested_Types	386
D.7.4	ASP_CommonPart	387
D.7.4.1	ASP_CommonPart_Definitions	387
D.7.4.1.1	Routing_Info	387
D.7.4.2	REQ_ASP_CommonPart	388
D.7.4.3	CNF_ASP_CommonPart	388
D.7.4.4	IND_ASP_CommonPart	388

D.7.5	MBMS_CommonDefs.....	388
D.8	CDMA2000_ASP_TypeDefs.....	389
D.8.1	CDMA2000_Common	389
D.8.1.1	CDMA2000_SystemContants.....	389
D.8.1.2	CDMA2000_Routing.....	389
D.8.1.3	CDMA2000_TimingInfo	390
D.8.1.4	CDMA2000_ReqAspCommonPart	391
D.8.1.5	CDMA2000_IndAspCommonPart	392
D.8.1.6	CDMA2000_CnfAspCommonPart	392
D.8.2	CDMA2000_PowerLevel.....	393
D.8.3	CDMA2000_Data	394
D.8.4	CDMA2000_CellConfiguration	396
D.8.5	CDMA2000_HRPD	398
D.8.5.1	CDMA2000_PDN_Defs	398
D.8.5.2	CDMA2000_SubProtocols	399
D.8.5.3	HRPD_Indications	401
D.8.5.4	HRPD_Commands	404
D.8.6	CDMA2000_RTT1X.....	407
D.8.6.1	RTT1X_Indications	407
D.8.6.2	RTT1X_Commands.....	410
D.8.7	System_Interface	412
D.9	CDMA2000_CommonDefs.....	415
D.10	EUTRA_ASP_CDMA2000TunnellingDefs	419
D.11	EUTRA_ASP_VirtualNoiseDefs	420
D.12	UTRAN_ASP_VirtualNoiseDefs.....	421
D.13	WLAN_ASP_TypeDefs	422
D.14	SideLinkUE_ASP_TypeDefs.....	434
D.14.1	SideLinkUE_Data	434
D.14.2	SideLinkUE_Configuration.....	436
D.14.2.1	SL_Routing_Timing	436
D.14.2.2	SL_SystemRequestAsp	438
D.14.2.2.1	SL_RequestAspCommon_Part	438
D.14.2.2.2	Discovery_Specific	441
D.14.2.2.3	Communication_Specific	443
D.14.2.2.4	SL_Security.....	449
D.14.2.3	SL_SystemConfirmAsp	450
D.14.2.4	SL_SystemIndicationAsp	450
D.14.2.5	SL_System_Interface	452
D.15	CommonDefs	453
D.16	EUTRA_NB_ASP_TypeDefs	456
D.16.1	Cell_Configuration	456
D.16.1.1	Cell_Configuration_Common	456
D.16.1.2	Uplink_Physical_Layer_Configuration	457
D.16.1.3	Common_MAC_Configuration	457
D.16.1.4	Random_Access_Procedure	459
D.16.2	System_Indications	461
D.17	EUTRA_NB_CommonDefs.....	461
D.17.1	Common_Types	461
D.17.2	RRC_Nested_Types	462
D.17.3	ASP_CommonPart	462
D.17.3.1	ASP_CommonPart_Definitions	462
D.17.3.1.1	Routing_Info	462
D.17.3.1.2	Timing_Info	462
D.17.3.2	REQ_ASP_CommonPart	463
D.17.3.3	CNF_ASP_CommonPart	463

D.17.3.4	IND_ASP_CommonPart.....	464
D.17.4	L2Data_CommonDefs.....	464
D.18	References to TTCN-3	466
Annex E (informative):	Upper Tester Scenarios	467
E.1	No confirmation	467
E.2	Immediate confirmation	467
E.3	Late response.....	469
E.4	Multiple responses.....	470
Annex F (informative):	TTCN-3 Definitions	473
F.1	NBIOT_ASP_TypeDefs.....	473
F.1.1	ASN1_Container	473
F.1.2	System_Configuration.....	474
F.1.3	Cell_Configuration.....	477
F.1.3.1	Cell_Configuration_Common.....	477
F.1.3.2	Downlink_Physical_Layer_Configuration	479
F.1.3.2.1	Physical_Channels	479
F.1.3.2.2	Physical_Signals	482
F.1.3.3	Uplink_Physical_Layer_Configuration	483
F.1.3.4	Common_MAC_Configuration	484
F.1.3.5	Random_Access_Procedure	487
F.1.3.6	System_Information_Control	490
F.1.3.7	Paging_Control	492
F.1.3.8	UE_Specific_Channel_Configuration	492
F.1.3.8.1	UE_Specific_Channel_Configuration_DL	492
F.1.3.8.2	UE_Specific_Channel_Configuration_UL	493
F.1.4	Cell_Power_Attenuation	494
F.1.5	Radio_Bearer_Configuration	494
F.1.5.1	RLC_Configuration	494
F.1.5.2	MAC_Configuration.....	495
F.1.6	AS_Security	498
F.1.7	Paging_Trigger.....	499
F.1.8	RLC_Counts.....	500
F.1.9	PDCP_Count	500
F.1.10	L1_MAC_Test_Mode	502
F.1.11	System_Interface	502
F.2	NBIOT_ASP_SrbDefs	503
F.2.1	SRB_DATA_ASPs	503
F.2.2	Port_Definitions	505
F.3	NBIOT_ASP_L2DataDefs	505
F.3.1	System_Interface	505
F.4	EUTRA_NB_ASP_L2DataDefs	506
F.4.1	PDU_TypeDefs	506
F.4.1.1	MAC_PDU	506
F.4.1.2	RLC_PDU.....	509
F.4.1.2.1	Common.....	509
F.4.1.2.2	TM_Data	510
F.4.1.2.3	UM_Data	510
F.4.1.2.4	AM_Data	512
F.4.1.2.5	AM_Status	514
F.4.1.3	PDCP	517
F.4.2	DRB_Primitive_Definitions	523
F.4.2.1	DRB_Common	523
F.4.2.2	Downlink	524
F.4.2.3	Uplink	525

F.5	NasEmu_AspTypes_NBIOT	526
F.5.1	System_Interface	526
F.6	NBIOT_CommonDefs	528
F.6.1	NBIOT_Common_Types	528
F.6.2	NBIOT_RRC_Nested_Types	529
F.6.3	NBIOT_ASP_CommonPart	529
F.6.3.1	NBIOT_ASP_CommonPart_Definitions	529
F.6.3.1.1	NBIOT_Routing_Info	529
F.6.3.2	REQ_ASP_CommonPart	530
F.6.3.3	NBIOT_CNF_ASP_CommonPart	530
F.6.3.4	NBIOT_IND_ASP_CommonPart	531
F.7	NBIOT_Imported_EUTRA ASN1_Types	531
F.8	NBIOT_ASP_VirtualNoiseDefs	531
F.9	CommonDefs	533
F.10	EUTRA_NB_ASP_TypeDefs	533
F.10.1	Cell_Configuration	533
F.10.1.1	Cell_Configuration_Common	534
F.10.1.2	Uplink_Physical_Layer_Configuration	535
F.10.1.3	Common_MAC_Configuration	535
F.10.1.4	Random_Access_Procedure	536
F.10.2	System_Indications	538
F.11	EUTRA_NB_CommonDefs	538
F.11.1	Common_Types	538
F.11.2	RRC_Nested_Types	538
F.11.3	ASP_CommonPart	538
F.11.3.1	ASP_CommonPart_Definitions	538
F.11.3.1.1	Routing_Info	538
F.11.3.1.2	Timing_Info	539
F.11.3.2	REQ_ASP_CommonPart	540
F.11.3.3	CNF_ASP_CommonPart	540
F.11.3.4	IND_ASP_CommonPart	540
F.11.4	L2Data_CommonDefs	541
F.12	References to TTCN-3	543
Annex G (informative):	Change history	544
History		643

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part 3 of a multi-part conformance test specification for the 3GPP evolved User Equipment (UE). The specification contains a TTCN-3 design frame work and the detailed test specifications in TTCN-3 for evolved UE at the UE-E-UTRAN radio interface.

- 3GPP TS 36.523-1 [1]: "User Equipment (UE) conformance specification; Part 1: Protocol conformance specification".
- 3GPP TS 36.523-2 [2]: "User Equipment (UE) conformance specification; Part 2: Implementation Conformance Statement (ICS) proforma specification".
- **3GPP TS 36.523-3: "Test Suites"** (the present document).

1 Scope

The present document specifies the protocol and signalling conformance testing in TTCN-3 for the 3GPP UE at the UE-E-UTRAN radio interface.

The following TTCN test specification and design considerations can be found in the present document:

- the test system architecture;
- the overall test suite structure;
- the test models and ASP definitions;
- the test methods and usage of communication ports definitions;
- the test configurations;
- the design principles and assumptions;
- TTCN styles and conventions;
- the partial PIXIT proforma;
- the test suites.

The Abstract Test Suites designed in the document are based on the test cases specified in prose (3GPP TS 36.523-1 [1]). The applicability of the individual test cases is specified in the test ICS proforma specification (3GPP TS 36.523-2 [1]).

The present document is valid for TTCN development for LTE, LTE-Advanced and LTE-Advanced Pro (including NB-IoT) UE conformance test according to 3GPP Releases starting from Release 8 up to the Release indicated on the cover page of the present document.

In the remainder of the present document, unless explicitly stated otherwise, the term E-UTRA(N) implicitly refers to the Wideband part of E-UTRA(N) known as WB-E-UTRA(N). The Narrowband part of E-UTRA(N) is always explicitly referred to as NB-IoT.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document unless the context in which the reference is made suggests a different Release is relevant (information on the applicable release in a particular context can be found in e.g. test case title, description or applicability, message description or content).

- [1] 3GPP TS 36.523-1: "User Equipment (UE) conformance specification; Part 1: Protocol conformance specification".
- [2] 3GPP TS 36.523-2: "User Equipment (UE) conformance specification; Part 2: Implementation Conformance Statement (ICS) proforma specification".
- [3] 3GPP TS 36.508: "Common test environments for User Equipment (UE) conformance testing".
- [4] 3GPP TS 36.509: "Terminal logical test interface; Special conformance testing functions".