

ETSI TS 123 402 V14.6.0 (2018-01)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Architecture enhancements for non-3GPP accesses
(3GPP TS 23.402 version 14.6.0 Release 14)**



Reference

RTS/TSGS-0223402ve60

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	11
Introduction	11
1 Scope	12
2 References	12
3 Definitions, Symbols and Abbreviations.....	15
3.1 Definitions.....	15
3.2 Abbreviations	16
4 Architecture Model and Concepts	17
4.1 Concepts	17
4.1.0 General Concepts.....	17
4.1.1 General Concepts for Interworking Between E-UTRAN and CDMA2000.....	17
4.1.2 General Concepts for Interworking Between 3GPP Accesses and WiMAX	18
4.1.3 IP Mobility Management Selection Principles	18
4.1.3.1 Static Configuration of Inter-technology Mobility Mechanism	18
4.1.3.2 Networks Supporting Multiple IP Mobility Mechanisms	18
4.1.3.2.1 IP Mobility Management Selection During Initial Attach to a Non-3GPP Access	19
4.1.3.2.2 IPMS solutions.....	20
4.1.3.2.3 IP Mobility Management Selection on Handover between accesses.....	20
4.1.4 Trusted/untrusted non-3GPP access network detection.....	21
4.1.5 Non-seamless WLAN offload.....	21
4.2 Architecture Reference Model	22
4.2.1 Architecture for 3GPP Accesses with PMIP-based S5/S8.....	22
4.2.2 Non-roaming Architectures for EPS.....	22
4.2.3 Roaming Architectures for EPS.....	25
4.3 Network Elements	29
4.3.1 Access Networks	29
4.3.1.1 E-UTRAN	29
4.3.1.2 Trusted and Untrusted Non-3GPP Access Network	29
4.3.2 MME.....	30
4.3.3 Gateway	30
4.3.3.1 General.....	30
4.3.3.2 Serving GW.....	30
4.3.3.3 PDN GW	31
4.3.4 ePDG	31
4.3.5 PCRF	32
4.3.5.1 Home PCRF	32
4.3.5.2 Visited PCRF	32
4.4 Reference Points.....	32
4.4.1 List of Reference Points.....	32
4.4.2 Reference Point Requirements.....	34
4.4.2.1 S5 Reference Point Requirements.....	34
4.4.2.2 Void.....	34
4.4.2.3 Void.....	34
4.4.2.4 Void.....	34
4.5 High Level Functions	35
4.5.1 PDN GW Selection Function for Non-3GPP Accesses for S2a and S2b.....	35
4.5.1a PDN GW Selection Function for eHRPD with SIPTO support.....	36
4.5.2 PDN GW Selection Function for S2c	36
4.5.3 Serving GW Selection Function for Non-3GPP Accesses.....	37
4.5.4 ePDG Selection.....	37

4.5.4.1	General	37
4.5.4.2	ePDG FQDNs Construction	37
4.5.4.3	UE Configuration By HPLMN	38
4.5.4.4	UE ePDG Selection Procedure	38
4.5.4.5	ePDG Selection with DNS-based Discovery of Regulatory Requirements	39
4.5.4a	ePDG Selection for Emergency Services	40
4.5.4a.1	General	40
4.5.4a.2	Emergency ePDG Selection Procedure	40
4.5.5	PCRF Selection	40
4.5.6	DSMIPv6 Home Link Detection Function	40
4.5.7	IMS Emergency Session Support	41
4.5.7.1	Overview	41
4.5.7.2	IMS Emergency Session Support over WLAN access to EPC	41
4.5.7.2.1	Introduction	41
4.5.7.2.2	Architecture Reference Model for Emergency Services	42
4.5.7.2.3	PDN GW selection function for Emergency Services	42
4.5.7.2.4	QoS for Emergency Services	43
4.5.7.2.5	PCC for Emergency Services	43
4.5.7.2.6	IP Address Allocation	43
4.5.7.2.7	Handling of PDN Connections for Emergency Bearer Services	43
4.5.7.2.8	Network provided WLAN Location Information	43
4.5.7.2.9	Determination of location	45
4.5.7.2.10	Support of PS handover with 3GPP EPC	45
4.5.8	APN congestion Control Function for eHRPD	46
4.5.9	GTP-C signalling based Load and Overload Control for trusted and untrusted WLAN	46
4.5.9.1	GTP-C load control	46
4.5.9.2	GTP-C overload control	46
4.6	Identities	48
4.6.1	User Identification	48
4.6.2	EPS bearer identity with GTP based S2b/S2a	48
4.7	IP Address Allocation	48
4.7.1	IP Address Allocation with PMIP-based S5/S8	48
4.7.2	IP Address Allocation in Trusted Non-3GPP IP Access using PMIPv6 on S2a	53
4.7.3	IP Address Allocation in Untrusted Non-3GPP IP Access using PMIPv6 or GTP on S2b	56
4.7.4	IP Address Allocation using S2c	56
4.7.5	IPv6 Prefix Delegation using S2c	57
4.7.6	IPv6 Prefix Delegation using PMIP-based S5/S8	57
4.8	Network Discovery and Selection	59
4.8.0	General Principles	59
4.8.1	Architecture for Access Network Discovery Support Functions	60
4.8.2	Network Elements	61
4.8.2.1	Access Network Discovery and Selection Function (ANDSF)	61
4.8.2.1.1	General	61
4.8.2.1.2	Inter-System Mobility Policy	61
4.8.2.1.3	Access Network Discovery Information	62
4.8.2.1.4	Inter-System Routing Policy	62
4.8.2.1.5	Inter-APN Routing Policy	63
4.8.2.1.6	WLAN Selection Policy	64
4.8.2.1.7	VPLMNs with preferred WLAN Selection Rules	65
4.8.2.1.8	Void	66
4.8.2.1.9	Home Network Preferences	66
4.8.2.1.10	Visited Network Preferences	66
4.8.2a	UE Procedures	67
4.8.2a.1	Selection of Active ANDSF Rules	67
4.8.2a.2	UE Behavior Based on the ANDSF Information	68
4.8.2b	WLAN Selection based on WLANSF	70
4.8.3	Reference Points	72
4.8.4	ANDSF Discovery	72
4.8.5	Void	72
4.8.6	Support of RAN Assistance Information	72
4.8.6.1	General	72
4.8.6.2	ANDSF Rules Utilizing RAN Assistance Information	72

4.8.6.3	Evaluation of ANDSF Rules with RAN Validity Conditions	73
4.8.6.4	Co-existence with RAN Rules	74
4.8.7	Support of LWA, LWIP and RCLWI	75
4.8.7.1	General	75
4.8.7.2	Co-existence with LWA and RCLWI	75
4.8.7.3	Co-existence with LWIP	76
4.9	Authentication and Security	76
4.9.1	Access Authentication in non-3GPP Accesses	76
4.9.2	Tunnel Authentication	76
4.9.3	Support for EAP Re-Authentication	76
4.10	QoS Concepts	77
4.10.1	General	77
4.10.2	Void	77
4.10.3	The EPS Bearer with PMIP-based S5/S8 and E-UTRAN access	77
4.10.4	Application of PCC in the Evolved Packet System	78
4.10.5	PDN connectivity service with GTP based S2b.....	79
4.11	Charging for Non-3GPP Accesses	80
4.12	Multiple PDN Support.....	80
4.13	Detach principles.....	81
5	Functional Description and Procedures for 3GPP Accesses with PMIP-based S5/S8.....	81
5.1	Control and User Plane Protocol Stacks.....	81
5.1.1	Void.....	81
5.1.2	General.....	81
5.1.3	Control Plane	82
5.1.3.1	Serving GW - PDN GW.....	82
5.1.4	User Plane.....	83
5.1.4.1	UE – PDN GW User Plane with E-UTRAN.....	83
5.1.4.2	UE – PDN GW User Plane with 2G access via the S4 Interface	84
5.1.4.3	UE – PDN GW User Plane with 3G Access via the S4 Interface	85
5.1.4.4	UE – PDN-GW User Plane with 3G Access via the S12 Interface	85
5.2	Initial E-UTRAN Attach with PMIP-based S5 or S8.....	86
5.3	Detach for PMIP-based S5/S8.....	89
5.4	Dedicated Bearer Procedures for E-UTRAN Access with PMIP-based S5/S8.....	91
5.4.1	General.....	91
5.4.2	Dedicated Bearer Activation.....	92
5.4.3	Bearer Modification with Bearer QoS Update.....	92
5.4.3.1	PCC Initiated Bearer Modification with Bearer QoS Update	92
5.4.3.2	HSS-Initiated Subscribed QoS Modification	92
5.4.4	Dedicated Bearer Modification without Bearer QoS Update.....	93
5.4.5	Dedicated Bearer Deactivation	94
5.4.5.1	PCC-initiated Dedicated Bearer Deactivation.....	94
5.4.5.2	Void.....	94
5.4.5.3	MME-initiated Dedicated Bearer Deactivation.....	94
5.5	UE-initiated Resource Request and Release.....	95
5.6	Multiple PDN Support with PMIP-based S5/S8	96
5.6.1	UE requested PDN connectivity	96
5.6.2	PDN Disconnection	98
5.6.2.1	UE, MME or S-GW initiated PDN Disconnection	98
5.6.2.2	PDN-GW-initiated PDN Disconnection	99
5.7	Handover and Tracking area Update Procedures for PMIP-based S5/S8 Interface.....	100
5.7.0	Intra-LTE TAU and Inter-eNodeB Handover without Serving GW Relocation	100
5.7.1	Intra-LTE TAU and Inter-eNodeB Handover with Serving GW Relocation.....	101
5.7.2	TAU/RAU or Handover between GERAN A/Gb Mode or UTRAN Iu Mode and E-UTRAN.....	102
5.8	ME Identity Check Procedures for PMIP-based S5/S8.....	105
5.9	UE-triggered Service Request for PMIP-based S5/S8	105
5.10	PMIP-based S5/S8 procedures for GERAN/UTRAN over S4.....	106
5.10.1	General.....	106
5.10.2	GPRS procedures that update the PDN GW	107
5.10.3	UE allocated resources.....	108
5.10.4	Network allocated resources	109
5.10.5	UE released resources.....	109

5.10.6	PDN GW released resources.....	109
5.10.7	Attach.....	110
5.10.8	Detach interaction using S4	110
5.10.9	Interaction with CGI/SAI reporting using S4	110
5.10.10	RAU Procedure Support	110
5.11	PDN GW initiated IPv4 address Delete Procedure	110
5.12	Location Change Reporting Procedure for PMIP-based S5/S8.....	112
5.13	Support for Machine Type Communications (MTC).....	112
5.13.1	General.....	112
5.13.2	PDN GW control of overload	113
5.13.3	Usage of low access priority indicator.....	113
6	Functional Description and Procedures for Trusted Non-3GPP IP Accesses	113
6.1	Control and User Plane Protocol Stacks	113
6.1.1	Protocol Stacks for S2a.....	113
6.1.2	Protocol Stacks for S2c over Trusted Non-3GPP IP Accesses	115
6.2	Initial Attach on S2a.....	115
6.2.1	Initial Attach Procedure with PMIPv6 on S2a and Anchoring in PDN GW	115
6.2.2	Void	118
6.2.3	Initial Attach procedure with MIPv4 FACoA on S2a and Anchoring in PDN-GW	118
6.2.4	Initial Attach Procedure with PMIPv6 on S2a and Chained S2a and PMIP-based S8	121
6.3	Initial Attach Procedure with DSMIPv6 on S2c in Trusted Non-3GPP IP Access	122
6.4	Detach and PDN Disconnection for S2a	125
6.4.1	UE/Trusted Non-3GPP IP Access Network Initiated Detach and UE/Trusted Non-3GPP IP Access requested PDN Disconnection Procedure with PMIPv6.....	125
6.4.1.1	Non-Roaming, Home Routed Roaming and Local Breakout Case	125
6.4.1.2	Chained PMIP-based S8-S2a Roaming Case	127
6.4.2	HSS/AAA Initiated Detach Procedure with PMIPv6	128
6.4.2.1	Non-Roaming, Home Routed Roaming and Local Breakout Case	128
6.4.2.2	Chained PMIP-based S8-S2a Roaming Case	129
6.4.3	UE-initiated Detach Procedure and UE-Requested PDN Disconnection Procedure with MIPv4 FACoA.....	130
6.4.4	Network Initiated Detach Procedure with MIPv4 FACoA	131
6.4.5	HSS/AAA-initiated detach procedure with MIPv4 FACoA	132
6.5	Detach and PDN Disconnection for S2c in Trusted Non-3GPP IP Access	133
6.5.1	General.....	133
6.5.2	UE-initiated PDN disconnection Procedure	134
6.5.3	HSS / AAA-initiated Detach Procedure.....	135
6.5.4	PDN GW-initiated PDN Disconnection Procedure	136
6.6	Network-initiated Dynamic PCC	137
6.6.1	Network-initiated Dynamic PCC on S2a	137
6.6.2	Network-initiated Dynamic PCC for S2c over Trusted Non-3GPP IP Access	138
6.7	UE-initiated Resource Request and Release.....	139
6.7.1	UE-initiated Resource Request and Release on S2a	139
6.7.2	UE-initiated Resource Request for S2c over Trusted Non-3GPP IP Access	140
6.8	UE-initiated Connectivity to Additional PDN.....	140
6.8.1	UE-initiated Connectivity to Additional PDN with PMIPv6 on S2a.....	140
6.8.1.0	General	140
6.8.1.1	Non-Roaming, Home Routed Roaming and Local Breakout Case	140
6.8.1.2	Chained PMIP-based S8-S2a Roaming Case	142
6.8.2	UE-initiated Connectivity to Additional PDN with MIPv4 FACoA on S2a.....	143
6.8.3	UE-initiated Connectivity to Additional PDN from Trusted Non-3GPP IP Access with DSMIPv6 on S2c	144
6.9	Void.....	144
6.10	PDN GW reallocation upon attach on S2c	145
6.11	S2c Bootstrapping via DSMIPv6 Home Link over a Trusted Access	146
6.12	PDN GW initiated Resource Allocation Deactivation	146
6.12.1	PDN GW initiated Resource Allocation Deactivation with S2a PMIP.....	146
6.12.2	PDN GW initiated Resource Allocation Deactivation with S2a MIPv4.....	147
6.12.3	PDN GW initiated Resource Allocation Deactivation for Chained PMIP-based S8-S2a Roaming	148
6.12.4	Void	149
6.13	PDN GW initiated IPv4 address Delete Procedure	149

6.14	Non-3GPP access initiated IPv4 address Delete Procedure	150
6.15	IPv4 Home Address Release Procedure for S2c.....	151
6.16	Enhanced security support for S2c	153
6.16.1	General.....	153
6.16.2	Activation of enhanced security for S2c	153
6.16.3	De-activation of enhanced security for S2c	154
7	Functional Description and Procedures for Un-trusted Non-3GPP IP Accesses	155
7.1	Control and User Plane Protocol Stacks.....	155
7.1.1	Protocol Options for S2b	155
7.1.2	Protocol Options for S2c over Un-trusted Non-3GPP IP Accesses	156
7.2	Initial Attach on S2b.....	157
7.2.1	Initial Attach with PMIPv6 on S2b.....	157
7.2.2	Void	159
7.2.3	Initial Attach Procedure with PMIPv6 on S2b and Chained S2b and PMIP-based S8.....	159
7.2.4	Initial Attach with GTP on S2b	159
7.2.5	Initial Attach for emergency session (GTP on S2b)	162
7.3	Initial Attach Procedure for S2c in Untrusted Non-3GPP IP Access	164
7.4	Detach and PDN Disconnection for S2b.....	165
7.4.1	UE/ePDG-initiated Detach Procedure and UE-Requested PDN Disconnection with PMIPv6 on S2b	165
7.4.1.1	Non-Roaming, Home Routed Roaming and Local Breakout Case	165
7.4.1.2	Chained PMIP-based S8-S2b Roaming Case.....	167
7.4.2	HSS/AAA-initiated Detach Procedure with PMIPv6 on S2b	167
7.4.2.1	Non-Roaming, Home Routed Roaming and Local Breakout Case	167
7.4.2.2	Chained PMIP-based S8-S2b Roaming Case.....	167
7.4.3	UE/ePDG-initiated Detach Procedure and UE-Requested PDN Disconnection with GTP on S2b.....	168
7.4.3.1	Non-Roaming, Home Routed Roaming and Local Breakout Case	168
7.4.4	HSS/AAA-initiated Detach Procedure with GTP on S2b.....	169
7.4.4.1	Non-Roaming, Home Routed Roaming and Local Breakout Case	169
7.5	Detach and PDN Disconnection for S2c in Un-trusted Non-3GPP IP Access	170
7.5.1	General.....	170
7.5.2	UE-Initiated PDN disconnection Procedure	170
7.5.3	HSS / AAA-initiated Detach Procedure.....	171
7.5.4	PDN GW-initiated PDN Disconnection Procedure	173
7.6	UE-initiated Connectivity to Additional PDN.....	174
7.6.1	UE-initiated Connectivity to Additional PDN with PMIPv6 on S2b.....	174
7.6.2	UE-initiated Connectivity to Additional PDN from Un-trusted Non-3GPP IP Access with DSMIPv6 on S2c	175
7.6.3	UE-initiated Connectivity to Additional PDN with GTP on S2b	175
7.7	Void.....	176
7.8	S2c Bootstrapping via DSMIPv6 Home Link over an Un-Trusted Access.....	177
7.9	PDN GW initiated Resource Allocation Deactivation	177
7.9.1	PDN GW initiated Resource Allocation Deactivation with PMIPv6 on S2b	177
7.9.2	PDN GW initiated Resource Allocation Deactivation with GTP on S2b	178
7.10	Dedicated S2b bearer activation with GTP on S2b	179
7.11	S2b bearer modification with GTP on S2b.....	181
7.11.1	PDN GW initiated bearer modification	181
7.11.2	HSS Initiated Subscribed QoS Modification	182
8	Handovers without Optimizations Between 3GPP Accesses and Non-3GPP IP Accesses.....	183
8.1	Common Aspects for Handover without Optimizations for Multiple PDNs.....	183
8.2	Handovers between non-3GPP IP access with PMIPv6 on S2a/S2b and 3GPP Access	184
8.2.1	Handover from Trusted or Untrusted Non-3GPP IP Access with PMIPv6 on S2a/S2b to 3GPP Access.....	184
8.2.1.1	General Procedure for GTP based S5/S8 for E-UTRAN Access	184
8.2.1.2	Using PMIP-based S5/S8.....	187
8.2.1.3	General Procedure for GTP-based S5/S8 for UTRAN/GERAN.....	190
8.2.1.4	Using PMIP-based S5/S8.....	193
8.2.2	3GPP Access to Trusted Non-3GPP IP Access Handover with PMIPv6 on S2a	194
8.2.3	3GPP Access to Untrusted Non-3GPP IP Access Handover with PMIPv6 on S2b.....	197
8.2.4	Void	200
8.2.5	Void	200

8.2.6	Non-3GPP IP Access to 3GPP Access Handover with PMIPv6 on S2a/b for Chained PMIP-based S8..	200
8.2.7	3GPP Access to Non-3GPP IP Access Handover with PMIPv6 on S2a/b for Chained PMIP-based S8..	201
8.2.8	Void	204
8.2.9	Void	204
8.3	Handover from 3GPP access to Trusted Non-3GPP IP Access with MIPv4 FACoA on S2a	205
8.3b	Handover from Trusted Non-3GPP IP Access with MIPv4 FACoA on S2a to 3GPP access	207
8.4	Handovers with DSMIPv6 on S2c	208
8.4.1	Trusted or Untrusted Non-3GPP IP Access with DSMIPv6 over S2c to 3GPP Access Handover.....	208
8.4.2	3GPP Access to Trusted Non-3GPP IP Access Handover with DSMIPv6 over S2c.....	209
8.4.3	3GPP Access to Untrusted Non-3GPP IP Access Handover with DSMIPv6 over S2c.....	211
8.5	Handover with Access Network Discovery and Selection	214
8.5.1	Handover between 3GPP Access and Trusted / Untrusted Non-3GPP IP Access with access network discovery and selection	214
8.6	Handovers between non-3GPP IP access with GTP on S2b and 3GPP Access	215
8.6.1	Handover from Untrusted Non-3GPP IP Access with GTP on S2b to 3GPP Access.....	215
8.6.1.1	General Procedure for GTP based S5/S8 for E-UTRAN Access	215
8.6.1.2	General Procedure for GTP-based S5/S8 for UTRAN/GERAN.....	217
8.6.2	Handover from 3GPP access to untrusted Non-3GPP IP Access with GTP on S2b.....	218
8.6.2.1	3GPP Access to Untrusted Non-3GPP IP Access Handover with GTP on S2b.....	218
9	Handovers with Optimizations Between E-UTRAN Access and CDMA2000 Access	221
9.1	Architecture and Reference Points	221
9.1.1	Architecture for Optimized Handovers between E-UTRAN Access and cdma2000 HRPD Access.....	221
9.1.2	Reference Points	222
9.1.2.1	Reference Point List	222
9.1.2.2	Requirements for the S101 Reference Point	222
9.1.2.3	S101 Protocol Stack	223
9.1.2.4	S101 Session Identifier	223
9.1.2.5	Requirements for the S103 Reference Point	223
9.1.2.6	S103 Protocol Stack	223
9.2	Overview of Handover Procedures	224
9.2.1	General.....	224
9.2.2	Support for HO of IMS Emergency Sessions	224
9.3	Optimized Active Handover: E-UTRAN Access to cdma2000 HRPD Access.....	225
9.3.0	Introduction.....	225
9.3.1	Pre-registration Phase	225
9.3.2	Handover Phase	228
9.4	Optimized Idle-mode Mobility: E-UTRAN Access to cdma2000 HRPD Access.....	231
9.5	Void.....	232
9.5.1	Void	232
9.5.2	Void	232
9.6	Void.....	232
9.7	S101 Tunnel Redirection Procedure.....	232
10	Handovers with Optimizations Between 3GPP Accesses and Mobile WiMAX.....	234
10.1	Optimizations for network-controlled dual radio handover	234
10.1.1	General Principles.....	234
11	Handover Optimizations Applicable to All Non-3GPP Accesses.....	234
12	Interactions Between HSS and AAA Server	235
12.0	General	235
12.1	Location Management Procedures	235
12.1.1	UE Registration Notification	235
12.1.2	AAA-initiated UE De-registration Notification.....	236
12.1.3	HSS-initiated UE De-registration Notification	236
12.1.4	PDN GW Identity Notification from AAA Server	237
12.1.5	PDN GW Identity Notification from MME/SGSN.....	238
12.2	Subscriber Profile Management Procedures.....	239
12.2.1	HSS-initiated User Profile Update Procedure.....	239
12.2.2	AAA-initiated Provide User Profile Procedure.....	239
12.3	Authentication Procedures.....	240
13	Information Storage.....	240

13.0	General	240
13.1	HSS	240
13.2	MME	241
13.3	S-GW	241
13.4	Handling of Wild Card APN	241
13.5	ePDG	241
13.6	TWAN	242
14	Void	242
15	Functional Description and Procedures for 3GPP Accesses with S2c	242
15.1	S2c Bootstrapping via DSMIPv6 Home Link	242
16	Architecture, Functional description and Procedures for GTP and PMIPv6 based S2a over Trusted WLAN Access	244
16.1	Architecture and Functional Description	244
16.1.1	Architecture	244
16.1.2	High level functions	246
16.1.3	Reference points	248
16.1.3.1	STa reference point	248
16.1.3.2	SWw reference point	249
16.1.3.3	S2a reference point	249
16.1.4	Protocol Stacks	249
16.1.4A	Control Plane	252
16.1.4A.1	Negotiation of connection mode	252
16.1.4A.2	EAP-AKA' extensions	253
16.1.4A.3	PDN connection management Control plane	253
16.1.4A.3.1	WLAN Control Protocol (WLCP)	253
16.1.4B	User plane	254
16.1.4B.1	User plane for PDN connection	254
16.1.5	IP address allocation	254
16.1.5.1	General	254
16.1.5.2	IP address allocation in Transparent Single-Connection Mode	255
16.1.5.3	IP address allocation in Single-Connection Mode	255
16.1.5.4	IP address allocation in Multi-Connection Mode	256
16.1.6	Bearer model for PDN connectivity service with GTP based S2a	257
16.1.7	Access Network information reporting in case of a TWAN Access	257
16.2	Initial Attach in WLAN on S2a	259
16.2.1	Initial Attach in WLAN on GTP S2a	259
16.2.1a	Initial Attach in WLAN for Emergency Service on GTP S2a	264
16.2.2	Initial Attach in WLAN on PMIP S2a	267
16.2.3	HSS retrieval of information about an UE from the TWAN serving that UE	268
16.3	Detach and PDN disconnection in WLAN on S2a	269
16.3.1	Detach and PDN disconnection in WLAN on GTP S2a	269
16.3.1.1	UE/TWAN Initiated Detach and UE/TWAN requested PDN Disconnection Procedure in WLAN on GTP S2a	269
16.3.1.2	HSS/AAA Initiated Detach Procedure in WLAN on GTP S2a	270
16.3.2	Detach and PDN disconnection in WLAN on PMIP S2a	271
16.3.2.1	UE/TWAN Initiated Detach and UE/TWAN requested PDN Disconnection Procedure in WLAN on PMIP S2a	271
16.3.2.2	HSS/AAA Initiated Detach Procedure in WLAN on PMIP S2a	271
16.4	PDN GW initiated Resource Allocation Deactivation in WLAN on S2a	272
16.4.1	PDN GW initiated Resource Allocation Deactivation in WLAN on GTP S2a	272
16.4.2	PDN GW initiated Resource Allocation Deactivation in WLAN on PMIP S2a	273
16.5	Dedicated bearer activation in WLAN on GTP S2a	273
16.6	Network-initiated bearer modification in WLAN on GTP S2a	275
16.6.1	PDN GW Initiated Bearer Modification	275
16.6.2	HSS Initiated Bearer Modification	276
16.7	Detach in WLAN on S2a for Multi-connection Mode	277
16.7.1	Detach in WLAN on GTP S2a	277
16.7.1.1	UE/TWAN Initiated Detach Procedure in WLAN on GTP S2a	277
16.7.1.2	HSS/AAA Initiated Detach Procedure in WLAN on GTP S2a	278
16.7.2	Detach in WLAN on PMIP S2a	278

16.7.2.1	UE/TWAN Initiated Detach Procedure in WLAN on PMIP S2a.....	278
16.7.2.2	HSS/AAA Initiated Detach Procedure in WLAN on PMIP S2a.....	279
16.8	UE Initiated PDN connectivity request procedure in WLAN on S2a for Multi-connection Mode	279
16.8.1	Supporting GTP S2a	279
16.8.2	Supporting PMIP S2a	281
16.9	UE/TWAN Initiated PDN disconnection for Multi-connection Mode.....	282
16.9.1	Supporting GTP S2a	282
16.9.2	Supporting PMIP S2a	283
16.10	Handover procedure from 3GPP access to WLAN on S2a	283
16.10.1	Handover procedure from 3GPP access to WLAN on S2a in single-connection mode.....	283
16.10.1.1	Handover in single-connection mode from 3GPP access to WLAN on GTP S2a	283
16.10.1.2	Handover in single-connection mode from 3GPP access to WLAN on PMIP S2a.....	286
16.10.2	Handover procedure from 3GPP access to WLAN on S2a in multi-connection mode.....	287
16.10.2.1	Handover in multi-connection mode from 3GPP access to WLAN on GTP S2a	287
16.10.2.2	Handover in multi-connection mode from 3GPP access to WLAN on PMIP S2a.....	289
16.11	Handover procedure from WLAN on S2a to 3GPP access	289
17	E-UTRAN-HRPD Inter-RAT SON Support.....	290
17.1	Architecture and Interface	290
17.1.1	Architecture for E-UTRAN-HRPD Inter-RAT SON Support	290
17.1.2	Reference Points	290
17.1.2.1	Reference Point List	290
17.1.2.2	Requirements for the S121 interface	290
17.1.2.3	S121 Protocol Stack	290
Annex A (informative):	GTP - PMIP Roaming	292
A.1	Direct Peering Scenario.....	292
A.2	Proxy-based interworking	294
Annex B (informative):	Guidance for Contributors to this Specification	296
Annex C (informative):	Handover Flows Between Non-3GPP Accesses.....	297
C.1	General	297
C.2	Trusted Non-3GPP IP Access to Trusted Non-3GPP IP Access with DSMIPv6 over S2c Handover	297
C.3	Untrusted Non-3GPP IP Access with PMIPv6 to Trusted Non-3GPP IP Access with PMIPv6 Handover in the Non-Roaming Scenario	298
C.4	Trusted/Untrusted Non-3GPP IP Access with DSMIPv6 to Trusted Non-3GPP IP Access with PMIPv6 Handover in the Non-Roaming Scenario	299
C.5	Handover Between Two Untrusted Non-3GPP IP Accesses Connected to the Same ePDG.....	301
C.6	Handovers between APs of a Non-3GPP Trusted WLAN Access on S2a.....	302
Annex D (informative):	Void	303
Annex E (informative):	Gateway Relocation in the Trusted Non-3GPP IP Access	304
E.1	Gateway Relocation with PMIPv6 on S2a	304
E.2	Gateway Relocation with MIPv4 FACoA on S2a.....	305
Annex F (informative):	Deployment of Non-3GPP Trusted WLAN Access on S2a	307
Annex G (informative):	Change History	308
History		310

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

Guidance to Readers of this Specification

In order to reduce the number of procedures in this specification certain editorial practices have been adopted. Though there are many independent factors, such as variants of S5/S8/S2b and attachment cases, these are in essence quite similar. So, rather than presenting the permutations of these factors separately and thereby needlessly repeating normative text, conventions have been adopted to combine this information in single procedures.

The S5 and S8 reference points in the EPC architecture have been defined to have both a GTP and PMIP variant. The GTP variant is documented in TS 23.401 [4], while the PMIP variant is documented in this specification. Every effort has been made to eliminate duplication of normative text common to both specifications. Many figures in this specification refer to procedures in TS 23.401 [4] to achieve this end. Common procedures between TS 23.401 [4] and TS 23.402 (this specification), are represented in this specification in figures by text in shaded box(es) that reference the appropriate figure and steps in TS 23.401 [4]. The details of the common steps are only captured in TS 23.401 [4].

The S2b reference point in the EPC architecture has also been defined to have both a GTP and PMIP variant. Both variants are documented in this specification. Every effort has been made to eliminate duplication of normative text common to both variants. Figures for the GTP variant of S2b refer to figures defined for the PMIP variant of S2b to achieve this end. Common procedures for both variants are represented in figures for GTP based S2b by text in shaded box(es) that reference the appropriate figure and steps defined for PMIP based S2b. The details of the common steps are only captured for the PMIP variant of S2b.

Attachment cases (as discussed in clauses 6.2.1 and 7.2.1) have been combined in a single figure. The different attachment cases can be accommodated by including optional items in the flows, for instance, a vPCRF that is only employed during when a roaming case or LBO is specified.

Multiple APN interactions may occur for many of the procedures defined in this specification. These interactions complicate the flows by introducing certain operations that may occur multiple times. Rather than produce unique flows for this purpose, we indicate where this possibility may occur in text.

1 Scope

This document specifies the stage 2 service description for providing IP connectivity using non-3GPP accesses to the Evolved 3GPP Packet Switched domain. In addition, for E-UTRAN and non-3GPP accesses, the specification describes the Evolved 3GPP PS Domain where the protocols between its Core Network elements are IETF-based.

ITU-T Recommendation I.130 [2] describes a three-stage method for characterisation of telecommunication services, and ITU-T Recommendation Q.65 [3] defines stage 2 of the method.

The specification covers both roaming and non-roaming scenarios and covers all aspects, including mobility between 3GPP and non 3GPP accesses, policy control and charging, and authentication, related to the usage of non-3GPP accesses.

TS 23.401 [4] covers architecture aspects common to the Evolved 3GPP Packet Switched domain.

The procedures defined in the present document for WLAN access selection and PLMN selection replace the corresponding I-WLAN procedures specified in TS 23.234 [5].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] ITU-T Recommendations I.130: "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [3] ITU-T Recommendation Q.65: "The unified functional methodology for the characterization of services and network capabilities".
- [4] 3GPP TS 23.401: "General Packet Radio Service (GPRS) Enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) access".
- [5] 3GPP TS 23.234: "3GPP System to Wireless Local Area Network (WLAN) Interworking; System Description".
- [6] 3GPP TS 36.300: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description Stage 2".
- [7] Void.
- [8] IETF RFC 5213: "Proxy Mobile IPv6".
- [9] IETF RFC 5996: "Internet Key Exchange Protocol Version 2 (IKEv2)".
- [10] IETF RFC 5555: "Mobile IPv6 support for dual stack Hosts and Routers (DSMIPv6)".
- [11] IETF RFC 3748: "Extensible Authentication Protocol (EAP)".
- [12] IETF RFC 5944: "IP Mobility Support for IPv4, revised".
- [13] Void.