

BSI Standards Publication

Aerospace series - Cables, electrical, for general purpose, single and multicore assembly - XLETFE Family - Jacketed or screened and jacketed

Part 005: Tin plated copper - Operating temperatures, between - 65°C and 135°C - Dual extruded wall for open applications, with jacket without screen - UV laser printable - Product standard



BS EN 4612-005:2019 BRITISH STANDARD

National foreword

This British Standard is the UK implementation of EN 4612-005:2019. It supersedes BS EN 4612-005:2011, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee ACE/6, Aerospace avionic electrical and fibre optic technology.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019 Published by BSI Standards Limited 2019

ISBN 978 0 539 03573 5

ICS 49.060

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 August 2019.

Amendments/corrigenda issued since publication

Date Text affected

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 4612-005

August 2019

ICS 49.060

Supersedes EN 4612-005:2011

English Version

Aerospace series - Cables, electrical, for general purpose, single and multicore assembly - XLETFE Family - Jacketed or screened and jacketed - Part 005: Tin plated copper - Operating temperatures, between - 65 °C and 135 °C - Dual extruded wall for open applications, with jacket without screen - UV laser printable - Product standard

Série aérospatiale - Câbles, électriques, d'usage général, mono et multiconducteurs - Famille XLETFE - Gainés ou blindés et gainés - Partie 005 : Cuivre étamé - Températures de fonctionnement comprises entre - 65 °C et 135 °C - Fil double isolé pour applications externes, gainé non blindé - Marquable au laser UV - Norme de produit

Luft- und Raumfahrt - Ein- und mehradrige elektrische Leitungen zur allgemeinen Verwendung - XLETFE-Familie - Ummantelt oder geschirmt und ummantelt -Teil 005: Kupfer verzinnt - Betriebstemperaturen zwischen -65 °C und 135 °C - doppelt extrudierte Isolierung für offene Anwendungen, ummantelt ohne Schirm - UV-Laser bedruckbar - Produktnorm

This European Standard was approved by CEN on 5 May 2019.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword		Page	
		3	
1	Scope		
2	Normative references	4	
3	Terms, definitions and symbols	4	
4	Materials and construction	5	
5	Required characteristics	6	
6	Quality assurance	8	
7	Designation	8	
8	Identification and marking	8	
9	Packaging, labelling and delivery lengths	8	
10	Technical specification	8	

European foreword

This document (EN 4612-005:2019) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by February 2020, and conflicting national standards shall be withdrawn at the latest by February 2020.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 4612-005:2011.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

1 Scope

This document specifies the characteristics of UV laser printable jacket, tin plated copper conductor, electrical cables, Crosslinked Ethylene Tetra Fluoro Ethylene co-polymer XLETFE family for use in the on-board electrical systems of aircraft at operating temperatures between – $65\,^{\circ}$ C and $135\,^{\circ}$ C operating at voltages not exceeding $600\,V$ rms at sea level. This insulation system has been used in aerospace applications using $115\,V$ (phase-to-neutral) $400\,Hz$ ac and $28\,Vdc$. Verification of the suitability of cables for use in other electrical systems is the responsibility of the user.

These cables are suitable for airframe use without additional protection. In case of conflict between this standard and other referenced documents the requirements of this standard shall take precedence.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 2235, Aerospace series — Single and multicore electrical cables, screened and jacketed — Technical specification

EN 3475-100 (all parts), Aerospace series — Cables, electrical, aircraft use — Test methods — Part 100: General

EN 4611-004, Aerospace series — Cables, electrical, for general purpose, single and multicore assembly — XLETFE Family — Part 004: Tin plated copper — Operating temperatures, between – 65 °C and 135 °C — Dual extruded wall for open applications — UV laser printable — Product standard

EN 4612-002, Aerospace series — Cables electrical, for general purpose, single and multicore assembly — XLETFE Family — Jacketed or screened and jacketed — Part 002: General

EN 9133, Aerospace series — Quality Management Systems — Qualification Procedure for Aerospace Standard Products

3 Terms, definitions and symbols

For the purposes of this document, the terms, definitions and symbols given in EN 3475-100 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp