American National Standard



Performance Requirements for

Trap Seal Primer – Drainage Types and Electric Design Types

ASSE Board Approved: February 2023

ANSI Approved: April 2023

ICS Codes: 23.060.99 | 91.140.70





General Information

Neither this standard, nor any portion thereof, may be reproduced without the written consent of ASSE International.

No product may be said to be listed by ASSE unless the manufacturer has applied to ASSE International, has had the product tested according to the applicable standards, and when the product has passed the test, displays the ASSE Seal on the product.

Instructions for receiving the authorization to display the seal are available from the ASSE International office. Organizations wishing to adopt or list any ASSE standard should print the ASSE standard number on the cover page first in equal or larger type to that of the adopting or listing organization.

ASSE International Mokena, IL Copyright © 2023, 2015, 2001, 1986 All rights reserved.

Foreword

This foreword shall not be considered a part of the standard. However, it is offered to provide background information.

ASSE standards are developed in the interest of consumer safety. The ASSE Product Standards Committee encourages manufacturers to develop performance requirement standards and testing procedures for their products. These standards have the consensus of the manufacturers and others who have pertinent interests in plumbing systems and are acceptable to this organization.

For many years, the method of priming traps has been with the use of a water supply trap primer, which is activated by flow in the water supply piping. This method of priming utilizes primers that comply with ASSE 1018, Performance Requirements for Trap Seal Primer Valves – Potable Water Supplied. This standard addresses alternate methods to ASSE 1018 and addresses trap primers utilizing electric design and drainage-type trap seal primers.

Although many of the material specifications are detailed within Section 5.1 of this standard, it is the responsibility of the manufacturer and the installer to comply with the relevant jurisdictional requirements.

The ASSE 1044 working group, which developed this standard revision, was set up within the framework of the ASSE International Product Standards Committee.

Recognition is made of the time volunteered by members of the working group and of the support of the manufacturers, who also participated in the meetings for this standard.

This standard does not imply ASSE International's endorsement of a product that conforms to these requirements. Compliance with this standard does not imply acceptance by any code body.

It is recommended that these trap seal primers be installed, consistent with local codes, by qualified and trained professionals.

This standard was promulgated in accordance with procedures developed by the American National Standards Institute (ANSI).

2022 Product Standards Committee

Tsan-Liang Su, PhD – Chairman Stevens Institute of Technology Hoboken, NJ, USA

Karl Abrahamson

Saint Paul Department of Safety and Inspections Cottage Grove, MN, USA

John Bertrand

Watts Water Technologies Cleveland, OH, USA

Julia Briggs

NSF International Ann Arbor, MI, USA

William Briggs Jr.

TSF Engineering New York, NY, USA

Terry Burger (non-voting)

ASSE International Cleveland, OH, USA

William Chapin

Professional Code Consulting, LLC Cullman, AL, USA

Mark E. Fish

Zurn Industries, LLC Cary, NC, USA

Fernando Fernandez

Toto USA Inc. Ontario, CA, USA

Ron George

Plumb-Tech Design & Consulting Services LLC Newport, MI, USA

Mark Gibeault

Kohler Company Kohler, WI, USA

Daniel Gleiberman

Sloan Valve Company Los Angeles, CA, USA **Brandon Gunnell**

Precision Plumbing Products Portland, OR, USA

Chris Haldiman

Watts Water Technologies Springfield, MO, USA

John F. Higdon, P.E.

Supply Source Products Matthews, NC, USA

Jim Kendzel

American Supply Association Itasca, IL, USA

Ramiro Mata

ASPE

Mentor, OH, USA

Bob Neff

Delta Faucet Pendleton, IN, USA

David Orton

NSF International Ann Arbor, MI, USA

Thomas Pitcherello

Self

Bordentown, NJ, USA

Daniel Rademacher

Viega, LLC Butte, MT, USA

Shabbir Rawalpindiwala

Self

Kohler, WI, USA

Billy Smith

ASPE

Montgomery, AL, USA

Chris Wright

Ontario Pipe Trades Council Dundalk, ON, Canada

Chris White (non-voting)

ASSE International Mokena, IL, USA

1044 Working Group

Robert Burnham

Zurn Industries, LLC Erie, PA, USA

Terry Burger (non-voting)

ASSE International Cleveland, OH, USA

Brandon Gunnell

Precision Plumbing Products Portland, OR, USA

Mark Fish

Zurn Industries, LLC Cary, NC, USA

Dan Gleiberman

Sloan Valve Company Los Angeles, CA, USA

Kevin Hardwick

Precision Plumbing Products Portland, OR, USA

Ramiro Mata

ASPE

Mentor, OH, USA

Jerry McDanal

Jay R. Smith Mfg. Co. Montgomery, AL, USA

Anthony Stanaland

Jay R. Smith Mfg. Co. Montgomery, AL, USA

Contents

1.0	General	
	1.1	Application
	1.2	Scope
	1.3	Reference Standards
2.0	Test Specimens	
	2.1	Sample Selection
	2.2	Drawings
	2.3	Rejection
3.0	General	
	3.1	Fixture Tailpiece Trap Seal Primers
	3.2	Fill Valve (Ballcock) Trap Seal Primers
	3.3	Flushometer Tailpiece/Trap Seal Primers
	3.4	Electric Trap Seal Primers
	3.5	Multiport Electric Trap Primers
	3.6	Backflow Protection
	3.7	Trap Primer Adapter
4.0	Performance Requirements and Compliance Testing	
	4.1	Hydrostatic Test for Electric Type Trap Primer
	4.2	Verification of Manufacturer's Performance Rating
	4.3	Cycle Test for Electric Trap Seal Primer
	4.4	Trap Primer Adapter Leakage Test
5.0	Detailed Requirements	
	Figure 1	
	5.1	Materials
	5.2	Documentation
	5.3	Markings
6.0	Definitions9	
	Figure 2	

ASSE/ANSI 1044-2023 Trap Seal Primer – Drainage Types and Electric Design Types

1.0 General

1.1 Application

Trap seal primers are primarily designed to supply water to floor drain traps that have infrequent use and in which water evaporation would allow sewer gas to enter the premises.

The trap seal primers covered by this standard are designed to supply water to a drain trap to provide and maintain its water seal by using a supply from a fixture drain line, fill valve (ballcock), flushometer valve tailpiece or an electric trap seal primer. The rate of water flow to the trap shall be permitted to be fixed or adjustable.

1.2 Scope

1.2.1 Description

This standard covers trap primers used in conjunction with fill valves and flushometer valves, electrical trap primers and trap primer adapters, and specifies requirements for materials, physical characteristics, performance testing, and markings.

The trap seal primers are of 4 types:

- a) Those that are installed on waste line tail pieces from fixtures, such as lavatories, sinks and similar fixtures where grease is not normally generated;
- b) Those that are used in conjunction with fill valve (ballcock) assemblies;
- c) Those that receive flow from flushometer valves; and
- d) Those electric trap seal primers that discharge water automatically and are upstream of the air gap or vacuum breaker.

1.2.2 Working Pressure

Pressurized trap seal primers covered by this standard are designed for a working water pressure range of 25 to 125 psi (172 to 862 kPa).

1.2.3 Connections

- **1.2.3.1** Tapered pipe threads shall comply with ASME B1.20.1.
- **1.2.3.2** Dry seal pipe threads shall comply with ASME B1.20.3.
- **1.2.3.3** Compression assemblies shall comply with SAE J 512.
- **1.2.3.4** Solder connection fittings shall comply with ASME B16.18, ASME B16.22, ASME B16.23 or ASME B16.29.

1.3 Reference Standards

- ASME A112.1.2-2022, Air Gaps in Plumbing Systems (For Plumbing Fixtures and Water-Connected Receptors
- ASME B1.20.1-2018, Pipe Threads, General Purpose (Inch)
- ASME B1.20.3-1976 (R2018), Dryseal Pipe Threads (Inch)
- ASME B16.18-2021, Cast Copper Alloy Solder Joint Pressure Fittings
- ASME B16.22-2021, Wrought Copper and Copper Alloy Solder-Joint Pressure Fittings
- ASME B16.23-2021, Cast Copper Alloy Solder Joint Drainage Fittings: DWV