BS EN ISO 10819:2013+A1:2019 Incorporating corrigendum August 2015



BSI Standards Publication

Mechanical vibration and shock - Handarm vibration - Measurement and evaluation of the vibration transmissibility of gloves at the palm of the hand

bsi.

National foreword

This British Standard is the UK implementation of EN ISO 10819:2013+A1:2019. It is identical to ISO 10819:2013, incorporating amendment 1:2019. It supersedes BS EN ISO 10819:2013, which is withdrawn.

The start and finish of text introduced or altered by amendment is indicated in the text by tags. Tags indicating changes to ISO text carry the number of the ISO amendment. For example, text altered by ISO amendment A1 is indicated by A1 (A1).

The UK participation in its preparation was entrusted to Technical Committee GME/21/6, Mechanical vibration, shock and condition monitoring - Human exposure to mechanical vibration and shock.

A list of organizations represented on this committee can be obtained on request to its secretary.

BSI, as a member of CEN, is obliged to publish EN ISO 10819:2013+A1:2019 as a British Standard. However, attention is drawn to the fact that during the development of this European Standard, the UK committee voted against its approval.

The UK Technical Committee GME/21/6, which includes technical specialists from the Health and Safety Executive, agrees that gloves passing the test defined in this standard do not normally provide any protection from vibration, and can increase the risk from vibration transmitted to the fingers.

In the opinion of the UK committee, the pictogram defined in this standard (Figure B.1) does not convey appropriate information on the control of vibration risk. It cannot replace a risk assessment by the employer or guarantee conformity with health and safety regulations.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019 Published by BSI Standards Limited 2019

ISBN 978 0 580 97498 4

ICS 13.340.40; 17.160; 13.160

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2013.

Amendments/corrigenda issued since publication

Date	Text affected
31 August 2015	Implementation of CEN Correction Notice 7 August 2013: the European foreword now contains infor- mation regarding the background of the project
28 February 2019	Implementation of ISO amendment 1:2019 with CEN endorsement A1:2019

EUROPEAN STANDARD

NORME EUROPÉENNE

EN ISO 10819:2013 +A1

EUROPÄISCHE NORM

February 2019

ICS 13.340.40; 13.160

English Version

Mechanical vibration and shock - Hand-arm vibration - Measurement and evaluation of the vibration transmissibility of gloves at the palm of the hand (ISO 10819:2013)

Vibrations et chocs mécaniques - Vibrations main-bras - Mesurage et évaluation du facteur de transmission des vibrations par les gants à la paume de la main (ISO 10819:2013) Mechanische Schwingungen und Stöße - Hand-Arm-Schwingungen - Messung und Bewertung der Schwingungsübertragung von Handschuhen in der Handflächez ISO 10819:2013)

This European Standard was approved by CEN on 29 May 2013.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

© 2019 CEN

All rights of exploitation in any form and by any means reserved worldwide for CEN national Members Ref. No. EN ISO 10819:2013+A1:2019: E

European foreword

This document (EN ISO 10819:2013) has been prepared by Technical Committee ISO/TC 108 "Mechanical vibration, shock and condition monitoring" in collaboration with Technical Committee CEN/TC 231 "Mechanical vibration and shock" the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2014, and conflicting national standards shall be withdrawn at the latest by January 2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 10819:1996.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive.

For relationship with EU Directive, see informative <u>Annex ZA</u>, which is an integral part of this document.

The main changes to the first edition EN ISO 10819:1996 are stronger criteria for antivibration gloves and the addition of a method for measuring the material thickness.

To place anti-vibration gloves on the market of the European Union (EU), manufacturers or their authorised representatives established within the EU shall make sure that they cover all Basic Health and Safety Requirements (BHSRs) applicable to their products under the foreseeable conditions of use for which such Personal Protective Equipment (PPE) is intended (EU Directive 89/686/EEC on PPE). If the relevant harmonized European Standards do not cover all applicable BHSRs they have, in addition to the application of these standards, to assess the conformity to those BHSRs not covered by using other relevant technical specifications and test methods.

This European Standard EN ISO 10819 is intended to confirm the vibration reducing properties of gloves placed on the EU market as anti-vibration gloves.

To mark anti-vibration gloves with the CE conformity mark they must also satisfy the BHSRs of the PPE Directive using harmonised European Standards, such as EN 388 and EN 420. As such, manufacturers or their authorised representatives established within the EU shall make an application for type-examination to an approved inspection body (notified body).

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 10819:2013 has been approved by CEN as EN ISO 10819:2013 without any modification.

Foreword to amendment A1

This document (EN ISO 10819:2013/A1:2019) has been prepared by Technical Committee ISO/TC 108 "Mechanical vibration, shock and condition monitoring" in collaboration with Technical Committee CEN/TC 231 "Mechanical vibration and shock" the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 2019, and conflicting national standards shall be withdrawn at the latest by August 2019.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For the relationship with EU Directive(s), see informative <u>Annex ZA</u>, which is an integral part of this document.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 10819:2013/Amd 1:2019 has been approved by CEN as EN ISO 10819:2013/A1:2019 without any modification.

Annex ZA

(informative)

Relationship between this European Standard and the essential health and safety requirements of Regulation (EU) 2016/425 aimed to be covered

This European Standard has been prepared under a Commission's standardization request to provide one voluntary means of conforming to essential health and safety requirements of Regulation (EU) 2016/425 of the European parliament and of the council of 9 March 2016 on personal protective equipment.

Once this standard is cited in the Official Journal of the European Union under that Regulation, compliance with the normative clauses of this standard given in Table ZA.1 confers, within the limits of the scope of this standard, a presumption of conformity with the corresponding essential health and safety requirements of that Regulation, and associated EFTA regulations.

Table ZA.1 — Correspondence between this European Standard and Annex II of Regulation(EU) 2016/425

Essential health and safety re- quirements of Regulation (EU) 2016/425	Clauses of this EN	Remarks/Notes
3.1.3. Mechanical vibration	Clause 9, Clause 10 and Annex B.	None.

WARNING 1 Presumption of conformity stays valid only as long as a reference to this European Standard is maintained in the list published in the Official Journal of the European Union. Users of this standard should consult frequently the latest list published in the Official Journal of the European Union.

WARNING 2 Other Union legislation may be applicable to the product(s) falling within the scope of this standard.

BS EN ISO 10819:2013+A1:2019 ISO 10819:2013+A1:2019

Contents

Introduction viii 1 Scope 1 2 Normative references 1 3 Terms and definitions 2 4 Symbols and abbreviations 2 5 Measuring principle and equipment 3 5.1 General principle and setup 3 5.1 General requirements 4 5.2.2 Transducer mounting 44 5.2.3 Frequency analyses 5 5.2.4 Grip force measuring system 5 5.3 Vibration excitation system 6 5.3.2 Position of the excitation system 7 6.1 Measurement conditions 7 6.1.1 Test subjects 7 6.1.2 Test gloves 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the pain adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 12 6.3.1 Prest condit	Fore	eword		vii			
1 Scope 1 2 Normative references 1 3 Terms and definitions 2 4 Symbols and abbreviations 2 5 Measuring principle and setup 3 5.1 General principle and setup 3 5.2 Measuring cquipment 4 5.2.1 General requirements 4 5.2.2 Transducer mounting 4 5.2.3 Frequency analyses 5 5.3.4 Grip force measuring system 5 5.3 Vibration excitation system 6 5.3.1 Characteristics of the instrumented handle 6 5.3.2 Position of the excitation system 7 6.1 Measurement conditions 7 6.1.1 Test subjects 7 6.1.2 Test gloves 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the paim adaptor in glove vibration transmissibility tests 8 6.2 Vibration exignal 12 6.3	Intr	oductio	n	viii			
2 Normative references 1 3 Terms and definitions 2 4 Symbols and abbreviations 2 5 Measuring principle and equipment 3 5.1 General principle and setup 3 5.2 Measuring equipment 4 5.2.1 General requirements 4 5.2.2 Transducer mounting 4 5.2.3 Frequency analyses 5 5.2.4 Grip force measuring system 5 5.3 Vibration excitation system 6 5.3.1 Characteristics of the instrumented handle 6 5.3.2 Preoformance 7 6.1 Measurement conditions and procedure 7 6.1.1 Test subjects 7 6.1.2 Test gloves 7 6.1.3 Test subject's posture 7 6.1.4 Test subject's posture 7 6.1.5 Preparation 11 6.3.1 Preparation 11 6.3.2 Measurements with he bare adaptor 11 6.3.3 Required numb							
3 Terms and definitions 2 4 Symbols and abbreviations 2 5 Measuring principle and equipment 3 5.1 General requirements 4 5.2.1 General requirements 4 5.2.2 Transducer mounting 4 5.2.3 Frequency analyses 5 5.4 Grip force measuring system 5 5.3 Vibration excitation system 6 5.3.1 Characteristics of the instrumented handle 6 5.3.2 Position of the excitation system 7 5.3 Performance 7 6 Measurement conditions 7 6.1.1 Test subject's posture 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 6.3 Test procedure 11 6.3.1 Preparation 11 6.3.1 Preparation 12 7.1	2	-	•				
4 Symbols and abbreviations 2 5 Measuring principle and setup 3 5.1 General principle and setup 3 5.2 Measuring equipment 4 5.2.1 General requirements 4 5.2.2 Transducer mounting 5 5.2.3 Frequency analyses 5 5.2.4 Grip force measuring system 5 5.2.5 Feed force measuring system 6 5.3 Vibration excitation system 6 5.3.1 Characteristics of the instrumented handle 6 5.3.2 Performance 7 6.1 Measurement conditions and procedure 7 6.1.2 Test subjects 7 6.1.3 Test conditions 7 6.1.4 Test subjects 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 6.3 Test procedure 11 6.3.2 Resurements with the bare adaptor 11 6.3.3 Measurements with gloved hand 12 <th></th> <th></th> <th colspan="4"></th>							
5 Measuring principle and setup 3 5.1 General principle and setup 3 5.2 Measuring equipment 4 5.2.1 General requirements 4 5.2.2 Transducer mounting 4 5.2.3 Frequency analyses 5 5.2.4 Grip force measuring system 5 5.3.2 Vibration excitation system 6 5.3.1 Characteristics of the instrumented handle 6 5.3.2 Position of the excitation system 7 5.3.3 Performance 7 6 Measurement conditions 7 6.1.1 Test subjects 7 6.1.2 Test gloves 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 11 6.3.3 Preparation 11 6.3.4 Measurements with proved hand 12 6.3 Test procedure 12 <td< td=""><td>_</td><td></td><td colspan="5"></td></td<>	_						
5.1 General principle and setup. 3 5.2 Measuring equipment. 4 5.2.1 General requirements 4 5.2.2 Transducer mounting 4 5.2.3 Frequency analyses 5 5.2.4 Grip force measuring system 5 5.2.5 Feed force measuring system 5 5.3.1 Characteristics of the instrumented handle 6 5.3.2 Position of the excitation system 7 5.3.3 Performance 7 6.1 Measurement conditions and procedure 7 6.1.1 Test subjects 7 6.1.2 Test subjects 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 9.3 Test procedure 11 6.3.1 Preparation 11 6.3.2 Reasurements with gloved hand 12 6.3.4 Measurements with gloved hand 12	-	-					
5.2 Measuring equipment 4 5.2.1 General requirements 4 5.2.2 Transducer mounting 4 5.2.3 Frequency analyses 5 5.2.4 Grip force measuring system 5 5.3.1 Characteristics of the instrumented handle 6 5.3.1 Characteristics of the instrumented handle 6 5.3.2 Position of the excitation system 7 5.3.3 Performance 7 6.1 Measurement conditions and procedure 7 6.1.1 Test subjects 7 6.1.2 Test subject's posture 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 6.3 Test subject's posture 7 6.1.4 Test subject's aposture 11 6.3.1 Preparation 11 6.3.2 Measurements with the bare adaptor 111 6.3.3 Required number of tests	5						
5.2.1 General requirements 4 5.2.2 Transducer mounting 4 5.2.3 Frequency analyses 5 5.2.4 Grip force measuring system 5 5.3 Vibration excitation system 6 5.3 Vibration excitation system 6 5.3 Desition of the excitation system 7 5.3 Performance 7 6.1 Measurement conditions 7 6.1.1 Test subjects 7 6.1.2 Test subjects 7 6.1.3 Test subject's posture 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 9 6.3 Test procedure 11 6.3.4 Measurements with gloved hand 12 6.3 Measurements with gloved hand 12 6.3.4 Measurements with resilient material 12 6.3.5 Required number of tests 12 7 Calculation of results 12							
5.2.2 Transducer mounting 4 5.2.3 Frequency analyses 5 5.2.4 Grip force measuring system 5 5.2.5 Feed force measuring system 5 5.3 Vibration excitation system 6 5.3.1 Characteristics of the instrumented handle 6 5.3.2 Position of the excitation system 7 5.3.3 Performance 7 6.1 Measurement conditions and procedure 7 6.1.1 Test subjects 7 6.1.2 Test conditions 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 6.3 Test procedure 11 6.3.4 Measurements with gloved hand 12 6.3.4 Measurements with gloved hand 12 6.3.5 Required number of tests 12 7.1 Calculation of transmissibility 14 7.2 Bare palm adaptor vibra		5.2					
5.2.3 Frequency analyses 5 5.2.4 Grip force measuring system 5 5.2.5 Feed force measuring system 5 5.3 Vibration excitation system 6 5.3.1 Characteristics of the instrumented handle 6 5.3.2 Position of the excitation system 7 5.3.3 Performance 7 6 Measurement conditions 7 6.1.1 Test subjects 7 6.1.2 Test gloves 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 6.3 Test procedure 11 6.3.1 Preparation 11 6.3.2 Measurements with the bare adaptor 11 6.3.3 Measurements with resilient material 12 6.3 Test procedure 11 6.3.4 Measurements with resilient material 12 6.3.5 Required number of tests 1			1				
5.2.4 Grip force measuring system 5 5.2.5 Feed force measuring system 5 5.3 Vibration excitation system 6 5.3.1 Characteristics of the instrumented handle 6 5.3.2 Position of the excitation system 7 5.3.3 Performance 7 6.1 Measurement conditions. 7 6.1.1 Test subjects 7 6.1.2 Test gloves 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 6.3 Test procedure 11 6.3.1 Preparation 11 6.3.2 Measurements with gloved hand 12 6.3.4 Measurements with resilient material 12 6.3.5 Required number of tests 12 7.1 Calculation of results 12 7.1.3 Frequency-weighted vibration transmissibility 14 7.2 Bare palm adaptor vib			0				
5.2.5 Feed force measuring system 5 5.3 Vibration excitation system 6 5.3.1 Characteristics of the instrumented handle 6 5.3.2 Position of the excitation system 7 5.3.3 Performance 7 5.3.3 Performance 7 6.1 Measurement conditions 7 6.1.1 Test subjects 7 6.1.2 Test gloves 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 9 6.3 Test procedure 11 6.3.1 Preparation 11 6.3.2 Measurements with gloved hand 12 6.3.4 Measurements with gloved hand 12 6.3.5 Required number of tests 12 7 Evaluation of results 12 7.1 Calculation of transmissibility 12 7.1.2 One-third-octave frequency ranges							
5.3.1 Characteristics of the instrumented handle 6 5.3.2 Position of the excitation system 7 5.3.3 Performance 7 6 Measurement conditions and procedure 7 6.1 Measurement conditions 7 6.1.1 Test subjects 7 6.1.2 Test gloves 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 6.3 Test procedure 11 6.3.1 Preparation 11 6.3.2 Measurements with the bare adaptor 11 6.3.3 Measurements with gloved hand 12 6.3.4 Measurements with growed hand 12 6.3.5 Required number of tests 12 7 Calculation of transmissibility 12 7.1.1 General 12 7.1.2 One-third-octave frequency ranges 13 7.1.3 Frequency-weighted vibration transmi							
5.3.2 Position of the excitation system 7 5.3.3 Performance 7 6 Measurement conditions and procedure 7 6.1 Measurement conditions 7 6.1.1 Test subjects 7 6.1.2 Test gloves 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 6.3 Test procedure 11 6.3.4 Measurements with the bare adaptor 11 6.3.5 Required number of tests 12 7 A.4 Measurements with gloved hand 12 6.3.5 Required number of tests 12 7 Calculation of transmissibility 12 7.1.1 General 12 7.1.2 One-third-octave frequency ranges 13 7.1.3 Frequency-weighted vibration transmissibility 14 7.2.1 One-third-octave vibration transmissibility 15 7.3.1		5.3	Vibration excitation system	6			
5.3.3 Performance 7 6 Measurement conditions and procedure 7 6.1 Measurement conditions 7 6.1.1 Test subjects 7 6.1.2 Test gloves 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 6.3 Test procedure 11 6.3.1 Preparation 11 6.3.2 Measurements with the bare adaptor 11 6.3.3 Measurements with resilient material 12 6.3.4 Measurements with resilient material 12 6.3.5 Required number of tests 12 7 7.1 General 12 7.1.1 General 12 7.1.2 One-third-octave frequency ranges 13 7.1.3 Frequency-weighted vibration transmissibility 14 7.2.2 Frequency-weighted vibration transmissibility 15 7.3 Uncorrected							
6 Measurement conditions and procedure 7 6.1 Measurement conditions 7 6.1.1 Test subjects 7 6.1.2 Test gloves 7 6.1.3 Test conditions 7 6.1.4 Test conditions 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 6.3 Test procedure 11 6.3.1 Preparation 11 6.3.2 Measurements with be bare adaptor 11 6.3.3 Measurements with gloved hand 12 6.3.4 Measurements with resilient material 12 6.3.5 Required number of tests 12 7.1 Calculation of transmissibility 12 7.1.2 One-third-octave frequency ranges 13 7.2 Bare palm adaptor vibration transmissibility 14 7.2.1 One-third-octave vibration transmissibility 14 7.2.3.1 One-third-octave vibration transmissibility 15 7.3.1 One-third-octave vibration transmissibility 15							
6.1 Measurement conditions 7 6.1.1 Test subjects 7 6.1.2 Test gloves 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 6.3 Test procedure 11 6.3.1 Preparation 11 6.3.2 Measurements with bloved hand 12 6.3.4 Measurements with gloved hand 12 6.3.5 Required number of tests 12 7 Calculation of transmissibility 12 7.1.1 Galculation of transmissibility 12 7.1.2 One-third-octave frequency ranges 13 7.1.3 Frequency-weighted acceleration values 13 7.2.5 Bare palm adaptor vibration transmissibility 14 7.2.2 Frequency-weighted vibration transmissibility 14 7.3.1 One-third-octave vibration transmissibility 15 7.3.2 Frequency-weighted vibration transmissibility 16<			5.3.3 Performance	7			
6.1.1Test subjects.76.1.2Test gloves76.1.3Test conditions.76.1.4Test subject's posture76.1.5Position of the palm adaptor in glove vibration transmissibility tests.86.2Vibration signal96.3Test procedure.116.3.1Preparation.116.3.2Measurements with the bare adaptor.116.3.3Measurements with gloved hand126.3.4Measurements with resilient material126.3.5Required number of tests.127Calculation of results127.1Calculation of transmissibility.127.1.2One-third-octave frequency ranges.137.1.3Frequency-weighted acceleration values137.2Bare palm adaptor vibration transmissibility.147.2.1One-third-octave vibration transmissibility.157.3Uncorrected glove vibration transmissibility.157.3.1One-third-octave vibration transmissibility.167.4.1One-third-octave vibration transmissibility.167.4.2Frequency-weighted vibration transmissibility.167.4.1One-third-octave vibration transmissibility.167.3.2Frequency-weighted vibration transmissibility.167.4.2Frequency-weighted vibration transmissibility.167.4.2Frequency-weighted vibration transmissibility.167.3.3General168.1<	6		surement conditions and procedure	7			
6.1.2 Test gloves 7 6.1.3 Test conditions 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests 8 6.2 Vibration signal 9 6.3 Test procedure 11 6.3.1 Preparation 11 6.3.2 Measurements with the bare adaptor 11 6.3.3 Measurements with gloved hand 12 6.3.4 Measurements with resilient material 12 6.3.5 Required number of tests 12 7.1 Calculation of transmissibility 12 7.1.1 General 12 7.1.2 One-third-octave frequency ranges 13 7.1.3 Frequency-weighted acceleration values 13 7.2 Bare palm adaptor vibration transmissibility 14 7.2.1 One-third-octave vibration transmissibility 15 7.3.1 One-third-octave vibration transmissibility 15 7.3.2 Frequency-weighted vibration transmissibility 16 7.4.2 Frequency-weighted vibration transm		6.1					
6.1.3 Test conditions. 7 6.1.4 Test subject's posture 7 6.1.5 Position of the palm adaptor in glove vibration transmissibility tests. 8 6.2 Vibration signal 9 6.3 Test procedure. 11 6.3.1 Preparation 11 6.3.2 Measurements with the bare adaptor. 11 6.3.3 Measurements with gloved hand 12 6.3.4 Measurements with resilient material 12 6.3.5 Required number of tests 12 7.1 Calculation of transmissibility. 12 7.1.1 General 12 7.1.2 One-third-octave frequency ranges 13 7.1.3 Frequency-weighted acceleration values 13 7.2 Bare palm adaptor vibration transmissibility 14 7.2.1 One-third-octave vibration transmissibility 15 7.3.1 One-third-octave vibration transmissibility 15 7.3.1 One-third-octave vibration transmissibility 16 7.4.2 Frequency-weighted vibration transmissibility 16 7.4.1 <							
6.1.4Test subject's posture76.1.5Position of the palm adaptor in glove vibration transmissibility tests86.2Vibration signal96.3Test procedure116.3.1Preparation116.3.2Measurements with the bare adaptor116.3.3Measurements with gloved hand126.3.4Measurements with resilient material126.3.5Required number of tests127Evaluation of results127.1Calculation of transmissibility127.1.1General127.1.2One-third-octave frequency ranges137.1.3Frequency-weighted vibration transmissibility147.2.4Frequency-weighted vibration transmissibility147.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility157.3.2Frequency-weighted vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.1General168.1Calculation of statistical values168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility178.3Frequency-weighted vibration transmissibility17							
6.1.5Position of the palm adaptor in glove vibration transmissibility tests86.2Vibration signal96.3Test procedure116.3.1Preparation116.3.2Measurements with the bare adaptor116.3.3Measurements with gloved hand126.3.4Measurements with resilient material126.3.5Required number of tests127.1Calculation of results127.1.1General127.1.2One-third-octave frequency ranges137.1.3Frequency-weighted acceleration values137.2Bare palm adaptor vibration transmissibility147.2.1One-third-octave vibration transmissibility157.3.1One-third-octave vibration transmissibility157.3.2Frequency-weighted vibration transmissibility167.4Corrected glove vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.3General168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility							
6.2Vibration signal96.3Test procedure116.3.1Preparation116.3.2Measurements with the bare adaptor116.3.3Measurements with gloved hand126.3.4Measurements with resilient material126.3.5Required number of tests127Evaluation of results127.1Calculation of transmissibility127.1.2One-third-octave frequency ranges137.1.3Frequency-weighted acceleration values137.2Bare palm adaptor vibration transmissibility147.2.1One-third-octave vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility178.3Frequency-weighted vibration transmissibility17							
6.3Test procedure.116.3.1Preparation.116.3.2Measurements with the bare adaptor116.3.3Measurements with gloved hand.126.3.4Measurements with resilient material.126.3.5Required number of tests.127Evaluation of results127.1Calculation of transmissibility.127.1.1General.127.1.2One-third-octave frequency ranges.137.1.3Frequency-weighted acceleration values137.2Bare palm adaptor vibration transmissibility.147.2.1One-third-octave vibration transmissibility147.2.2Frequency-weighted vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility167.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values.168.1General.168.2One-third-octave vibration transmissibility.178.3Frequency-weighted vibration transmissibility.17		62					
6.3.1Preparation116.3.2Measurements with the bare adaptor116.3.3Measurements with gloved hand126.3.4Measurements with resilient material126.3.5Required number of tests127Evaluation of results127.1Calculation of transmissibility127.1.1General127.1.2One-third-octave frequency ranges137.1.3Frequency-weighted acceleration values137.2Bare palm adaptor vibration transmissibility147.2.1One-third-octave vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility157.3.2Frequency-weighted vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.3General168.4General168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17							
6.3.2Measurements with the bare adaptor116.3.3Measurements with gloved hand126.3.4Measurements with resilient material126.3.5Required number of tests127Evaluation of results127.1Calculation of transmissibility127.1.1General127.1.2One-third-octave frequency ranges137.1.3Frequency-weighted acceleration values137.2Bare palm adaptor vibration transmissibility147.2.1One-third-octave vibration transmissibility147.2.2Frequency-weighted vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility167.4.1One-third-octave vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17		0.0					
6.3.3Measurements with gloved hand126.3.4Measurements with resilient material126.3.5Required number of tests127Evaluation of results127.1Calculation of transmissibility127.1.1General127.1.2One-third-octave frequency ranges137.1.3Frequency-weighted acceleration values137.2Bare palm adaptor vibration transmissibility147.2.1One-third-octave vibration transmissibility147.2.2Frequency-weighted vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility167.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.3General168.4General168.5Calculation of statistical values168.6Calculation of statistical values168.7General168.8Frequency-weighted vibration transmissibility178.3Frequency-weighted vibration transmissibility17							
6.3.4Measurements with resilient material126.3.5Required number of tests127Evaluation of results127.1Calculation of transmissibility127.1.1General127.1.2One-third-octave frequency ranges137.1.3Frequency-weighted acceleration values137.2Bare palm adaptor vibration transmissibility147.2.1One-third-octave vibration transmissibility147.2.2Frequency-weighted vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility157.3.2Frequency-weighted vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17							
7Evaluation of results127.1Calculation of transmissibility127.1.1General127.1.2One-third-octave frequency ranges137.1.3Frequency-weighted acceleration values137.2Bare palm adaptor vibration transmissibility147.2.1One-third-octave vibration transmissibility147.2.2Frequency-weighted vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility167.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility167.4.1One-third-octave vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17			6.3.4 Measurements with resilient material				
7.1Calculation of transmissibility127.1.1General127.1.2One-third-octave frequency ranges137.1.3Frequency-weighted acceleration values137.2Bare palm adaptor vibration transmissibility147.2.1One-third-octave vibration transmissibility147.2.2Frequency-weighted vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility157.3.2Frequency-weighted vibration transmissibility167.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17			6.3.5 Required number of tests				
7.1.1General127.1.2One-third-octave frequency ranges137.1.3Frequency-weighted acceleration values137.2Bare palm adaptor vibration transmissibility147.2.1One-third-octave vibration transmissibility147.2.2Frequency-weighted vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility157.3.2Frequency-weighted vibration transmissibility167.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17	7	Eval	uation of results				
7.1.2One-third-octave frequency ranges137.1.3Frequency-weighted acceleration values137.2Bare palm adaptor vibration transmissibility147.2.1One-third-octave vibration transmissibility147.2.2Frequency-weighted vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility157.3.2Frequency-weighted vibration transmissibility167.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17		7.1	Calculation of transmissibility				
7.1.3Frequency-weighted acceleration values137.2Bare palm adaptor vibration transmissibility147.2.1One-third-octave vibration transmissibility147.2.2Frequency-weighted vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility157.3.2Frequency-weighted vibration transmissibility167.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17			7.1.1 General				
7.2Bare palm adaptor vibration transmissibility147.2.1One-third-octave vibration transmissibility147.2.2Frequency-weighted vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility157.3.2Frequency-weighted vibration transmissibility167.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17							
7.2.1One-third-octave vibration transmissibility147.2.2Frequency-weighted vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility157.3.2Frequency-weighted vibration transmissibility167.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17							
7.2.2Frequency-weighted vibration transmissibility157.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility157.3.2Frequency-weighted vibration transmissibility167.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17		7.2					
7.3Uncorrected glove vibration transmissibility157.3.1One-third-octave vibration transmissibility157.3.2Frequency-weighted vibration transmissibility167.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17							
7.3.1One-third-octave vibration transmissibility157.3.2Frequency-weighted vibration transmissibility167.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17		F 0					
7.3.2Frequency-weighted vibration transmissibility167.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17		7.3					
7.4Corrected glove vibration transmissibility167.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17							
7.4.1One-third-octave vibration transmissibility167.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17		74					
7.4.2Frequency-weighted vibration transmissibility168Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17		7.4					
8Calculation of statistical values168.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17							
8.1General168.2One-third-octave vibration transmissibility178.3Frequency-weighted vibration transmissibility17	8	Calc					
 8.2 One-third-octave vibration transmissibility 17 8.3 Frequency-weighted vibration transmissibility 17 	U						
8.3 Frequency-weighted vibration transmissibility		-					
			5				
	9						

BS EN ISO 10819:2013+A1:2019 ISO 10819:2013+A1:2019

9.2 Vibration transmissibility of the gloves9.3 Construction of the gloves	
9.3 Construction of the gloves	
9.3.1 Glove vibration-reducing material thickness	
9.3.2 Measurement of the thickness of the glove vibration-reducing material	
9.3.3 Lacks (gap) between the palm and thumb sections of glove vibration-	
reducing material	
9.3.4 Requirements within the European Union	
10 Test report	
Annex A (informative) Examples of handles with force and acceleration measuring systems	
Annex B (normative) Further requirements for protective gloves against vibration	
Bibliography	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2, <u>www.iso.org/directives</u>.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received, <u>www.iso.org/patents</u>.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

The committee responsible for this document is ISO/TC 108, *Mechanical vibration, shock and condition monitoring*, Subcommittee SC 4, *Human exposure to mechanical vibration and shock*.

This second edition cancels and replaces the first edition (ISO 10819:1996), of which it constitutes a technical revision. The main changes are stronger criteria for antivibration gloves and the addition of a method for measuring the material thickness.

Introduction

Because of the growing demand to reduce health risks associated with exposure to hand-transmitted vibration, gloves with vibration-reducing materials are often used to attenuate vibration transmitted to the hands. These gloves normally provide little reduction in hand-transmitted vibration at frequencies below 150 Hz. Some gloves can increase the vibration transmitted to the hands at these low frequencies. Gloves with vibration-reducing materials that meet the requirements of this International Standard to be classified as an antivibration glove can be expected to reduce hand-transmitted vibration at frequencies above 150 Hz. These gloves can reduce but not eliminate health risks associated with hand-transmitted vibration exposure.

Field observations indicate that gloves with vibration-reducing materials can result in positive and negative health effects. Positive health effects can occur with gloves that reduce finger tingling and numbress and that keep the hands warm and dry. Negative health effects can occur with gloves that increase the vibration transmitted to the hands at low frequencies and that increase hand and arm fatigue because they increase the hand grip effort required to control a vibrating machine.

Gloves tested in accordance with the requirements of this International Standard are evaluated in a controlled laboratory environment. The actual vibration attenuation of a glove in a work environment can differ from that measured in a controlled laboratory environment.

Vibration transmissibility measurements made in accordance with the requirements of this International Standard are performed only at the palm of the hand. The transmission of vibration to the fingers is not measured. When evaluating the effectiveness of a glove with a vibration-reducing material used to reduce vibration transmitted to the hand, vibration transmission to the fingers should also be assessed. However, research subsequent to the publication of this International Standard is needed to develop a measurement procedure that can be used to measure the vibration transmissibility of gloves at the fingers.

The measurement procedure specified in this International Standard only addresses glove properties that can reduce health risks associated with hand-transmitted vibration in work environments. It does not address glove properties necessary to reduce other hand-related health and safety risks in work environments.

The measurement procedure specified in this International Standard can also be used to measure the vibration transmissibility of a material that is being evaluated for use to cover a handle of a machine or for potential use in a glove.

Mechanical vibration and shock - Hand-arm vibration -Measurement and evaluation of the vibration transmissibility of gloves at the palm of the hand

WARNING — This International Standard defines a screening test procedure for measuring the vibration transmission through gloves with an embedded vibration-reducing material. Many factors not addressed in this International Standard can influence the transmission of vibration through these gloves. Therefore, use the vibration transmissibility values obtained in accordance with this International Standard with caution in the assessment of the vibration-reducing effects of gloves.

1 Scope

This International Standard specifies a method for the laboratory measurement, data analysis, and reporting of the vibration transmissibility of a glove with a vibration-reducing material that covers the palm, fingers, and thumb of the hand. This International Standard specifies vibration transmissibility in terms of vibration transmitted from a handle through a glove to the palm of the hand in one-third-octave frequency bands with centre frequencies of 25 Hz to 1 250 Hz.

The measurement procedure specified in this International Standard can also be used to measure the vibration transmissibility of a material that is being evaluated for use to cover a handle of a machine or for potential use in a glove. However, results from this test cannot be used to certify that a material used to cover a handle meets the requirements of this International Standard to be classified as an antivibration covering. A material tested in this manner could later be placed in a glove. When this is the case, the glove needs to be tested in accordance with the measurement procedure of this International Standard and needs to meet the vibration attenuation performance requirements of this International Standard in order to be classified as an antivibration glove.

NOTE ISO 13753^[1] defines a method for screening materials used for vibration attenuation on the handles of machines and for gloves.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2041, Mechanical vibration, shock and condition monitoring — Vocabulary

ISO 5349-1, Mechanical vibration — Measurement and evaluation of human exposure to hand-transmitted vibration — Part 1: General requirements

ISO 5805, Mechanical vibration and shock — Human exposure — Vocabulary

ISO 8041, Human response to vibration — Measuring instrumentation

IEC 61260, Electroacoustics — Octave-band and fractional-octave-band filters

A) EN 388:2016, Protective gloves against mechanical risks (A)

A) EN 420+A1:2009, Protective gloves — General requirements and test methods (A)